

## PACKAGING AND DISTRIBUTING

Create, package and distribute your own python application

---

José Antonio Perdiguero López

 <https://github.com/PeRDy>

 <https://www.linkedin.com/in/josé-antonio-perdiguero-lópez-732a9768/>

@ perdy.hh@gmail.com

April 19, 2017

Málaga Python MeetUp

- ① Introduction
  - Why should I distribute my application?
  - Versioning
  - Tools and Services
- ② Creation
  - Storing the project
  - Create the project skeleton
  - Project hierarchy
  - Bind services
- ③ Packaging
  - Test your application
  - Creating a package
- ④ Distributing
  - Register the application
  - Upload a new version
- ⑤ Conclusion
  - Full workflow
  - Simplified workflow

## Introduction

---

# Why should I distribute my application?

- Given enough eyeballs, all bugs are shallow.

---

<sup>1</sup><https://opensource.com/life/15/12/why-open-source>

# Why should I distribute my application?

- Given enough eyeballs, all bugs are shallow.
- Upstream improvements.

---

<sup>1</sup><https://opensource.com/life/15/12/why-open-source>

# Why should I distribute my application?

- Given enough eyeballs, all bugs are shallow.
- Upstream improvements.
- Force multiplier.

---

<sup>1</sup><https://opensource.com/life/15/12/why-open-source>

# Why should I distribute my application?

- Given enough eyeballs, all bugs are shallow.
- Upstream improvements.
- Force multiplier.
- Modular.

---

<sup>1</sup><https://opensource.com/life/15/12/why-open-source>

# Why should I distribute my application?

- Given enough eyeballs, all bugs are shallow.
- Upstream improvements.
- Force multiplier.
- Modular.
- Great advertising.

---

<sup>1</sup><https://opensource.com/life/15/12/why-open-source>



# Why should I distribute my application?

- Given enough eyeballs, all bugs are shallow.
- Upstream improvements.
- Force multiplier.
- Modular.
- Great advertising.
- Attract talent.

---

<sup>1</sup><https://opensource.com/life/15/12/why-open-source>

# Why should I distribute my application?

- Given enough eyeballs, all bugs are shallow.
- Upstream improvements.
- Force multiplier.
- Modular.
- Great advertising.
- Attract talent.
- Stand on the shoulders of giants.

---

<sup>1</sup><https://opensource.com/life/15/12/why-open-source>

# Why should I distribute my application?

- Given enough eyeballs, all bugs are shallow.
- Upstream improvements.
- Force multiplier.
- Modular.
- Great advertising.
- Attract talent.
- Stand on the shoulders of giants.
- Best technical interview possible.

---

<sup>1</sup><https://opensource.com/life/15/12/why-open-source>

# Why should I distribute my application?

- Given enough eyeballs, all bugs are shallow.
- Upstream improvements.
- Force multiplier.
- Modular.
- Great advertising.
- Attract talent.
- Stand on the shoulders of giants.
- Best technical interview possible.
- Show your code.

---

<sup>1</sup><https://opensource.com/life/15/12/why-open-source>

## Version schema

A normal version must be denoted by `X.Y.Z` where `X`, `Y` and `Z` are positive integers. `X` represents the major version, `Y` the minor version and `Z` the patch version. Version `1.0.0` defines the public API.

---

<sup>1</sup><http://semver.org/>

## Version schema

A normal version must be denoted by `X.Y.Z` where `X`, `Y` and `Z` are positive integers. `X` represents the major version, `Y` the minor version and `Z` the patch version. Version `1.0.0` defines the public API.

## Version upgrade

Given a version number, increment:

**Major** version when you make incompatible API changes. Reset minor and patch version to `0`.

**Minor** version when you add functionality in a backwards-compatible manner. Reset patch version to `0`.

**Patch** version when you make backwards-compatible bug fixes.

---

<sup>1</sup><http://semver.org/>

## Prospector

Static code analysis using different tools.

<https://github.com/landscapeio/prospector>

## Prospector

Static code analysis using different tools.

<https://github.com/landscapeio/prospector>

## Sphinx

Create documentation for your project.

<https://github.com/sphinx-doc/sphinx>



## Prospector

Static code analysis using different tools.

<https://github.com/landscapeio/prospector>

## Sphinx

Create documentation for your project.

<https://github.com/sphinx-doc/sphinx>

## Bumpversion

Utility to upgrade your project version.

<https://github.com/peritus/bumpversion>

## Prospector

Static code analysis using different tools.

<https://github.com/landscapeio/prospector>

## Sphinx

Create documentation for your project.

<https://github.com/sphinx-doc/sphinx>

## Bumpversion

Utility to upgrade your project version.

<https://github.com/peritus/bumpversion>

## Pre-commit

Utility that does some checks before git commits.

<https://github.com/pre-commit/pre-commit>

### Tox

Run your tests using many different python interpreters.

<https://github.com/tox-dev/tox>

### Tox

Run your tests using many different python interpreters.

<https://github.com/tox-dev/tox>

### Clinner

Utility to create powerful Command Line Interfaces with a few lines.

<https://github.com/PeRDy/clinner>

### Tox

Run your tests using many different python interpreters.

<https://github.com/tox-dev/tox>

### Clinner

Utility to create powerful Command Line Interfaces with a few lines.

<https://github.com/PeRDy/clinner>

### Cookiecutter

Application that creates project skeletons using Jinja templates.

<https://github.com/audreyr/cookiecutter>

### Tox

Run your tests using many different python interpreters.

<https://github.com/tox-dev/tox>

### Clinner

Utility to create powerful Command Line Interfaces with a few lines.

<https://github.com/PeRDy/clinner>

### Cookiecutter

Application that creates project skeletons using Jinja templates.

<https://github.com/audreyr/cookiecutter>

### Cookiecutter Template

Cookiecutter template for Python packages.

<https://github.com/PeRDy/cookiecutter-python-package>

## PyPI

Python Package Index, the main repository of python software.

<https://pypi.python.org/pypi>

## PyPI

Python Package Index, the main repository of python software.

<https://pypi.python.org/pypi>

## GitHub

Repositories for your source code. <https://github.com>



## PyPI

Python Package Index, the main repository of python software.

<https://pypi.python.org/pypi>

## GitHub

Repositories for your source code. <https://github.com>

## Travis

Continuous Integration service. <https://travis-ci.org/>

## PyPI

Python Package Index, the main repository of python software.

<https://pypi.python.org/pypi>

## GitHub

Repositories for your source code. <https://github.com>

## Travis

Continuous Integration service. <https://travis-ci.org/>

## Coveralls

Keeps the changes of test coverage of your code. <https://coveralls.io>

## PyPI

Python Package Index, the main repository of python software.

<https://pypi.python.org/pypi>

## GitHub

Repositories for your source code. <https://github.com>

## Travis

Continuous Integration service. <https://travis-ci.org/>

## Coveralls

Keeps the changes of test coverage of your code. <https://coveralls.io>

## ReadTheDocs

Stores and serves documentation for your project. <https://readthedocs.io>

## Creation

---


# Storing the project

## Create a new repository

A repository contains all the files for your project, including the revision history.

Owner

Repository name

 PeRDy ▾ /  ✓

Great repository names are short and memorable. Need inspiration? How about **furry-adventure**.

Description (optional)

☒  **Public**  
Anyone can see this repository. You choose who can commit.

☐  **Private**  
You choose who can see and commit to this repository.

☐ **Initialize this repository with a README**

This will let you immediately clone the repository to your computer. Skip this step if you're importing an existing repository.

Add .gitignore: **None** ▾ | Add a license: **None** ▾ 

Create repository

## Cookiecutter context

Define all variables needed by cookiecutter to properly create the project skeleton, these variables can be found in *cookiecutter.json* file.

# Create the project skeleton

## Cookiecutter context

Define all variables needed by cookiecutter to properly create the project skeleton, these variables can be found in *cookiecutter.json* file.

## Create skeleton

Execute cookiecutter with previously defined context to create the project skeleton.

# Create the project skeleton

## Cookiecutter context

Define all variables needed by cookiecutter to properly create the project skeleton, these variables can be found in *cookiecutter.json* file.

## Create skeleton

Execute cookiecutter with previously defined context to create the project skeleton.

## Commit & push


Time to do your first commit and push to repository:

```
git remote add origin git@github.com:PeRDy/foo.git
git commit -a -m "Initial commit"
git push
```




## Documentation folder

The place that keeps all the documentation source files as well as the doc config file.



- doc/source
- tests
- {{ cookiecutter.app\_slug }}
- .gitignore
- .pre-commit-config.yaml
- .prospector.yaml
- .travis.yml
- CHANGELOG.rst
- CONTRIBUTORS.rst
- LICENSE
- MANIFEST.in
- README.rst
- build.py
- requirements-tests.txt
- requirements.txt
- setup.cfg
- setup.py
- tox.ini



A screenshot of a file explorer interface showing a list of files and folders. The 'tests' folder is highlighted in blue. The list includes:

- doc/source
- tests
- {{ cookiecutter.app\_slug }}
- .gitignore
- .pre-commit-config.yaml
- .prospector.yaml
- .travis.yml
- CHANGELOG.rst
- CONTRIBUTORS.rst
- LICENSE
- MANIFEST.in
- README.rst
- build.py
- requirements-tests.txt
- requirements.txt
- setup.cfg
- setup.py
- tox.ini


## Documentation folder

The place that keeps all the documentation source files as well as the doc config file.

## Tests folder

All tests files are stored in a tests folder where tests collectors can gather them without problems.

# Project hierarchy



```
doc/source
tests
{{ cookiecutter.app_slug }}
.gitignore
.pre-commit-config.yaml
.prospector.yaml
.travis.yml
CHANGELOG.rst
CONTRIBUTORS.rst
LICENSE
MANIFEST.in
README.rst
build.py
requirements-tests.txt
requirements.txt
setup.cfg
setup.py
tox.ini
```

## Documentation folder


The place that keeps all the documentation source files as well as the doc config file.

## Tests folder

All tests files are stored in a tests folder where tests collectors can gather them without problems.

## Application folder

The application itself, the *python package* distributed, and the same that other users will import in their applications.



- doc/source
- tests
- {{ cookiecutter.app\_slug }}
- .gitignore
- .pre-commit-config.yaml
- .prospector.yaml
- .travis.yml
- CHANGELOG.rst
- CONTRIBUTORS.rst
- LICENSE
- MANIFEST.in
- README.rst
- build.py
- requirements-tests.txt
- requirements.txt
- setup.cfg
- setup.py
- tox.ini

## Documentation folder

The place that keeps all the documentation source files as well as the doc config file.

## Tests folder

All tests files are stored in a tests folder where tests collectors can gather them without problems.

## Application folder

The application itself, the *python package* distributed, and the same that other users will import in their applications.

## Root files

Files that keeps in the root directory are usually:

- Tools configuration.
- Services configuration.
- Build scripts.
- Metadata.

### Manifest

This file, `MANIFEST.in`, with own syntax<sup>1</sup> defines the directories and files that will be included in the distributable package.

---

<sup>1</sup><https://docs.python.org/3/distutils/commandref.html#dist-cmd>

### Manifest

This file, `MANIFEST.in`, with own syntax<sup>1</sup> defines the directories and files that will be included in the distributable package.

### Requirements

List all requirements of your project, that are added as dependencies when installed. Usually requirements are splitted in two files:

`requirements.txt` for real dependencies and

`requirements-tests.txt` for dependencies necessities to test the project.

---

<sup>1</sup><https://docs.python.org/3/distutils/commandref.html#dist-cmd>

### Manifest

This file, `MANIFEST.in`, with own syntax<sup>1</sup> defines the directories and files that will be included in the distributable package.

### Requirements

List all requirements of your project, that are added as dependencies when installed. Usually requirements are splitted in two files:

`requirements.txt` for real dependencies and

`requirements-tests.txt` for dependencies necessities to test the project.

### Metadata

Metadata files: `README.rst`, `CONTRIBUTORS.rst`, `CHANGELOG.rst` and `LICENSE`.

---

<sup>1</sup><https://docs.python.org/3/distutils/commandref.html#dist-cmd>

### Tools and Services config

Configuration files for tools and services: `setup.cfg`,  
`.pre-commit-config.yaml`, `.prospector.yaml`, `.travis.yml`,  
`.gitignore`.



### Tools and Services config

Configuration files for tools and services: `setup.cfg`,  
`.pre-commit-config.yaml`, `.prospector.yaml`, `.travis.yml`,  
`.gitignore`.

### Setup

Main file that defines how the project will be packaged, gather metadata from other files and provides an interface to create distributable packages.

### Tools and Services config

Configuration files for tools and services: `setup.cfg`,  
`.pre-commit-config.yaml`, `.prospector.yaml`, `.travis.yml`,  
`.gitignore`.

### Setup

Main file that defines how the project will be packaged, gather metadata from other files and provides an interface to create distributable packages.

### Tox

Tox file, `tox.ini`, defines the environments and commands that tox executes. In this case, defines an environment for each python version that should be tested, another for run lint tools and the last one for compile documentation.

### Build


The build file, **build.py**, is the entrypoint for everything related to build, including *testing*, *packaging* and *distributing*. This is a command line application using *Clinner* that provides a set of utility commands such as:

- Run tests and code coverage.
- Run lint.
- Run tox.
- Create documentation.
- Upgrade version, create package and upload to pypi.


## José Antonio Perdiguero

[Sync account](#)


We're only showing your public repositories. You can find your private projects on [travis-ci.com](https://travis-ci.com).



























1  
Click the repository switch on



2  
Add .travis.yml file to your repository






























3  
Trigger your first build with a git push

		PeRDy/ai-models
		PeRDy/behave-django
		PeRDy/celery
		PeRDy/celery-tools
		PeRDy/clinner
		PeRDy/cookiecutter-python-app
		PeRDy/cookiecutter-python-package
		PeRDy/django
		PeRDy/django-audit-tools
		PeRDy/django-configurations
		PeRDy/django-haystack
		PeRDy/django-numpy





















## ADD REPO

To add repositories that are private on Github or Bitbucket you will need a Coveralls Pro subscription for the GitHub user / org or Bitbucket team. Click the 'Add Subscription' button next to the user or organization name to add a private repo plan.

	<b>PERDY</b> / <i>ai-models</i>	
	<b>PERDY</b> / <i>behave-django</i>	
	<b>PERDY</b> / <i>celery</i>	
	<b>PERDY</b> / <i>celery-tools</i>	
	<b>PERDY</b> / <i>clinner</i>	 
	<b>PERDY</b> / <i>cookiecutter-python-app</i>	
	<b>PERDY</b> / <i>cookiecutter-python-package</i>	
	<b>PERDY</b> / <i>django</i>	
	<b>PERDY</b> / <i>django-audit-tools</i>	 
	<b>PERDY</b> / <i>django-configurations</i>	
	<b>PERDY</b> / <i>django-haystack</i>	
	<b>PERDY</b> / <i>django-numpy</i>	

**SUBSCRIPTIONS**  
**GITHUB**  
 **PERDY**

## Import a Repository

	PeRDy/ai-models <a href="https://github.com/PeRDy/ai-models.git">https://github.com/PeRDy/ai-models.git</a>	
	PeRDy/behave-django <a href="https://github.com/PeRDy/behave-django.git">https://github.com/PeRDy/behave-django.git</a>	
	PeRDy/celery <a href="https://github.com/PeRDy/celery.git">https://github.com/PeRDy/celery.git</a>	
	PeRDy/celery-tools <a href="https://github.com/PeRDy/celery-tools.git">https://github.com/PeRDy/celery-tools.git</a>	
	PeRDy/clinner <a href="https://github.com/PeRDy/clinner.git">https://github.com/PeRDy/clinner.git</a>	
	PeRDy/cookiecutter-python-app <a href="https://github.com/PeRDy/cookiecutter-python-app.git">https://github.com/PeRDy/cookiecutter-python-app.git</a>	
	PeRDy/cookiecutter-python-package <a href="https://github.com/PeRDy/cookiecutter-python-package.git">https://github.com/PeRDy/cookiecutter-python-package.git</a>	
	PeRDy/django <a href="https://github.com/PeRDy/django.git">https://github.com/PeRDy/django.git</a>	
	PeRDy/django-audit-tools <a href="https://github.com/PeRDy/django-audit-tools.git">https://github.com/PeRDy/django-audit-tools.git</a>	
	PeRDy/django-configurations <a href="https://github.com/PeRDy/django-configurations.git">https://github.com/PeRDy/django-configurations.git</a>	



You can import your project manually if it isn't listed here or connected to one of your accounts.

Import Manually

## Packaging

---

# Test your application

## Development

Run tests while developing using nose.

```
python build.py test
```



# Test your application

## Development

Run tests while developing using nose.

```
python build.py test
```

## Multi-environment

Once development is done, run tests against all different interpreters supported to check compatibility.

```
python build.py tox
```

# Test your application

## Development

Run tests while developing using nose.

```
python build.py test
```

## Multi-environment

Once development is done, run tests against all different interpreters supported to check compatibility.

```
python build.py tox
```

## Continuous Integration

Development is done, tests pass in every environment, so code can be uploaded to repository safely. Once a commit is done:

**Travis** run tests in every environment and will notify in case any test didn't pass. When all tests pass,

**Coveralls** records current code coverage. In the same commit,

**ReadTheDocs** gets the code, build docs and updates the project's doc page.

### Egg

Source distribution.

```
python setup.py sdist
```

### Egg

Source distribution.

```
python setup.py sdist
```

### Wheel

Built and binary distribution.

```
python setup.py bdist_wheel
```

```
[ @clinner ]( ~/Desarrollo/clinner )[ ?:master 45f1118 ] ( @PeRDy-XPS )
>>> python build.py -h
usage: build.py [-h] [-s SETTINGS] [-q] [--dry-run]
               {nose,prospector,sphinx,tox,dist} ...

optional arguments:
  -h, --help            show this help message and exit
  -s SETTINGS, --settings SETTINGS
                        Module or object with Clinner settings in format
                        "package.module[:Object]"
  -q, --quiet            Quiet mode. No standard output other than executed
                        application
  --dry-run             Dry run. Skip commands execution, useful to check
                        which commands will be executed and execution order

Commands:
  {nose,prospector,sphinx,tox,dist}
  nose                  Run unit tests
  prospector            Run prospector lint
  sphinx                Sphinx doc
  tox                   Run tox
  dist                  Bump version, create package and upload it
```

## Distributing

---

## PyPI account

Create a PyPI<sup>1</sup> account. Configure `.pypirc` file with PyPI credentials.

---

<sup>1</sup><https://pypi.python.org/pypi>

<sup>2</sup><https://github.com/pypa/twine>

## PyPI account

Create a PyPI<sup>1</sup> account. Configure `.pypirc` file with PyPI credentials.

## Application register

Use twine<sup>2</sup> with a package of your application to register it in PyPI:

```
twine register dist/project-name.whl
```

---

<sup>1</sup><https://pypi.python.org/pypi>

<sup>2</sup><https://github.com/pypa/twine>



### Upload packages


Use twine again to upload all packages to PyPI:

```
twine upload dist/project-name.whl  
twine upload dist/project-name.tar.gz
```


## Conclusion

---


# Full workflow




# Full workflow




# Full workflow



# Full workflow



# Simplified workflow I



### Workflow execution

```
cookiecutter <project_name>  
...code...  
python build.py dist (patch|minor|major)  
git push
```



# Open source your code !

