

Suds Enviro SudSceptor

HYDRODYNAMIC SEPARATOR

DATA SHEET: SEHDS1200

OVERVIEW

The SudSceptor is a Hydrodynamic Separator with a unique design with a proven and tested performance. Designed for use within SUDS treatment trains, providing certainty of water quality treatment, enabling enhanced amenity and bio-diversity downstream. Protecting and defending downstream controlled waters from sediment bound pollutants. Units within the SudSceptor Range have been designed in accordance with * NJDEP protocol, + "best advice" (in part as NJDEP only covers TSS), British Water Code of Practice. Please note that USA NJDEP has no regulatory role or authority in the UK and Ireland. It can be used on-line or off-line and with or without an external by-pass unit. Multi treatment water purification processes are involved.

DESIGN CERTIFICATION & TESTING



- NJDEP 2015 & 2020
- DIBt.

PERFORMANCE

The SudSceptor removes sediment bound contaminants. Available in different flows and conditions. The SudSceptor removes over 50% of fine TSS (0-20 75 microns) at design flows and up to 99% of TDS 0.1 to 0.4mm (coarse).

MITIGATION INDICES	TSS	Total Metals	Total Hydrocarbons
NJDEP*	0.5	—	—
SUDSCEPTOR	0.5	0.40	0.50
British Water Code of Practice^	0.5	0.38	0.53



* NJDEP protocol, + "best advice" (in part as NJDEP only covers TSS), British Water Code of Practice



FEATURES & BENEFITS

- Single Piece Unit
- Cannot air lock
- Wide variety of connection availabilities
- Inlet deflector Plate creates the cyclic process
- Floatable materials and liquids are retained
- Settled solids are prevented from remobilisation
- A uniformed flow pathway is ensured by a distributed upwards flow.
- Weir ensures optimised flow pathways
- Easy maintenance
- 10 year warranty

INNER VORTEX OUTER VORTEX



OPTIONAL POLISHING FILTER

RHINOPOD is designed to absorb a wide range of harmful substances: Oils and PAH, Phosphorous, Nitrogen, phosphate (PO₄), the 33 prioritised substances in the EU directive as well as heavy metals, including Cadmium, Copper, Zinc, Nickel, Lead, Mercury...

TECHNICAL DATA

Overall Height:	3455mm
Chamber ID:	1200mm
Height to Invert:	923mm
Height to Inlet centre:	2100mm
Max Inlet/Outlet ID:	600mm
Sediment Storage Capacity:	415litres
Oil/Debris Storage Capacity:	370litres

CHAMBER OPTIONS

We recommend SudSceptor SEHDS750, SEHDS1000 and SEHDS1200 units are manufactured within twinwall chambers. Models : SEHDS1500, SEHDS1800, SEHDS2500 are manufactured within Glass Reinforced Plastic (GRP) chambers. The SudSceptor range hydraulic flow rates have larger pipe connection sizes, ideal for sites where higher peak flows are anticipated or required. The SudSceptor series also afford ease of connection to the structural wall drainage pipes commonly used in the UK stormwater drainage market.

INSTALLATION: The installation design should consider traffic loadings, ground conditions and variable ground water elevations. If in any doubt consult your schemes' Designer/Engineer. A suitably qualified professional is required to sign off the installation.

