

RHINO Rainwater

RAINWATER HARVESTING

1000 - 3300 L | DATA SHEET

DRAFT - VERIFY BEFORE ISSUE



OVERVIEW

RHINO rainwater harvesting systems collect, store and reuse rainwater from roof areas. Below-ground HDPE storage tanks are available from 1000 to 3300 litres, with direct, indirect and gravity-fed system configurations.

Harvested water is filtered before it enters the tank and is reused for non-potable supply, reducing mains water consumption and the load on the drainage system. A mains water top-up keeps the system available through dry periods.

1000
litres

1400
litres

2200
litres

2400
litres

3300
litres

DESIGN COMPLIANCE

- BS EN 16941-1:2018 on-site non-potable water systems, rainwater
- Water Supply (Water Fittings) Regulations 1999
- Building Regulations Part G and Part H
- WRAS approved components

APPLICATIONS

- Toilet flushing and WC supply
- Garden and landscape irrigation
- Vehicle washing and washdown
- Laundry and non-potable domestic use
- Commercial building water reduction strategies

SYSTEM TYPES

DIRECT

Water pumped directly from storage to points of use

INDIRECT

Water pumped to an elevated cistern, then gravity-fed

GRAVITY

Water fed by gravity from storage to points of use

No general arrangement drawing for this product is held in the SuDS Enviro drawing pack. Tank dimensions are confirmed at order.

FEATURES & BENEFITS

- Capacities from 1000 to 3300 litres
- Three system types: direct, indirect, gravity
- Below-ground HDPE storage tanks
- Integral first-flush diverter and filter
- Mains water backup for dry periods
- Reduces mains demand and drainage loading

SPECIFICATION

Material	HDPE, rotationally moulded
Capacities	1000, 1400, 2200, 2400, 3300 litres
System types	Direct, indirect, gravity
Installation	Below ground
Filtration	Pre-tank filter, first-flush diverter
Mains backup	Integral mains water top-up
Product code	RWH-[capacity]L-[DIR, IND or GRV]

CAPACITY RANGE

CAPACITY	DIRECT	INDIRECT	GRAVITY
1000 litres	RWH-1000L-DIR	RWH-1000L-IND	RWH-1000L-GRV
1400 litres	RWH-1400L-DIR	RWH-1400L-IND	RWH-1400L-GRV
2200 litres	RWH-2200L-DIR	RWH-2200L-IND	RWH-2200L-GRV
2400 litres	RWH-2400L-DIR	RWH-2400L-IND	RWH-2400L-GRV
3300 litres	RWH-3300L-DIR	RWH-3300L-IND	RWH-3300L-GRV

Product codes combine the tank capacity with the system type. Tank dimensions and connection details are confirmed at order.

HOW TO SPECIFY

- 1 SYSTEM TYPE**
Choose direct, indirect or gravity supply to suit the building.
- 2 ROOF CATCHMENT AREA**
Enter the effective roof catchment area in square metres.
- 3 TANK CAPACITY**
Select 1000, 1400, 2200, 2400 or 3300 litres.
- 4 ANNUAL RAINFALL**
Add the average annual rainfall in millimetres, if known.

TWO BENEFITS FROM ONE TANK

Every litre of rainwater reused for flushing, irrigation or washdown is a litre not drawn from the mains. Water held in the tank during rainfall is also kept out of the drainage system, reducing the load downstream.

COMPLIANCE

- BS EN 16941-1:2018
- Water Fittings Regulations 1999
- WRAS approved components
- Building Regulations Part G
- Building Regulations Part H

DRAFT - VERIFY BEFORE ISSUE

No official data sheet or general arrangement drawing for RHINO rainwater harvesting is held in the SuDS Enviro drawing pack. Content is taken from the configurator product data and rule set. BS 8515:2009 has been replaced by BS EN 16941-1:2018 and is no longer cited. Confirm capacities, dimensions and approvals before issue.

SPECIFY RHINO RAINWATER

Send us the roof area, the intended reuse and the preferred system type, and we will size the tank.

COMPANY	SuDS Enviro
ENQUIRIES	sales@sudsenviron.com
TELEPHONE	01224 057 700
WEB	www.sudsenviron.com