

RHINO Grease Separator

BELOW-GROUND FOG SEPARATOR

BS EN 1825 | DATA SHEET

DRAFT - VERIFY BEFORE ISSUE

OVERVIEW

The RHINO grease separator is a below-ground unit for larger-scale fats, oils and grease (FOG) management. It is designed for high-output commercial kitchens, food processing facilities and catering operations that need compliant pre-treatment before discharge to sewer.

Each unit is sized to the site's peak covers per day and design flow rate. The multi-chamber design gives enhanced FOG separation, and the large grease storage capacity reduces how often the unit has to be emptied.

HOW IT WORKS

Kitchen waste water flows through the chambers in turn. Fats, oils and grease rise and are held back in storage while the separated water passes forward to the outlet. An integral sample point allows the discharge to be sampled for trade effluent monitoring.

DESIGN COMPLIANCE

- BS EN 1825-1:2004 grease separators, principles of design
- BS EN 1825-2:2002 selection of nominal size
- BS EN 12056-1 gravity drainage inside buildings
- Building Regulations Part H1
- Water Industry Act 1991, trade effluent consent

WHERE IT IS USED

- Large restaurant and hotel complexes
- Food processing and manufacturing plants
- Hospital and institutional catering
- Event and festival catering operations



APPLICATIONS | SIZED PER SITE

RESTAURANT

Commercial restaurant kitchen

HOTEL

Hotel kitchen and food service

CATERING

Commercial catering or canteen

FOOD PROCESSING

Food processing or manufacturing facility

No general arrangement drawing for this product is held in the SuDS Enviro drawing pack. Project dimensions are confirmed at sizing.

FEATURES & BENEFITS

- Sized by peak covers per day and flow rate
- Below-ground installation, out of the way
- Multi-chamber design for enhanced FOG separation
- Large grease storage, fewer emptying visits
- Compatible with grease management dosing
- Integral sample point for trade effluent monitoring

SPECIFICATION

Material	HDPE, rotationally moulded
Installation	Below ground
Chambers	Multi-chamber separation
Sizing	Peak covers per day and flow rate (L/s)
Sample point	Integral
Dosing	Compatible with grease management dosing
Product code	GS-REST, GS-HTL, GS-CAT, GS-FP

SELECTING A SEPARATOR

APPLICATION	TYPICAL SITE	PRODUCT CODE	SIZED ON
Restaurant	Commercial restaurant kitchen	GS-REST	Peak covers per day and flow rate
Hotel	Hotel kitchen and food service	GS-HTL	Peak covers per day and flow rate
Catering	Commercial catering or canteen	GS-CAT	Peak covers per day and flow rate
Food processing	Food processing or manufacturing facility	GS-FP	Peak covers per day and flow rate

Separator size is selected under BS EN 1825-2 from the peak covers and the design flow rate. Our team confirms the unit and its dimensions for each project.

HOW TO SPECIFY

- 1 APPLICATION**
Choose the site type: restaurant, hotel, catering or food processing.
- 2 PEAK COVERS PER DAY**
Enter the peak number of covers (meals served) per day.
- 3 DESIGN FLOW RATE**
Enter the design flow rate from the kitchen in litres per second.
- 4 SIZING AND QUOTATION**
Our team selects the separator under BS EN 1825-2 and confirms its dimensions for the project.

GREASE TRAP OR SEPARATOR

Smaller kitchens can use the RHINO GT grease trap range, rated from 150 to 600 covers per day and fitted under the sink or on the floor. The below-ground grease separator is for higher-output sites that need more storage and a sample point for monitoring.

COMPLIANCE

- BS EN 1825-1:2004
- BS EN 1825-2:2002
- BS EN 12056-1
- Building Regulations Part H1
- Water Industry Act 1991

DRAFT - VERIFY BEFORE ISSUE

No official data sheet or general arrangement drawing for the RHINO grease separator is held in the SuDS Enviro drawing pack. Content is taken from the configurator product data and rule set. Confirm sizes, capacities and dimensions before issue.

SPECIFY A SEPARATOR

Send us the application, peak covers per day and design flow rate, and we will size the separator.

COMPANY	SuDS Enviro
ENQUIRIES	sales@sudsenviron.com
TELEPHONE	01224 057 700
WEB	www.sudsenviron.com