

RHINO GT

GREASE TRAP

MICRO | MINI | MIdI | JUMBO | DATA SHEET

DRAFT - VERIFY BEFORE ISSUE



OVERVIEW

The RHINO GT range captures fats, oils and grease (FOG) from commercial kitchen waste water before it reaches the drain. Four models, Micro, Mini, Midi and Jumbo, cover kitchens from 150 to 600 covers per day.

Each body is rotationally moulded in one piece of HDPE with a round access cover on a raised collar, so the trap can be opened for routine emptying and cleaning.

Micro

150 covers

Mini

300 covers

Midi

300 covers

Jumbo

600 covers



RHINO GT Micro. Product photograph. 830 x 640 x 630 mm, 150 covers per day.

HOW IT WORKS

Waste water enters through the inlet and is slowed by the integral internal baffle. Fats, oils and grease float to the surface and heavier solids settle, while the separated water passes on to the outlet. Retained FOG and sludge are removed through the access cover at each service.

DESIGN COMPLIANCE

- BS EN 1825-1:2004 grease separators, principles of design
- BS EN 1825-2:2002 selection of nominal size
- Building Regulations Part H1, FOG pre-treatment
- Water Industry Act 1991, trade effluent consent

APPLICATIONS

- Restaurant and takeaway kitchens
- Hotel and hospitality catering
- School and hospital kitchens
- Food preparation areas, canteens and staff kitchens

SELECTING A MODEL

Choose the model from the number of covers served per day, then confirm the inlet and outlet connection sizes for the kitchen waste pipework.

FEATURES & BENEFITS

- Four models from 150 to 600 covers per day
- One-piece HDPE body for hygiene and durability
- Integral internal baffle system
- Round access cover for cleaning and FOG removal
- Direct connection to kitchen waste pipes
- Under-sink or floor-mounted installation

SPECIFICATION

Models	Micro, Mini, Midi, Jumbo
Capacity	150 to 600 covers per day
Material	HDPE, rotationally moulded, one piece
Separation	Integral internal baffle
Access	Round access cover on raised collar
Installation	Under-sink or floor-mounted
Connections	Inlet and outlet sizes confirmed at order
Product code	GT-[MODEL], for example GT-MICRO

SIZE RANGE



Product photographs, shown at different sizes to fit the row. No dimensioned general arrangement drawing for the GT range is held in the SuDS Enviro drawing pack.

MODEL	COVERS PER DAY	SLUDGE CAPACITY	LENGTH	WIDTH	HEIGHT	BODY
Micro	150	100 L	830 mm	640 mm	630 mm	Single
Mini	300	250 L	1700 mm	640 mm	630 mm	Twin
Midi	300	180 L	1100 mm	720 mm	860 mm	Single
Jumbo	600	400 L	2240 mm	720 mm	860 mm	Twin

Overall external dimensions. Mini and Jumbo are twin-body units, pairing the Micro and Midi bodies; Mini and Midi share the 300 covers per day rating, with Mini on the lower, longer footprint and Midi on the taller, shorter one.

INSTALLATION

- Fit under the sink for low-output kitchens or floor-mounted for higher volumes
- Connect directly to the kitchen waste pipework
- Keep the access cover clear and reachable for servicing

MAINTENANCE

Empty retained FOG and sludge through the access cover at regular intervals, set by the kitchen's output. The sludge capacity for each model is given in the table above.

COMPLIANCE

- BS EN 1825-1:2004
- BS EN 1825-2:2002
- Building Regulations Part H1
- Water Industry Act 1991

SPECIFY RHINO GT

Tell us the covers served per day and the waste pipe sizes, and we will confirm the model.

COMPANY	SuDS Enviro
ENQUIRIES	sales@sudsenviron.com
TELEPHONE	01224 057 700
WEB	www.sudsenviron.com

DRAFT - VERIFY BEFORE ISSUE

No official RHINO GT data sheet or general arrangement drawing is held in the SuDS Enviro drawing pack. Figures are taken from the configurator product data and the official product photographs. Confirm the Midi rating and the connection sizes before issue.