AnoDe: A Reproducible Benchmark and Deployable Platform for Visual Anomaly Detection in Manufacturing

Moh Hasbi Alfarizi*, Albertus Reinaldo Manibuy, Daffa Elgo Santosa,
Harun Yahya, Jeremy Christian Hutagalung
Department of Mathematics, Faculty of Mathematics and Natural Sciences, Universitas Gadjah Mada, Yogyakarta, Indonesia
*Corresponding author; responsible for the reproduction, benchmark and platform described here.

***Abstract*—Manual visual inspection does not scale with production volume and degrades with inspector fatigue. AnoDe is a platform that benchmarks unsupervised image anomaly detectors and deploys one per product family for quality inspection. This paper reproduces an earlier version of AnoDe, built as a university capstone, whose code was lost. We reimplemented six methods (seven configurations) and evaluated them on MVTec AD and MVTec LOCO AD under one protocol: a fixed split, decision thresholds set without test labels, pixel-level localisation metrics, and several seeds. The reproduction confirms the earlier ranking but corrects its report. Its best in-house model, called "Res2Net", was a feature autoencoder on ResNet-50 (0.980 image AUROC; 0.901 with an actual Res2Net backbone). Its accuracy and F1 were tuned on test labels. Its GLASS and CSAD scores (0.999 and 0.957) were the authors' released checkpoints. Both official training scripts keep the checkpoint with the best *test* score. Retraining both shows that this choice adds at most 0.002 AUROC on MVTec AD but 0.015 (GLASS) and 0.006 (CSAD) on LOCO, and up to 0.046 on logical anomalies. For deployment, the strongest benchmark model is not the most usable one: the released GLASS checkpoints leave no unseen normal images to calibrate a threshold and flag 33.5% of good parts. PatchCore, trained on our split, flags 10.1% while recalling 88.7% of defects. The deployed platform combines PatchCore (MVTec AD and user-defined products) and CSAD (LOCO) with heatmaps, P-charts and a yield-based capability index. Code, results and the live platform are public.**

***Index Terms*—anomaly detection, industrial inspection, reproducibility, statistical process control, MVTec AD, MVTec LOCO AD**

I. Introduction

Defect inspection at the end of a production line decides which units are shipped, reworked or scrapped. When humans inspect, errors grow with fatigue and volume [1]. Unsupervised image anomaly detection (IAD) needs only images of good parts for training, which suits factories where defects are rare and varied. Methods are compared on the MVTec AD benchmark [2], [3]. MVTec LOCO AD [4] adds *logical* anomalies, such as missing, extra or misplaced components, that are invisible to purely local detectors.

AnoDe began as a capstone project in which a team benchmarked several IAD methods and designed a web platform that picks a detector per product and reports the batch defect rate with statistical process control. The original notebooks and prototype were lost, and the report could not be re-checked. This paper rebuilds the project from scratch and makes every number reproducible. Our contributions are:

- A benchmark of six methods (seven configurations) on both MVTec datasets under one protocol, with label-free thresholds, AUPRO localisation, three seeds for trained models and per-image latency (Section III).
- An audit of the original report against the surviving notebooks and the released checkpoints (Section IV-B).
- A measurement of how much test-set checkpoint selection, built into the official GLASS and CSAD training scripts, inflates reported scores (Section IV-C).
- A deployment study: which models can be calibrated without test labels, how robust they are to JPEG compression, and how process capability should be read from anomaly scores. All of it is implemented in an open-source platform (Section V).

II. Related Work

Reconstruction. Autoencoders trained on normal images flag high reconstruction error [5], but they often reconstruct defects too. **Embedding methods** compare features of a pretrained network with those of normal images: globally (kNN), per patch in SPADE [6] and PaDiM [7], or with a coreset memory bank in PatchCore [8]. **Synthesis methods** train a discriminator on artificial anomalies: DRAEM [9], SimpleNet [10] and GLASS [11], which synthesises near-in-distribution anomalies by gradient ascent at the feature and image levels. **Logical anomaly detection** needs global reasoning. CSAD [12] segments components with pseudo-labels from foundation models and combines a patch histogram with a local–global student–teacher branch derived from EfficientAD [13]. Backbones used here are ResNet-50 [14], WideResNet-50 [15] and Res2Net-50 [16].

III. Experimental Setup

A. Datasets

MVTec AD has 5,354 images in 15 categories (5 textures, 10 objects), with pixel masks for every defect. MVTec LOCO AD has 5 categories with separate logical and structural test sets and an official validation split. The released archive

TABLE I
MODELS. "ORIG." NOTES DIFFERENCES FROM THE ORIGINAL NOTEBOOKS.

Model	Definition
AE (L2)	The original fully convolutional AE (3 conv + pool, 3 transposed conv), MSE loss, 100 epochs; score = image MSE. Orig.: warm-started from another category's checkpoint; here trained from scratch.
ResNet-50 + kNN	Global-pooled ResNet-50 features, the 500 highest-variance dimensions, mean distance to the k=50 nearest normal images (as in the notebook).
Feature AE	The report's "Res2Net": layer2+layer3 features (3×3 aggregation, 1536 ch.) reconstructed by a 1×1-conv AE (latent 100), 50 epochs; score = mean of the 10 largest errors. Orig.: ResNet-50 backbone, which we keep; we add the Res2Net-50 variant the report names.
PatchCore	WideResNet-50 layer2+3, 10% greedy coreset, b=9 re-weighting [8]. Orig.: ResNet-50 with a random subsample.
GLASS	Official code [11]; released checkpoints, plus our training (Sec. IV-C).
CSAD	Official code [12]; released LOCO checkpoints, plus our training (Sec. IV-C).

contains 3,651 images. Its *splicing connectors* category has 360 training and 60 validation images, where the paper's table lists 354 and 59 (3,644 in total). Before any experiment, a script checks every split's image and mask count. Since the official download links returned HTTP 404 at the time of writing, the datasets were taken from Kaggle copies that pass this check.

B. Models

Table I defines each model. Where an original notebook survives, we follow it and change only what was methodologically wrong. Where the report cites a published method, we implement that method.

C. Protocol

All our models see the image resized to 256×256 without cropping (the official GLASS and CSAD code keeps its own preprocessing). For MVTec AD, 10% of the normal training images are held out with a fixed seed. LOCO uses its official validation split. The decision threshold is

$$\tau = \mu_{\text{val}} + 3\,\sigma_{\text{val}}, \tag{1}$$

computed from the anomaly scores of the held-out normal images, the same 3σ rule as a Shewhart chart. Test labels are never used to choose a threshold, an epoch or a hyperparameter. We report image AUROC; pixel AUROC and AUPRO up to 30% FPR [3] on MVTec AD; logical and structural AUROC (and their mean) on LOCO; F1 at τ; and per-image latency at batch size 1 after warm-up on a Kaggle NVIDIA T4. The threshold-free F1-max is kept only as an optimistic reference. Trained models run three seeds and are reported as mean ± std. The metrics are unit-tested, and AUPRO agrees with a brute-force threshold sweep to within 3×10^{-4}.

TABLE II
MVTEC AD, MEAN OVER 15 CATEGORIES. F1 USES THE LABEL-FREE THRESHOLD τ; MS = PER-IMAGE LATENCY (T4).

Model	I-AUROC	P-AUROC	AUPRO	F1@τ	ms
AE (L2)	0.606±.001	0.751	0.509	0.152	7.9
ResNet-50 + kNN	0.802	–	–	0.515	7.7
Feature AE (ResNet-50)	0.980±.000	0.976	0.918	**0.931**	7.7
Feature AE (Res2Net-50)	0.901±.016	0.970	0.890	0.739	11.8
PatchCore	0.982	0.982	0.928	0.915	33.6
GLASS, released	**0.999**	**0.993**	**0.969**	n/a	31.9

TABLE III
MVTEC LOCO AD, MEAN OVER 5 CATEGORIES (IMAGE AUROC).

Model	Logical	Structural	Mean	F1@τ
AE (L2)	0.587	0.738	0.662±.005	0.189
ResNet-50 + kNN	0.747	0.717	0.732	0.376
Feature AE (ResNet-50)	0.749	0.886	0.817±.002	0.592
Feature AE (Res2Net-50)	0.737	0.771	0.754±.033	0.382
PatchCore	0.786	0.857	0.822	0.490
GLASS, ours (50 ep., last)	0.713	0.913	0.813	0.530
CSAD, ours (12k it., last)	0.945	0.913	0.929	**0.816**
CSAD, released	**0.977**	**0.937**	**0.957**	0.802

IV. RESULTS

A. Detection and localisation

Fig. 1 and Tables II–III summarise the benchmark. Per-category results are in Table V and the repository. On MVTec AD the embedding methods are close: PatchCore reaches 0.982 image AUROC. Roth et al. report 0.991 with a 224 px center crop that removes background [8], so our implementation is consistent. The feature autoencoder reaches 0.980 and the best F1 at the label-free threshold (0.931). The released GLASS checkpoints lead on every metric. The plain autoencoder reconstructs many defects and ranks near chance on several categories. ResNet-50 + kNN, which uses one global vector per image, misses small defects (grid 0.334).

On LOCO, every model without explicit component reasoning stays below 0.79 logical AUROC, while CSAD reaches 0.977 (0.945 when we train it with a fifth of the official schedule). For structural anomalies the gap is smaller: GLASS and CSAD trained by us both reach 0.913, against 0.937 for the released CSAD. The ranking supports the original report's design, which assigns a component-aware model to logical constraints.

B. Audit of the original report

Table IV compares the report with our runs. Where the report's numbers came from the team's own models, ours agree in ranking and roughly in level. The autoencoder in particular reproduces the per-category pattern (e.g. wood 0.94 vs 0.94, metal nut 0.30 vs 0.32). Five issues explain the remaining differences:

1) The "Res2Net" model used a ResNet-50 backbone. A real Res2Net-50 backbone does worse (0.901) and varies more between seeds (grid 0.82±0.20).




Fig. 1. Image AUROC, mean over categories. Left: MVTec AD. Right: MVTec LOCO AD, split into logical (orange) and structural (blue) anomalies. Released checkpoints were selected on the test set by their authors.

TABLE IV
ORIGINAL REPORT VS. THIS REPRODUCTION (MEAN IMAGE AUROC).

Model	Report	Ours	Note
AE (L2)	0.663	0.606	no warm start
ResNet-50 + kNN	0.739	0.802	ImageNet normalisation
"Res2Net" (feature AE)	0.972	0.980	ResNet-50 backbone
PatchCore	0.959	0.982	published method
GLASS	0.999	0.999	released ckpt.
CSAD (LOCO)	0.957	0.957	released ckpt.

2) Accuracy and F1 used thresholds tuned on test labels (F1-optimal on the test set). This explains F1 ≈ 0.97 in the report against 0.93 at a label-free threshold.
3) GLASS (0.999) and CSAD (0.957) match the authors' released checkpoints to four decimals. The team did not train these models.
4) Two table rows are duplicated: PatchCore's *pill* row equals the feature AE's, and the autoencoder's *zipper* F1 and runtime equal ResNet-50 + kNN's.
5) The runtime column mixes training time (AE, feature AE) with test time (kNN, PatchCore), without units or hardware.

C. Test-set checkpoint selection

The official GLASS script evaluates on the test set after every epoch and keeps the epoch with the highest image plus pixel AUROC. CSAD's scripts do the same every 2 segmentor epochs and every 1,000 iterations of its student–teacher (LGST) branch. The released GLASS checkpoints record their epoch: of 640 epochs, metal nut stops at 5, transistor at 52, capsule at 56, and wood at 637. To measure the effect, we trained GLASS with the official code on all LOCO categories and on zipper, wood and transistor. We used 50 epochs instead of 640, since a T4 needs about 100 s per epoch. We logged the official test evaluation every five epochs for analysis only. The last epoch is our reported model. On MVTec AD the two agree within 0.002 (0.995 vs 0.996). On LOCO,




Fig. 2. LOCO, one seed: AUROC of the checkpoint the official scripts pick on the test set, minus that of the last checkpoint, for our GLASS (left) and CSAD (right) training.

selection adds 0.015 mean AUROC and 0.046 logical AUROC, with +0.10 on pushpins (Fig. 2). Because the criterion mixes image and pixel scores, it also trades structural performance away on pushpins and screw bag.

We trained CSAD the same way: the segmentor for its full 120 epochs, and the LGST for 12,000 of 60,000 iterations, since a T4 runs 1.2 iterations/s (about 14 h per category for the full schedule). We logged the test evaluation every 10 epochs and 2,000 iterations. Selecting each stage on the test set adds 0.006 mean AUROC (logical +0.008, structural +0.005), less than for GLASS. For three of five categories the best LGST iteration is the last. Selection does not help calibration: F1 at τ drops from 0.816 to 0.657. Under the selected states, one juice-bottle validation image scores far above the rest and inflates σ. Our last-state CSAD stays 0.028 below the released checkpoints (0.929 vs 0.957). That gap mixes a five times longer schedule with selection every 1,000 iterations. Released scores of both methods are therefore upper bounds, and the optimism matters most on LOCO.

V. Deployment

A. Platform

AnoDe is a FastAPI service with a React interface that runs on a CPU (a Docker image is provided). The public demo on Hugging Face Spaces is a static build: the deployed models were run once on every sample image, and the quality control computations run in the browser, because free Spaces no longer host Docker containers. A user picks a product, inspects images (upload, camera or a simulated line), sees a heatmap and segmentation per unit (Fig. 3), and closes the batch. Batches feed a quality report. Users can add products of their own from 10–100 images of good parts: PatchCore needs no training loop, so its memory bank is built on the server in minutes, and 20% of the images are held out to set τ.

B. Which model can be deployed?

A deployed detector needs a threshold, and a label-free threshold needs normal images the model has not seen. Models trained on our split have them. The released GLASS checkpoints were trained on every normal training image, and they score new normal images much higher than their own training images. With τ computed on images they were trained on, they flag 33.5% of good test parts. Their discriminator's natural 0.5 cut-off flags 31.7%. PatchCore flags 10.1% and recalls 88.7% of defects, and the feature AE flags 7.2% and recalls 90.5% (Fig. 4). The platform therefore deploys PatchCore for MVTec AD products. For LOCO it deploys the released CSAD checkpoints, which never train on the official validation split (1.8% false alarms). CPU latency on an Apple M1 is about 180 ms per image for PatchCore and 400 ms for CSAD.

C. Robustness to image compression

Cameras and browsers often deliver JPEG. On two good *juice bottle* images, our CPU runtime reproduces the official CSAD scores on the original PNGs (0.72 and −0.22 times τ; official 0.51 and −0.20). Saving the same images as JPEG at quality 90 moves them to 1.93 and 0.98 at full resolution, and to 3.17 and 1.36 at 512 px: false alarms. Resizing to 512 px as PNG does not (0.49 and 0.19). PatchCore classified all 12 *bottle* samples correctly from JPEG. The platform stores samples as PNG and captures camera frames losslessly. Compression robustness should be part of IAD evaluation.

D. Statistical process control

Each closed batch adds a point to a P-chart of the defective fraction. Its limits $\bar{p} \pm 3\sqrt{\bar{p}(1-\bar{p})/n_i}$ depend on the batch size n_i [17]. Process capability is read from the continuous score s/τ against the upper specification limit USL = 1:

$$C_{pk} = \frac{\mathrm{USL} - \mu}{3\sigma}, \qquad C_{pk}^{\mathrm{yield}} = \frac{\Phi^{-1}(1-p)}{3}, \tag{2}$$

where p is the fraction above the USL. A batch that mixes good and defective parts has a bimodal score distribution, which inflates σ. For 25 simulated batches drawn from real *bottle* test scores (Fig. 5), the normal-theory index is 0.31, while the yield-based index, which is consistent with the observed 3.2% defect rate, is 0.62. The report shows both and flags the one out-of-control batch, which carries a fourfold defect rate.

VI. Limitations

GLASS and CSAD were retrained with short schedules (50 of 640 epochs; 12,000 of 60,000 LGST iterations) and one seed, so their gap to the released checkpoints mixes schedule length with test-set selection. Validation sets contain 6 (toothbrush) to 69 (pushpins) normal images, so thresholds and false-alarm rates vary between categories. Latency was measured on a T4 and on a laptop CPU, not on factory hardware. Finally, MVTec images are well lit and aligned, and real lines will need their own normal images, which the custom-product workflow is designed for.

VII. Conclusion

Rebuilding AnoDe from its report confirmed its main design: a strong local detector for surface defects and a component-aware model for logical constraints. It also corrected the report's model description, threshold practice and provenance of results. Two lessons apply beyond this project. Scores from checkpoints selected on the test set should be reported as upper bounds, and the gap is largest on logical anomalies. A model is deployable only if its threshold can be calibrated without test labels, which ranks PatchCore above a higher-scoring released GLASS checkpoint in practice. Code, per-run results, the model bundle and the live platform are public.

Acknowledgment

Experiments ran on free Kaggle GPUs. We thank the authors of GLASS and CSAD for releasing their code and checkpoints, and MVTec Software GmbH for the datasets (CC BY-NC-SA 4.0).

Availability

Code and results: https://github.com/Peanut2Butter9/anode.
Platform: https://huggingface.co/spaces/peanut2butter9/anode.
Models: https://huggingface.co/peanut2butter9/anode-models.

References

[1] J. Liu, G. Xie, J. Wang, S. Li, C. Wang, F. Zheng, and Y. Jin, "Deep industrial image anomaly detection: A survey," *Machine Intelligence Research*, vol. 21, pp. 104–135, 2024.

[2] P. Bergmann, M. Fauser, D. Sattlegger, and C. Steger, "MVTec AD – A comprehensive real-world dataset for unsupervised anomaly detection," in *Proc. CVPR*, 2019, pp. 9592–9600.

[3] P. Bergmann, K. Batzner, M. Fauser, D. Sattlegger, and C. Steger, "The MVTec anomaly detection dataset: A comprehensive real-world dataset for unsupervised anomaly detection," *Int. J. Comput. Vis.*, vol. 129, no. 4, pp. 1038–1059, 2021.

[4] P. Bergmann, K. Batzner, M. Fauser, D. Sattlegger, and C. Steger, "Beyond dents and scratches: Logical constraints in unsupervised anomaly detection and localization," *Int. J. Comput. Vis.*, vol. 130, pp. 947–969, 2022.

[5] P. Bergmann, S. Löwe, M. Fauser, D. Sattlegger, and C. Steger, "Improving unsupervised defect segmentation by applying structural similarity to autoencoders," in *Proc. VISAPP*, 2019, pp. 372–380.




Fig. 3. Deployed PatchCore on MVTec AD test images, as shown by the platform. Scores are given relative to the product's threshold τ; colour saturates at 2τ, and areas below 0.7τ are left uncoloured.




Fig. 4. MVTec AD at the label-free threshold τ: false alarms on good parts vs. recall on defects. Released GLASS uses τ from images it was trained on.

[6] N. Cohen and Y. Hoshen, "Sub-image anomaly detection with deep pyramid correspondences," arXiv:2005.02357, 2020.

[7] T. Defard, A. Setkov, A. Loesch, and R. Audigier, "PaDiM: A patch distribution modeling framework for anomaly detection and localization," in *Proc. ICPR Workshops*, 2021, pp. 475–489.

[8] K. Roth, L. Pemula, J. Zepeda, B. Schölkopf, T. Brox, and P. Gehler, "Towards total recall in industrial anomaly detection," in *Proc. CVPR*, 2022, pp. 14318–14328.

[9] V. Zavrtanik, M. Kristan, and D. Skočaj, "DRAEM – A discriminatively trained reconstruction embedding for surface anomaly detection," in *Proc. ICCV*, 2021, pp. 8330–8339.

[10] Z. Liu, Y. Zhou, Y. Xu, and Z. Wang, "SimpleNet: A simple network for image anomaly detection and localization," in *Proc. CVPR*, 2023, pp. 20402–20411.

[11] Q. Chen, H. Luo, C. Lv, and Z. Zhang, "A unified anomaly synthesis strategy with gradient ascent for industrial anomaly detection and localization," in *Proc. ECCV*, 2024.

[12] Y.-H. Hsieh and S.-H. Lai, "CSAD: Unsupervised component segmentation for logical anomaly detection," in *Proc. BMVC*, 2024.

[13] K. Batzner, L. Heckler, and R. König, "EfficientAD: Accurate visual anomaly detection at millisecond-level latencies," in *Proc. WACV*, 2024, pp. 128–138.

[14] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. CVPR*, 2016, pp. 770–778.

[15] S. Zagoruyko and N. Komodakis, "Wide residual networks," in *Proc. BMVC*, 2016.

[16] S.-H. Gao, M.-M. Cheng, K. Zhao, X.-Y. Zhang, M.-H. Yang, and P. Torr, "Res2Net: A new multi-scale backbone architecture," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 43, no. 2, pp. 652–662, 2021.

[17] D. C. Montgomery, *Introduction to Statistical Quality Control*, 8th ed. Hoboken, NJ, USA: Wiley, 2019.

Appendix




Fig. 5. Quality report for a simulated bottle line (2,987 units scored by the deployed PatchCore). Left: P-chart with batch-size-dependent limits and one out-of-control batch. Right: score distribution (log scale) against USL = τ.

TABLE V
IMAGE AUROC PER CATEGORY. MVTEC AD (TOP) AND LOCO, MEAN OF LOGICAL AND STRUCTURAL (BOTTOM). FAE = FEATURE AUTOENCODER.

Category	AE	kNN	FAE-R50	FAE-R2N	PatchCore	GLASS†	CSAD*	CSAD†
bottle	.727	.974	1.00	.997	1.00	1.00		
cable	.488	.799	.983	.917	.993	.998		
capsule	.647	.816	.961	.825	.973	.999		
carpet	.371	.703	.981	.979	.988	.998		
grid	.878	.334	.982	.820	.987	1.00		
hazelnut	.910	.902	1.00	.860	1.00	1.00		
leather	.408	.870	1.00	1.00	1.00	1.00		
metal nut	.295	.813	1.00	.990	.998	1.00		
pill	.598	.720	.957	.902	.954	.993		
screw	.705	.591	.922	.461	.937	1.00		
tile	.775	.989	1.00	.999	1.00	1.00		
toothbrush	.567	.803	.961	.919	.928	1.00		
transistor	.473	.827	.964	.917	.999	.999		
wood	.941	.981	.994	.962	.990	.999		
zipper	.301	.910	.991	.959	.983	.999		
breakfast box	.623	.803	.848	.825	.818	.832*	.896	.928
juice bottle	.661	.868	.955	.937	.956	.961*	.926	.957
pushpins	.652	.652	.742	.727	.742	.724*	.942	.970
screw bag	.700	.581	.709	.651	.708	.755*	.945	.971
splicing conn.	.676	.757	.833	.630	.884	.793*	.934	.958

†released checkpoints.
*our training, last checkpoint (GLASS 50 epochs, CSAD 12k iterations).