

Devops-crm-project documentation

1. Project Overview

The devops-crm-project is a Twenty CRM application scaffolded using the Twenty Apps SDK. It is a Node.js/TypeScript project managed with Yarn 4 and connects to a local Twenty server running in Docker.

- package.json – Yarn 4 project and Twenty SDK dependencies
- .nvmrc – pins Node.js version to 24.5.0
- SETUP.md – original manual setup instructions
- src/ and public/ – application source code

2. Original Manual Setup Process

The original setup required running the following commands from the project root:

```
git clone https://github.com/PearlThoughts-Intern-DevOps/devops-crm-project.git
```

```
cd devops-crm-project
```

```
yarn install
```

```
yarn twenty docker:start
```

```
yarn twenty dev
```

After starting the application, open <http://localhost:2020> in a browser and use the development login credentials:

- Email: tim@apple.dev
- Password: tim@apple.dev

3. Automation Using setup_crm.py

To simplify the setup process and avoid using a shell script, I created setup_crm.py, a plain Python script using only the Python standard library. The script automates the complete local setup flow.

1. Check required tools

Checks node, yarn, and docker and prints their installed versions. It also compares the installed Node.js version with .nvmrc and gives a warning if they do not match.

2. Verify project directory

Checks that package.json exists and contains Twenty-related packages. This prevents the script from being run accidentally in an unrelated directory.

3. Install dependencies

Runs yarn install and stops with a clear error if the command fails.

4. Start Twenty server

Runs `yarn twenty docker:start` and then runs `yarn twenty docker:status` to report the Docker/Twenty server status.

5. Check port 2020

Checks whether port 2020 is already in use and warns the user before starting the development server.

6. Start development server

Runs `yarn twenty dev` in the foreground and displays the local application URL and development login credentials.

4. Error Handling

All external commands are executed through a common `run()` wrapper. The wrapper checks the actual exit code of each command. If a command fails, the script stops and displays a clear error message instead of continuing silently.

5. How to Run the Automation

Run the following command from the project root, where `setup_crm.py` and `package.json` are located:

```
python setup_crm.py
```

6. Issues Faced and Solutions

Issue	Cause	Solution
Yarn command not found	Yarn 4 was not available by default or an outdated Yarn installation was present.	Enable Corepack and activate the required Yarn version: <code>corepack enable && corepack prepare yarn@4.13.0 --activate</code>
Docker command not found / Docker unavailable	Docker Desktop was not installed or was not running.	Install Docker Desktop and make sure Docker is running before executing <code>yarn twenty docker:start</code> .
Node.js version mismatch	The installed Node.js version did not match the version specified in <code>.nvmrc</code> (24.5.0).	Install and use Node.js 24.5.0 with nvm: <code>nvm install 24.5.0 && nvm use 24.5.0</code> .
Port 2020 already in use	A previous Twenty development server was still running or another application was using port 2020.	Stop the old process or check the Twenty Docker status, then run the setup again.

7. Git Workflow

```
cd devops-crm-project
```

```
git checkout -b <your-name>
```

```
git add setup_crm.py CRM_TASK_DOCS.md
```

```
git commit -m "Add Python automation script for local setup and startup"
```

```
git push -u origin <your-name>
```

After pushing the branch, create a Pull Request in the same repository (PearlThoughts-Intern-DevOps/devops-crm-project) and compare the feature branch against main.

8. Pull Request

Suggested title:

Automate local setup and startup with Python script

Suggested PR summary:

This PR adds setup_crm.py, a Python script that automates the local setup and startup process for the Twenty CRM app. It replaces the need to manually run yarn install, yarn twenty docker:start, and yarn twenty dev in sequence.

- Checks Node.js, Yarn, and Docker versions.
- Warns if the installed Node.js version differs from .nvmrc.
- Verifies that the script is being run from the correct project directory.
- Installs project dependencies using yarn install.
- Starts the local Twenty server using Docker.
- Reports Docker/Twenty status.
- Checks whether port 2020 is already in use.
- Starts the Twenty development server.
- Provides clear error handling for failed commands.