


Decorrelation Gap: KODIM23

768x512 | 24-bit RGB | PNG (lossless)

Parrot Close-up | Three-dimensional (PC1 = 70.3%)

5. Decorrelation Efficiency & Blue Independence




6. 4:2:0 Chroma Subsampling – Information Cost

Channel	PSNR (dB)
R	42.40 dB
G	48.10 dB
B	39.97 dB
Overall	42.37 dB


Method: BT.601 RGB→YCbCr | 2x box downsample Cb,Cr | nearest upsample | BT.601 inverse

7. PCA Baseline Reference (Baetzel 2026a)
Eigendecomposition



Eigenvector Loadings				
	R	G	B	Eigenvalue
PC1	-0.6100	-0.5732	-0.5472	6155.85
PC2	-0.7170	0.1051	0.6891	1784.85
PC3	0.3375	-0.8126	0.4751	815.24

8. PCA Derived Metrics



9. Redundancy Profile

Classification:	Three-dimensional CN: 7.55 PC1: 70.3%
RGB Correlation:	Avg r = 0.559545 R-G: 0.6147 R-B: 0.4231 G-B: 0.6408
YCbCr Residual:	Avg r = 0.196579 Y-Cb: -0.2343 Y-Cr: 0.0095 Cb-Cr: -0.3459
Efficiency:	64.9% of KLT ceiling Gap: 0.1966 avg r remaining
Blue Channel:	35.9% independent 4:2:0 PSNR: 42.37 dB

References

[1] Baetzel, J. (2026a). "Statistical Characterization of Inter-Channel Redundancy Structure"

[2] Wallace, G.K. "The JPEG still picture compression standard." IEEE Trans. CE 38(1), 1992.

[3] ITU-R Recommendation BT.601: Studio Encoding Parameters, 1982.

[4] Watanabe, S. "Karhunen-Loeve Expansion and Factor Analysis," pp. 635-660, 1965.