


# Numpy

Luis Pedro Coelho

Programming for Scientists

September 16, 2012






- Numeric (1995)
- Numarray (for large arrays)
- scipy.core (briefly, around 2005)
- numpy (2005)

# Currently



- numpy 1.6
- *de facto* standard
- very stable



`numpy.array` or `numpy.ndarray`.


Multi-dimensional array of numbers.

# numpy example




```
import numpy as np
A = np.array([
    [0,1,2],
    [2,3,4],
    [4,5,6],
    [6,7,8]])
print A[0,0]
print A[0,1]
print A[1,0]
```

# Some Array Properties




```
import numpy as np
A = np.array([
    [0,1,2],
    [2,3,4],
    [4,5,6],
    [6,7,8]])
print A.shape
print A.size
```

# Some Array Functions



```
...  
print A.max()  
print A.min()
```

- `max()`: maximum
- `min()`: minimum
- `ptp()`: spread ( $\text{max} - \text{min}$ )
- `sum()`: sum
- `std()`: standard deviation
- ...




- `np.exp`
- `np.sin`
- ...

All of these work **element-wise**!



# Arithmetic Operations



```
import numpy as np
A = np.array([0,1,2,3])
B = np.array([1,1,2,2])

print A + B
print A * B
print A / B
```



Mixing arrays of different dimensions


```
import numpy as np
A = np.array([
    [0,0,1],
    [1,1,2],
    [1,2,2],
    [3,2,2]
])
B = np.array([2,1,2])

print A + B
print A * B
```



Special case: scalar.

```
import numpy as np
A = np.arange(100)
print A + 2
A += 2
```




`numpy.ndarray` is a homogeneous array of numbers.

## Types

- Boolean
- `int8`, `int16`, ...
- `uint8`, `uint16`,...
- `float32`, `float64`,...
- ...


Some types are only available in some platforms (e.g., `float96`).

# Object Construction



```
import numpy as np
A = np.array([0,1,1], np.float32)
A = np.array([0,1,1], float)
A = np.array([0,1,1], bool)
```

# Reduction



```
A = np.array([
    [0,0,1],
    [1,2,3],
    [2,4,2],
    [1,0,1]])
print A.max(0)
print A.max(1)
print A.max()
```

prints

[2,4,3]

[1,3,4,1]

4


The same is true for many other functions.

# Slicing



```
import numpy as np
A = np.array([
    [0,1,2],
    [2,3,4],
    [4,5,6],
    [6,7,8]])
print A[0]
print A[0].shape
print A[1]
print A[:,2]
```


# Slices Share Memory!



```
import numpy as np
A = np.array([
    [0,1,2],
    [2,3,4],
    [4,5,6],
    [6,7,8]])
B = A[0]
B[0] = -1
print A[0,0]
```




# Pass is By Reference



```
def double(A):  
    A *= 2
```

```
A = np.arange(20)  
double(A)
```

# Pass is By Reference



```
def double(A):
```

```
    A *= 2
```

```
A = np.arange(20)
```

```
double(A)
```

```
A = np.arange(20)
```


```
B = A.copy()
```

# Logical Arrays




```
A = np.array([-1,0,1,2,-2,3,4,-2])  
print (A > 0)
```

# Logical Arrays II



```
A = np.array([-1,0,1,2,-2,3,4,-2])  
print ( (A > 0) & (A < 3) ).mean()
```


What does this do?




```
A[A < 0] = 0
```

or

```
A *= (A > 0)
```



```
print 'Mean of positives ', A[A > 0].mean()
```




## Constructing Arrays

```
A = np.zeros((10,10), dtype=np.int8)
B = np.ones(10)
C = np.arange(100).reshape((10,10))
...
```


## Multiple Dimensions

```
img = np.zeros((1024,1024,3), dtype=np.uint8)
```



<http://docs.scipy.org/doc/>





Matplotlib is a **plotting library** for Python.

```
import pylab
import numpy as np
X = np.linspace(-4,+4,1000)
pylab.plot(X,np.exp(-X**2))
pylab.xlabel(r '$x$ ')
pylab.ylabel(r '$\exp(-x^{\{2\}})$ ')
pylab.savefig('gaussian.pdf')
```

<http://matplotlib.sf.net/>

# Matplotlib Example

