

## **Linux capable RISC-V CPU for IOb-SoC**

**Pedro Nuno de Melo Antunes**

Thesis to obtain the Master of Science Degree in

### **Electrical and Computer Engineering**

Supervisor(s): Prof. José João Henriques Teixeira de Sousa

#### **Examination Committee**

Supervisor: Prof. José João Henriques Teixeira de Sousa

Member of the Committee: Prof. Horácio Cláudio De Campos Neto

**September 18, 2022**



# Abstract

Blablabla



# Honor Declaration

“Declaro por minha honra de que ”

Local, Date

Signature



# Contents

<b>List of Figures</b> . . . . .	<b>I</b>
<b>List of Tables</b> . . . . .	<b>III</b>
<b>Code Listing</b> . . . . .	<b>V</b>
<b>Acronyms</b> . . . . .	<b>VII</b>
<b>1 Introduction</b> . . . . .	<b>1</b>
1.1 Motivation . . . . .	1
1.2 Objectives . . . . .	1
<b>2 Must Have Concepts</b> . . . . .	<b>3</b>
2.1 The IOb-SoC Template . . . . .	3
2.1.1 Internal Buses . . . . .	3
2.1.2 How peripherals work . . . . .	3
2.2 Open Source Verification tools . . . . .	3
2.3 RISC-V architecture . . . . .	4
2.4 What is the UART16550? . . . . .	4
2.5 The Linux Boot Flow . . . . .	4
2.5.1 Bootloader firmware . . . . .	4
2.5.2 What is a device tree? . . . . .	4
2.6 Simulation . . . . .	4
<b>3 Existing Technologies</b> . . . . .	<b>5</b>
3.1 Closed source RISC-V Embedded Systems . . . . .	5
3.1.1 Andes Technology . . . . .	6
3.1.2 SiFive . . . . .	6
3.2 Open-Source Solutions . . . . .	7
3.2.1 CVA6 [19] . . . . .	7
3.2.2 The Berkeley Out-of-Order RISC-V Processor . . . . .	8
3.2.3 SpinalHDL . . . . .	8
<b>4 Hardware Developed</b> . . . . .	<b>9</b>
4.1 Simulation Unit Under Test Wrapper . . . . .	9
4.2 VexRiscv Wrapper . . . . .	9
4.3 UART16550 Wrapper . . . . .	9
4.4 CLINT Unit . . . . .	9
4.5 PLIC Unit Wrapper . . . . .	9

<b>5</b>	<b>Software Developed</b>	<b>11</b>
5.1	Python Console	11
5.2	Verilator Testbench	11
5.3	Barebones Interrupt Routine	11
5.4	IOb-SoC Linux Stage 0 Bootloader	11
5.5	IOb-SoC on OpenSBI	11
5.6	IOb-SoC Device Tree	11
5.7	IOb-SoC Linux <i>'rootfs'</i>	11
5.8	Makefiles	11
<b>6</b>	<b>Products of the expedition, AKA Project Results</b>	<b>13</b>
6.1	FPGA Resources Consumption	13
6.2	Run/Boot Linux Performance	13
<b>7</b>	<b>Contributed Repositories</b>	<b>15</b>
<b>8</b>	<b>Conclusions</b>	<b>17</b>
8.1	Achievements	17
8.2	Future Work	17
<b>A</b>	<b>Annex</b>	<b>VII</b>
A.1	Annex 1	VII
A.2	Annex 2	VII
	<b>Bibliography</b>	<b>IX</b>



## List of Figures



# List of Tables

3.1	CPU comparison table . . . . .	8
-----	--------------------------------	---



## Code Listing



# Acronyms

**CLINT** Core-local Interrupt Controller.

**CPU** Central Processing Unit.

**CSR** Control and status register.

**ISA** Instruction set architecture.

**M** Machine.

**PLIC** Platform-Level Interrupt Controller.

**S** Supervisor.

**SoC** System on a chip.

**U** User.





# **1 | Introduction**

## **1.1 Motivation**

## **1.2 Objectives**



## 2 | Must Have Concepts

During this chapter, we're going to discuss topics that help understand the technology developments made along the thesis project.

### 2.1 The IOB-SoC Template

#### 2.1.1 Internal Buses

#### 2.1.2 How peripherals work

### 2.2 Open Source Verification tools

For testing purposes, it is important to have a good hardware simulation environment. For that, we take advantage of already existing and well-developed tools. There exist a number of simulation tools, most of them are proprietary, as for example *'xcelium'* from *'Candence'*. Its utilization can increase the cost of a project significantly. In this Thesis we will make an effort of using open-source, free to use, verification tools. In specific, we will take advantage of *'Icarus Verilog'* and *'Verilator'*. Although both tools are for verification, they serve different purposes, due to their characteristics.

- ***'Icarus Verilog'*** is a Logic Simulator that uses verilog or system-verilog testbenches to test the UUT (Unit Under Test). Unfortunately, its support for system-verilog is limited and some designs might not run in this simulator. *'Icarus Verilog'* is also known as *'IVerilog'*.

After compiling the hardware design, *'IVerilog'* outputs a file which can be run line by line to simulate designed logic.

- ***'Verilator'***

**The biggest differences** are: *'Verilator'* only represents logic signal as 1's or 0's, contrary to *'IVerilog'* which also represents unknown values as X's; Since *'Verilator'* ends up being a C++ program it is much faster to run the simulation than with *'IVerilog'*; On another perspective *'Verilator'* is slower than *'IVerilog'* to interpret the hardware logic design. As such, it is easier to use *'IVerilog'* to detect errors on the design, but it is better to use *'Verilator'* for more complexed simulations.

## 2.3 RISC-V architecture

The RISC-V **CLINT** is described The RISC-V **PLIC** was first described in the privilege instructions documentation, but since version 1.10 it was moved to its own document.

## 2.4 What is the UART16550?

## 2.5 The Linux Boot Flow

### 2.5.1 Bootloader firmware

### 2.5.2 What is a device tree?

## 2.6 Simulation

<https://www.sifive.com/blog/risc-v-qemu-part-1-privileged-isa-hifive1-virtio>

## 3 | Existing Technologies

There already exists embedded microcontrollers capable of running Linux. Big companies as for example ARM, Qualcomm, MediaTek, Intel and AMD have created microcontroller capable of running Linux. But the processor architecture of those microcontrollers is not open-source, much less the microcontroller itself.

As an example, the *Raspberry Pi 4* is a very capable and cheap board where a developer can test and implement new software running in Linux. The Raspberry CPU is an *Cortex-A72* [1] witch is a System on Chip (SoC) developed by ARM on their ARMv8 64-bit CPU architecture. But if someone wanted to use the Raspberry as a base for his costume hardware design, that would be impossible. And thus appears the need for open-source hardware that allows creating something new without having to start from scratch every time. This led to the appearance of RISC-V the open-source CPU architecture.

### 3.1 Closed source RISC-V Embedded Systems

Since then, a few companies using RISC-V have appeared. RISC-V CPUs are already present in the automotive and IoT markets, besides AI chips in data centers. Due to the RISC-V ISA royalty free license new StartUps tend to look at RISC-V CPUs as a solution for their cores. Even if the CPU Core isn't free to use it ends up being a cheaper solution.

While creating new products companies proved how advantageous the RISC-V architecture was. Furthermore, they have contributed to open-source software, hardware and documentation. Some companies with a big recognitions involved with RISC-V technology are:

- *Western Digital* who now uses RISC-V in its external storage disks.
- *Microchip* as launched the first RISC-V-Based System-on-Chip (SoC) FPGA, *PolarFire*.
- *Antmicro/Microsemi* <sup>1</sup> have built a software called Renode that is used to develop, debug and test multi-node RISC-V device systems.
- *BeagleBoard.org*, *Seeed Studio* and *StarFive* worked together to build the first affordable RISC-V computer designed to run Linux, *BeagleV* [3]. The board is priced around 150€.

These companies have all helped pave the way for a full-feature Operating System based on the Linux kernel to be compatible with the RISC-V architecture. However, there are two companies that have a bigger impact on RISC-V CPU design, those are Andes Technology and SiFive.

---

<sup>1</sup>Microchip has acquired Microsemi Corporation in May 2018.

#### 3.1.1 Andes Technology

Andes Technology is one of the founder members of the RISC-V International. Since it is highly involved with RISC-V it ended up being one of the major contributor (and maintainer) of the RISC-V tool-chain. This is important because the RISC-V ISA is merely an instruction set architecture, there needs to exist complementing software, such as compiler and development tools.

Nowadays Andes CPU's are applied nearly everywhere, from telecommunications, storage controllers, touch screen sensors to data centers, etc. Andes Technologies has had incredible success using RISC-V technology, as prove they have shipped billions of embedded SoC with RISC-V processors based on their RISC-V ISA variant, AndeStar™ V5.

Andes CPUs witch are capable of running Linux are the *A25* [16] and *AX25* [17]. Both support single and double precision floating point, the RISC-V P-extension (draft) DSP/SIMD ISA and an MMU (Memory Management Unit) for Linux applications. Besides that both enable the use of Machine (M), User (U) and Supervisor (S) Privilege levels that allow running Linux and other advanced operating systems with protection between kernel and user programs. Furthermore, both have L1 instruction and data cache. The difference between them is that *A25* is based on 32-bit architecture and the *AX25* is 64-bit. This leads to the *AX25* being ideal for embedded applications that need to access address space over 4GB, and the *A25* being smaller in gate count. Both CPUs can be implemented on the *AE350* [15] SoC allowing to use these CPUs on developer boards, for example in the *ADP-XC7K160/410* [14].

#### 3.1.2 SiFive

SiFive is a company that was born from the RISC-V ISA. SiFive was founded by three researchers from the University of California Berkeley, Krste Asanović, Yunsup Lee, and Andrew Waterman. Those researchers were deeply involved with the development of the RISC-V ISA, from working on the base ISA to working on the floating point numbers and compressed instructions ISA extensions. It is no surprise that the first company to release a chip and development board that implemented the RISC-V ISA was SiFive. This happened in 2016 one year after the company was founded.

In 2017 SiFive launched *U54* [8] witch was the first RISC-V CPU capable of running a full fledged Operating System like Linux. With it they launched the *U54-MC* [9] SoC that had four *U54* 64-bit cores. Furthermore, the *U54-MC* implemented the initial CLINT and PLIC unit. The development of the CLINT and the PLIC made by SiFive would eventually lead to the documentation and specification of the respective hardware components with witch RISC-V systems must be compliant if they proclaim to use either one. One year after, in 2018, they launched *HiFive Unleashed* [6] witch was the first board that implemented the *U54* CPU and

run a Linux OS with a desktop environment (DE). The *HiFive Unleashed* has been discontinued and better hardware has been made available.

SiFive has since then extended their *U Cores* product lineup. All *U* cores are 64-bit application processors capable of running Linux. The highest performance core is the *U74* [10]. The core architecture is RV64GBC which means it supports the RISC-V I, M, A, F, D, B and C ISA extensions (explained in **\*ref section in previous chapter\***). This CPU has already been applied to multiple boards, for example, the *BeagleV* has a SoC with dual core SiFive *U74* CPU. SiFive has also launched its own development board, *HiFive Unmatched* [7], with four *U74* cores on the *U74-MC* [11] SoC. Furthermore, in 2021, Canonical the developers behind Ubuntu have announced the OS support for both the HiFive Unmatched and HiFive Unleashed.

## 3.2 Open-Source Solutions

Built upon the RISC-V open-source Instruction set architecture, various CPU designs have emerged. Some of them are fully open-source and might be implemented in other projects. Those CPUs were mostly developed by Universities research groups or by individuals with a grant.

RISC-V CPUs are most popular in simple systems. Consequently there exists a widely variety of open-source CPUs which are implemented on multiple embedded microcontrollers. A few examples of those CPUs would be the PicoRV32 [18], NEORV32 [13], DarkRISCV [4] and Ibex [5] from lowRISC. Those will not be discussed in detail on this paper since they do not meet the requirements to run the Linux Kernel. Those CPUs generally support Machine (M) level privilege mode and some also support Supervisor (S) mode. Moreover, none of the given examples support the Atomic RISC-V ISA extension. This extension is essential to run Linux.

To run a Linux based Operating System an application processor is needed. This means that the processor should have the required Control and status register (CSR), support M+S+U privilege modes and support atomic instructions. An open-source solution would be either the CVA6 [19] (previously known as Ariane), (BOOM [20]) or VexRiscv [12] from SpinalHDL.

### 3.2.1 CVA6

*OpenPiton* [2]

## 3.2.2 The Berkeley Out-of-Order RISC-V Processor

The Berkeley Out-of-Order RISC-V Processor (*BOOM* [20]) ... rocket-chip from CHIPS Alliance

## 3.2.3 SpinalHDL

VexRiscv and NaxRiscv Talk about litex-vexriscv!

	ARM	Andes Technology		SiFive		PULP platform	UC Berkeley	SpinalHDL	
	Cortex-A72	A25	AX25	U54	U74	CVA6	BOOM	VexRiscv	NaxRiscv
Architecture bit widths	64-bit	32-bit	64-bit	64-bit	64-bit	32/64-bit	64-bit	32-bit	64-bit
MMU	Y	Y	Y	Y	Y	Y	Y	Y	Y
FPU	Y	Y	Y	Y	Y	X	Y	X	Y
16-bit instructions	X	Y	Y	Y	Y	Y	Y	Y	X
Cache L1(I+D)	Y	Y	Y	Y	Y	Y	Y	Y	Y
Interrupt Controller	X	Y	Y	Y	Y	X	X	X	X
S+U+M Mode	N/A	Y	Y	Y	Y	Y	Y	Y	Y
GNU/Linux	Y	X	Y	Y	Y	Y	Y	X	Y
Open-Source	X	X	X	X	X	Y	Y	Y	Y

**Table 3.1:** CPU comparison table



## **4 | Hardware Developed**

### **4.1 Simulation Unit Under Test Wrapper**

### **4.2 VexRiscv Wrapper**

### **4.3 UART16550 Wrapper**

### **4.4 CLINT Unit**

### **4.5 PLIC Unit Wrapper**



## **5 | Software Developed**

### **5.1 Python Console**

### **5.2 Verilator Testbench**

### **5.3 Barebones Interrupt Routine**

### **5.4 IOb-SoC Linux Stage 0 Bootloader**

### **5.5 IOb-SoC on OpenSBI**

### **5.6 IOb-SoC Device Tree**

### **5.7 IOb-SoC Linux '*rootfs*'**

### **5.8 Makefiles**



## **6 | Products of the expedition, AKA Project Results**

### **6.1 FPGA Resources Consumption**

### **6.2 Run/Boot Linux Performance**



## 7 | Contributed Repositories

- **iob-soc**
- **iob-soc-vexriscv**
- **iob-lib**
- **iob-vexriscv**
- **iob-uart16550**
- **iob-clint**
- **iob-plic**





## **8 | Conclusions**

### **8.1 Achievements**

### **8.2 Future Work**



## **A | Annex**

### **A.1 Annex 1**

Annex 1

### **A.2 Annex 2**

Annex 2



# Bibliography

- [1] Arm Holdings (arm). *The Cortex-A72 processor specifications*. <<https://developer.arm.com/Processors/Cortex-A72>>.
- [2] Jonathan Balkind et al. "OpenPiton: An Open Source Manycore Research Framework". In: *Proceedings of the Twenty-First International Conference on Architectural Support for Programming Languages and Operating Systems*. ASPLOS '16. Atlanta, Georgia, USA: ACM, 2016, pp. 217–232. ISBN: 978-1-4503-4091-5. DOI: 10.1145/2872362.2872414. <<http://doi.acm.org/10.1145/2872362.2872414>>.
- [3] Seeed Studio BeagleBoard.org and StarFive. *BeagleV, The First Affordable RISC-V Computer Designed to Run Linux*. <<https://beagleboard.org/static/beagleV/beagleV.html>>.
- [4] darklife. *DarkRISCV*. <<https://github.com/darklife/darkriscv>>.
- [5] lowRISC. *Ibex RISC-V Core*. <<https://github.com/lowRISC/ibex>>.
- [6] SiFive. *HiFive Unleashed*. <<https://www.sifive.com/boards/hifive-unleashed>>.
- [7] SiFive. *HiFive Unmatched*. <<https://www.sifive.com/boards/hifive-unmatched>>.
- [8] SiFive. *U54*. <<https://www.sifive.com/cores/u54>>.
- [9] SiFive. *U54-MC*. <<https://www.sifive.com/cores/u54-mc>>.
- [10] SiFive. *U74*. <<https://www.sifive.com/cores/u74>>.
- [11] SiFive. *U74-MC*. <<https://www.sifive.com/cores/u74-mc>>.
- [12] SpinalHDL. *VexRiscv*. <<https://github.com/SpinalHDL/VexRiscv>>.
- [13] stnolting. *The NEORV32 RISC-V Processor*. <<https://github.com/stnolting/neorv32>>.
- [14] Andes Technology. *ADP-XC7K160/410, FPGA Based Development Platform*. <<http://www.andestech.com/en/products-solutions/andeshape-platforms/adp-xc7k160-410/>>.
- [15] Andes Technology. *AE350 Platform*. <<http://www.andestech.com/en/products-solutions/andeshape-platforms/ae350-axi-based-platform-pre-integrated-with-n25f-nx25f-a25-ax25/>>.
- [16] Andes Technology. *AndesCore™ A25, Compact High-Speed 32-bit CPU for Real-time and Linux Applications*. <<http://www.andestech.com/tw/%E7%94%A2%E5%93%81%E8%88%87%E8%A7%A3%E6%B1%BA%E6%96%B9%E6%A1%88/andescore-processors/riscv-a25/>>.
- [17] Andes Technology. *AndesCore™ AX25, Compact High-Speed 64-bit CPU for Real-time and Linux Applications*. <<http://www.andestech.com/tw/%E7%94%A2%E5%93%81%E8%88%87%E8%A7%A3%E6%B1%BA%E6%96%B9%E6%A1%88/andescore-processors/riscv-ax25/>>.

## *Bibliography*

- [18] YosysHQ. *PicoRV32 - A Size-Optimized RISC-V CPU*. 2015. <<https://github.com/YosysHQ/picorv32>>.
- [19] F. Zaruba and L. Benini. “The Cost of Application-Class Processing: Energy and Performance Analysis of a Linux-Ready 1.7-GHz 64-Bit RISC-V Core in 22-nm FDSOI Technology”. In: *IEEE Transactions on Very Large Scale Integration (VLSI) Systems* 27.11 (Oct. 2019), pp. 2629–2640. ISSN: 1557-9999. DOI: 10.1109/TVLSI.2019.2926114.
- [20] Jerry Zhao et al. “SonicBOOM: The 3rd Generation Berkeley Out-of-Order Machine”. In: (May 2020).