Practical Assignment II (KAFKA)

1 Introduction

The practical assignment II is focused on using Apache Kafka's Quality Attributes.

2 Description

The project is about a simulation of processing data from sensors in a Kafka cluster. There will be several Use Cases and for each one a solution must be built.

The file sensor.txt contains all the data collected from several sensors. The format is as follows:

XXXXX -> string containing the sensor ID

ZZZ.ZZ -> real number containing a temperature in °C.

YYYYYY -> integer time stamp

The data is ordered by its timestamp.

3 Use Cases (UC)

General Requirements

- A Kafka Cluster, beyond Zookeeper, includes:
 - 1 to maximum 6 Brokers
 - o 1 Topic named as Sensor
 - o 1 to maximum 6 Partitions
 - o 1 to maximum 3 replicas with. You must choose the advisable value of min.insync.replicas
- Beyond the Kafka Cluster (Brokers and Zookeeper) there are at least three additional processes:
 - o PSOURCE:
 - responsible for reading sensor data (records) from the file sensor.txt and sending it to PProducer according to the requirements of each
 UC
 - there can be only one Thread responsible for reading the data from sensor.txt
 - there must be one Thread sending data for each Kafka Producer
 - Mandatory:
 - data sent to PProducer relies on Java Sockets.
 - all Java Threads must run inside the process PSource
 - PSource contains one process only: PSource.java

O PPRODUCER:

- responsible for receiving records from PSOURCE and sending them to a Kafka Cluster according to the requirements of each UC
- may include one or more Kafka Producers
- each Kafka Producer must be implemented as a Java Thread
- data received from PSource relies on Java Sockets
- PProducer plays the role of a server and provides one server socket only.
- all Java Threads must run inside the process PProducer
- PProducer contains one process only: PProducer.java
- one GUI by Kafka Producer
- at least, each GUI must provide:
 - all the records received from PSOURCE
 - total number of records received
 - total number of records received by sensor ID

PCONSUMER:

- responsible for reading records from the Kafka Cluster and to process them according to the requirements of each UC
- may include one or more Kafka Consumers
- may include one or more Group Consumers
- one GUI by Kafka Consumer and/or by Group Consumer
- each Kafka Consumer must be implemented as Java Thread
- all Java Threads must run inside the process PConsumer
- PConsumer contains one process only: PConsumer.java
- at least, each GUI must provide:
 - all the records received from the Kafka Cluster
 - total number of records received
 - total number of records received by sensor ID
- Each Use Case must be implemented in a way it can be demonstrated separately from the remaining UCs
- Create one Java project only (PA2_GXX, XX is your group id) and for each UC:
 - o create one Package named as UCn (n is the UC id)
 - 3 processes: PSOURCE, PPRODUCER and PCONSUMER
 - o Scripts to launch the Kafka Cluster
- Whenever necessary, concurrency must be used to improve performance
- In each Kafka Producer class and in each Kafka Consumer class it is mandatory to instantiate a Java Properties object and set into it <u>all</u> the required properties
- If a property (from a Kafka Producer or Kafka Consumer) is important you must set its value explicitly even if you intend to use the default value
- You cannot use: idempotence property and Kafka Transactions.
- The solution for each UC must be considered the optimal one

- You must use the KAFKA libraries published in the e-learning platform
- You cannot use MAVEN

UC_1

PSOURCE:

Role: records are read from sensor.txt and sent to PPRODUCER such a way an optimal solution can be implemented

PPRODUCER:

Role: records are displayed and sent to the Kafka Cluster
Performance: default: do not forget to set the default values explicitly

Data ordering: PCONSUMER needs to receive and process the records in their original order as in sensor.txt

Data loss: records can be lost
Constraints: one Kafka Producer only

PCONSUMER:

Role: records are read from the Kafka Cluster and displayed

Data ordering: check if records keep their original order

Data duplication: any

Constraints: one Kafka Producer only

UC_2

PSOURCE:

Role: records are read from sensor.txt and sent to PPRODUCER such a way an optimal solution can be implemented

PPRODUCER:

Role: records are displayed and sent to the Kafka Cluster

Performance: minimize latency

Data ordering: PCONSUMER needs to receive and process records by sensor ID and then ordered as in sensor.txt

Data loss: some records can be lost, but minimize the possibility of losing all records of a sensor ID

Constraints: 6 Kafka Producers

PCONSUMER:

Role: records are read from the Kafka Cluster and displayed

Data ordering: each Kafka Consumer must check if records are of one sensor ID only and if they keep their relative original order as in sensor.txt

Data duplication: records can be reprocessed

Constraints: 6 Kafka Consumers

UC_3

SOURCE:

Role: records are read from sensor.txt and sent to PPRODUCER such a way an optimal solution can be implemented

PPRODUCER:

Role: records are displayed and sent to the Kafka Cluster

Performance: maximum throughput

Data ordering: records can be reordered

Data loss: minimize the possibility of losing records but while minimizing the impact on the overall performance

Constraints: 3 Kafka Producers

PCONSUMER:

Role: records are read from the Kafka Cluster and displayed

Data duplication: records can be reprocessed but try to avoid some degree of reprocessing

Constraints: 1 Consumer Group with 3 Kafka Consumers

UC_4

SOURCE:

Role: records are read from sensor.txt and sent to PPRODUCER such a way an optimal solution can be implemented

PPRODUCER:

Role: records are displayed and sent to the Kafka Cluster

Performance: any

Data ordering: records cannot be reordered

Data loss: minimize the possibility of losing records

Constraints: 6 Kafka Producers

PCONSUMER:

Role: records are read from the Kafka Cluster and displayed

Constraints:

UC_5

SOURCE:

Role: records are read from sensor.txt and sent to PPRODUCER such a way an optimal solution can be implemented

PPRODUCER:

Role: records are displayed and sent to the Kafka Cluster

Constraints: 6 partitions

PCONSUMER:

Role: records are read from the Kafka Cluster and the maximum and minimum temperatures are displayed and computed following

the Voting Replication tactic

Data reprocessing: records can be reprocessed

Constraints: 3 Group Consumers each with 3 Consumers

UC_6

SOURCE:

Role: records are read from sensor.txt and sent to PPRODUCER such a way an optimal solution can be implemented

PPRODUCER:

Role: records are displayed and sent to the Kafka Cluster

Constraints: 6 partitions

PCONSUMER:

Role: records are read from the Kafka Cluster by a Consumer Group with 3 Consumers

the average temperature is displayed and computed following the Voting Replication tactic

Data reprocessing: minimize the possibility of reprocessing records in case a Kafka Consumer crashes

4 Assignment Submission

• Project and folder root name must be: PA2_GXX, where XX is your group number;

Each project must be compressed with 7zip and sent to omp@ua.pt till 2021 May 16 09:00;

- Do not send Kafka libraries but send any additional library required to run your project;
- Report (PDF):
 - o For each UC:
 - what is implemented and working correctly
 - what is not implemented or not working correctely
- Assessment Rules for Grading:
 - Each UC 3 points 3 x 6 = 18 points;
 - Java Doc 1 point
 - Report 1 point