

Crear instancia utilizando un script.

Ejecutar Instancia

Detalles *

Origen

Sabor *

Redes

Puertos de red

Grupos de Seguridad

Par de Claves

Configuración

Grupo de servidores

Sugerencias de planificación

Metadatos

Puede personalizar la instancia después de lanzarla con las opciones disponibles aquí. "Script personalizado" es análogo a "User Data" en otros sistemas.

Cargar Script personalizado desde un fichero

Seleccionar archivo Ninguno archivo selec.

Script personalizado (Modificado)

Tamaño del contenido: 483 bytes de 16.00 KB

```
# instalacion de servidor de bases de datos
apt-get update
apt-get install -y mariadb-server
sed -i "s/. *bind-address.*/bind-address = 0.0.0.0/" /etc/mysql/mariadb.conf.d/50-server.cnf
sudo mariadb -e "GRANT ALL PRIVILEGES ON *.* TO 'xuwira31'@'%
IDENTIFIED BY '208060';"
systemctl restart mariadb.service
```

Partición de Disco

Automático

☐ Unidad de configuración

✕ Cancelar

< Anterior

Siguiente >

Ejecutar Instancia

Conectarme a mi MariaDB.

```
cesgaxuser@proba-mera-mariadb:~$ mariadb -uxuwira31 -p208060
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 35
Server version: 10.6.12-MariaDB-0ubuntu0.22.04.1 Ubuntu 22.04

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> use empleados;
Database changed
```

Conectarme al MariaDB de Pana.

```
cesgaxuser@proba-mera-mariadb:~$ mariadb -uxuwira37 -pabc123 -h10.133.28.204
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 36
Server version: 10.6.12-MariaDB-0ubuntu0.22.04.1 Ubuntu 22.04

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> show databases;
+-----+
| Database |
+-----+
| empresa |
| information_schema |
| mysql |
| performance_schema |
| sys |
| world |
+-----+
```

Insertar un nuevo empleado en su base de datos.

```
MariaDB [empresa]> insert into empleados values (5, 'Pedro', 'Mera', 'Jefe (De verdad)', 99999999, '2022-01-02');
Query OK, 1 row affected (0.011 sec)
```

Crear una base de datos en el MariaDB de Dani

```
cesgaxuser@proba-mera-mariadb:~$ mariadb -uxuwira -p1234abc. -h10.133.27.205
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 60
Server version: 10.3.38-MariaDB-0ubuntu0.20.04.1 Ubuntu 20.04

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> create database PEDROMERA;
Query OK, 1 row affected (0.002 sec)

MariaDB [(none)]> use PEDROMERA
Database changed
MariaDB [PEDROMERA]>
```