

## Some cool title

Aaron A. Gauthier, Avijeet Kartikay and Pedro Uria Rodriguez

Machine Learning II

GWU

April 24, 2019

# Table of Contents

- 1 Introduction
  - Objective
  - Motivation
- 2 Data
  - Data Format
  - Dataset/s
- 3 Encoding
  - General Thoughts
  - Notes
  - Rests and Holds
  - Multivoice polyphony
- 4 Neural Network stuff
- 5 Conclusions
  - Mmmm
  - The End

# Automatic Music Generation

TODO

- Mmmm

# Automatic Music Generation

TODO

- Mmmm
- Woooo

# Automatic Music Generation

TODO

- Mmmm
- Woooo

And sooo..

# Automatic Music Generation

TODO

- Mmmm
- Woooo

And sooo..

- Yeahhh

# Automatic Music Generation

TODO

- Mmmm
- Woooo

And sooo..

- Yeahhh
- lolll

# Automatic Music Generation

TODO

- Mmmm
- Woooo

And sooo..

- Yeahhh
- lolll
- Heh



# Motivation

TODO

# MIDI

- Protocol that stores music data and metadata, and allows different instruments and software to communicate with each other.

# MIDI

- Protocol that stores music data and metadata, and allows different instruments and software to communicate with each other.

It is made up by a series of events, with info regarding:

# MIDI

- Protocol that stores music data and metadata, and allows different instruments and software to communicate with each other.

It is made up by a series of events, with info regarding:

- Location in time
- Duration in time
- Pitch, intensity and tempo
- Other metadata

# Data Sources

TODO

# Overview

- MIDI files provide us with more info than we need

# Overview

- MIDI files provide us with more info than we need
- We are going to use a many-hot encoding approach

# Overview

- MIDI files provide us with more info than we need
- We are going to use a many-hot encoding approach

Thus...



# Overview

- MIDI files provide us with more info than we need
- We are going to use a many-hot encoding approach

Thus...

- Tempo will not be encoded: Too many possible values
- Intensity will not be encoded: Same reason

We are essentially losing expressiveness info in order to reduce the complexity of the network.

# Many-one-hot Encoding

- Python's `music21` library to read `.mid` files.
- Preprocess the `stream` objects to get the data for the time events.

# Many-one-hot Encoding

- Python's `music21` library to read `.mid` files.
- Preprocess the `stream` objects to get the data for the time events.



$$\bar{p}_t = [0, 0, \dots, 1, 0, 0, 0, 1, 0, 0, 1, 0, 0, \dots, 0]$$

# Many-one-hot Encoding

- Python's `music21` library to read `.mid` files.
- Preprocess the `stream` objects to get the data for the time events.



$$\bar{p}_t = [0, 0, \dots, 1, 0, 0, 0, 1, 0, 0, 1, 0, 0, \dots, 0]$$

- Create a sequence where each input vector  $\bar{p}_t$  corresponds to the duration of the shortest note on the piece/s:

$$\text{Time Step} \equiv \Delta_t = t_1 - t_0 = t_2 - t_1 = \dots$$

## Two extra dimensions

- Rests are essential to music. Add component #88 to encode rests.

## Two extra dimensions

- Rests are essential to music. Add component #88 to encode rests.
- If a note is longer than the time step, it will be split into more than one vector. Suppose we have:

## Two extra dimensions

- Rests are essential to music. Add component #88 to encode rests.
- If a note is longer than the time step, it will be split into more than one vector. Suppose we have:

time step =  $\text{♩}$ , event at  $t_i = \text{♩}$

## Two extra dimensions

- Rests are essential to music. Add component #88 to encode rests.
- If a note is longer than the time step, it will be split into more than one vector. Suppose we have:

time step =  $\text{♩}$ , event at  $t_i = \text{♩} \Rightarrow \bar{p}_{t_i} = [0, 0, \dots, 1, 0, 0, \dots]$



## Two extra dimensions

- Rests are essential to music. Add component #88 to encode rests.
- If a note is longer than the time step, it will be split into more than one vector. Suppose we have:

time step =  $\text{♩}$ , event at  $t_i = \text{♩} \Rightarrow \bar{p}_{t_i} = [0, 0, \dots, 1, 0, 0, \dots]$  and  
 $\bar{p}_{t_{i+1}} = [0, 0, \dots, 1, 0, 0, \dots] = \bar{p}_{t_i}$

## Two extra dimensions

- Rests are essential to music. Add component #88 to encode rests.
- If a note is longer than the time step, it will be split into more than one vector. Suppose we have:

time step =  $\text{♩}$ , event at  $t_i = \text{♩} \Rightarrow \bar{p}_{t_i} = [0, 0, \dots, 1, 0, 0, \dots]$  and  
 $\bar{p}_{t_{i+1}} = [0, 0, \dots, 1, 0, 0, \dots] = \bar{p}_{t_i} \Rightarrow \text{♩} \text{♩} \neq \text{♩}$

## Two extra dimensions

- Rests are essential to music. Add component #88 to encode rests.
- If a note is longer than the time step, it will be split into more than one vector. Suppose we have:

time step =  $\text{♩}$ , event at  $t_i = \text{♩} \Rightarrow \bar{p}_{t_i} = [0, 0, \dots, 1, 0, 0, \dots]$  and  
 $\bar{p}_{t_{i+1}} = [0, 0, \dots, 1, 0, 0, \dots] = \bar{p}_{t_i} \Rightarrow \text{♩} \text{♩} \neq \text{♩}$

- Add *hold* component #89, which indicates that the notes played at a time event shall be held. We end up with:

## Two extra dimensions

- Rests are essential to music. Add component #88 to encode rests.
- If a note is longer than the time step, it will be split into more than one vector. Suppose we have:

time step =  $\text{♩}$ , event at  $t_i = \text{♩} \Rightarrow \bar{p}_{t_i} = [0, 0, \dots, 1, 0, 0, \dots]$  and  
 $\bar{p}_{t_{i+1}} = [0, 0, \dots, 1, 0, 0, \dots] = \bar{p}_{t_i} \Rightarrow \text{♩} \text{♩} \neq \text{♩}$

- Add *hold* component #89, which indicates that the notes played at a time event shall be held. We end up with:

$\bar{p}_{t_i} = [0, 0, \dots, 1, 0, 0, \dots, 1], \bar{p}_{t_{i+1}} = [0, 0, \dots, 1, 0, 0, \dots, 0] \Rightarrow \text{♩}$

# Combining Melody & Harmony

TODO

hhh

TODO

# Whatever

Something

# Happy Music Generation!

Some cool pic!