

In [1]:

#Para iniciar o programa, é necessário importar alguma bibliotecas que são bastante utilizadas de machine learning e manipulação dos dados.

```
import numpy as np #Biblioteca "matemática"
import pandas as pd #Biblioteca para manipulação e análise de dados
import matplotlib.pyplot as plt #Extensão da biblioteca que faz a plotagem de gráficos e pontuações
import seaborn as sns
import os #Funcionalidade simplificadas de sistema operacionais
```

In [3]:

#Neste segundo momento, é feito o acesso a pasta aonde está o arquivo .CSV que iremos utilizar.

```
df=pd.read_csv('measures_v2.csv', usecols=[0,1,2,3,4,5,6,7,8,9,10,11])
```

In [4]:

#Como podemos observar no dataset, existe um grande número de colunas para nossa variável, a temperatura do rotor. Para isto, colocaremos ela como nosso Target.

```
df.head()
```

Out[4]:

	u_q	coolant	stator_winding	u_d	stator_tooth	motor_speed	i_d	
0	-0.450682	18.805172	19.086670	-0.350055	18.293219	0.002866	0.004419	0.000
1	-0.325737	18.818571	19.092390	-0.305803	18.294807	0.000257	0.000606	-0.000
2	-0.440864	18.828770	19.089380	-0.372503	18.294094	0.002355	0.001290	0.000
3	-0.327026	18.835567	19.083031	-0.316199	18.292542	0.006105	0.000026	0.002
4	-0.471150	18.857033	19.082525	-0.332272	18.291428	0.003133	-0.064317	0.037

In [5]:

```
#Então pegamos a coluna com os valores de pm e as declaramos como o Target
target = df.pop('pm') #Temperatura do rotor
#Após isto a colocamos é feita a concatenação dela novamente no tabela de dados, porém agora
df = pd.concat([df, target], axis=1)
#Aqui é utilizado a função sample para embalagem dos valores.
df = df.sample(frac=1,random_state=0) #embaralha os dados do dataframe #Ajuda a prevenir o
df.head()
```

Out[5]:

	u_q	coolant	stator_winding	u_d	stator_tooth	motor_speed	
372073	41.938923	18.744030	66.684830	-123.478027	46.080647	4749.964355	-187.964
766578	-0.431508	59.902590	85.079312	-0.878644	76.299257	0.057160	-2.000
1319224	-1.541598	33.149664	48.669293	-0.333442	45.330586	0.001482	-2.000
643478	42.387482	44.949261	104.791174	-123.337533	90.274398	5112.368164	-181.587
552128	15.335679	18.755226	113.366333	-130.067474	84.144737	3999.963135	-205.157

In [6]:

```
#Como pode ser visto, o Index de nosso dataframe estava desorganizado. Utilizando o Reset i
#Tendo o index organizado novamente.
df.reset_index(drop=True, inplace=True) #Faz com que o Index volte a ser o que era antes
df.head()
```

Out[6]:

	u_q	coolant	stator_winding	u_d	stator_tooth	motor_speed	i_d
0	41.938923	18.744030	66.684830	-123.478027	46.080647	4749.964355	-187.964111 7
1	-0.431508	59.902590	85.079312	-0.878644	76.299257	0.057160	-2.000745
2	-1.541598	33.149664	48.669293	-0.333442	45.330586	0.001482	-2.000673
3	42.387482	44.949261	104.791174	-123.337533	90.274398	5112.368164	-181.587703 6
4	15.335679	18.755226	113.366333	-130.067474	84.144737	3999.963135	-205.157623 9

In [7]:

```
#Neste momento fazemos a divisão de nosso banco de dados em 75% e 25% a partir do quantidade
split_index=int(len(df) * 0.75)

#Então aqui fazemos uma jogada bem típica de machine Learning onde é separado o conjunto de
train_df = df[:split_index] #Primeiros 75%
test_df = df[split_index:] #outros 25% restantes

#É possível observar pela saída dos dados que temos exatamente 25% de linhas para o teste e
#75% de linhas para o treino de nosso algoritmo.
train_df.info()
test_df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 998112 entries, 0 to 998111
Data columns (total 12 columns):
#   Column                Non-Null Count  Dtype
---  -
0   u_q                    998112 non-null float64
1   coolant                998112 non-null float64
2   stator_winding         998112 non-null float64
3   u_d                    998112 non-null float64
4   stator_tooth           998112 non-null float64
5   motor_speed            998112 non-null float64
6   i_d                    998112 non-null float64
7   i_q                    998112 non-null float64
8   stator_yoke            998112 non-null float64
9   ambient                998112 non-null float64
10  torque                 998112 non-null float64
11  pm                     998112 non-null float64
dtypes: float64(12)
memory usage: 91.4 MB

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 332704 entries, 998112 to 1330815
Data columns (total 12 columns):
#   Column                Non-Null Count  Dtype
---  -
0   u_q                    332704 non-null float64
1   coolant                332704 non-null float64
2   stator_winding         332704 non-null float64
3   u_d                    332704 non-null float64
4   stator_tooth           332704 non-null float64
5   motor_speed            332704 non-null float64
6   i_d                    332704 non-null float64
7   i_q                    332704 non-null float64
8   stator_yoke            332704 non-null float64
9   ambient                332704 non-null float64
10  torque                 332704 non-null float64
11  pm                     332704 non-null float64
dtypes: float64(12)
memory usage: 30.5 MB
```

In [9]:

```
#Então aqui é colocado os valores de X_train como sendo todas as colunas menos a última,  
#isto é feito para isolar o valor Target que queremos predizer e que havia sido colocado pa  
X_train = train_df.to_numpy()[ :, :-1]  
#Aqui é capturada apenas a última coluna para termos o valor o qual o X_train deve alcançar  
y_train = train_df.to_numpy()[ :, -1]  
#Nesta parte, é feito exatamente a mesma coisa, porém agora sendo utilizado o conjunto de t  
X_test = test_df.to_numpy()[ :, :-1]  
y_test = test_df.to_numpy()[ :, -1]
```

Agora que temos os dados tratados, será instalado o algoritmo TPOT que irá atuar na parte de treinamento do modelo.

In [10]:

```
!pip install tpot
!pip install pydataset
```

Collecting tpot

Downloading TPOT-0.11.7-py3-none-any.whl (87 kB)

Requirement already satisfied: scikit-learn>=0.22.0 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from tpot) (1.0.2)

Requirement already satisfied: scipy>=1.3.1 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from tpot) (1.7.3)

Requirement already satisfied: joblib>=0.13.2 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from tpot) (1.1.0)

Requirement already satisfied: tqdm>=4.36.1 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from tpot) (4.64.0)

Collecting stopit>=1.1.1

Downloading stopit-1.1.2.tar.gz (18 kB)

Collecting xgboost>=1.1.0

Downloading xgboost-1.6.1-py3-none-win_amd64.whl (125.4 MB)

Collecting deap>=1.2

Downloading deap-1.3.1-cp39-cp39-win_amd64.whl (108 kB)

Requirement already satisfied: pandas>=0.24.2 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from tpot) (1.4.2)

Requirement already satisfied: numpy>=1.16.3 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from tpot) (1.21.5)

Collecting update-checker>=0.16

Downloading update_checker-0.18.0-py3-none-any.whl (7.0 kB)

Requirement already satisfied: python-dateutil>=2.8.1 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from pandas>=0.24.2->tpot) (2.8.2)

Requirement already satisfied: pytz>=2020.1 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from pandas>=0.24.2->tpot) (2021.3)

Requirement already satisfied: six>=1.5 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from python-dateutil>=2.8.1->pandas>=0.24.2->tpot) (1.16.0)

Requirement already satisfied: threadpoolctl>=2.0.0 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from scikit-learn>=0.22.0->tpot) (2.2.0)

Requirement already satisfied: colorama in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from tqdm>=4.36.1->tpot) (0.4.4)

Requirement already satisfied: requests>=2.3.0 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from update-checker>=0.16->tpot) (2.27.1)

Requirement already satisfied: idna<4,>=2.5 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from requests>=2.3.0->update-checker>=0.16->tpot) (3.3)

Requirement already satisfied: urllib3<1.27,>=1.21.1 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from requests>=2.3.0->update-checker>=0.16->tpot) (1.26.9)

Requirement already satisfied: charset-normalizer~2.0.0 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from requests>=2.3.0->update-checker>=0.16->tpot) (2.0.4)

Requirement already satisfied: certifi>=2017.4.17 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from requests>=2.3.0->update-checker>=0.16->tpot) (2021.10.8)

Building wheels for collected packages: stopit

Building wheel for stopit (setup.py): started

Building wheel for stopit (setup.py): finished with status 'done'

Created wheel for stopit: filename=stopit-1.1.2-py3-none-any.whl size=11956 sha256=382a9c35f840eb2e14981965775040849d65f453f374122c1944764e11823a3c

Stored in directory: c:\users\pedro h bunn schmitt\appdata\local\pip\cache\wheels\48\8c\93\3afb1916772591fe6bcc25cdf8b1c5bdc362f0ec8e2f0fd413

Successfully built stopit

```
Installing collected packages: xgboost, update-checker, stopit, deap, tpot
Successfully installed deap-1.3.1 stopit-1.1.2 tpot-0.11.7 update-checker-0.
18.0 xgboost-1.6.1
Collecting pydataset
  Downloading pydataset-0.2.0.tar.gz (15.9 MB)
Requirement already satisfied: pandas in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from pydataset) (1.4.2)
Requirement already satisfied: python-dateutil>=2.8.1 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from pandas->pydataset) (2.8.2)
Requirement already satisfied: numpy>=1.18.5 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from pandas->pydataset) (1.21.5)
Requirement already satisfied: pytz>=2020.1 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from pandas->pydataset) (2021.3)
Requirement already satisfied: six>=1.5 in c:\users\pedro h bunn schmitt\anaconda3\lib\site-packages (from python-dateutil>=2.8.1->pandas->pydataset) (1.16.0)
Building wheels for collected packages: pydataset
  Building wheel for pydataset (setup.py): started
  Building wheel for pydataset (setup.py): finished with status 'done'
  Created wheel for pydataset: filename=pydataset-0.2.0-py3-none-any.whl size=15939432 sha256=ca954c5fb061b130ef2c45e99d7c12e92acea0d30fad99e919b351f3af1fd21
  Stored in directory: c:\users\pedro h bunn schmitt\appdata\local\pip\cache\wheels\6b\86\a7\f71cb84c7bff804d83e293615a20c0531234397b796aee2645
Successfully built pydataset
Installing collected packages: pydataset
Successfully installed pydataset-0.2.0
```

Agora iremos trazer da biblioteca do TPOT a parte do modelo de regressão que ela oferece.

In [11]:

```
from tpot import TPOTRegressor
```

```
C:\Users\Pedro H Bunn Schmitt\anaconda3\lib\site-packages\tpot\builtins\__init__.py:36: UserWarning: Warning: optional dependency `torch` is not available. - skipping import of NN models.
  warnings.warn("Warning: optional dependency `torch` is not available. - skipping import of NN models.")
```

Agora iremos utilizar TPOT Regressor para treinar nosso modelo

In [14]:

```
#Neste momento estamos colocando os parâmetros ao TPOT
tpot = TPOTRegressor(generations=10,population_size=50,verbosity=2,random_state=5, max_time
#Agora iremos fazer o Fit de nossos dados ao modelo.
tpot.fit(X_train,y_train)
print(tpot.score(X_test,y_test))
```

152.94 minutes have elapsed. TPOT will close down.

TPOT closed during evaluation in one generation.

WARNING: TPOT may not provide a good pipeline if TPOT is stopped/interrupted in a early generation.

TPOT closed prematurely. Will use the current best pipeline.

Best pipeline: KNeighborsRegressor(input_matrix, n_neighbors=73, p=1, weight
s=distance)
-15.47738737774374

In [13]:

```
preds_test = tpot.predict(X_test)
print(r2_score(y_test, preds_test))
```

NameError

Traceback (most recent call last)

Input In [13], in <cell line: 2>()

```
1 preds_test = tpot.predict(X_test)
----> 2 print(r2_score(y_test, preds_test))
```

NameError: name 'r2_score' is not defined