



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME	NOMINAL VALUE	MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Angle error to Cam 11 A6 - Lobe 1	180,000	179,969	179,900	180,100	-0,031	
2	Angle error to Cam 11 A6 - Lobe 2	300,000	299,944	299,900	300,100	-0,056	
3	Angle error to Cam 11 A6 - Lobe 3	60,000	59,932	59,900	60,100	-0,068	
4	Angle error to Cam 11 A6 - Lobe 4	240,000	239,958	239,900	240,100	-0,042	
5	Angle error to Cam 11 A6 - Lobe 5	120,000	119,978	119,900	120,100	-0,022	
6	Angle error to Cam 11 A6 - Lobe 6	0,000	0,000	-0,100	0,100	0,000	
7	Angle error to UZ - Lobe 1	55,500	55,469	55,400	55,600	-0,031	
8	Angle error to UZ - Lobe 2	175,500	175,444	175,400	175,600	-0,056	
9	Angle error to UZ - Lobe 3	295,500	295,432	295,400	295,600	-0,068	
10	Angle error to UZ - Lobe 4	115,500	115,458	115,400	115,600	-0,042	
11	Angle error to UZ - Lobe 5	355,500	355,478	355,400	355,600	-0,022	
12	Angle error to UZ - Lobe 6	235,500	235,500	235,400	235,600	0,000	
13	Angulo entre as superficies	40,000	40,003	39,875	40,125	0,003	
14	BC Radius Error - Lobe 1	25,000	24,955	24,900	25,100	-0,045	
15	BC Radius Error - Lobe 2	25,000	24,945	24,900	25,100	-0,055	
16	BC Radius Error - Lobe 3	25,000	24,935	24,900	25,100	-0,065	
17	BC Radius Error - Lobe 4	25,000	24,929	24,900	25,100	-0,071	
18	BC Radius Error - Lobe 5	25,000	24,927	24,900	25,100	-0,073	
19	BC Radius Error - Lobe 6	25,000	24,915	24,900	25,100	-0,085	
20	BC Runout - Lobe 1	0,000	0,002	0,000	0,040	0,002	
21	BC Runout - Lobe 2	0,000	0,006	0,000	0,040	0,006	
22	BC Runout - Lobe 3	0,000	0,002	0,000	0,040	0,002	
23	BC Runout - Lobe 4	0,000	0,002	0,000	0,040	0,002	
24	BC Runout - Lobe 5	0,000	0,003	0,000	0,040	0,003	
25	BC Runout - Lobe 6	0,000	0,008	0,000	0,040	0,008	
26	Concave/Convex - Lobe 1	0,000	-0,001	-0,005	0,005	-0,001	
27	Concave/Convex - Lobe 2	0,000	0,000	-0,005	0,005	0,000	
28	Concave/Convex - Lobe 3	0,000	0,000	-0,005	0,005	0,000	
29	Concave/Convex - Lobe 4	0,000	0,000	-0,005	0,005	0,000	
30	Concave/Convex - Lobe 5	0,000	0,000	-0,005	0,005	0,000	
31	Concave/Convex - Lobe 6	0,000	0,000	-0,005	0,005	0,000	
32	Cylindricity - A	0,000	0,006	0,000	0,020	0,006	
33	Cylindricity - B	0,000	0,004	0,000	0,020	0,004	
34	Cylindricity - C	0,000	0,003	0,000	0,020	0,003	
35	Cylindricity - D	0,000	0,003	0,000	0,020	0,003	
36	Cylindricity - E	0,000	0,003	0,000	0,020	0,003	
37	Cylindricity - F	0,000	0,005	0,000	0,020	0,005	
38	Cylindricity - G	0,000	0,002	0,000	0,020	0,002	
39	Distancia U para o Eixo de Rot	39,700	39,648	39,650	39,750	-0,052	-0,002
40	Distancia Z para o Eixo de Rot	39,700	39,676	39,650	39,750	-0,024	
41	Lift Difference - Lobe 1	0,000	0,004	-0,010	0,010	0,004	
42	Lift Difference - Lobe 2	0,000	-0,003	-0,010	0,010	-0,003	
43	Lift Difference - Lobe 3	0,000	0,003	-0,010	0,010	0,003	
44	Lift Difference - Lobe 4	0,000	0,003	-0,010	0,010	0,003	
45	Lift Difference - Lobe 5	0,000	-0,003	-0,010	0,010	-0,003	
46	Lift Difference - Lobe 6	0,000	-0,003	-0,010	0,010	-0,003	
47	Lift Error BC - Lobe 1	0,000	0,001	-0,025	0,025	0,001	
48	Lift Error BC - Lobe 2	0,000	-0,004	-0,025	0,025	-0,004	



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Lift Error BC - Lobe 3	0.000	-0.001	-0.025	0.025	-0.001	
2	Lift Error BC - Lobe 4	0.000	0.001	-0.025	0.025	0.001	
3	Lift Error BC - Lobe 5	0.000	-0.002	-0.025	0.025	-0.002	
4	Lift Error BC - Lobe 6	0.000	0.005	-0.025	0.025	0.005	
5	Lift Error Closing Ramp - Lobe 1	0.000	0.029	-0.050	0.050	0.029	
6	Lift Error Closing Ramp - Lobe 2	0.000	0.019	-0.050	0.050	0.019	
7	Lift Error Closing Ramp - Lobe 3	0.000	0.017	-0.050	0.050	0.017	
8	Lift Error Closing Ramp - Lobe 4	0.000	0.020	-0.050	0.050	0.020	
9	Lift Error Closing Ramp - Lobe 5	0.000	0.016	-0.050	0.050	0.016	
10	Lift Error Closing Ramp - Lobe 6	0.000	0.029	-0.050	0.050	0.029	
11	Lift Error Nose - Lobe 1	0.000	0.018	-0.100	0.100	0.018	
12	Lift Error Nose - Lobe 2	0.000	0.010	-0.100	0.100	0.010	
13	Lift Error Nose - Lobe 3	0.000	0.012	-0.100	0.100	0.012	
14	Lift Error Nose - Lobe 4	0.000	0.016	-0.100	0.100	0.016	
15	Lift Error Nose - Lobe 5	0.000	0.010	-0.100	0.100	0.010	
16	Lift Error Nose - Lobe 6	0.000	0.030	-0.100	0.100	0.030	
17	Lift Error Opening Ramp - Lobe 1	0.000	0.033	-0.050	0.050	0.033	
18	Lift Error Opening Ramp - Lobe 2	0.000	0.018	-0.050	0.050	0.018	
19	Lift Error Opening Ramp - Lobe 3	0.000	0.018	-0.050	0.050	0.018	
20	Lift Error Opening Ramp - Lobe 4	0.000	0.021	-0.050	0.050	0.021	
21	Lift Error Opening Ramp - Lobe 5	0.000	0.017	-0.050	0.050	0.017	
22	Lift Error Opening Ramp - Lobe 6	0.000	0.030	-0.050	0.050	0.030	
23	Meas Diam [Center]- A	35.967	35.964	35.959	35.975	-0.003	
24	Meas Diam [Center]- B	35.967	35.972	35.959	35.975	0.005	
25	Meas Diam [Center]- C	35.967	35.963	35.959	35.975	-0.004	
26	Meas Diam [Center]- D	35.967	35.970	35.959	35.975	0.003	
27	Meas Diam [Center]- E	35.967	35.961	35.959	35.975	-0.006	
28	Meas Diam [Center]- F	35.967	35.967	35.959	35.975	0.000	
29	Meas Diam [Center]- G	47.967	47.977	47.959	47.975	0.010	0.002
30	Meas Diam [Inf]- A	35.967	35.966	35.959	35.975	-0.001	
31	Meas Diam [Inf]- B	35.967	35.969	35.959	35.975	0.002	
32	Meas Diam [Inf]- C	35.967	35.960	35.959	35.975	-0.007	
33	Meas Diam [Inf]- D	35.967	35.967	35.959	35.975	0.000	
34	Meas Diam [Inf]- E	35.967	35.959	35.959	35.975	-0.008	
35	Meas Diam [Inf]- F	35.967	35.966	35.959	35.975	-0.001	
36	Meas Diam [Inf]- G	47.967	47.978	47.959	47.975	0.011	0.003
37	Meas Diam [Sup]- A	35.967	35.961	35.959	35.975	-0.006	
38	Meas Diam [Sup]- B	35.967	35.973	35.959	35.975	0.006	
39	Meas Diam [Sup]- C	35.967	35.963	35.959	35.975	-0.004	
40	Meas Diam [Sup]- D	35.967	35.970	35.959	35.975	0.003	
41	Meas Diam [Sup]- E	35.967	35.961	35.959	35.975	-0.006	
42	Meas Diam [Sup]- F	35.967	35.967	35.959	35.975	0.000	
43	Meas Diam [Sup]- G	47.967	47.977	47.959	47.975	0.010	0.002
44	Parallelism - A	0.000	0.001	0.000	0.015	0.001	
45	Parallelism - B	0.000	0.001	0.000	0.015	0.001	
46	Parallelism - C	0.000	0.000	0.000	0.015	0.000	
47	Parallelism - D	0.000	0.000	0.000	0.015	0.000	
48	Parallelism - E	0.000	0.000	0.000	0.015	0.000	



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Parallelism - F	0.000	0.001	0.000	0.015	0.001	
2	Parallelism - G	0.000	0.001	0.000	0.015	0.001	
3	Parallelism - Lobe 1	0.000	0.001	0.000	0.020	0.001	
4	Parallelism - Lobe 2	0.000	0.000	0.000	0.020	0.000	
5	Parallelism - Lobe 3	0.000	0.000	0.000	0.020	0.000	
6	Parallelism - Lobe 4	0.000	0.000	0.000	0.020	0.000	
7	Parallelism - Lobe 5	0.000	0.000	0.000	0.020	0.000	
8	Parallelism - Lobe 6	0.000	0.001	0.000	0.020	0.001	
9	Runout [Adj] - A	0.000	0.012	0.000	0.030	0.012	
10	Runout [Adj] - B	0.000	0.006	0.000	0.030	0.006	
11	Runout [Adj] - C	0.000	0.009	0.000	0.030	0.009	
12	Runout [Adj] - D	0.000	0.005	0.000	0.030	0.005	
13	Runout [Adj] - E	0.000	0.006	0.000	0.030	0.006	
14	Runout [Adj] - F	0.000	0.006	0.000	0.030	0.006	
15	Runout [Adj] - G	0.000	0.009	0.000	0.030	0.009	
16	Runout [B-C] - A	0.000	0.012	0.000	0.120	0.012	
17	Runout [E-F] - G	0.000	0.009	0.000	0.120	0.009	
18	Runout [Ext] - B	0.000	0.013	0.000	0.120	0.013	
19	Runout [Ext] - C	0.000	0.031	0.000	0.120	0.031	
20	Runout [Ext] - D	0.000	0.034	0.000	0.120	0.034	
21	Runout [Ext] - E	0.000	0.031	0.000	0.120	0.031	
22	Runout [Ext] - F	0.000	0.021	0.000	0.120	0.021	
23	Runout [Gage] - A	0.000	0.015	0.000	0.120	0.015	
24	Runout [Gage] - B	0.000	0.006	0.000	0.120	0.006	
25	Runout [Gage] - C	0.000	0.023	0.000	0.120	0.023	
26	Runout [Gage] - D	0.000	0.034	0.000	0.120	0.034	
27	Runout [Gage] - E	0.000	0.029	0.000	0.120	0.029	
28	Runout [Gage] - F	0.000	0.021	0.000	0.120	0.021	
29	Runout [Gage] - G	0.000	0.023	0.000	0.120	0.023	
30	Angle error to Cam 1 - Lobe 2	0.000	-0.843	-0.125	0.125	-0.843	-0.718
31	Angle error to Cam 1 - Lobe 3	0.000	0.315	-0.125	0.125	0.315	0.190
32	Angle error to Cam 1 - Lobe 4	0.000	-0.131	-0.125	0.125	-0.131	-0.006
33	Angle error to Cam 1 - Lobe 5	0.000	-1.579	-0.125	0.125	-1.579	-1.454
34	Angle error to Cam 1 - Lobe 6	0.000	0.452	-0.125	0.125	0.452	0.327
35	Angle error to Cam 1 - Lobe 7	0.000	0.172	-0.125	0.125	0.172	0.047
36	Angle error to Cam 1 - Lobe 8	0.000	-0.466	-0.125	0.125	-0.466	-0.341
37	Angle error to Cam 1 - Lobe 9	0.000	0.167	-0.125	0.125	0.167	0.042
38	Angle error to Cam 1 - Lobe 10	0.000	0.034	-0.125	0.125	0.034	
39	Angle error to Cam 1 - Lobe 11	0.000	-1.569	-0.125	0.125	-1.569	-1.444
40	Angle error to Cam 1 - Lobe 12	0.000	0.407	-0.125	0.125	0.407	0.282
41	Angle error to Cam 1 - Lobe 13	0.000	-0.092	-0.125	0.125	-0.092	
42	Angle error to Cam 1 - Lobe 14	0.000	-1.212	-0.125	0.125	-1.212	-1.087
43	Angle error to Cam 1 - Lobe 15	0.000	0.235	-0.125	0.125	0.235	0.110
44	Angle error to Pin - Lobe 1	0.000	-0.093	-0.250	0.250	-0.093	
45	Angle error to Pin - Lobe 2	0.000	-0.936	-0.250	0.250	-0.936	-0.686
46	Angle error to Pin - Lobe 3	0.000	0.222	-0.250	0.250	0.222	
47	Angle error to Pin - Lobe 4	0.000	-0.224	-0.250	0.250	-0.224	
48	Angle error to Pin - Lobe 5	0.000	-1.672	-0.250	0.250	-1.672	-1.422



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Angle error to Pin - Lobe 6	0.000	0.359	-0.250	0.250	0.359	0.109
2	Angle error to Pin - Lobe 7	0.000	0.079	-0.250	0.250	0.079	
3	Angle error to Pin - Lobe 8	0.000	-0.559	-0.250	0.250	-0.559	-0.309
4	Angle error to Pin - Lobe 9	0.000	0.074	-0.250	0.250	0.074	
5	Angle error to Pin - Lobe 10	0.000	-0.059	-0.250	0.250	-0.059	
6	Angle error to Pin - Lobe 11	0.000	-1.663	-0.250	0.250	-1.663	-1.413
7	Angle error to Pin - Lobe 12	0.000	0.314	-0.250	0.250	0.314	0.064
8	Angle error to Pin - Lobe 13	0.000	-0.185	-0.250	0.250	-0.185	
9	Angle error to Pin - Lobe 14	0.000	-1.305	-0.250	0.250	-1.305	-1.055
10	Angle error to Pin - Lobe 15	0.000	0.142	-0.250	0.250	0.142	
11	Angle of Cam 1 to ref.	127.800	127.707	127.550	128.050	-0.093	
12	BC Radius Error - Lobe 1	0.000	0.424	-0.100	0.100	0.424	0.324
13	BC Radius Error - Lobe 2	0.000	0.446	-0.100	0.100	0.446	0.346
14	BC Radius Error - Lobe 3	0.000	0.363	-0.100	0.100	0.363	0.263
15	BC Radius Error - Lobe 4	0.000	0.453	-0.100	0.100	0.453	0.353
16	BC Radius Error - Lobe 5	0.000	0.485	-0.100	0.100	0.485	0.385
17	BC Radius Error - Lobe 6	0.000	0.372	-0.100	0.100	0.372	0.272
18	BC Radius Error - Lobe 7	0.000	0.366	-0.100	0.100	0.366	0.266
19	BC Radius Error - Lobe 8	0.000	0.420	-0.100	0.100	0.420	0.320
20	BC Radius Error - Lobe 9	0.000	0.357	-0.100	0.100	0.357	0.257
21	BC Radius Error - Lobe 10	0.000	0.438	-0.100	0.100	0.438	0.338
22	BC Radius Error - Lobe 11	0.000	0.542	-0.100	0.100	0.542	0.442
23	BC Radius Error - Lobe 12	0.000	0.351	-0.100	0.100	0.351	0.251
24	BC Radius Error - Lobe 13	0.000	0.425	-0.100	0.100	0.425	0.325
25	BC Radius Error - Lobe 14	0.000	0.429	-0.100	0.100	0.429	0.329
26	BC Radius Error - Lobe 15	0.000	0.331	-0.100	0.100	0.331	0.231
27	BC Runout - Lobe 1	0.000	0.112	0.000	0.040	0.112	0.072
28	BC Runout - Lobe 2	0.000	0.079	0.000	0.040	0.079	0.039
29	BC Runout - Lobe 3	0.000	0.217	0.000	0.040	0.217	0.177
30	BC Runout - Lobe 4	0.000	0.089	0.000	0.040	0.089	0.049
31	BC Runout - Lobe 5	0.000	0.065	0.000	0.040	0.065	0.025
32	BC Runout - Lobe 6	0.000	0.234	0.000	0.040	0.234	0.194
33	BC Runout - Lobe 7	0.000	0.098	0.000	0.040	0.098	0.058
34	BC Runout - Lobe 8	0.000	0.095	0.000	0.040	0.095	0.055
35	BC Runout - Lobe 9	0.000	0.130	0.000	0.040	0.130	0.090
36	BC Runout - Lobe 10	0.000	0.135	0.000	0.040	0.135	0.095
37	BC Runout - Lobe 11	0.000	0.161	0.000	0.040	0.161	0.121
38	BC Runout - Lobe 12	0.000	0.253	0.000	0.040	0.253	0.213
39	BC Runout - Lobe 13	0.000	0.111	0.000	0.040	0.111	0.071
40	BC Runout - Lobe 14	0.000	0.072	0.000	0.040	0.072	0.032
41	BC Runout - Lobe 15	0.000	0.197	0.000	0.040	0.197	0.157
42	BC Velocity Error - Lobe 1	0.000	0.010	0.000	0.010	0.010	
43	BC Velocity Error - Lobe 2	0.000	0.016	0.000	0.010	0.016	0.006
44	BC Velocity Error - Lobe 3	0.000	0.009	0.000	0.010	0.009	
45	BC Velocity Error - Lobe 4	0.000	0.020	0.000	0.010	0.020	0.010
46	BC Velocity Error - Lobe 5	0.000	0.010	0.000	0.010	0.010	
47	BC Velocity Error - Lobe 6	0.000	0.014	0.000	0.010	0.014	0.004
48	BC Velocity Error - Lobe 7	0.000	0.010	0.000	0.010	0.010	0.000



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	BC Velocity Error - Lobe 8	0.000	0.014	0.000	0.010	0.014	0.004
2	BC Velocity Error - Lobe 9	0.000	0.012	0.000	0.010	0.012	0.002
3	BC Velocity Error - Lobe 10	0.000	0.010	0.000	0.010	0.010	0.000
4	BC Velocity Error - Lobe 11	0.000	0.022	0.000	0.010	0.022	0.012
5	BC Velocity Error - Lobe 12	0.000	0.020	0.000	0.010	0.020	0.010
6	BC Velocity Error - Lobe 13	0.000	0.011	0.000	0.010	0.011	0.001
7	BC Velocity Error - Lobe 14	0.000	0.012	0.000	0.010	0.012	0.002
8	BC Velocity Error - Lobe 15	0.000	0.014	0.000	0.010	0.014	0.004
9	Center Deviation - Lobe 1	0.000	-0.004	-0.003	0.020	-0.004	-0.001
10	Center Deviation - Lobe 2	0.000	0.001	-0.003	0.020	0.001	
11	Center Deviation - Lobe 3	0.000	-0.001	-0.003	0.020	-0.001	
12	Center Deviation - Lobe 4	0.000	-0.001	-0.003	0.020	-0.001	
13	Center Deviation - Lobe 5	0.000	0.002	-0.003	0.020	0.002	
14	Center Deviation - Lobe 6	0.000	0.000	-0.003	0.020	0.000	
15	Center Deviation - Lobe 7	0.000	-0.002	-0.003	0.020	-0.002	
16	Center Deviation - Lobe 8	0.000	0.001	-0.003	0.020	0.001	
17	Center Deviation - Lobe 9	0.000	-0.003	-0.003	0.020	-0.003	0.000
18	Center Deviation - Lobe 10	0.000	-0.004	-0.003	0.020	-0.004	-0.001
19	Center Deviation - Lobe 11	0.000	-0.002	-0.003	0.020	-0.002	
20	Center Deviation - Lobe 12	0.000	-0.004	-0.003	0.020	-0.004	-0.001
21	Center Deviation - Lobe 13	0.000	-0.002	-0.003	0.020	-0.002	
22	Center Deviation - Lobe 14	0.000	-0.005	-0.003	0.020	-0.005	-0.003
23	Center Deviation - Lobe 15	0.000	-0.002	-0.003	0.020	-0.002	
24	Cir_Mancal_A	0.000		0.000	0.010		
25	Dia_Mancal_A	84.953		-0.011	0.011		
26	Ecc-Ref [Gage] - A	0.000	0.078	0.000	0.035	0.078	0.043
27	Ecc-Ref [Gage] - B	0.000	0.042	0.000	0.035	0.042	0.007
28	Ecc-Ref [Gage] - C	0.000	0.020	0.000	0.035	0.020	
29	Ecc-Ref [Gage] - D	0.000	0.024	0.000	0.035	0.024	
30	Ecc-Ref [Gage] - E	0.000	0.028	0.000	0.035	0.028	
31	Ecc-Ref [Gage] - F	0.000	0.045	0.000	0.035	0.045	0.010
32	Ecc-Ref [Part] - A	0.000	0.000	0.000	0.070	0.000	
33	Ecc-Ref [Part] - B	0.000	0.031	0.000	0.070	0.031	
34	Ecc-Ref [Part] - C	0.000	0.014	0.000	0.070	0.014	
35	Ecc-Ref [Part] - D	0.000	0.028	0.000	0.070	0.028	
36	Ecc-Ref [Part] - E	0.000	0.054	0.000	0.070	0.054	
37	Ecc-Ref [Part] - F	0.000	0.000	0.000	0.070	0.000	
38	Lift Difference Nose - Lobe 1	0.000	0.014	0.000	0.010	0.014	0.004
39	Lift Difference Nose - Lobe 2	0.000	0.020	0.000	0.010	0.020	0.010
40	Lift Difference Nose - Lobe 3	0.000	0.011	0.000	0.010	0.011	0.001
41	Lift Difference Nose - Lobe 4	0.000	0.015	0.000	0.010	0.015	0.005
42	Lift Difference Nose - Lobe 5	0.000	0.038	0.000	0.010	0.038	0.028
43	Lift Difference Nose - Lobe 6	0.000	0.012	0.000	0.010	0.012	0.002
44	Lift Difference Nose - Lobe 7	0.000	0.012	0.000	0.010	0.012	0.002
45	Lift Difference Nose - Lobe 8	0.000	0.019	0.000	0.010	0.019	0.009
46	Lift Difference Nose - Lobe 9	0.000	0.015	0.000	0.010	0.015	0.005
47	Lift Difference Nose - Lobe 10	0.000	0.014	0.000	0.010	0.014	0.004
48	Lift Difference Nose - Lobe 11	0.000	0.031	0.000	0.010	0.031	0.021



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Lift Difference Nose - Lobe 12	0.000	0.013	0.000	0.010	0.013	0.003
2	Lift Difference Nose - Lobe 13	0.000	0.016	0.000	0.010	0.016	0.006
3	Lift Difference Nose - Lobe 14	0.000	0.050	0.000	0.010	0.050	0.040
4	Lift Difference Nose - Lobe 15	0.000	0.012	0.000	0.010	0.012	0.002
5	Lift Difference Ramp - Lobe 1	0.000	0.010	0.000	0.010	0.010	0.000
6	Lift Difference Ramp - Lobe 2	0.000	0.021	0.000	0.010	0.021	0.011
7	Lift Difference Ramp - Lobe 3	0.000	0.018	0.000	0.010	0.018	0.008
8	Lift Difference Ramp - Lobe 4	0.000	0.017	0.000	0.010	0.017	0.007
9	Lift Difference Ramp - Lobe 5	0.000	0.032	0.000	0.010	0.032	0.022
10	Lift Difference Ramp - Lobe 6	0.000	0.018	0.000	0.010	0.018	0.008
11	Lift Difference Ramp - Lobe 7	0.000	0.013	0.000	0.010	0.013	0.003
12	Lift Difference Ramp - Lobe 8	0.000	0.010	0.000	0.010	0.010	0.000
13	Lift Difference Ramp - Lobe 9	0.000	0.011	0.000	0.010	0.011	0.001
14	Lift Difference Ramp - Lobe 10	0.000	0.013	0.000	0.010	0.013	0.003
15	Lift Difference Ramp - Lobe 11	0.000	0.033	0.000	0.010	0.033	0.023
16	Lift Difference Ramp - Lobe 12	0.000	0.018	0.000	0.010	0.018	0.008
17	Lift Difference Ramp - Lobe 13	0.000	0.010	0.000	0.010	0.010	
18	Lift Difference Ramp - Lobe 14	0.000	0.020	0.000	0.010	0.020	0.010
19	Lift Difference Ramp - Lobe 15	0.000	0.024	0.000	0.010	0.024	0.014
20	Lift Error Nose - Lobe 1	0.000	0.151	0.000	0.100	0.151	0.051
21	Lift Error Nose - Lobe 2	0.000	0.320	0.000	0.100	0.320	0.220
22	Lift Error Nose - Lobe 3	0.000	0.113	0.000	0.100	0.113	0.013
23	Lift Error Nose - Lobe 4	0.000	0.152	0.000	0.100	0.152	0.052
24	Lift Error Nose - Lobe 5	0.000	0.636	0.000	0.100	0.636	0.536
25	Lift Error Nose - Lobe 6	0.000	0.114	0.000	0.100	0.114	0.014
26	Lift Error Nose - Lobe 7	0.000	0.046	0.000	0.100	0.046	
27	Lift Error Nose - Lobe 8	0.000	0.194	0.000	0.100	0.194	0.094
28	Lift Error Nose - Lobe 9	0.000	0.102	0.000	0.100	0.102	0.002
29	Lift Error Nose - Lobe 10	0.000	0.164	0.000	0.100	0.164	0.064
30	Lift Error Nose - Lobe 11	0.000	0.562	0.000	0.100	0.562	0.462
31	Lift Error Nose - Lobe 12	0.000	0.219	0.000	0.100	0.219	0.119
32	Lift Error Nose - Lobe 13	0.000	0.132	0.000	0.100	0.132	0.032
33	Lift Error Nose - Lobe 14	0.000	0.458	0.000	0.100	0.458	0.358
34	Lift Error Nose - Lobe 15	0.000	0.130	0.000	0.100	0.130	0.030
35	Lift Error Ramp - Lobe 1	0.000	0.125	0.000	0.050	0.125	0.075
36	Lift Error Ramp - Lobe 2	0.000	0.228	0.000	0.050	0.228	0.178
37	Lift Error Ramp - Lobe 3	0.000	0.110	0.000	0.050	0.110	0.060
38	Lift Error Ramp - Lobe 4	0.000	0.162	0.000	0.050	0.162	0.112
39	Lift Error Ramp - Lobe 5	0.000	0.442	0.000	0.050	0.442	0.392
40	Lift Error Ramp - Lobe 6	0.000	0.112	0.000	0.050	0.112	0.062
41	Lift Error Ramp - Lobe 7	0.000	0.054	0.000	0.050	0.054	0.004
42	Lift Error Ramp - Lobe 8	0.000	0.171	0.000	0.050	0.171	0.121
43	Lift Error Ramp - Lobe 9	0.000	0.080	0.000	0.050	0.080	0.030
44	Lift Error Ramp - Lobe 10	0.000	0.155	0.000	0.050	0.155	0.105
45	Lift Error Ramp - Lobe 11	0.000	0.421	0.000	0.050	0.421	0.371
46	Lift Error Ramp - Lobe 12	0.000	0.166	0.000	0.050	0.166	0.116
47	Lift Error Ramp - Lobe 13	0.000	0.129	0.000	0.050	0.129	0.079
48	Lift Error Ramp - Lobe 14	0.000	0.300	0.000	0.050	0.300	0.250



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Lift Error Ramp - Lobe 15	0.000	0.080	0.000	0.050	0.080	0.030
2	Meas Diam - A	84.953	85.497	0.015	0.030	0.544	85.467
3	Meas Diam - B	84.953	85.478	0.015	0.030	0.525	85.448
4	Meas Diam - C	84.953	85.444	0.015	0.030	0.491	85.414
5	Meas Diam - D	84.953	85.470	0.015	0.030	0.517	85.440
6	Meas Diam - E	84.953	85.460	0.015	0.030	0.507	85.430
7	Meas Diam - F	84.953	85.495	0.015	0.030	0.542	85.465
8	Parallelism - Lobe 1	0.000	0.013	-0.015	0.015	0.013	
9	Parallelism - Lobe 2	0.000	0.015	-0.015	0.015	0.015	
10	Parallelism - Lobe 3	0.000	0.014	-0.015	0.015	0.014	
11	Parallelism - Lobe 4	0.000	0.017	-0.015	0.015	0.017	0.002
12	Parallelism - Lobe 5	0.000	0.012	-0.015	0.015	0.012	
13	Parallelism - Lobe 6	0.000	0.013	-0.015	0.015	0.013	
14	Parallelism - Lobe 7	0.000	0.010	-0.015	0.015	0.010	
15	Parallelism - Lobe 8	0.000	0.012	-0.015	0.015	0.012	
16	Parallelism - Lobe 9	0.000	0.018	-0.015	0.015	0.018	0.003
17	Parallelism - Lobe 10	0.000	0.027	-0.015	0.015	0.027	0.012
18	Parallelism - Lobe 11	0.000	0.006	-0.015	0.015	0.006	
19	Parallelism - Lobe 12	0.000	0.019	-0.015	0.015	0.019	0.004
20	Parallelism - Lobe 13	0.000	0.027	-0.015	0.015	0.027	0.012
21	Parallelism - Lobe 14	0.000	0.021	-0.015	0.015	0.021	0.006
22	Parallelism - Lobe 15	0.000	0.023	-0.015	0.015	0.023	0.008
23	Roundness - A	0.000	0.049	0.000	0.010	0.049	0.039
24	Roundness - B	0.000	0.037	0.000	0.010	0.037	0.027
25	Roundness - C	0.000	0.038	0.000	0.010	0.038	0.028
26	Roundness - D	0.000	0.050	0.000	0.010	0.050	0.040
27	Roundness - E	0.000	0.044	0.000	0.010	0.044	0.034
28	Roundness - F	0.000	0.053	0.000	0.010	0.053	0.043
29	Runout - A	0.000	0.049	0.000	0.100	0.049	
30	Runout - B	0.000	0.087	0.000	0.100	0.087	
31	Runout - C	0.000	0.049	0.000	0.100	0.049	
32	Runout - D	0.000	0.079	0.000	0.100	0.079	
33	Runout - E	0.000	0.124	0.000	0.100	0.124	0.024
34	Runout - F	0.000	0.053	0.000	0.100	0.053	
35	Taper Error - Lobe 1	0.000	-0.003	-0.020	0.020	-0.003	
36	Taper Error - Lobe 2	0.000	0.019	-0.020	0.020	0.019	
37	Taper Error - Lobe 3	0.000	0.005	-0.020	0.020	0.005	
38	Taper Error - Lobe 4	0.000	-0.003	-0.020	0.020	-0.003	
39	Taper Error - Lobe 5	0.000	0.013	-0.020	0.020	0.013	
40	Taper Error - Lobe 6	0.000	0.003	-0.020	0.020	0.003	
41	Taper Error - Lobe 7	0.000	-0.008	-0.020	0.020	-0.008	
42	Taper Error - Lobe 8	0.000	0.006	-0.020	0.020	0.006	
43	Taper Error - Lobe 9	0.000	0.003	-0.020	0.020	0.003	
44	Taper Error - Lobe 10	0.000	-0.009	-0.020	0.020	-0.009	
45	Taper Error - Lobe 11	0.000	0.000	-0.020	0.020	0.000	
46	Taper Error - Lobe 12	0.000	-0.002	-0.020	0.020	-0.002	
47	Taper Error - Lobe 13	0.000	-0.006	-0.020	0.020	-0.006	
48	Taper Error - Lobe 14	0.000	-0.010	-0.020	0.020	-0.010	



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Taper Error - Lobe 15	0.000	-0.009	-0.020	0.020	-0.009	