



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME	NOMINAL VALUE	MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Angle error to Cam 1 - Lobe 2	0,000	-0,843	-0,125	0,125	-0,843	-0,718
2	Angle error to Cam 1 - Lobe 3	0,000	0,315	-0,125	0,125	0,315	0,190
3	Angle error to Cam 1 - Lobe 4	0,000	-0,131	-0,125	0,125	-0,131	-0,006
4	Angle error to Cam 1 - Lobe 5	0,000	-1,579	-0,125	0,125	-1,579	-1,454
5	Angle error to Cam 1 - Lobe 6	0,000	0,452	-0,125	0,125	0,452	0,327
6	Angle error to Cam 1 - Lobe 7	0,000	0,172	-0,125	0,125	0,172	0,047
7	Angle error to Cam 1 - Lobe 8	0,000	-0,466	-0,125	0,125	-0,466	-0,341
8	Angle error to Cam 1 - Lobe 9	0,000	0,167	-0,125	0,125	0,167	0,042
9	Angle error to Cam 1 - Lobe 10	0,000	0,034	-0,125	0,125	0,034	
10	Angle error to Cam 1 - Lobe 11	0,000	-1,569	-0,125	0,125	-1,569	-1,444
11	Angle error to Cam 1 - Lobe 12	0,000	0,407	-0,125	0,125	0,407	0,282
12	Angle error to Cam 1 - Lobe 13	0,000	-0,092	-0,125	0,125	-0,092	
13	Angle error to Cam 1 - Lobe 14	0,000	-1,212	-0,125	0,125	-1,212	-1,087
14	Angle error to Cam 1 - Lobe 15	0,000	0,235	-0,125	0,125	0,235	0,110
15	Angle error to Pin - Lobe 1	0,000	-0,093	-0,250	0,250	-0,093	
16	Angle error to Pin - Lobe 2	0,000	-0,936	-0,250	0,250	-0,936	-0,686
17	Angle error to Pin - Lobe 3	0,000	0,222	-0,250	0,250	0,222	
18	Angle error to Pin - Lobe 4	0,000	-0,224	-0,250	0,250	-0,224	
19	Angle error to Pin - Lobe 5	0,000	-1,672	-0,250	0,250	-1,672	-1,422
20	Angle error to Pin - Lobe 6	0,000	0,359	-0,250	0,250	0,359	0,109
21	Angle error to Pin - Lobe 7	0,000	0,079	-0,250	0,250	0,079	
22	Angle error to Pin - Lobe 8	0,000	-0,559	-0,250	0,250	-0,559	-0,309
23	Angle error to Pin - Lobe 9	0,000	0,074	-0,250	0,250	0,074	
24	Angle error to Pin - Lobe 10	0,000	-0,059	-0,250	0,250	-0,059	
25	Angle error to Pin - Lobe 11	0,000	-1,663	-0,250	0,250	-1,663	-1,413
26	Angle error to Pin - Lobe 12	0,000	0,314	-0,250	0,250	0,314	0,064
27	Angle error to Pin - Lobe 13	0,000	-0,185	-0,250	0,250	-0,185	
28	Angle error to Pin - Lobe 14	0,000	-1,305	-0,250	0,250	-1,305	-1,055
29	Angle error to Pin - Lobe 15	0,000	0,142	-0,250	0,250	0,142	
30	Angle of Cam 1 to ref.	127,800	127,707	127,550	128,050	-0,093	
31	BC Radius Error - Lobe 1	0,000	0,424	-0,100	0,100	0,424	0,324
32	BC Radius Error - Lobe 2	0,000	0,446	-0,100	0,100	0,446	0,346
33	BC Radius Error - Lobe 3	0,000	0,363	-0,100	0,100	0,363	0,263
34	BC Radius Error - Lobe 4	0,000	0,453	-0,100	0,100	0,453	0,353
35	BC Radius Error - Lobe 5	0,000	0,485	-0,100	0,100	0,485	0,385
36	BC Radius Error - Lobe 6	0,000	0,372	-0,100	0,100	0,372	0,272
37	BC Radius Error - Lobe 7	0,000	0,366	-0,100	0,100	0,366	0,266
38	BC Radius Error - Lobe 8	0,000	0,420	-0,100	0,100	0,420	0,320
39	BC Radius Error - Lobe 9	0,000	0,357	-0,100	0,100	0,357	0,257
40	BC Radius Error - Lobe 10	0,000	0,438	-0,100	0,100	0,438	0,338
41	BC Radius Error - Lobe 11	0,000	0,542	-0,100	0,100	0,542	0,442
42	BC Radius Error - Lobe 12	0,000	0,351	-0,100	0,100	0,351	0,251
43	BC Radius Error - Lobe 13	0,000	0,425	-0,100	0,100	0,425	0,325
44	BC Radius Error - Lobe 14	0,000	0,429	-0,100	0,100	0,429	0,329
45	BC Radius Error - Lobe 15	0,000	0,331	-0,100	0,100	0,331	0,231
46	BC Runout - Lobe 1	0,000	0,112	0,000	0,040	0,112	0,072
47	BC Runout - Lobe 2	0,000	0,079	0,000	0,040	0,079	0,039
48	BC Runout - Lobe 3	0,000	0,217	0,000	0,040	0,217	0,177



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	BC Runout - Lobe 4	0.000	0.089	0.000	0.040	0.089	0.049
2	BC Runout - Lobe 5	0.000	0.065	0.000	0.040	0.065	0.025
3	BC Runout - Lobe 6	0.000	0.234	0.000	0.040	0.234	0.194
4	BC Runout - Lobe 7	0.000	0.098	0.000	0.040	0.098	0.058
5	BC Runout - Lobe 8	0.000	0.095	0.000	0.040	0.095	0.055
6	BC Runout - Lobe 9	0.000	0.130	0.000	0.040	0.130	0.090
7	BC Runout - Lobe 10	0.000	0.135	0.000	0.040	0.135	0.095
8	BC Runout - Lobe 11	0.000	0.161	0.000	0.040	0.161	0.121
9	BC Runout - Lobe 12	0.000	0.253	0.000	0.040	0.253	0.213
10	BC Runout - Lobe 13	0.000	0.111	0.000	0.040	0.111	0.071
11	BC Runout - Lobe 14	0.000	0.072	0.000	0.040	0.072	0.032
12	BC Runout - Lobe 15	0.000	0.197	0.000	0.040	0.197	0.157
13	BC Velocity Error - Lobe 1	0.000	0.010	0.000	0.010	0.010	
14	BC Velocity Error - Lobe 2	0.000	0.016	0.000	0.010	0.016	0.006
15	BC Velocity Error - Lobe 3	0.000	0.009	0.000	0.010	0.009	
16	BC Velocity Error - Lobe 4	0.000	0.020	0.000	0.010	0.020	0.010
17	BC Velocity Error - Lobe 5	0.000	0.010	0.000	0.010	0.010	
18	BC Velocity Error - Lobe 6	0.000	0.014	0.000	0.010	0.014	0.004
19	BC Velocity Error - Lobe 7	0.000	0.010	0.000	0.010	0.010	0.000
20	BC Velocity Error - Lobe 8	0.000	0.014	0.000	0.010	0.014	0.004
21	BC Velocity Error - Lobe 9	0.000	0.012	0.000	0.010	0.012	0.002
22	BC Velocity Error - Lobe 10	0.000	0.010	0.000	0.010	0.010	0.000
23	BC Velocity Error - Lobe 11	0.000	0.022	0.000	0.010	0.022	0.012
24	BC Velocity Error - Lobe 12	0.000	0.020	0.000	0.010	0.020	0.010
25	BC Velocity Error - Lobe 13	0.000	0.011	0.000	0.010	0.011	0.001
26	BC Velocity Error - Lobe 14	0.000	0.012	0.000	0.010	0.012	0.002
27	BC Velocity Error - Lobe 15	0.000	0.014	0.000	0.010	0.014	0.004
28	Center Deviation - Lobe 1	0.000	-0.004	-0.003	0.020	-0.004	-0.001
29	Center Deviation - Lobe 2	0.000	0.001	-0.003	0.020	0.001	
30	Center Deviation - Lobe 3	0.000	-0.001	-0.003	0.020	-0.001	
31	Center Deviation - Lobe 4	0.000	-0.001	-0.003	0.020	-0.001	
32	Center Deviation - Lobe 5	0.000	0.002	-0.003	0.020	0.002	
33	Center Deviation - Lobe 6	0.000	0.000	-0.003	0.020	0.000	
34	Center Deviation - Lobe 7	0.000	-0.002	-0.003	0.020	-0.002	
35	Center Deviation - Lobe 8	0.000	0.001	-0.003	0.020	0.001	
36	Center Deviation - Lobe 9	0.000	-0.003	-0.003	0.020	-0.003	0.000
37	Center Deviation - Lobe 10	0.000	-0.004	-0.003	0.020	-0.004	-0.001
38	Center Deviation - Lobe 11	0.000	-0.002	-0.003	0.020	-0.002	
39	Center Deviation - Lobe 12	0.000	-0.004	-0.003	0.020	-0.004	-0.001
40	Center Deviation - Lobe 13	0.000	-0.002	-0.003	0.020	-0.002	
41	Center Deviation - Lobe 14	0.000	-0.005	-0.003	0.020	-0.005	-0.003
42	Center Deviation - Lobe 15	0.000	-0.002	-0.003	0.020	-0.002	
43	Cir_Mancal_A	0.000		0.000	0.010		
44	Dia_Mancal_A	84.953		-0.011	0.011		
45	Ecc-Ref [Gage] - A	0.000	0.078	0.000	0.035	0.078	0.043
46	Ecc-Ref [Gage] - B	0.000	0.042	0.000	0.035	0.042	0.007
47	Ecc-Ref [Gage] - C	0.000	0.020	0.000	0.035	0.020	
48	Ecc-Ref [Gage] - D	0.000	0.024	0.000	0.035	0.024	



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Ecc-Ref [Gage] - E	0.000	0.028	0.000	0.035	0.028	
2	Ecc-Ref [Gage] - F	0.000	0.045	0.000	0.035	0.045	0.010
3	Ecc-Ref [Part] - A	0.000	0.000	0.000	0.070	0.000	
4	Ecc-Ref [Part] - B	0.000	0.031	0.000	0.070	0.031	
5	Ecc-Ref [Part] - C	0.000	0.014	0.000	0.070	0.014	
6	Ecc-Ref [Part] - D	0.000	0.028	0.000	0.070	0.028	
7	Ecc-Ref [Part] - E	0.000	0.054	0.000	0.070	0.054	
8	Ecc-Ref [Part] - F	0.000	0.000	0.000	0.070	0.000	
9	Lift Difference Nose - Lobe 1	0.000	0.014	0.000	0.010	0.014	0.004
10	Lift Difference Nose - Lobe 2	0.000	0.020	0.000	0.010	0.020	0.010
11	Lift Difference Nose - Lobe 3	0.000	0.011	0.000	0.010	0.011	0.001
12	Lift Difference Nose - Lobe 4	0.000	0.015	0.000	0.010	0.015	0.005
13	Lift Difference Nose - Lobe 5	0.000	0.038	0.000	0.010	0.038	0.028
14	Lift Difference Nose - Lobe 6	0.000	0.012	0.000	0.010	0.012	0.002
15	Lift Difference Nose - Lobe 7	0.000	0.012	0.000	0.010	0.012	0.002
16	Lift Difference Nose - Lobe 8	0.000	0.019	0.000	0.010	0.019	0.009
17	Lift Difference Nose - Lobe 9	0.000	0.015	0.000	0.010	0.015	0.005
18	Lift Difference Nose - Lobe 10	0.000	0.014	0.000	0.010	0.014	0.004
19	Lift Difference Nose - Lobe 11	0.000	0.031	0.000	0.010	0.031	0.021
20	Lift Difference Nose - Lobe 12	0.000	0.013	0.000	0.010	0.013	0.003
21	Lift Difference Nose - Lobe 13	0.000	0.016	0.000	0.010	0.016	0.006
22	Lift Difference Nose - Lobe 14	0.000	0.050	0.000	0.010	0.050	0.040
23	Lift Difference Nose - Lobe 15	0.000	0.012	0.000	0.010	0.012	0.002
24	Lift Difference Ramp - Lobe 1	0.000	0.010	0.000	0.010	0.010	0.000
25	Lift Difference Ramp - Lobe 2	0.000	0.021	0.000	0.010	0.021	0.011
26	Lift Difference Ramp - Lobe 3	0.000	0.018	0.000	0.010	0.018	0.008
27	Lift Difference Ramp - Lobe 4	0.000	0.017	0.000	0.010	0.017	0.007
28	Lift Difference Ramp - Lobe 5	0.000	0.032	0.000	0.010	0.032	0.022
29	Lift Difference Ramp - Lobe 6	0.000	0.018	0.000	0.010	0.018	0.008
30	Lift Difference Ramp - Lobe 7	0.000	0.013	0.000	0.010	0.013	0.003
31	Lift Difference Ramp - Lobe 8	0.000	0.010	0.000	0.010	0.010	0.000
32	Lift Difference Ramp - Lobe 9	0.000	0.011	0.000	0.010	0.011	0.001
33	Lift Difference Ramp - Lobe 10	0.000	0.013	0.000	0.010	0.013	0.003
34	Lift Difference Ramp - Lobe 11	0.000	0.033	0.000	0.010	0.033	0.023
35	Lift Difference Ramp - Lobe 12	0.000	0.018	0.000	0.010	0.018	0.008
36	Lift Difference Ramp - Lobe 13	0.000	0.010	0.000	0.010	0.010	
37	Lift Difference Ramp - Lobe 14	0.000	0.020	0.000	0.010	0.020	0.010
38	Lift Difference Ramp - Lobe 15	0.000	0.024	0.000	0.010	0.024	0.014
39	Lift Error Nose - Lobe 1	0.000	0.151	0.000	0.100	0.151	0.051
40	Lift Error Nose - Lobe 2	0.000	0.320	0.000	0.100	0.320	0.220
41	Lift Error Nose - Lobe 3	0.000	0.113	0.000	0.100	0.113	0.013
42	Lift Error Nose - Lobe 4	0.000	0.152	0.000	0.100	0.152	0.052
43	Lift Error Nose - Lobe 5	0.000	0.636	0.000	0.100	0.636	0.536
44	Lift Error Nose - Lobe 6	0.000	0.114	0.000	0.100	0.114	0.014
45	Lift Error Nose - Lobe 7	0.000	0.046	0.000	0.100	0.046	
46	Lift Error Nose - Lobe 8	0.000	0.194	0.000	0.100	0.194	0.094
47	Lift Error Nose - Lobe 9	0.000	0.102	0.000	0.100	0.102	0.002
48	Lift Error Nose - Lobe 10	0.000	0.164	0.000	0.100	0.164	0.064



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Lift Error Nose - Lobe 11	0.000	0.562	0.000	0.100	0.562	0.462
2	Lift Error Nose - Lobe 12	0.000	0.219	0.000	0.100	0.219	0.119
3	Lift Error Nose - Lobe 13	0.000	0.132	0.000	0.100	0.132	0.032
4	Lift Error Nose - Lobe 14	0.000	0.458	0.000	0.100	0.458	0.358
5	Lift Error Nose - Lobe 15	0.000	0.130	0.000	0.100	0.130	0.030
6	Lift Error Ramp - Lobe 1	0.000	0.125	0.000	0.050	0.125	0.075
7	Lift Error Ramp - Lobe 2	0.000	0.228	0.000	0.050	0.228	0.178
8	Lift Error Ramp - Lobe 3	0.000	0.110	0.000	0.050	0.110	0.060
9	Lift Error Ramp - Lobe 4	0.000	0.162	0.000	0.050	0.162	0.112
10	Lift Error Ramp - Lobe 5	0.000	0.442	0.000	0.050	0.442	0.392
11	Lift Error Ramp - Lobe 6	0.000	0.112	0.000	0.050	0.112	0.062
12	Lift Error Ramp - Lobe 7	0.000	0.054	0.000	0.050	0.054	0.004
13	Lift Error Ramp - Lobe 8	0.000	0.171	0.000	0.050	0.171	0.121
14	Lift Error Ramp - Lobe 9	0.000	0.080	0.000	0.050	0.080	0.030
15	Lift Error Ramp - Lobe 10	0.000	0.155	0.000	0.050	0.155	0.105
16	Lift Error Ramp - Lobe 11	0.000	0.421	0.000	0.050	0.421	0.371
17	Lift Error Ramp - Lobe 12	0.000	0.166	0.000	0.050	0.166	0.116
18	Lift Error Ramp - Lobe 13	0.000	0.129	0.000	0.050	0.129	0.079
19	Lift Error Ramp - Lobe 14	0.000	0.300	0.000	0.050	0.300	0.250
20	Lift Error Ramp - Lobe 15	0.000	0.080	0.000	0.050	0.080	0.030
21	Meas Diam - A	84.953	85.497	0.015	0.030	0.544	85.467
22	Meas Diam - B	84.953	85.478	0.015	0.030	0.525	85.448
23	Meas Diam - C	84.953	85.444	0.015	0.030	0.491	85.414
24	Meas Diam - D	84.953	85.470	0.015	0.030	0.517	85.440
25	Meas Diam - E	84.953	85.460	0.015	0.030	0.507	85.430
26	Meas Diam - F	84.953	85.495	0.015	0.030	0.542	85.465
27	Parallelism - Lobe 1	0.000	0.013	-0.015	0.015	0.013	
28	Parallelism - Lobe 2	0.000	0.015	-0.015	0.015	0.015	
29	Parallelism - Lobe 3	0.000	0.014	-0.015	0.015	0.014	
30	Parallelism - Lobe 4	0.000	0.017	-0.015	0.015	0.017	0.002
31	Parallelism - Lobe 5	0.000	0.012	-0.015	0.015	0.012	
32	Parallelism - Lobe 6	0.000	0.013	-0.015	0.015	0.013	
33	Parallelism - Lobe 7	0.000	0.010	-0.015	0.015	0.010	
34	Parallelism - Lobe 8	0.000	0.012	-0.015	0.015	0.012	
35	Parallelism - Lobe 9	0.000	0.018	-0.015	0.015	0.018	0.003
36	Parallelism - Lobe 10	0.000	0.027	-0.015	0.015	0.027	0.012
37	Parallelism - Lobe 11	0.000	0.006	-0.015	0.015	0.006	
38	Parallelism - Lobe 12	0.000	0.019	-0.015	0.015	0.019	0.004
39	Parallelism - Lobe 13	0.000	0.027	-0.015	0.015	0.027	0.012
40	Parallelism - Lobe 14	0.000	0.021	-0.015	0.015	0.021	0.006
41	Parallelism - Lobe 15	0.000	0.023	-0.015	0.015	0.023	0.008
42	Roundness - A	0.000	0.049	0.000	0.010	0.049	0.039
43	Roundness - B	0.000	0.037	0.000	0.010	0.037	0.027
44	Roundness - C	0.000	0.038	0.000	0.010	0.038	0.028
45	Roundness - D	0.000	0.050	0.000	0.010	0.050	0.040
46	Roundness - E	0.000	0.044	0.000	0.010	0.044	0.034
47	Roundness - F	0.000	0.053	0.000	0.010	0.053	0.043
48	Runout - A	0.000	0.049	0.000	0.100	0.049	



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Runout - B	0.000	0.087	0.000	0.100	0.087	
2	Runout - C	0.000	0.049	0.000	0.100	0.049	
3	Runout - D	0.000	0.079	0.000	0.100	0.079	
4	Runout - E	0.000	0.124	0.000	0.100	0.124	0.024
5	Runout - F	0.000	0.053	0.000	0.100	0.053	
6	Taper Error - Lobe 1	0.000	-0.003	-0.020	0.020	-0.003	
7	Taper Error - Lobe 2	0.000	0.019	-0.020	0.020	0.019	
8	Taper Error - Lobe 3	0.000	0.005	-0.020	0.020	0.005	
9	Taper Error - Lobe 4	0.000	-0.003	-0.020	0.020	-0.003	
10	Taper Error - Lobe 5	0.000	0.013	-0.020	0.020	0.013	
11	Taper Error - Lobe 6	0.000	0.003	-0.020	0.020	0.003	
12	Taper Error - Lobe 7	0.000	-0.008	-0.020	0.020	-0.008	
13	Taper Error - Lobe 8	0.000	0.006	-0.020	0.020	0.006	
14	Taper Error - Lobe 9	0.000	0.003	-0.020	0.020	0.003	
15	Taper Error - Lobe 10	0.000	-0.009	-0.020	0.020	-0.009	
16	Taper Error - Lobe 11	0.000	0.000	-0.020	0.020	0.000	
17	Taper Error - Lobe 12	0.000	-0.002	-0.020	0.020	-0.002	
18	Taper Error - Lobe 13	0.000	-0.006	-0.020	0.020	-0.006	
19	Taper Error - Lobe 14	0.000	-0.010	-0.020	0.020	-0.010	
20	Taper Error - Lobe 15	0.000	-0.009	-0.020	0.020	-0.009	
21	Angle error to Cam 11 A6 - Lobe 1	180.000	0.000	-0.250	0.250	-180.000	
22	Angle error to Cam 11 A6 - Lobe 2	300.000	289.904	-0.250	0.250	-10.096	289.654
23	Angle error to Cam 11 A6 - Lobe 3	60.000	76.304	-0.250	0.250	16.304	76.054
24	Angle error to Cam 11 A6 - Lobe 4	240.000	222.694	-0.250	0.250	-17.306	222.444
25	Angle error to Cam 11 A6 - Lobe 5	120.000	152.600	-0.250	0.250	32.600	152.350
26	Angle error to Cam 11 A6 - Lobe 6	0.000	-999.900	-0.250	0.250	-999.900	-999.650
27	Angle error to UZ - Lobe 1	306.200	306.177	-0.100	0.100	-0.023	306.077
28	Angle error to UZ - Lobe 2	236.100	236.081	-0.100	0.100	-0.019	235.981
29	Angle error to UZ - Lobe 3	22.500	22.481	-0.100	0.100	-0.019	22.381
30	Angle error to UZ - Lobe 4	168.900	168.870	-0.100	0.100	-0.030	168.770
31	Angle error to UZ - Lobe 5	98.800	98.777	-0.100	0.100	-0.023	98.677
32	Angle error to UZ - Lobe 6	128.750	-999.900	-0.100	0.100	-1128.650	-999.800
33	Angulo entre as superficies	40.000	-999.900	-0.125	0.125	-1039.900	-999.775
34	BC Radius Error - Lobe 1	25.000	25.057	-0.100	0.100	0.057	24.957
35	BC Radius Error - Lobe 2	25.000	25.036	-0.100	0.100	0.036	24.936
36	BC Radius Error - Lobe 3	25.000	25.029	-0.100	0.100	0.029	24.929
37	BC Radius Error - Lobe 4	25.000	25.023	-0.100	0.100	0.023	24.923
38	BC Radius Error - Lobe 5	25.000	25.025	-0.100	0.100	0.025	24.925
39	BC Radius Error - Lobe 6	25.000	-999.900	-0.100	0.100	-1024.900	-999.800
40	BC Runout - Lobe 1	0.000	0.003	0.000	0.040	0.003	
41	BC Runout - Lobe 2	0.000	0.004	0.000	0.040	0.004	
42	BC Runout - Lobe 3	0.000	0.002	0.000	0.040	0.002	
43	BC Runout - Lobe 4	0.000	0.005	0.000	0.040	0.005	
44	BC Runout - Lobe 5	0.000	0.019	0.000	0.040	0.019	
45	BC Runout - Lobe 6	0.000	-999.900	0.000	0.040	-999.900	-999.900
46	Concave/Convex - Lobe 1	0.000	0.001	-0.005	0.005	0.001	
47	Concave/Convex - Lobe 2	0.000	0.001	-0.005	0.005	0.001	
48	Concave/Convex - Lobe 3	0.000	0.001	-0.005	0.005	0.001	



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Concave/Convex - Lobe 4	0.000	0.001	-0.005	0.005	0.001	
2	Concave/Convex - Lobe 5	0.000	0.001	-0.005	0.005	0.001	
3	Concave/Convex - Lobe 6	0.000	-999.900	-0.005	0.005	-999.900	-999.895
4	Cylindricity - A	0.000	0.008	0.000	0.020	0.008	
5	Cylindricity - B	0.000	0.002	0.000	0.020	0.002	
6	Cylindricity - C	0.000	0.002	0.000	0.020	0.002	
7	Cylindricity - D	0.000	0.006	0.000	0.020	0.006	
8	Cylindricity - E	0.000	0.007	0.000	0.020	0.007	
9	Cylindricity - F	0.000	0.015	0.000	0.020	0.015	
10	Cylindricity - G	0.000	0.014	0.000	0.020	0.014	
11	Diametro A [Center]	35.967		-0.008	0.008		
12	Diametro A [Inf]	35.967		-0.008	0.008		
13	Diametro A [Sup]	35.967		-0.008	0.008		
14	Diametro B [Center]	35.967		-0.008	0.008		
15	Diametro B [Inf]	35.967		-0.008	0.008		
16	Diametro B [Sup]	35.967		-0.008	0.008		
17	Diametro C [Center]	35.967		-0.008	0.008		
18	Diametro C [Inf]	35.967		-0.008	0.008		
19	Diametro C [Sup]	35.967		-0.008	0.008		
20	Diametro D [Center]	35.967		-0.008	0.008		
21	Diametro D [Inf]	35.967		-0.008	0.008		
22	Diametro D [Sup]	35.967		-0.008	0.008		
23	Diametro E [Center]	35.967		-0.008	0.008		
24	Diametro E [Inf]	35.967		-0.008	0.008		
25	Diametro E [Sup]	35.967		-0.008	0.008		
26	Diametro F [Center]	47.967		-0.008	0.008		
27	Diametro F [Inf]	47.967		-0.008	0.008		
28	Diametro F [Sup]	47.967		-0.008	0.008		
29	Diametro G [Center]	47.967		-0.008	0.008		
30	Diametro G [Inf]	47.967		-0.008	0.008		
31	Diametro G [Sup]	47.967		-0.008	0.008		
32	Distancia U para o Eixo de Rot	39.700	-999.900	-0.050	0.050	-1039.600	-999.850
33	Distancia Z para o Eixo de Rot	39.700	-999.900	-0.050	0.050	-1039.600	-999.850
34	Lift Difference - Lobe 1	0.000	0.003	0.000	0.010	0.003	
35	Lift Difference - Lobe 2	0.000	0.003	0.000	0.010	0.003	
36	Lift Difference - Lobe 3	0.000	0.003	0.000	0.010	0.003	
37	Lift Difference - Lobe 4	0.000	0.003	0.000	0.010	0.003	
38	Lift Difference - Lobe 5	0.000	0.003	0.000	0.010	0.003	
39	Lift Difference - Lobe 6	0.000	-999.900	-0.010	0.010	-999.900	-999.890
40	Lift Error BC - Lobe 1	0.000	-0.002	-0.025	0.025	-0.002	
41	Lift Error BC - Lobe 2	0.000	-0.002	-0.025	0.025	-0.002	
42	Lift Error BC - Lobe 3	0.000	-0.001	-0.025	0.025	-0.001	
43	Lift Error BC - Lobe 4	0.000	0.003	-0.025	0.025	0.003	
44	Lift Error BC - Lobe 5	0.000	0.010	-0.025	0.025	0.010	
45	Lift Error BC - Lobe 6	0.000	-999.900	-0.025	0.025	-999.900	-999.875
46	Lift Error Closing Ramp - Lobe 1	0.000	0.039	-0.050	0.050	0.039	
47	Lift Error Closing Ramp - Lobe 2	0.000	0.030	-0.050	0.050	0.030	
48	Lift Error Closing Ramp - Lobe 3	0.000	0.030	-0.050	0.050	0.030	



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Lift Error Closing Ramp - Lobe 4	0.000	0.031	-0.050	0.050	0.031	
2	Lift Error Closing Ramp - Lobe 5	0.000	0.032	-0.050	0.050	0.032	
3	Lift Error Closing Ramp - Lobe 6	0.000	-999.900	-0.050	0.050	-999.900	-999.850
4	Lift Error Nose - Lobe 1	0.000	0.033	-0.050	0.050	0.033	
5	Lift Error Nose - Lobe 2	0.000	0.025	-0.050	0.050	0.025	
6	Lift Error Nose - Lobe 3	0.000	0.024	-0.050	0.050	0.024	
7	Lift Error Nose - Lobe 4	0.000	0.025	-0.050	0.050	0.025	
8	Lift Error Nose - Lobe 5	0.000	0.032	-0.050	0.050	0.032	
9	Lift Error Nose - Lobe 6	0.000	-999.900	-0.050	0.050	-999.900	-999.850
10	Lift Error Opening Ramp - Lobe 1	0.000	0.041	-0.100	0.100	0.041	
11	Lift Error Opening Ramp - Lobe 2	0.000	0.032	-0.100	0.100	0.032	
12	Lift Error Opening Ramp - Lobe 3	0.000	0.031	-0.100	0.100	0.031	
13	Lift Error Opening Ramp - Lobe 4	0.000	0.032	-0.100	0.100	0.032	
14	Lift Error Opening Ramp - Lobe 5	0.000	0.034	-0.100	0.100	0.034	
15	Lift Error Opening Ramp - Lobe 6	0.000	-999.900	-0.025	0.025	-999.900	-999.875
16	Meas Diam [Center]- A	36.000	35.958	-0.050	-0.025	-0.042	35.983
17	Meas Diam [Center]- B	36.000	35.963	-0.050	-0.025	-0.037	35.988
18	Meas Diam [Center]- C	36.000	35.964	-0.050	-0.025	-0.036	35.989
19	Meas Diam [Center]- D	36.000	35.958	-0.050	-0.025	-0.042	35.983
20	Meas Diam [Center]- E	36.000	35.962	-0.050	-0.025	-0.038	35.987
21	Meas Diam [Center]- F	48.000	47.965	-0.050	-0.025	-0.035	47.990
22	Meas Diam [Center]- G	48.000	47.965	-0.050	-0.025	-0.035	47.990
23	Meas Diam [Inf]- A	36.000	35.966	-0.050	-0.025	-0.034	35.991
24	Meas Diam [Inf]- B	36.000	35.964	-0.050	-0.025	-0.036	35.989
25	Meas Diam [Inf]- C	36.000	35.962	-0.050	-0.025	-0.038	35.987
26	Meas Diam [Inf]- D	36.000	35.965	-0.050	-0.025	-0.035	35.990
27	Meas Diam [Inf]- E	36.000	35.971	-0.050	-0.025	-0.029	35.996
28	Meas Diam [Inf]- F	48.000	47.991	-0.050	-0.025	-0.009	48.016
29	Meas Diam [Inf]- G	48.000	47.990	-0.050	-0.025	-0.010	48.015
30	Meas Diam [Sup]- A	36.000	35.954	-0.050	-0.025	-0.046	35.979
31	Meas Diam [Sup]- B	36.000	35.961	-0.050	-0.025	-0.039	35.986
32	Meas Diam [Sup]- C	36.000	35.963	-0.050	-0.025	-0.037	35.988
33	Meas Diam [Sup]- D	36.000	35.956	-0.050	-0.025	-0.044	35.981
34	Meas Diam [Sup]- E	36.000	35.961	-0.050	-0.025	-0.039	35.986
35	Meas Diam [Sup]- F	48.000	47.965	-0.050	-0.025	-0.035	47.990
36	Meas Diam [Sup]- G	48.000	47.966	-0.050	-0.025	-0.034	47.991
37	Parallelism - A	0.000	0.000	0.000	0.015	0.000	
38	Parallelism - B	0.000	0.001	0.000	0.015	0.001	
39	Parallelism - C	0.000	0.000	0.000	0.015	0.000	
40	Parallelism - D	0.000	0.000	0.000	0.015	0.000	
41	Parallelism - E	0.000	0.000	0.000	0.015	0.000	
42	Parallelism - F	0.000	0.000	0.000	0.015	0.000	
43	Parallelism - G	0.000	0.001	0.000	0.015	0.001	
44	Parallelism - Lobe 1	0.000	0.001	0.000	0.020	0.001	
45	Parallelism - Lobe 2	0.000	0.001	0.000	0.020	0.001	
46	Parallelism - Lobe 3	0.000	0.000	0.000	0.020	0.000	
47	Parallelism - Lobe 4	0.000	0.001	0.000	0.020	0.001	
48	Parallelism - Lobe 5	0.000	0.001	0.000	0.020	0.001	



Part name
C.C. / Device
Part ident
Time/Date

3445 / Adcole
/3445/Adcole

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Parallelism - Lobe 6	0.000	-999.900	0.000	0.020	-999.900	-999.900
2	Runout [Adj] - A	0.000	0.002	0.000	0.120	0.002	
3	Runout [Adj] - B	0.000	0.010	0.000	0.120	0.010	
4	Runout [Adj] - C	0.000	0.026	0.000	0.120	0.026	
5	Runout [Adj] - D	0.000	0.034	0.000	0.120	0.034	
6	Runout [Adj] - E	0.000	0.022	0.000	0.120	0.022	
7	Runout [Adj] - F	0.000	0.004	0.000	0.120	0.004	
8	Runout [Adj] - G	0.000	0.002	0.000	0.120	0.002	
9	Runout [B-C] - A	0.000	0.002	0.000	0.030	0.002	
10	Runout [E-F] - G	0.000	0.002	0.000	0.030	0.002	
11	Runout [Ext] - B	0.000	0.005	0.000	0.030	0.005	
12	Runout [Ext] - C	0.000	0.006	0.000	0.030	0.006	
13	Runout [Ext] - D	0.000	0.011	0.000	0.030	0.011	
14	Runout [Ext] - E	0.000	0.004	0.000	0.030	0.004	
15	Runout [Ext] - F	0.000	0.002	0.000	0.030	0.002	
16	Runout [Gage] - A	0.000	0.016	0.000	0.050	0.016	
17	Runout [Gage] - B	0.000	0.015	0.000	0.050	0.015	
18	Runout [Gage] - C	0.000	0.024	0.000	0.050	0.024	
19	Runout [Gage] - D	0.000	0.011	0.000	0.030	0.011	
20	Runout [Gage] - E	0.000	0.024	0.000	0.050	0.024	
21	Runout [Gage] - F	0.000	0.045	0.000	0.050	0.045	
22	Runout [Gage] - G	0.000	0.048	0.000	0.050	0.048	