



Part name
C.C. / Device
Part ident
Time/Date

1865230 / OP_120
/3445/Adcole
18/03/2026 13:41

	CHARACTERISTIC NAME	NOMINAL VALUE	MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Angle error to Cam 1 - Lobe 2	0,000	-0,008	-0,125	0,125	-0,008	
2	Angle error to Cam 1 - Lobe 3	0,000	-0,023	-0,125	0,125	-0,023	
3	Angle error to Cam 1 - Lobe 4	0,000	-0,017	-0,125	0,125	-0,017	
4	Angle error to Cam 1 - Lobe 5	0,000	-0,004	-0,125	0,125	-0,004	
5	Angle error to Cam 1 - Lobe 6	0,000	-0,028	-0,125	0,125	-0,028	
6	Angle error to Cam 1 - Lobe 7	0,000	-0,023	-0,125	0,125	-0,023	
7	Angle error to Cam 1 - Lobe 8	0,000	-0,008	-0,125	0,125	-0,008	
8	Angle error to Cam 1 - Lobe 9	0,000	-0,009	-0,125	0,125	-0,009	
9	Angle error to Cam 1 - Lobe 10	0,000	-0,009	-0,125	0,125	-0,009	
10	Angle error to Cam 1 - Lobe 11	0,000	0,002	-0,125	0,125	0,002	
11	Angle error to Cam 1 - Lobe 12	0,000	-0,007	-0,125	0,125	-0,007	
12	Angle error to Pin - Lobe 1	0,000	0,043	-0,250	0,250	0,043	
13	Angle error to Pin - Lobe 2	0,000	0,035	-0,250	0,250	0,035	
14	Angle error to Pin - Lobe 3	0,000	0,020	-0,250	0,250	0,020	
15	Angle error to Pin - Lobe 4	0,000	0,026	-0,250	0,250	0,026	
16	Angle error to Pin - Lobe 5	0,000	0,039	-0,250	0,250	0,039	
17	Angle error to Pin - Lobe 6	0,000	0,015	-0,250	0,250	0,015	
18	Angle error to Pin - Lobe 7	0,000	0,020	-0,250	0,250	0,020	
19	Angle error to Pin - Lobe 8	0,000	0,035	-0,250	0,250	0,035	
20	Angle error to Pin - Lobe 9	0,000	0,034	-0,250	0,250	0,034	
21	Angle error to Pin - Lobe 10	0,000	0,034	-0,250	0,250	0,034	
22	Angle error to Pin - Lobe 11	0,000	0,045	-0,250	0,250	0,045	
23	Angle error to Pin - Lobe 12	0,000	0,036	-0,250	0,250	0,036	
24	Angle of Cam 1 to ref.	127,900	127,943	255,550	256,050	0,043	-127,607
25	BC Radius Error - Lobe 1	0,000	0,026	-0,100	0,100	0,026	
26	BC Radius Error - Lobe 2	0,000	0,027	-0,100	0,100	0,027	
27	BC Radius Error - Lobe 3	0,000	0,022	-0,100	0,100	0,022	
28	BC Radius Error - Lobe 4	0,000	0,020	-0,100	0,100	0,020	
29	BC Radius Error - Lobe 5	0,000	0,014	-0,100	0,100	0,014	
30	BC Radius Error - Lobe 6	0,000	0,017	-0,100	0,100	0,017	
31	BC Radius Error - Lobe 7	0,000	0,007	-0,100	0,100	0,007	
32	BC Radius Error - Lobe 8	0,000	0,003	-0,100	0,100	0,003	
33	BC Radius Error - Lobe 9	0,000	-0,012	-0,100	0,100	-0,012	
34	BC Radius Error - Lobe 10	0,000	-0,004	-0,100	0,100	-0,004	
35	BC Radius Error - Lobe 11	0,000	0,003	-0,100	0,100	0,003	
36	BC Radius Error - Lobe 12	0,000	0,002	-0,100	0,100	0,002	
37	BC Runout - Lobe 1	0,000	0,012	0,000	0,040	0,012	
38	BC Runout - Lobe 2	0,000	0,002	0,000	0,040	0,002	
39	BC Runout - Lobe 3	0,000	0,004	0,000	0,040	0,004	
40	BC Runout - Lobe 4	0,000	0,005	0,000	0,040	0,005	
41	BC Runout - Lobe 5	0,000	0,003	0,000	0,040	0,003	
42	BC Runout - Lobe 6	0,000	0,006	0,000	0,040	0,006	
43	BC Runout - Lobe 7	0,000	0,006	0,000	0,040	0,006	
44	BC Runout - Lobe 8	0,000	0,003	0,000	0,040	0,003	
45	BC Runout - Lobe 9	0,000	0,002	0,000	0,040	0,002	
46	BC Runout - Lobe 10	0,000	0,003	0,000	0,040	0,003	
47	BC Runout - Lobe 11	0,000	0,003	0,000	0,040	0,003	
48	BC Runout - Lobe 12	0,000	0,007	0,000	0,040	0,007	



Part name
C.C. / Device
Part ident
Time/Date

1865230 / OP_120
/3445/Adcole
18/03/2026 13:41

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	BC Velocity Error - Lobe 1	0.000	0.001	0.000	0.010	0.001	
2	BC Velocity Error - Lobe 2	0.000	0.000	0.000	0.010	0.000	
3	BC Velocity Error - Lobe 3	0.000	0.000	0.000	0.010	0.000	
4	BC Velocity Error - Lobe 4	0.000	0.000	0.000	0.010	0.000	
5	BC Velocity Error - Lobe 5	0.000	0.000	0.000	0.010	0.000	
6	BC Velocity Error - Lobe 6	0.000	0.000	0.000	0.010	0.000	
7	BC Velocity Error - Lobe 7	0.000	0.000	0.000	0.010	0.000	
8	BC Velocity Error - Lobe 8	0.000	0.000	0.000	0.010	0.000	
9	BC Velocity Error - Lobe 9	0.000	0.000	0.000	0.010	0.000	
10	BC Velocity Error - Lobe 10	0.000	0.000	0.000	0.010	0.000	
11	BC Velocity Error - Lobe 11	0.000	0.000	0.000	0.010	0.000	
12	BC Velocity Error - Lobe 12	0.000	0.001	0.000	0.010	0.001	
13	Center Deviation - Lobe 1	0.000	0.000	-0.003	0.010	0.000	
14	Center Deviation - Lobe 2	0.000	-0.001	-0.003	0.010	-0.001	
15	Center Deviation - Lobe 3	0.000	0.000	-0.003	0.010	0.000	
16	Center Deviation - Lobe 4	0.000	-0.001	-0.003	0.010	-0.001	
17	Center Deviation - Lobe 5	0.000	0.000	-0.003	0.010	0.000	
18	Center Deviation - Lobe 6	0.000	0.000	-0.003	0.010	0.000	
19	Center Deviation - Lobe 7	0.000	0.000	-0.003	0.010	0.000	
20	Center Deviation - Lobe 8	0.000	-0.001	-0.003	0.010	-0.001	
21	Center Deviation - Lobe 9	0.000	-0.001	-0.003	0.010	-0.001	
22	Center Deviation - Lobe 10	0.000	-0.001	-0.003	0.010	-0.001	
23	Center Deviation - Lobe 11	0.000	-0.001	-0.003	0.010	-0.001	
24	Center Deviation - Lobe 12	0.000	-0.001	-0.003	0.010	-0.001	
25	Diametro_Mancal_A	84.953	84.973	84.968	84.983	0.020	
26	Diametro_Mancal_B	84.953	84.974	84.968	84.983	0.021	
27	Diametro_Mancal_C	84.953	84.975	84.968	84.983	0.022	
28	Diametro_Mancal_D	84.953	84.971	84.968	84.983	0.018	
29	Diametro_Mancal_E	84.953	84.972	84.968	84.983	0.019	
30	Diametro_Mancal_F	84.953	84.969	84.968	84.983	0.016	
31	Diametro_Mancal_G	84.953	84.972	84.968	84.983	0.019	
32	Ecc-Ref [Gage] - A	0.000	0.018	0.000	0.035	0.018	
33	Ecc-Ref [Gage] - B	0.000	0.020	0.000	0.035	0.020	
34	Ecc-Ref [Gage] - C	0.000	0.015	0.000	0.035	0.015	
35	Ecc-Ref [Gage] - D	0.000	0.006	0.000	0.035	0.006	
36	Ecc-Ref [Gage] - E	0.000	0.005	0.000	0.035	0.005	
37	Ecc-Ref [Gage] - F	0.000	0.004	0.000	0.035	0.004	
38	Ecc-Ref [Gage] - G	0.000	0.005	0.000	0.035	0.005	
39	Ecc-Ref [Part] - A	0.000	0.000	0.000	0.070	0.000	
40	Ecc-Ref [Part] - B	0.000	0.015	0.000	0.070	0.015	
41	Ecc-Ref [Part] - C	0.000	0.015	0.000	0.070	0.015	
42	Ecc-Ref [Part] - D	0.000	0.011	0.000	0.070	0.011	
43	Ecc-Ref [Part] - E	0.000	0.009	0.000	0.070	0.009	
44	Ecc-Ref [Part] - F	0.000	0.005	0.000	0.070	0.005	
45	Ecc-Ref [Part] - G	0.000	0.000	0.000	0.070	0.000	
46	Lift Difference Nose - Lobe 1	0.000	0.002	0.000	0.010	0.002	
47	Lift Difference Nose - Lobe 2	0.000	0.002	0.000	0.010	0.002	
48	Lift Difference Nose - Lobe 3	0.000	0.002	0.000	0.010	0.002	



Part name
C.C. / Device
Part ident
Time/Date

1865230 / OP_120
/3445/Adcole
18/03/2026 13:41

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Lift Difference Nose - Lobe 4	0.000	0.002	0.000	0.010	0.002	
2	Lift Difference Nose - Lobe 5	0.000	0.002	0.000	0.010	0.002	
3	Lift Difference Nose - Lobe 6	0.000	0.002	0.000	0.010	0.002	
4	Lift Difference Nose - Lobe 7	0.000	0.002	0.000	0.010	0.002	
5	Lift Difference Nose - Lobe 8	0.000	0.002	0.000	0.010	0.002	
6	Lift Difference Nose - Lobe 9	0.000	0.002	0.000	0.010	0.002	
7	Lift Difference Nose - Lobe 10	0.000	0.002	0.000	0.010	0.002	
8	Lift Difference Nose - Lobe 11	0.000	0.002	0.000	0.010	0.002	
9	Lift Difference Nose - Lobe 12	0.000	0.003	0.000	0.010	0.003	
10	Lift Difference Ramp - Lobe 1	0.000	0.004	0.000	0.010	0.004	
11	Lift Difference Ramp - Lobe 2	0.000	0.003	0.000	0.010	0.003	
12	Lift Difference Ramp - Lobe 3	0.000	0.003	0.000	0.010	0.003	
13	Lift Difference Ramp - Lobe 4	0.000	0.003	0.000	0.010	0.003	
14	Lift Difference Ramp - Lobe 5	0.000	0.002	0.000	0.010	0.002	
15	Lift Difference Ramp - Lobe 6	0.000	0.004	0.000	0.010	0.004	
16	Lift Difference Ramp - Lobe 7	0.000	0.002	0.000	0.010	0.002	
17	Lift Difference Ramp - Lobe 8	0.000	0.002	0.000	0.010	0.002	
18	Lift Difference Ramp - Lobe 9	0.000	0.002	0.000	0.010	0.002	
19	Lift Difference Ramp - Lobe 10	0.000	0.002	0.000	0.010	0.002	
20	Lift Difference Ramp - Lobe 11	0.000	0.003	0.000	0.010	0.003	
21	Lift Difference Ramp - Lobe 12	0.000	0.004	0.000	0.010	0.004	
22	Lift Error Nose - Lobe 1	0.000	0.011	0.000	0.100	0.011	
23	Lift Error Nose - Lobe 2	0.000	0.024	0.000	0.100	0.024	
24	Lift Error Nose - Lobe 3	0.000	0.016	0.000	0.100	0.016	
25	Lift Error Nose - Lobe 4	0.000	0.014	0.000	0.100	0.014	
26	Lift Error Nose - Lobe 5	0.000	0.014	0.000	0.100	0.014	
27	Lift Error Nose - Lobe 6	0.000	0.016	0.000	0.100	0.016	
28	Lift Error Nose - Lobe 7	0.000	0.012	0.000	0.100	0.012	
29	Lift Error Nose - Lobe 8	0.000	0.013	0.000	0.100	0.013	
30	Lift Error Nose - Lobe 9	0.000	0.013	0.000	0.100	0.013	
31	Lift Error Nose - Lobe 10	0.000	0.015	0.000	0.100	0.015	
32	Lift Error Nose - Lobe 11	0.000	0.018	0.000	0.100	0.018	
33	Lift Error Nose - Lobe 12	0.000	0.022	0.000	0.100	0.022	
34	Lift Error Ramp - Lobe 1	0.000	0.020	0.000	0.050	0.020	
35	Lift Error Ramp - Lobe 2	0.000	0.032	0.000	0.050	0.032	
36	Lift Error Ramp - Lobe 3	0.000	0.024	0.000	0.050	0.024	
37	Lift Error Ramp - Lobe 4	0.000	0.021	0.000	0.050	0.021	
38	Lift Error Ramp - Lobe 5	0.000	0.020	0.000	0.050	0.020	
39	Lift Error Ramp - Lobe 6	0.000	0.026	0.000	0.050	0.026	
40	Lift Error Ramp - Lobe 7	0.000	0.018	0.000	0.050	0.018	
41	Lift Error Ramp - Lobe 8	0.000	0.018	0.000	0.050	0.018	
42	Lift Error Ramp - Lobe 9	0.000	0.019	0.000	0.050	0.019	
43	Lift Error Ramp - Lobe 10	0.000	0.020	0.000	0.050	0.020	
44	Lift Error Ramp - Lobe 11	0.000	0.028	0.000	0.050	0.028	
45	Lift Error Ramp - Lobe 12	0.000	0.033	0.000	0.050	0.033	
46	Parallelism - Lobe 1	0.000	0.003	-0.015	0.015	0.003	
47	Parallelism - Lobe 2	0.000	0.002	-0.015	0.015	0.002	
48	Parallelism - Lobe 3	0.000	0.001	-0.015	0.015	0.001	



Part name
C.C. / Device
Part ident
Time/Date

1865230 / OP_120
/3445/Adcole
18/03/2026 13:41

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Parallelism - Lobe 4	0.000	0.001	-0.015	0.015	0.001	
2	Parallelism - Lobe 5	0.000	0.002	-0.015	0.015	0.002	
3	Parallelism - Lobe 6	0.000	0.002	-0.015	0.015	0.002	
4	Parallelism - Lobe 7	0.000	0.002	-0.015	0.015	0.002	
5	Parallelism - Lobe 8	0.000	0.002	-0.015	0.015	0.002	
6	Parallelism - Lobe 9	0.000	0.003	-0.015	0.015	0.003	
7	Parallelism - Lobe 10	0.000	0.002	-0.015	0.015	0.002	
8	Parallelism - Lobe 11	0.000	0.002	-0.015	0.015	0.002	
9	Parallelism - Lobe 12	0.000	0.002	-0.015	0.015	0.002	
10	Roundness - A	0.000	0.001	0.000	0.010	0.001	
11	Roundness - B	0.000	0.001	0.000	0.010	0.001	
12	Roundness - C	0.000	0.001	0.000	0.010	0.001	
13	Roundness - D	0.000	0.002	0.000	0.010	0.002	
14	Roundness - E	0.000	0.001	0.000	0.010	0.001	
15	Roundness - F	0.000	0.001	0.000	0.010	0.001	
16	Roundness - G	0.000	0.003	0.000	0.010	0.003	
17	Runout - A	0.000	0.001	0.000	0.100	0.001	
18	Runout - B	0.000	0.029	0.000	0.100	0.029	
19	Runout - C	0.000	0.031	0.000	0.100	0.031	
20	Runout - D	0.000	0.023	0.000	0.100	0.023	
21	Runout - E	0.000	0.018	0.000	0.100	0.018	
22	Runout - F	0.000	0.011	0.000	0.100	0.011	
23	Runout - G	0.000	0.003	0.000	0.100	0.003	
24	Taper Error - Lobe 1	0.000	-0.002	-0.020	0.020	-0.002	
25	Taper Error - Lobe 2	0.000	-0.003	-0.020	0.020	-0.003	
26	Taper Error - Lobe 3	0.000	-0.001	-0.020	0.020	-0.001	
27	Taper Error - Lobe 4	0.000	-0.002	-0.020	0.020	-0.002	
28	Taper Error - Lobe 5	0.000	0.000	-0.020	0.020	0.000	
29	Taper Error - Lobe 6	0.000	-0.001	-0.020	0.020	-0.001	
30	Taper Error - Lobe 7	0.000	0.000	-0.020	0.020	0.000	
31	Taper Error - Lobe 8	0.000	-0.001	-0.020	0.020	-0.001	
32	Taper Error - Lobe 9	0.000	-0.001	-0.020	0.020	-0.001	
33	Taper Error - Lobe 10	0.000	0.000	-0.020	0.020	0.000	
34	Taper Error - Lobe 11	0.000	0.002	-0.020	0.020	0.002	
35	Taper Error - Lobe 12	0.000	0.002	-0.020	0.020	0.002	