



Part name
C.C. / Device
Part ident
Time/Date

2181766 / OP_180
/3445/Adcole
18/03/2026 13:42

	CHARACTERISTIC NAME	NOMINAL VALUE	MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Angle error to Cam 1 - Lobe 2	0,000	-0,017	-0,125	0,125	-0,017	
2	Angle error to Cam 1 - Lobe 3	0,000	-0,034	-0,125	0,125	-0,034	
3	Angle error to Cam 1 - Lobe 4	0,000	-0,036	-0,125	0,125	-0,036	
4	Angle error to Cam 1 - Lobe 5	0,000	-0,050	-0,125	0,125	-0,050	
5	Angle error to Cam 1 - Lobe 6	0,000	-0,051	-0,125	0,125	-0,051	
6	Angle error to Cam 1 - Lobe 7	0,000	-0,029	-0,125	0,125	-0,029	
7	Angle error to Cam 1 - Lobe 8	0,000	-0,043	-0,125	0,125	-0,043	
8	Angle error to Cam 1 - Lobe 9	0,000	-0,047	-0,125	0,125	-0,047	
9	Angle error to Cam 1 - Lobe 10	0,000	-0,051	-0,125	0,125	-0,051	
10	Angle error to Pin - Lobe 1	0,000	0,065	-0,250	0,250	0,065	
11	Angle error to Pin - Lobe 2	0,000	0,048	-0,250	0,250	0,048	
12	Angle error to Pin - Lobe 3	0,000	0,031	-0,250	0,250	0,031	
13	Angle error to Pin - Lobe 4	0,000	0,029	-0,250	0,250	0,029	
14	Angle error to Pin - Lobe 5	0,000	0,015	-0,250	0,250	0,015	
15	Angle error to Pin - Lobe 6	0,000	0,014	-0,250	0,250	0,014	
16	Angle error to Pin - Lobe 7	0,000	0,036	-0,250	0,250	0,036	
17	Angle error to Pin - Lobe 8	0,000	0,022	-0,250	0,250	0,022	
18	Angle error to Pin - Lobe 9	0,000	0,018	-0,250	0,250	0,018	
19	Angle error to Pin - Lobe 10	0,000	0,014	-0,250	0,250	0,014	
20	Angle of Cam 1 to ref.	127,900	127,965	255,550	256,050	0,065	-127,585
21	BC Radius Error - Lobe 1	0,000	0,010	-0,100	0,100	0,010	
22	BC Radius Error - Lobe 2	0,000	-0,003	-0,100	0,100	-0,003	
23	BC Radius Error - Lobe 3	0,000	0,012	-0,100	0,100	0,012	
24	BC Radius Error - Lobe 4	0,000	0,007	-0,100	0,100	0,007	
25	BC Radius Error - Lobe 5	0,000	0,009	-0,100	0,100	0,009	
26	BC Radius Error - Lobe 6	0,000	0,008	-0,100	0,100	0,008	
27	BC Radius Error - Lobe 7	0,000	0,018	-0,100	0,100	0,018	
28	BC Radius Error - Lobe 8	0,000	0,020	-0,100	0,100	0,020	
29	BC Radius Error - Lobe 9	0,000	0,019	-0,100	0,100	0,019	
30	BC Radius Error - Lobe 10	0,000	0,019	-0,100	0,100	0,019	
31	BC Runout - Lobe 1	0,000	0,017	0,000	0,040	0,017	
32	BC Runout - Lobe 2	0,000	0,007	0,000	0,040	0,007	
33	BC Runout - Lobe 3	0,000	0,002	0,000	0,040	0,002	
34	BC Runout - Lobe 4	0,000	0,002	0,000	0,040	0,002	
35	BC Runout - Lobe 5	0,000	0,004	0,000	0,040	0,004	
36	BC Runout - Lobe 6	0,000	0,006	0,000	0,040	0,006	
37	BC Runout - Lobe 7	0,000	0,006	0,000	0,040	0,006	
38	BC Runout - Lobe 8	0,000	0,002	0,000	0,040	0,002	
39	BC Runout - Lobe 9	0,000	0,001	0,000	0,040	0,001	
40	BC Runout - Lobe 10	0,000	0,003	0,000	0,040	0,003	
41	BC Velocity Error - Lobe 1	0,000	0,000	0,000	0,010	0,000	
42	BC Velocity Error - Lobe 2	0,000	0,000	0,000	0,010	0,000	
43	BC Velocity Error - Lobe 3	0,000	0,000	0,000	0,010	0,000	
44	BC Velocity Error - Lobe 4	0,000	0,000	0,000	0,010	0,000	
45	BC Velocity Error - Lobe 5	0,000	0,000	0,000	0,010	0,000	
46	BC Velocity Error - Lobe 6	0,000	0,000	0,000	0,010	0,000	
47	BC Velocity Error - Lobe 7	0,000	0,000	0,000	0,010	0,000	
48	BC Velocity Error - Lobe 8	0,000	0,000	0,000	0,010	0,000	



Part name
C.C. / Device
Part ident
Time/Date

2181766 / OP_180
/3445/Adcole
18/03/2026 13:42

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	BC Velocity Error - Lobe 9	0.000	0.000	0.000	0.010	0.000	
2	BC Velocity Error - Lobe 10	0.000	0.000	0.000	0.010	0.000	
3	Center Deviation - Lobe 1	0.000	-0.001	-0.003	0.010	-0.001	
4	Center Deviation - Lobe 2	0.000	0.000	-0.003	0.010	0.000	
5	Center Deviation - Lobe 3	0.000	0.000	-0.003	0.010	0.000	
6	Center Deviation - Lobe 4	0.000	0.000	-0.003	0.010	0.000	
7	Center Deviation - Lobe 5	0.000	0.000	-0.003	0.010	0.000	
8	Center Deviation - Lobe 6	0.000	0.000	-0.003	0.010	0.000	
9	Center Deviation - Lobe 7	0.000	0.000	-0.003	0.010	0.000	
10	Center Deviation - Lobe 8	0.000	0.000	-0.003	0.010	0.000	
11	Center Deviation - Lobe 9	0.000	0.000	-0.003	0.010	0.000	
12	Center Deviation - Lobe 10	0.000	0.000	-0.003	0.010	0.000	
13	Cir_Mancal_A	0.000	0.001	0.000	0.010	0.001	
14	Dia_Mancal_A	84.953	84.973	84.968	84.983	0.020	
15	Ecc-Ref [Gage] - A	0.000	0.020	0.000	0.035	0.020	
16	Ecc-Ref [Gage] - B	0.000	0.029	0.000	0.035	0.029	
17	Ecc-Ref [Gage] - C	0.000	0.027	0.000	0.035	0.027	
18	Ecc-Ref [Gage] - D	0.000	0.020	0.000	0.035	0.020	
19	Ecc-Ref [Gage] - E	0.000	0.013	0.000	0.035	0.013	
20	Ecc-Ref [Gage] - F	0.000	0.005	0.000	0.035	0.005	
21	Ecc-Ref [Part] - A	0.000	0.000	0.000	0.070	0.000	
22	Ecc-Ref [Part] - B	0.000	0.016	0.000	0.070	0.016	
23	Ecc-Ref [Part] - C	0.000	0.018	0.000	0.070	0.018	
24	Ecc-Ref [Part] - D	0.000	0.011	0.000	0.070	0.011	
25	Ecc-Ref [Part] - E	0.000	0.008	0.000	0.070	0.008	
26	Ecc-Ref [Part] - F	0.000	0.000	0.000	0.070	0.000	
27	Lift Difference Nose - Lobe 1	0.000	0.002	0.000	0.010	0.002	
28	Lift Difference Nose - Lobe 2	0.000	0.002	0.000	0.010	0.002	
29	Lift Difference Nose - Lobe 3	0.000	0.002	0.000	0.010	0.002	
30	Lift Difference Nose - Lobe 4	0.000	0.001	0.000	0.010	0.001	
31	Lift Difference Nose - Lobe 5	0.000	0.001	0.000	0.010	0.001	
32	Lift Difference Nose - Lobe 6	0.000	0.001	0.000	0.010	0.001	
33	Lift Difference Nose - Lobe 7	0.000	0.001	0.000	0.010	0.001	
34	Lift Difference Nose - Lobe 8	0.000	0.001	0.000	0.010	0.001	
35	Lift Difference Nose - Lobe 9	0.000	0.001	0.000	0.010	0.001	
36	Lift Difference Nose - Lobe 10	0.000	0.001	0.000	0.010	0.001	
37	Lift Difference Ramp - Lobe 1	0.000	0.003	0.000	0.010	0.003	
38	Lift Difference Ramp - Lobe 2	0.000	0.002	0.000	0.010	0.002	
39	Lift Difference Ramp - Lobe 3	0.000	0.002	0.000	0.010	0.002	
40	Lift Difference Ramp - Lobe 4	0.000	0.002	0.000	0.010	0.002	
41	Lift Difference Ramp - Lobe 5	0.000	0.001	0.000	0.010	0.001	
42	Lift Difference Ramp - Lobe 6	0.000	0.001	0.000	0.010	0.001	
43	Lift Difference Ramp - Lobe 7	0.000	0.002	0.000	0.010	0.002	
44	Lift Difference Ramp - Lobe 8	0.000	0.001	0.000	0.010	0.001	
45	Lift Difference Ramp - Lobe 9	0.000	0.002	0.000	0.010	0.002	
46	Lift Difference Ramp - Lobe 10	0.000	0.001	0.000	0.010	0.001	
47	Lift Error Nose - Lobe 1	0.000	0.010	0.000	0.100	0.010	
48	Lift Error Nose - Lobe 2	0.000	0.025	0.000	0.100	0.025	



Part name
C.C. / Device
Part ident
Time/Date

2181766 / OP_180
/3445/Adcole
18/03/2026 13:42

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Lift Error Nose - Lobe 3	0.000	0.015	0.000	0.100	0.015	
2	Lift Error Nose - Lobe 4	0.000	0.015	0.000	0.100	0.015	
3	Lift Error Nose - Lobe 5	0.000	0.015	0.000	0.100	0.015	
4	Lift Error Nose - Lobe 6	0.000	0.009	0.000	0.100	0.009	
5	Lift Error Nose - Lobe 7	0.000	0.014	0.000	0.100	0.014	
6	Lift Error Nose - Lobe 8	0.000	0.017	0.000	0.100	0.017	
7	Lift Error Nose - Lobe 9	0.000	0.015	0.000	0.100	0.015	
8	Lift Error Nose - Lobe 10	0.000	0.014	0.000	0.100	0.014	
9	Lift Error Ramp - Lobe 1	0.000	0.016	0.000	0.050	0.016	
10	Lift Error Ramp - Lobe 2	0.000	0.028	0.000	0.050	0.028	
11	Lift Error Ramp - Lobe 3	0.000	0.019	0.000	0.050	0.019	
12	Lift Error Ramp - Lobe 4	0.000	0.018	0.000	0.050	0.018	
13	Lift Error Ramp - Lobe 5	0.000	0.018	0.000	0.050	0.018	
14	Lift Error Ramp - Lobe 6	0.000	0.011	0.000	0.050	0.011	
15	Lift Error Ramp - Lobe 7	0.000	0.016	0.000	0.050	0.016	
16	Lift Error Ramp - Lobe 8	0.000	0.019	0.000	0.050	0.019	
17	Lift Error Ramp - Lobe 9	0.000	0.017	0.000	0.050	0.017	
18	Lift Error Ramp - Lobe 10	0.000	0.016	0.000	0.050	0.016	
19	Meas Diam - B	84.953	84.971	84.968	84.983	0.018	
20	Meas Diam - C	84.953	84.975	84.968	84.983	0.022	
21	Meas Diam - D	84.953	84.975	84.968	84.983	0.022	
22	Meas Diam - E	84.953	84.972	84.968	84.983	0.019	
23	Meas Diam - F	84.953	84.974	84.968	84.983	0.021	
24	Parallelism - Lobe 1	0.000	0.004	-0.015	0.015	0.004	
25	Parallelism - Lobe 2	0.000	0.004	-0.015	0.015	0.004	
26	Parallelism - Lobe 3	0.000	0.003	-0.015	0.015	0.003	
27	Parallelism - Lobe 4	0.000	0.002	-0.015	0.015	0.002	
28	Parallelism - Lobe 5	0.000	0.001	-0.015	0.015	0.001	
29	Parallelism - Lobe 6	0.000	0.001	-0.015	0.015	0.001	
30	Parallelism - Lobe 7	0.000	0.002	-0.015	0.015	0.002	
31	Parallelism - Lobe 8	0.000	0.002	-0.015	0.015	0.002	
32	Parallelism - Lobe 9	0.000	0.001	-0.015	0.015	0.001	
33	Parallelism - Lobe 10	0.000	0.001	-0.015	0.015	0.001	
34	Roundness - B	0.000	0.001	0.000	0.010	0.001	
35	Roundness - C	0.000	0.001	0.000	0.010	0.001	
36	Roundness - D	0.000	0.002	0.000	0.010	0.002	
37	Roundness - E	0.000	0.001	0.000	0.010	0.001	
38	Roundness - F	0.000	0.002	0.000	0.010	0.002	
39	Runout - A	0.000	0.001	0.000	0.100	0.001	
40	Runout - B	0.000	0.032	0.000	0.100	0.032	
41	Runout - C	0.000	0.036	0.000	0.100	0.036	
42	Runout - D	0.000	0.022	0.000	0.100	0.022	
43	Runout - E	0.000	0.016	0.000	0.100	0.016	
44	Runout - F	0.000	0.002	0.000	0.100	0.002	
45	Taper Error - Lobe 1	0.000	-0.002	-0.020	0.020	-0.002	
46	Taper Error - Lobe 2	0.000	-0.001	-0.020	0.020	-0.001	
47	Taper Error - Lobe 3	0.000	0.000	-0.020	0.020	0.000	
48	Taper Error - Lobe 4	0.000	0.000	-0.020	0.020	0.000	



Part name
C.C. / Device
Part ident
Time/Date

2181766 / OP_180
/3445/Adcole
18/03/2026 13:42

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Taper Error - Lobe 5	0.000	0.000	-0.020	0.020	0.000	
2	Taper Error - Lobe 6	0.000	0.000	-0.020	0.020	0.000	
3	Taper Error - Lobe 7	0.000	0.000	-0.020	0.020	0.000	
4	Taper Error - Lobe 8	0.000	0.001	-0.020	0.020	0.001	
5	Taper Error - Lobe 9	0.000	0.000	-0.020	0.020	0.000	
6	Taper Error - Lobe 10	0.000	0.001	-0.020	0.020	0.001	