



Part name
C.C. / Device
Part ident
Time/Date

3070996 / OP_120
/3445/Adcole
11/09/2026 09:32

	CHARACTERISTIC NAME	NOMINAL VALUE	MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Angle error to Cam 11 A6 - Lobe 1	180,000	0,000	-0,250	0,250	-180,000	
2	Angle error to Cam 11 A6 - Lobe 2	304,400	289,904	-0,250	0,250	-14,496	289,654
3	Angle error to Cam 11 A6 - Lobe 3	300,000	76,304	-0,250	0,250	-223,696	76,054
4	Angle error to Cam 11 A6 - Lobe 4	64,400	222,694	-0,250	0,250	158,294	222,444
5	Angle error to Cam 11 A6 - Lobe 5	60,000	152,600	-0,250	0,250	92,600	152,350
6	Angle error to Cam 11 A6 - Lobe 6	184,400	-999,900	-0,250	0,250	-1184,300	-999,650
7	Angle error to UZ - Lobe 1	306,200	306,177	-0,100	0,100	-0,023	306,077
8	Angle error to UZ - Lobe 2	236,100	236,081	-0,100	0,100	-0,019	235,981
9	Angle error to UZ - Lobe 3	22,500	22,481	-0,100	0,100	-0,019	22,381
10	Angle error to UZ - Lobe 4	168,900	168,870	-0,100	0,100	-0,030	168,770
11	Angle error to UZ - Lobe 5	98,800	98,777	-0,100	0,100	-0,023	98,677
12	Angle error to UZ - Lobe 6	280,800	-999,900	-0,100	0,100	-1280,700	-999,800
13	Angulo entre as superficies	40,000	-999,900	-0,125	0,125	-1039,900	-999,775
14	BC Radius Error - Lobe 1	25,000	25,057	-0,100	0,100	0,057	24,957
15	BC Radius Error - Lobe 2	25,000	25,036	-0,100	0,100	0,036	24,936
16	BC Radius Error - Lobe 3	25,000	25,029	-0,100	0,100	0,029	24,929
17	BC Radius Error - Lobe 4	25,000	25,023	-0,100	0,100	0,023	24,923
18	BC Radius Error - Lobe 5	25,000	25,025	-0,100	0,100	0,025	24,925
19	BC Radius Error - Lobe 6	32,000	-999,900	-0,100	0,100	-1031,900	-999,800
20	BC Runout - Lobe 1	0,000	0,003	0,000	0,040	0,003	
21	BC Runout - Lobe 2	0,000	0,004	0,000	0,040	0,004	
22	BC Runout - Lobe 3	0,000	0,002	0,000	0,040	0,002	
23	BC Runout - Lobe 4	0,000	0,005	0,000	0,040	0,005	
24	BC Runout - Lobe 5	0,000	0,019	0,000	0,040	0,019	
25	BC Runout - Lobe 6	0,000	-999,900	0,000	0,040	-999,900	-999,900
26	Concave/Convex - Lobe 1	0,000	0,001	-0,005	0,005	0,001	
27	Concave/Convex - Lobe 2	0,000	0,001	-0,005	0,005	0,001	
28	Concave/Convex - Lobe 3	0,000	0,001	-0,005	0,005	0,001	
29	Concave/Convex - Lobe 4	0,000	0,001	-0,005	0,005	0,001	
30	Concave/Convex - Lobe 5	0,000	0,001	-0,005	0,005	0,001	
31	Concave/Convex - Lobe 6	0,000	-999,900	-0,005	0,005	-999,900	-999,895
32	Cylindricity - A	0,000	0,008	0,000	0,020	0,008	
33	Cylindricity - B	0,000	0,002	0,000	0,020	0,002	
34	Cylindricity - C	0,000	0,002	0,000	0,020	0,002	
35	Cylindricity - D	0,000	0,006	0,000	0,020	0,006	
36	Cylindricity - E	0,000	0,007	0,000	0,020	0,007	
37	Cylindricity - F	0,000	0,015	0,000	0,020	0,015	
38	Cylindricity - G	0,000	0,014	0,000	0,020	0,014	
39	Diametro A [Center]	35,967	35,958	-0,008	0,008	-0,009	35,950
40	Diametro A [Inf]	35,967	35,966	-0,008	0,008	-0,001	35,958
41	Diametro A [Sup]	35,967	35,954	-0,008	0,008	-0,013	35,946
42	Diametro B [Center]	35,967	35,963	-0,008	0,008	-0,004	35,955
43	Diametro B [Inf]	35,967	35,964	-0,008	0,008	-0,003	35,956
44	Diametro B [Sup]	35,967	35,961	-0,008	0,008	-0,006	35,953
45	Diametro C [Center]	35,967	35,964	-0,008	0,008	-0,003	35,956
46	Diametro C [Inf]	35,967	35,962	-0,008	0,008	-0,005	35,954
47	Diametro C [Sup]	35,967	35,963	-0,008	0,008	-0,004	35,955
48	Diametro D [Center]	35,967	35,958	-0,008	0,008	-0,009	35,950



Part name
C.C. / Device
Part ident
Time/Date

3070996 / OP_120
/3445/Adcole
11/09/2026 09:32

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Diametro D [Inf]	35.967	35.965	-0.008	0.008	-0.002	35.957
2	Diametro D [Sup]	35.967	35.956	-0.008	0.008	-0.011	35.948
3	Diametro E [Center]	35.967	35.962	-0.008	0.008	-0.005	35.954
4	Diametro E [Inf]	35.967	35.971	-0.008	0.008	0.004	35.963
5	Diametro E [Sup]	35.967	35.961	-0.008	0.008	-0.006	35.953
6	Diametro F [Center]	47.967	47.965	-0.008	0.008	-0.002	47.957
7	Diametro F [Inf]	47.967	47.991	-0.008	0.008	0.024	47.983
8	Diametro F [Sup]	47.967	47.965	-0.008	0.008	-0.002	47.957
9	Diametro G [Center]	47.967	47.965	-0.008	0.008	-0.002	47.957
10	Diametro G [Inf]	47.967	47.990	-0.008	0.008	0.023	47.982
11	Diametro G [Sup]	47.967	47.966	-0.008	0.008	-0.001	47.958
12	Distancia U para o Eixo de Rot	39.700	-999.900	-0.050	0.050	-1039.600	-999.850
13	Distancia Z para o Eixo de Rot	39.700	-999.900	-0.050	0.050	-1039.600	-999.850
14	Lift Difference - Lobe 1	0.000	0.003	0.000	0.010	0.003	
15	Lift Difference - Lobe 2	0.000	0.003	0.000	0.010	0.003	
16	Lift Difference - Lobe 3	0.000	0.003	0.000	0.010	0.003	
17	Lift Difference - Lobe 4	0.000	0.003	0.000	0.010	0.003	
18	Lift Difference - Lobe 5	0.000	0.003	0.000	0.010	0.003	
19	Lift Difference - Lobe 6	0.000	-999.900	-0.010	0.010	-999.900	-999.890
20	Lift Error BC - Lobe 1	0.000	-0.002	-0.025	0.025	-0.002	
21	Lift Error BC - Lobe 2	0.000	-0.002	-0.025	0.025	-0.002	
22	Lift Error BC - Lobe 3	0.000	-0.001	-0.025	0.025	-0.001	
23	Lift Error BC - Lobe 4	0.000	0.003	-0.025	0.025	0.003	
24	Lift Error BC - Lobe 5	0.000	0.010	-0.025	0.025	0.010	
25	Lift Error BC - Lobe 6	0.000	-999.900	-0.025	0.025	-999.900	-999.875
26	Lift Error Closing Ramp - Lobe 1	0.000	0.039	-0.050	0.050	0.039	
27	Lift Error Closing Ramp - Lobe 2	0.000	0.030	-0.050	0.050	0.030	
28	Lift Error Closing Ramp - Lobe 3	0.000	0.030	-0.050	0.050	0.030	
29	Lift Error Closing Ramp - Lobe 4	0.000	0.031	-0.050	0.050	0.031	
30	Lift Error Closing Ramp - Lobe 5	0.000	0.032	-0.050	0.050	0.032	
31	Lift Error Closing Ramp - Lobe 6	0.000	-999.900	-0.050	0.050	-999.900	-999.850
32	Lift Error Nose - Lobe 1	0.000	0.033	-0.050	0.050	0.033	
33	Lift Error Nose - Lobe 2	0.000	0.025	-0.050	0.050	0.025	
34	Lift Error Nose - Lobe 3	0.000	0.024	-0.050	0.050	0.024	
35	Lift Error Nose - Lobe 4	0.000	0.025	-0.050	0.050	0.025	
36	Lift Error Nose - Lobe 5	0.000	0.032	-0.050	0.050	0.032	
37	Lift Error Nose - Lobe 6	0.000	-999.900	-0.050	0.050	-999.900	-999.850
38	Lift Error Opening Ramp - Lobe 1	0.000	0.041	-0.100	0.100	0.041	
39	Lift Error Opening Ramp - Lobe 2	0.000	0.032	-0.100	0.100	0.032	
40	Lift Error Opening Ramp - Lobe 3	0.000	0.031	-0.100	0.100	0.031	
41	Lift Error Opening Ramp - Lobe 4	0.000	0.032	-0.100	0.100	0.032	
42	Lift Error Opening Ramp - Lobe 5	0.000	0.034	-0.100	0.100	0.034	
43	Lift Error Opening Ramp - Lobe 6	0.000	-999.900	-0.025	0.025	-999.900	-999.875
44	Meas Diam [Center]- A	36.000		-0.050	-0.025		
45	Meas Diam [Center]- B	36.000		-0.050	-0.025		
46	Meas Diam [Center]- C	36.000		-0.050	-0.025		
47	Meas Diam [Center]- D	36.000		-0.050	-0.025		
48	Meas Diam [Center]- E	36.000		-0.050	-0.025		



Part name
C.C. / Device
Part ident
Time/Date

3070996 / OP_120
/3445/Adcole
11/09/2026 09:32

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Meas Diam [Center]- F	48.000		-0.050	-0.025		
2	Meas Diam [Center]- G	48.000		-0.050	-0.025		
3	Meas Diam [Inf]- A	36.000		-0.050	-0.025		
4	Meas Diam [Inf]- B	36.000		-0.050	-0.025		
5	Meas Diam [Inf]- C	36.000		-0.050	-0.025		
6	Meas Diam [Inf]- D	36.000		-0.050	-0.025		
7	Meas Diam [Inf]- E	36.000		-0.050	-0.025		
8	Meas Diam [Inf]- F	48.000		-0.050	-0.025		
9	Meas Diam [Inf]- G	48.000		-0.050	-0.025		
10	Meas Diam [Sup]- A	36.000		-0.050	-0.025		
11	Meas Diam [Sup]- B	36.000		-0.050	-0.025		
12	Meas Diam [Sup]- C	36.000		-0.050	-0.025		
13	Meas Diam [Sup]- D	36.000		-0.050	-0.025		
14	Meas Diam [Sup]- E	36.000		-0.050	-0.025		
15	Meas Diam [Sup]- F	48.000		-0.050	-0.025		
16	Meas Diam [Sup]- G	48.000		-0.050	-0.025		
17	Parallelism - A	0.000	0.000	0.000	0.015	0.000	
18	Parallelism - B	0.000	0.001	0.000	0.015	0.001	
19	Parallelism - C	0.000	0.000	0.000	0.015	0.000	
20	Parallelism - D	0.000	0.000	0.000	0.015	0.000	
21	Parallelism - E	0.000	0.000	0.000	0.015	0.000	
22	Parallelism - F	0.000	0.000	0.000	0.015	0.000	
23	Parallelism - G	0.000	0.001	0.000	0.015	0.001	
24	Parallelism - Lobe 1	0.000	0.001	0.000	0.020	0.001	
25	Parallelism - Lobe 2	0.000	0.001	0.000	0.020	0.001	
26	Parallelism - Lobe 3	0.000	0.000	0.000	0.020	0.000	
27	Parallelism - Lobe 4	0.000	0.001	0.000	0.020	0.001	
28	Parallelism - Lobe 5	0.000	0.001	0.000	0.020	0.001	
29	Parallelism - Lobe 6	0.000	-999.900	0.000	0.020	-999.900	-999.900
30	Runout [Adj] - A	0.000	0.002	0.000	0.120	0.002	
31	Runout [Adj] - B	0.000	0.010	0.000	0.120	0.010	
32	Runout [Adj] - C	0.000	0.026	0.000	0.120	0.026	
33	Runout [Adj] - D	0.000	0.034	0.000	0.120	0.034	
34	Runout [Adj] - E	0.000	0.022	0.000	0.120	0.022	
35	Runout [Adj] - F	0.000	0.004	0.000	0.120	0.004	
36	Runout [Adj] - G	0.000	0.002	0.000	0.120	0.002	
37	Runout [B-C] - A	0.000	0.002	0.000	0.030	0.002	
38	Runout [E-F] - G	0.000	0.002	0.000	0.030	0.002	
39	Runout [Ext] - B	0.000	0.005	0.000	0.030	0.005	
40	Runout [Ext] - C	0.000	0.006	0.000	0.030	0.006	
41	Runout [Ext] - D	0.000	0.011	0.000	0.030	0.011	
42	Runout [Ext] - E	0.000	0.004	0.000	0.030	0.004	
43	Runout [Ext] - F	0.000	0.002	0.000	0.030	0.002	
44	Runout [Gage] - A	0.000	0.016	0.000	0.050	0.016	
45	Runout [Gage] - B	0.000	0.015	0.000	0.050	0.015	
46	Runout [Gage] - C	0.000	0.024	0.000	0.050	0.024	
47	Runout [Gage] - D	0.000	0.011	0.000	0.030	0.011	
48	Runout [Gage] - E	0.000	0.024	0.000	0.050	0.024	



Part name3070996 / OP_120

C.C. / Device/3445/Adcole

Part ident

Time/Date11/09/2026 09:32

	CHARACTERISTIC NAME		MEASURED VALUE	LOWER LIMIT	UPPER LIMIT	DEVIATION	EXCEEDANCE
1	Runout [Gage] - F	0.000	0.045	0.000	0.050	0.045	
2	Runout [Gage] - G	0.000	0.048	0.000	0.050	0.048	