

Ryanair - Task 2 - Java/Spring - Interconnecting Flights

Write a Spring Boot based RESTful API application which serves information about possible direct and interconnected flights (maximum 1 stop) based on the data consumed from external APIs.

Given:

The application can consume data from the following two microservices:

- Routes API: <https://services-api.ryanair.com/views/locate/3/routes> which returns a list of all available routes based on the airport's IATA codes. Please note that only routes with: connectingAirport set to null and operator set to RYANAIR should be used.

For example:

```
[
  {
    "airportFrom": "LUZ", # a departure airport IATA code
    "airportTo": "STN", # an arrival airport IATA code
    "connectingAirport": null, # a connecting airport IATA code
    "newRoute": false,
    "seasonalRoute": false,
    "operator": "RYANAIR",
    "group": "ETHNIC"
  },
  {
    "airportFrom": "CHQ",
    "airportTo": "SKG",
    "connectingAirport": null,
    "newRoute": false,
    "seasonalRoute": false,
    "operator": "RYANAIR",
    "group": "DOMESTIC"
  },
  (...)
]
```

- Schedules API: <https://services-api.ryanair.com/timtbl/3/schedules/{departure}/{arrival}/years/{year}/months/{month}> which returns a list of available flights for a given departure airport IATA code, an arrival airport IATA code, a year and a month.

For example (<https://services-api.ryanair.com/timtbl/3/schedules/DUB/WRO/years/2023/months/6>):

```

{
  "month": 6, # a month of a year
  "days": [
    {
      "day": 1, # a day of a month
      "flights": [ # a list of flights for given day
        {
          "number": "1926", # a flight number
          "departureTime": "18:00", # a departure time in the departure airport timezone
          "arrivalTime": "21:35" # an arrival time in the arrival airport timezone
        }
      ]
    },
    {
      "day": 3,
      "flights": [
        {
          "number": "1926",
          "departureTime": "17:25",
          "arrivalTime": "21:00"
        }
      ]
    }
  ],
  (...)
}

```

Requirements:

- The source code of the application should be delivered (ideally shared through GitHub or Bitbucket).
- The application should build to an executable JAR file.
- The application should response to following request URI with given query parameters:
<http://<HOST>/<CONTEXT>/interconnections?departure={departure}&arrival={arrival}&departureDateTime={departureDateTime}&arrivalDateTime={arrivalDateTime}> where:
 - departure - a departure airport IATA code
 - departureDateTime - a departure datetime in the departure airport timezone in ISO format
 - arrival - an arrival airport IATA code
 - arrivalDateTime - an arrival datetime in the arrival airport timezone in ISO format

for example: [http://localhost:8080/somevalidcontext/interconnections?](http://localhost:8080/somevalidcontext/interconnections?departure=DUB&arrival=WRO&departureDateTime=2018-03-01T07:00&arrivalDateTime=2018-03-03T21:00)

[departure=DUB&arrival=WRO&departureDateTime=2018-03-01T07:00&arrivalDateTime=2018-03-03T21:00](http://localhost:8080/somevalidcontext/interconnections?departure=DUB&arrival=WRO&departureDateTime=2018-03-01T07:00&arrivalDateTime=2018-03-03T21:00)

- The application should return a list of flights departing from a given departure airport not earlier than the specified departure datetime and arriving to a given arrival airport not later than the specified arrival datetime.
 The list should consist of:

- all direct flights if available (for example: DUB - WRO)
 - all interconnected flights with a maximum of one stop if available (for example: DUB - STN - WRO)
- For interconnected flights the difference between the arrival and the next departure should be 2h or greater
- The list should be of the following form:

```
[
  {
    "stops": 0,
    "legs": [
      {
        "departureAirport": "DUB",
        "arrivalAirport": "WRO",
        "departureDateTime": "2018-03-01T12:40",
        "arrivalDateTime": "2018-03-01T16:40"
      }
    ]
  },
  {
    "stops": 1,
    "legs": [
      {
        "departureAirport": "DUB",
        "arrivalAirport": "STN",
        "departureDateTime": "2018-03-01T06:25",
        "arrivalDateTime": "2018-03-01T07:35"
      },
      {
        "departureAirport": "STN",
        "arrivalAirport": "WRO",
        "departureDateTime": "2018-03-01T09:50",
        "arrivalDateTime": "2018-03-01T13:20"
      }
    ]
  }
]
```

We are looking for the solution to be well factored and to adhere to the SOLID principles.