REAL-TIME FRACTAL RENDERING

Non-Examined Assessment Optimised Fractal Rendering in

Toby Davis Hampton School January 15, 2023

Abstract

Write this bad boi when the thing is finished :)

Summary

1	Pro	ject Analysis	9
	1.1	A Brief Introduction to Fractals	٠
	1.2	Defining the Problem	4
	1.3	The End User	,
	1.4	Researching Existing Projects and User Requirements	8

1 Project Analysis

1.1 A Brief Introduction to Fractals

A fractal is "a curve or geometrical figure, each part of which has the same statistical character as the whole" [3].

Some fractals are defined by simple equations which exhibit chaotic behaviour. Arguably the most famous fractal, the Mandelbrot Set, is defined by the iterative equation, where $Z_0 = 0 + 0i$, and C is the initial value in the complex plane.

$$Z_{n+1} = Z_n^2 + C \quad : \quad Z_n, c \in \mathbb{C}$$

For a given point C to be in the Mandelbrot Set, the value of Z_n must remain bounded (i.e. not diverge to infinity) after the iterative series is repeated infinitely many times. This approach is used in most iterative fractal equations.




Figure 1: The standard Mandelbrot fractal[1]

Additionally, fractal variations can be created by changing the generating equation slightly. For example, changing the r in the Mandelbrot equation $(Z_{n+1} = Z_n^r + C)$ yields the following fractals.




Figure 2: (left) r = 3, (centre) r = 4, (right) r = 20

Other famous fractals include the Sierpiński Triangle, the Julia Set, Hilbert Spirals, etc. All are defined either by infinitely-recursive self-similar patterns or repeated equations.




Figure 3: (left) Sierpiński-Triangle, (centre) Part of the Mandelbrot Set, (right) Hilbert Curve

1.2 Defining the Problem

Fractals have been the subject of much debate and curiosity throughout history, but, due to the computational requirements of generating them, research into them was very limited until the rise of the electronic computer.

The newfound levels of processing power allowed increasingly detailed images to be generated, and mathematicians were able to better understand the underlying equations and seemingly chaotic nature of fractals. With the power of modern computers, it is possible to render some fractals in real-time and explore them to great depths, though there are still technical, physical and monetary hurdles to clear.

Many fractal rendering program exist online, however the majority of these are incomplete, inefficient applications that are not designed for high-performance and high zoom factors. While there are high-quality applications out there, the best ones are often quite expensive, making them inaccessible to the majority of potential-users. For example, some extremely advanced software costs almost £80[2].

Technological Limitations The further you zoom into a fractal, smaller the numbers you have to deal with. At lower zoom levels, this doesn't pose much of an issue, as 64 bit or even 32 bit floating point numbers often have the required precision to accurately render an image. At higher zoom levels, however, the precision of the numbers used starts to affect the image quality.

When zoomed in far enough, floating point rounding errors start to cause certain pixel positions to merge into one, causing unattractive "blocky" patterns in the image. Eventually, these blocks will consume the entire image and no more detail can be seen.

To get around this, it is possible to use high-precision floating point data types, though, since these are processed in software, not hardware, they are orders of magnitude slower than normal number types, and this can make the rendering process impractically slow.

Certain approaches can be taken to optimise the performance of high-performance number types. For example, it can be proven that Z_n will diverge to infinity if $|Z_n| > 2$ at any point. Additionally, advanced algorithms can mix fixed and multi-precision arithmetic to decrease the number of arithmetic operations that take place in software.

There are many fractal viewers freely available online already, though almost all of them suffer from at least one very significant flaw:

- 1. Lack of precision
- 2. Inadequate performance
- 3. Insufficient customisability
- 4. Limited file export options

5. No ability to save configuration to a file

Lack of precision

To increase performance, many simpler implementations use strictly 32- or 64-bit floating point values. Additionally, some implementations greatly reduce the number of samples run per pixel, meaning the fractal is lacking critical detail in some areas – particularly those closest to the border of the fractal.

While it is possible to increase the maximum number of iterations run per pixel, moving from 64-bit (machine word) to multi-precision (software) floating point incurs a *massive* performance hit, making it impractical in almost all cases.

Inadequate performance

Many naive fractal renderers do not implement the necessary optimisations for the program to run at real-time with a native resolution. This links closely with the lack of precision, since the two are extremely closely related.

Insufficient customisability

When rendering and exploring fractals there are a lot of settings that can change how it appears. For example, you can change the maximum number of iterations to allow, or the settings/algorithm for colouring the fractal.

Unfortunately, the vast majority of programs limit the customization of the fractal to the gradient used to colour it, not allowing the user to change any other settings.

Being able to change the most fundamental settings of the renderer allows for anyone using the software to gain a more intuitive understanding of both the fractal itself and the program.

Limited file export options

A surprising number of fractal rendering programs do not allow the final product to be saved to a file, which is a nice feature to have if you want to examine them further in more software, for example.

The ability to save configurations

Often, when exploring fractals, you come across areas of particular interest and would like to be able to return to that exact place in the future.

Very few programs actually implement this feature, and it is one which could be very useful in some circumstances.

1.3 The End User

A fast, fully-featured fractal viewer could be used by a wide range of people for a variety of different purposes.

Firstly, maths teachers could use the program to assist in their lessons, as well as providing students with an interactive resource to help with homework and to further their understanding.

Secondly, if the renderer is fast and precise, even at extremely high zoom levels, then it could be used by people researching fractals and examining their properties.

Finally, such a program could also be used by anyone who enjoys looking at fractals, which, most likely, provides a larger audience than the other users combined.

Combining these different user-bases, an efficient, intuitive fractal renderer could be used by a significant number of people for a broad spectrum of different purposes.

User Requirements

Unfortunately, each of the identified user groups will have a different set of specific requirements to be met. These will be covered later in the project, but it is likely that only a limited set of features can realistically be implemented.

1.4 Researching Existing Projects and User Requirements

Look at online renderers (including Google's one??) Look at offline renderers.

Pick out the best features

Talk to Josh Talk to teachers Talk to family

Identify the overarching requirements Identify things that would be nice to have, but not necessarily required

Details Gathered – TEMPORARY

Online Renderer

- 1. https://math.hws.edu/eck/js/mandelbrot/MB.html
- 2. Rectangle zoom box is AWFUL
- 3. Settings are useful

Adjustable resolution

Number of threads

Palette editor

Configuration Export

Offers multiprecision floating point

XaoS Renderer

- 1. https://fractalfoundation.org/resources/fractal-software/
- 2. Method of moving around is quite clunky
- 3. Almost every setting can be changed, which is good
- 4. Multiple fractals supported
- 5. Different colouring and shading options
- 6. Some VERY interesting algorithms at play for performance boosts

Some form of data retention between frames

Progressive rendering

Looks like a 128-bit float but no true multiprecision floating point

Multiple approximations followed by progressive refining of the fractal

References

- [1] Paul Bourke, Nov 2002.
- [2] Frederik Slijkerman. Ultra fractal: Advanced fractal software for windows and macos, Jul 2022.
- [3] Catherine Soanes and Sara Hawker. Compact Oxford English Dictionary of current English. Oxford University Press, 2013.