

REAL-TIME FRACTAL RENDERING

Non-Examined Assessment **Optimised Fractal Rendering in C++**

Toby Davis

Hampton School

March 17, 2023

Abstract

Write this bad boi when the thing is finished :)

Summary

1	Project Analysis	4
1.1	A Brief Introduction to Fractals	4
1.2	Defining the Problem	5
1.3	The End User	7
1.4	Analysis of Existing Programs	8
1.4.1	David J. Eck's Online Mandelbrot Renderer [4]	8
1.4.2	XaoS.js Online Mandelbrot Renderer [5]	9
1.4.3	XaoS Offline Fractal Renderer [6]	9
1.5	Program Requirements	11
2	Design Phase	15
2.1	Third Party Libraries	15
2.2	Library Heirarchy	15
2.3	The Debug Logger	17
2.4	Colour Palettes	17
2.5	The Fractal Class	18
2.5.1	Render Box States	20
2.5.2	Render Boxes	20
2.5.3	Render Box Statistics	20
2.5.4	Render Configurations	21
2.6	The Fractal Renderer Class	21
2.6.1	Configuration, Getters, Setters and Statistics	22
2.6.2	Constructors and Configurations	24
2.6.3	Rendering Algorithms	25
2.7	The Main Window	27
2.8	Additional Features	28
2.8.1	Movement History	28
2.8.2	Improved Selection Area	30
3	Technical Solution	31
3.1	Color Palette (colorPalette.hpp)	31
3.2	Color Palette (colorPalette.cpp)	32
3.3	Debug Logger (debug.hpp)	33
3.4	Debug Logger (debug.cpp)	34
3.5	Fractal Base Class Implementation (fractal.hpp)	37
3.6	Fractal Renderer Definition (fractalRenderer.hpp)	38

3.7	Fractal Renderer Implementation (<code>fractalRenderer.cpp</code>) . .	41
3.8	Generic Fractal Definition (<code>genericFractal.hpp</code>)	53
3.9	Generic Fractal Implementation (<code>genericFractal.cpp</code>)	54
3.10	History Definition(<code>history.hpp</code>)	57
3.11	History Implementation (<code>history.cpp</code>)	60
3.12	Main Window Definition (<code>mainWindow.hpp</code>)	63
3.13	Main Window Implementation (<code>mainWindow.cpp</code>)	66
3.14	Mandelbrot Fractal Definition (<code>mandelbrot.hpp</code>)	84
3.15	Mandelbrot Fractal Implementation (<code>mandelbrot.cpp</code>)	84
3.16	OpenGL Utilities Definition (<code>openglUtils.hpp</code>)	87
3.17	OpenGL Utilities Implementation (<code>openglUtils.cpp</code>)	87
3.18	Render Configuration Definition (<code>renderConfig.hpp</code>)	89
3.19	Render Configuration Implementation (<code>renderConfig.cpp</code>) . .	90
3.20	CMake File (<code>CMakeLists.txt</code>)	91
3.21	Main File (<code>main.cpp</code>)	91

1 Project Analysis

1.1 A Brief Introduction to Fractals

A fractal is “a curve or geometrical figure, each part of which has the same statistical character as the whole”[1].

Some fractals are defined by simple equations which exhibit chaotic behaviour. Arguably the most famous fractal, the Mandelbrot Set, is defined by the following iterative equation, where $Z_0 = 0 + 0i$ and C is the initial value in the complex plane.

$$Z_{n+1} = Z_n^2 + C \quad : \quad Z_n, c \in \mathbb{C} \quad (1)$$

For a given point C to be in the Mandelbrot Set, the value of Z_n must remain bounded (i.e. not diverge to infinity) after the iterative series is repeated infinitely many times. This approach is used in most iterative fractal equations.




Figure 1: The standard Mandelbrot fractal[2]

Additionally, fractal variations can be created by changing the generating equation slightly. For example, changing the r in the Mandelbrot equation ($Z_{n+1} = Z_n^r + C$) yields the following fractals.




Figure 2: (left) $r = 3$, (centre) $r = 4$, (right) $r = 20$

Other famous fractals include the Sierpiński Triangle, the Julia Set, Hilbert Spirals, etc. All are defined either by infinitely-recursive self-similar patterns or repeated equations.




Figure 3: (left) Sierpiński-Triangle, (centre) Part of the Mandelbrot Set, (right) Hilbert Curve

1.2 Defining the Problem

Fractals have been the subject of much debate and curiosity throughout history. However, due to the computational requirements of generating them, research into them was minimal until the rise of the electronic computer.

The newfound processing power allowed increasingly detailed images to be generated, and mathematicians could better understand fractals' underlying equations and seemingly chaotic nature.

With the power of modern computers, it is possible to render some fractals in real-time and explore them to great depths, though there are still technical, physical and monetary hurdles to clear.

Many fractal rendering programs exist online; however, most are incomplete, inefficient applications not designed for high performance and increased zoom factors. While many high-quality applications exist, the best ones are often quite expensive, making them inaccessible to most potential users. For example, some extremely advanced software costs almost £80[3].

Technological Limitations The further you zoom into a fractal, the smaller the numbers you have to deal with. At lower zoom levels, this doesn't pose much of an issue, as 64 bit or even 32 bit floating point numbers often have the required precision to render an image accurately. At higher zoom levels, however, the precision of the numbers used affects the image quality.

When zoomed in far enough, floating point rounding errors start to cause certain pixel positions to merge into one, causing unattractive “blocky” patterns in the image. Eventually, these blocks will consume the entire image, and no more detail can be seen.

To get around this, it is possible to use high-precision floating point data types. However, since these are processed in software, not hardware, they are orders of magnitude slower than normal number types, which can make the rendering process impractically slow.

Some techniques can be taken to optimise the performance of high-performance number types. For example, it can be proven that Z_n will diverge to infinity if $|Z_n| > 2$ at any point. Additionally, advanced algorithms can mix fixed and multi-precision arithmetic to decrease the number of operations performed in software.

Program Limitations Many fractal renderers do just that; render fractals. They don't support any render export features and do not allow for saving, reloading or sharing render configurations.

Some programs have methods to save the rendered fractals as image files but often have limiting export settings and don't support many resolutions. Some programs allow the current position and zoom level, among other information, to be exported to a file, allowing interesting fractal locations to be shared easily.

Precision vs Performance To increase rendering performance, most implementations of fractal renderers use 32- or 64-bit floating point numbers. Since operations on these data types are performed directly by hardware, they are highly efficient. Unfortunately, 64-bit floating point values can only accurately represent around 15 decimal places, so zooming in far enough will exceed this precision and cause visual glitches.

To circumvent this issue, it is possible to use multi-precision floating point types capable of representing hundreds, thousands or even millions of bits, allowing for near-infinite zooms. These numbers, however, are implemented in software and are many orders of magnitude slower than standard floating point types. It is possible to use multi-precision floating point arithmetic for sufficiently optimised programs, though the performance will be abysmal.

Furthermore, some areas of different fractals require a considerable number of iterations before a reasonable amount of detail can be obtained. As a result, potentially millions of calculations must be done to determine the colour for a single pixel.

The two main issues above become even more extreme when combined with the goal of near-infinite zooming. Due to the nature of many fractals, the number of iterations required to get high levels of detail in areas close to the border of the fractal increases with zoom. Additionally, deeper zooms need higher precision numbers to represent all the points accurately. Combine these, and the result is a slow, inefficient program.

1.3 The End User

Mathematics Teachers and Professors could use the program to assist in their lessons and provide students with an interactive resource to help with homework and further their understanding. This could dramatically increase students' engagement in studies and inspire them to pursue further degrees in mathematics. Additionally, less well-off schools could afford and use the software if the program is free and open source, increasing its accessibility.

Researchers and General Academia could use the high precision, deep zooms and fast renders to further their studies on the properties of fractals. Furthermore, the more advanced fractal export tools could be used to share the exact configurations of the areas they explore to accelerate the peer-review process.

Anyone Interested in Mathematics could explore fractals' beauty and share the rendered images with their friends and family. If the program is suitably intuitive, even young children would be able to use it, potentially inspiring an interest in mathematics.

1.4 Analysis of Existing Programs

1.4.1 David J. Eck's Online Mandelbrot Renderer [4]

David Eck's online Mandelbrot rendering program implements many nice-to-have features, including the ability to export the current render settings as an XML file, intuitive controls and various configuration settings. The user can easily change the colour palette, image resolution, the number of threads to use, and more.

This implementation also supports a multi-precision floating point type, which allows the renderer to zoom in "infinitely". Unfortunately, this renderer is written in Javascript rather than a faster language like Java or, better yet, C++; as a result, it can take a long time to render an image, especially at higher resolutions and quality settings.

Interface The interface for this renderer is quite primitive and, while intuitive, is not pleasant to use. The box select to zoom in can be frustrating to use and often results in poor framing since it zooms in immediately after releasing the mouse.

The status indicator shows the current render progress and is extremely limited. It shows the current pass of the renderer, the precision it is using and the number of rows completed, but there is nothing showing the estimated time remaining, the speed at which it is rendering, or the time elapsed since the render started.

Configuration While the renderer allows for the major settings to be changed, such as the maximum number of iterations to perform, the colour palette and the number of threads to use, many of the more advanced settings cannot be changed. For advanced applications, it is often useful to know *exactly* where the frame is centred in fractal space. An arguably more important feature is the ability to specify a location and scaling factor directly, instead of zooming in manually.

On the other hand, the ability to revert to default settings, combined with the lists of predefined settings for each option, make the program much more accessible for the less experienced. This feature is a must-have for a program aimed at a wide audience.

Render Quality While the user can specify the resolution at which to render the image, it must fit on the screen you are using. You cannot render a higher-resolution image to a file, for example. Furthermore, there are no options to configure anti-aliasing with this renderer, which means the image quality may not be as high as required for some purposes.

1.4.2 XaoS.js Online Mandelbrot Renderer [5]

The Fractal Foundation *XaoS.js* Mandelbrot renderer is relatively primitive, using only machine-precision floating point arithmetic and no options to configure the fractal. On the other hand, the renderer is intuitive, with a simple click-to-zoom interface, making it ideal for less knowledgeable users who want to explore fractals.

However, the *XaoS.js* renderer does implement some complex rendering algorithms. It maintains existing pixel information from the previous frame and uses it to refine the next one, creating a smoother transition progressively. Unfortunately, these rendering techniques result in significant artefacts when sufficiently zoomed in (though the limited number of iterations performed means the fractal is unrecognisable at this point).

1.4.3 XaoS Offline Fractal Renderer [6]

The Fractal Foundation *XaoS* fractal renderer is a much more advanced, offline version of the previously examined program. Since it is free and open-source, many people have contributed code and developed its rendering algorithms. As a result, it can render fractals much faster than other programs. However, the advanced techniques used cause artefacts to appear in the final renders, making it unsuitable for academic or research purposes since it is not a true likeness of the fractal.




Figure 4: Artefacting in XaoS' renderer

Interface *XaoS* has the same intuitive controls as the online implementation, but all the configuration options are hidden in awkward menus at the top of the screen.

Configuration With enough searching, almost every parameter about the fractal can be changed, including filters such as edge detection and anti-aliasing. This is incredibly useful for advanced users, as it enables them to adjust the appearance of the fractal to their exact needs, emphasising the features they are investigating.

File Export *XaoS* allows the user to export a configuration file or save the current render as an image. The configuration file contains the information required to reconstruct the image in the renderer, simplifying the sharing of fractals between users. The image export saves the current pixels of the screen to a file, meaning the image's resolution is limited to the size of the window. This is unfortunate for those who may want to save a high-resolution image but cannot make the window large enough to support this.




Figure 5: A low-quality image saved from XaoS

Supported Fractals The *XaoS* renderer supports 25 common fractals by default and can render simple user-defined fractals. While nice to have, this feature is unnecessary for a program to implement, assuming it supports at least two fractal types. Additionally, the user-defined fractals tend to render much slower than the built-in ones since optimised algorithms can be developed for them.

Precision *XaoS* uses fixed-precision arithmetic to perform calculations; hence, you cannot zoom into the fractals indefinitely. Given the performant nature of the program, it is unfortunate that this is not a feature since it could outcompete most other rendering programs.

1.5 Program Requirements

1. Rendering
2. Configuration
3. Interface and Movement
4. Import and Export
5. Installation

6. Performance

ID	Description	Importance
1.1	The program can render a fractal correctly	HIGH
1.2	Fractals can be rendered at high resolutions without artifacting	HIGH
1.3	The fractal can be coloured to bring out details	HIGH
1.4	Colouring algorithms can be isolated from the fractal rendering process, allowing different algorithms to be implemented more easily	HIGH
1.5	Anti-aliasing can be used to reduce noise and produce a cleaner image	MEDIUM
1.6	The background colour of the fractal can be changed	LOW
1.7	Fractal algorithms are optimised for the data type used	MEDIUM
1.8	Simple optimisations are made to accelerate the rate at which fractals are rendered	MEDIUM
1.9	Images can be rendered with high-precision floating point types, allowing for “infinite” zooms	HIGH
2.1	The area of the fractal currently being rendered, as well as the zoom factor, can be changed	HIGH
2.2	The number of threads used to render the fractal can be changed	MEDIUM
2.3	The maximum number of iterations allowed can be changed	HIGH
2.4	The bailout value can be changed	LOW
2.5	The anti-aliasing factor can be changed	HIGH
2.6	The image size can be changed independently of the image resolution	HIGH
2.7	The image resolution can be changed	HIGH
2.8	The colouring algorithm can be changed and customised	MEDIUM
2.9	Settings can be reset to default values	HIGH
2.10	The option to undo/redo changes to settings	LOW
2.11	Floating point precision can be customised	HIGH
2.12	Different fractals can be rendered	MEDIUM
2.13	Each fractal has predefined default settings which are loaded when a new fractal is selected	LOW

2.14	Settings are loaded from a JSON file at program startup	LOW
3.1	There is a graphical user interface (GUI)	HIGH
3.2	The GUI is fast and responsive	HIGH
3.3	Similar settings and options are contained in a single window which can be moved around the screen	MEDIUM
3.4	Input and numeric information fields should handle data to the current precision used by the program	HIGH
3.5	Not all menus are shown initially, and settings with different complexities can be shown or hidden	MEDIUM
3.6	Different workspaces can be selected from a menu, configuring the windows and settings shown for different levels of understanding – beginner, intermediate, advanced	LOW
3.7	The area to zoom into can be selected with the mouse	HIGH
3.8	The zoom box does not need to match the aspect ratio of the fractal	LOW
3.9	The zoom box can be moved and scaled after its creation, with the option to apply the zoom after the user is happy with it	MEDIUM
3.10	The current render progress, render time, render speed and estimated time remaining are displayed	HIGH
3.11	There is a history of previous frames rendered which can be reverted to	LOW
3.12	There is a way to zoom back out of the fractal	HIGH
3.13	The fractal should be rendered progressively, allowing the user to see roughly what is being rendered without having to wait for the full image	LOW
3.14	The current location can be copied to the clipboard easily	LOW
3.15	Any numeric input fields should accept scientific input formats	HIGH
4.1	The render configuration settings can be loaded from a JSON file at runtime	MEDIUM
4.2	The render configuration settings can be saved to a JSON file, allowing for easy sharing	MEDIUM
4.3	Images can be saved to a file	HIGH
4.4	The saved images can have a user-defined filetype, and are not limited to, for example, *.png	LOW

4.5	Images can be rendered separately from the main GUI, allowing incredibly high-resolution images to be saved	POSSIBILTYY
5.1	Program compiles on Windows	HIGH
5.2	Program compiles on MacOS	HIGH
5.3	Program compiles on Linux	HIGH
5.4	Program compiles with <code>msvc</code>	HIGH
5.5	Program compiles with <code>gcc/g++</code>	HIGH
5.6	Program compiles with <code>clang</code>	HIGH
5.7	Program is easy to compile from source with CMake (i.e. <code>cmake --build . --config Release</code>)	HIGH
5.8	Prebuilt executable is available for Windows	MEDIUM
5.9	Prebuilt executable is available for MacOS	MEDIUM
5.10	Prebuilt executable is available for Linux	MEDIUM
6.1	The program can render fractals in a reasonable time (under 2 seconds) on a single thread with machine word precision	HIGH
6.2	Multiple threads can be used to accelerate the rendering process	HIGH
6.3	The rendering algorithm runs on a separate thread to the GUI, ensuring the interface continues to refresh quickly	HIGH
6.4	Where possible, calculations are optimised to suit the data type being operated on	LOW
6.5	Some simple optimisations are implemented to accelerate the rendering of the fractals	MEDIUM
6.6	Low-quality images can be rendered quickly with multi-precision data types	MEDIUM

2 Design Phase

2.1 Third Party Libraries

Cinder [7] *Cinder* is a free, open-source graphics engine for C++. It provides a simple way to access OpenGL, ImGui and other tools, such as image loading and saving, optimised rendering in 2D and 3D, and more. I am using *Cinder* for this project instead of doing all the graphics processing with raw OpenGL because it dramatically simplifies the code and reduces the scope for hard-to-fix bugs.

This project uses a modified version of *Cinder* with updated libraries and a few extra features. Most significantly, this modified version includes a much newer version of ImGui and an altered build configuration to fix common compile errors on some platforms.



LibRapid [8] *LibRapid* is a high-performance library for mathematical applications, including optimised vector classes, complex number types and general mathematical functions. However, this library's most helpful feature is its support for MPFR and MPFR, which are highly-optimised multi-precision implementations. This will allow floating point calculations with more than 64 bits.

Incorporating an efficient multi-precision implementation into the project could allow for “infinite” fractal zooms since traditional floating-point limitations would no longer constrain the software.

Another feature of *LibRapid* used heavily in this project is the compiler- and system-agnostic macro definitions. Useful features like inlining of functions, no-discard specifiers and more are not implemented by all compilers and sometimes work differently on different operating systems. LibRapid implements macros which automatically detect the relevant information and define the most suitable replacement. This isn't strictly required for the project, but it might result in a slight performance improvement and can help reduce bugs.

Cinderbox Both of the afore mentioned libraries are packaged with *Cinderbox* for simple integration into *CMake* projects.

2.2 Library Hierarchy



2.3 The Debug Logger


Since the program is written in C++ and is a GUI application instead of a console application, there will not be a usable standard output to which debug information can be printed. To circumvent this issue, I will use a debug logger instance to write information to a file.



The logger's constructor will take a file path relative to the executable and attempt to open the specified file. If the document does not exist, it will be created for the user. The destructor will ensure that all buffers are flushed, and the file is closed. Without these checks, the program may terminate without saving the changes to be written to the file, and the debug log might be incomplete or corrupt. The logger will also have a priority level, optimising logging in release builds, as the user does not need all the information. For example, the logger could be configured to write only errors to the file in release mode. Finally, the logger has a function which enables the user to send data to be written to the file. New lines should be formatted appropriately, and logs should be timestamped. In addition to these functions, I will create a macro that captures the log statement's line number and filename, making tracebacks easier and faster during development.

2.4 Colour Palettes

A simple class containing a list of colours and a few helper methods is helpful for storing the colours and gradients used by the fractal rendering process. This class simplifies the act of colour palette generation and usage throughout the software, reducing bugs and improving the rate of development.




The colour merging function is a very simple static method of the class, which linearly interpolates between the colour's red, green and blue components.

$$\left\{ t \times (R - r) + r, \quad t \times (G - g) + g, \quad t \times (B - b) + b \right\} \quad (2)$$

Where t is the interpolation factor and $0 \leq t \leq 1$.

2.5 The Fractal Class

To support multiple fractal equations at runtime, each fractal will be implemented as a class inheriting from a main parent type. This is the fractal data type. It defines the functions required to iterate the fractal's equation from a given starting value, the logic to generate a colour from a starting point, an endpoint, and the number of iterations required to get there.



For example, the code below shows the definition of the Mandelbrot fractal class.

```

01  #pragma once
02
03  #include <fractal/genericFractal.hpp>
04
05  namespace frac {
06      class Mandelbrot : public Fractal {
07      public:
08          /// Constructor taking a RenderConfig object
09          /// \param config RenderConfig object
10          explicit Mandelbrot(const RenderConfig &config);
11          Mandelbrot(const Mandelbrot &) = delete;
12          Mandelbrot(Mandelbrot &&) = delete;
13          Mandelbrot &operator=(const Mandelbrot &) = delete;
14          Mandelbrot &operator=(Mandelbrot &&) = delete;
15
16          ~Mandelbrot() override = default;
17
18          LIBRAPID_NODISCARD std::pair<int64_t, lrc::Complex<LowPrecision>>
19          iterCoordLow(const lrc::Complex<LowPrecision> &coord) const
20              override;
21
22          LIBRAPID_NODISCARD std::pair<int64_t,

```

```
        lrc::Complex<HighPrecision>>
22        iterCoordHigh(const lrc::Complex<HighPrecision> &coord) const
            override;
23    };
24 } // namespace frac
```

2.5.1 Render Box States

An enum of valid states is required to keep track of each render box's current state. This is drawn to the main window on top of the fractal as it renders, providing the user with information about which areas are rendered, which are actively rendering and which areas are yet to be processed.

```
1  /// Represents the state of a render box
2  enum class RenderBoxState {
3      None, // Not yet assigned a state
4      Queued, // Queued to be rendered
5      Rendering, // Currently being rendered
6      Rendered // Rendered and ready to be written to the image
7  };
```

2.5.2 Render Boxes

The position information required to render a small area of the main fractal is contained within a RenderBox struct. These can be passed to a function inside the FractalRenderer class to be processed.

```
1  /// Stores the pixel-space coordinates of a region to render
2  struct RenderBox {
3      lrc::Vec2i topLeft;
4      lrc::Vec2i dimensions;
5      RenderBoxState state = RenderBoxState::None;
6      double renderTime = 0;
7  };
```

2.5.3 Render Box Statistics

To calculate the remaining time of the render and the fastest and slowest render box times, the program needs to know precisely how long each box took to render. To improve efficiency, a separate struct is created to store this data.

```
1 struct RenderBoxTimeStats {
2     double min = 0;
3     double max = 0;
4     double average = 0;
5     double remainingTime = 0;
6 };
```


2.5.4 Render Configurations

Arguably the most important helper class, the `RenderConfig` struct contains all the information required for a `FractalRenderer` instance to render an image. The information in this struct can also be saved to a JSON file and shared, allowing people to send specific configurations between users easily.

```
01 struct RenderConfig {
02     int64_t numThreads; // Number of threads to render on (max)
03     int64_t maxIters; // Largest number of iterations to allow
04     int64_t precision; // Precision (in bits) of floating point types
                        // used for arithmetic
05     LowPrecision bail; // Bailout value
06     int64_t antiAlias; // Anti-aliasing factor -- 1 = no anti-aliasing
07     lrc::Vec2i imageSize; // Size of the image to render
08     lrc::Vec2i boxSize; // Size of sub-regions to render (see RenderBox)
09     lrc::Vec<HighPrecision, 2> fracTopLeft; // The fractal-space center
                        // of the image
10     lrc::Vec<HighPrecision, 2> fracSize; // The width and height of the
                        // fractal space
11     lrc::Vec<HighPrecision, 2> originalFracSize; // Original size for
                        // zoom factor calculation
12     ColorPalette palette; // The palette to use for rendering the fractal
13 };
```

2.6 The Fractal Renderer Class

While it is essential to have a method of calculating the colour of a given point on the fractal (from the fractal class), it doesn't support rendering an entire image. This is the role of the fractal renderer class.




This class implements many functions at various levels of abstraction, allowing performance-critical sections of the code to be run with efficient, parallelised algorithms. At the same time, the high-level interfaces are easy to interact with and use.

2.6.1 Configuration, Getters, Setters and Statistics



These functions operate at a high level, allowing basic access to the information stored by the class. While simple, they are essential for the main program to function correctly, as there would be no way of accessing the rendered image, for example.

2.6.2 Constructors and Configurations



To render a fractal, much information is required about the dimensions of the image, the dimensions of the fractal, the origin in the complex plane, and more.

The fractal renderer class can parse a JSON object and load its configuration. By storing some data as a string instead of a number, it is possible to save and load high-precision numbers as well – this could be used to enable

fractal locations with extremely high zoom factors to be saved and shared easily.


The JSON snippet below shows a highly simplified version of the default configuration used within the software (for a full version, see the code-listing at the end of the document).

```
01 {
02     "renderConfig": {
03         "numThreads": 8,
04         "maxIters": 500,
05         "precision": 64,
06         "bail": 65536,
07         "antiAlias": 2,
08         "imageSize": {
09             "width": 800,
10             "height": 700
11         },
12         "colorPalette": [
13             {
14                 "red": 0.5568628,
15                 "green": 0.23137255,
16                 "blue": 0.27450982,
17                 "alpha": 1.0
18             },
19             {
20                 "red": 0.88235295,
21                 "green": 0.8666667,
22                 "blue": 0.56078434,
23                 "alpha": 1.0
24             }
25         ]
26     }
27 }
```

A vast number of configuration options can be configured in the file, including the threading options, render quality settings and even the size of the boxes to render in parallel.

The loadConfiguration method also enables the configuration to be changed or re-parsed at runtime, allowing quick and easy updates to the fractal settings.

2.6.3 Rendering Algorithms



The fractal renderer is responsible for creating an image buffer and setting the colour of each pixel in that image to represent the fractal at that location. Doing this efficiently is difficult, so the process is split into many small functions, providing fine-grained control over the algorithm.

Upon requesting the renderer to re-render the image, any existing render threads are halted, dependent image settings are recalculated, and the render-box queue is cleared.

Next, the render boxes are recalculated and pushed back to the render queue. Each box is dequeued by a thread in a thread pool and runs in parallel.


To optimise the rendering of each box, we can use the fact that if an outline can be drawn where every point is in the set, every point contained within that outline must also be within the set. Outlining each box before calculating the inner area makes it possible to check whether all points were in the set. If they were, we can quickly fill the rest of the box without calculating the colour of each pixel.

To calculate the colour of each pixel, we first call the `iterCoord` method of the fractal pointer stored to get the number of iterations required to exceed the bailout value (if it is exceeded at all), as well as the first point at which this occurs. This information is then passed to the fractal's colouring algorithm to generate a colour for the pixel. If anti-aliasing is enabled, this process is repeated for multiple points within the pixel, and the resulting colours are averaged. Anti-aliasing produces smoother images that appear to be higher

resolution, allowing for faster render times with high-quality results.

The fractal renderer class also implements routines to change the fractal-space coordinates to render. This is used to move the fractal when zooming in or out. For different use cases, there are methods to set the top left coordinate or the image's centre.

2.7 The Main Window



This class is responsible for creating, managing and drawing information to the window and controlling all the other classes mentioned previously.

When the window is created by *Cinder*, the setup routine is called, initializing the window's attributes. First, the settings JSON file is loaded, parsed and passed to the fractal renderer member. Next, the window itself is constructed and configured, including the framerate, enabling or disabling vertical syncing

(V-Sync), the window size and OpenGL depth buffer settings. Finally, *ImGui* is configured.

The `MainWindow` class is also responsible for drawing to the window. After setting the background colour, the *ImGui* windows are created and drawn. This produces most of the UI, but some extra parts must be drawn in later. Next, the fractal itself is drawn to the screen. An image texture is created and assigned the fractal image buffer, and a rectangle is drawn with the aforementioned texture. The rest of the UI is now drawn, including the render-box status indicators and the mouse selection.

When the application is requested to close, the cleanup routine is called. This signals any existing render threads to halt, ensures all members are correctly destructed and then destroys the window.

The window also has a variety of callback functions which are called when specific triggers occur. For example, functions are called every time the mouse is moved, dragged or pressed.


2.8 Additional Features

The features outlined previously comprise the vast majority of the program, but some additional features must also be designed and implemented. These are often the less critical features, though they still impact the user's interaction with the program.

2.8.1 Movement History

While we often take the “undo” and “redo” buttons for granted, they give us a powerful means of reverting unwanted changes. Furthermore, they allow the user to see what adjustments have been made to the fractal between movements, supporting verbal descriptions of how to arrive at fascinating points within the fractal.

Using a linked list, where each node stores a `RenderConfig` object and a `Surface`, it is possible to implement a move history into the program. Whenever the user requests to change a setting or move the origin of the fractal, the current surface and render configuration are appended to the history before the changes are applied. The algorithm to append to the linked list can be seen below.



The `MainWindow` class also stores a pointer to the current node in the history buffer. Using this, it is possible to detect whether there are changes before or after the current node by checking the validity of the previous and next pointers respectively.

When the user makes a change, the current node is checked against the end of the history buffer. If there are no changes after the current state, the new state is appended directly to the end of the buffer. However, if changes exist, it is necessary to destroy the rest of the tree with the `killChildren` method before appending the new configuration. To undo moves, the current

node is moved backwards down the list.

To make these commands as intuitive as possible, the undo and redo commands are triggered by pressing `ctrl+z` and `ctrl+shift+z` respectively. These are very common commands and will be easy to remember.

To show the user the current history, a small tab is rendered on the right side of the window. Each item in the history buffer is shown by drawing the saved surface, with the current item outlined to make it more obvious where in the history tree you are.

Mouse events within this tab are also supported, such as scrolling and clicking on frames to select items in the history.

Scrolling is implemented with a single offset which is increased or decreased as the mouse wheel is moved. The rate at which the window scrolls is defined by the `settings[‘menus’][‘history’][‘scrollSpeed’]` value in the settings JSON file.

2.8.2 Improved Selection Area

To improve the user-interface, the zoom selection box should not zoom in immediately after being drawn. Once the box is specified, it should be possible to drag the box around to more precisely specify where the zoom will occur. Additionally, keyboard inputs (for example, the arrow keys) should move the selected region.

To support dragging the box with the mouse, adding the mouse position delta between each frame to the current box’s position maintains the mouse’s location within the box and provides intuitive movement. The code below shows a simple implementation.

```
01 void MainWindow::mouseDrag(ci::app::MouseEvent event) {
02     if (ImGui::GetIO().WantCaptureMouse) return;
03
04     lrc::Vec2i delta = lrc::Vec2i(event.getPos()) - m_mousePos;
05     m_mousePos = event.getPos();
06
07     if (m_moveZoomBox) {
08         m_zoomBoxStart += delta;
09         m_zoomBoxEnd += delta;
10     }
11 }
```

3 Technical Solution

3.1 Color Palette (colorPalette.hpp)

```
01 #pragma once
02
03 namespace frac {
04     class ColorPalette {
05     public:
06         using ColorType = lrc::Vec<float, 4>;
07
08         ColorPalette() = default;
09         ColorPalette(const ColorPalette &) = default;
10         ColorPalette(ColorPalette &&) = default;
11         ColorPalette &operator=(const ColorPalette &) = default;
12         ColorPalette &operator=(ColorPalette &&) = default;
13
14         /// Append a new colour to the palette
15         /// \param color The colour to add
16         void addColor(const ColorType &color);
17
18         /// Return the number of colours in the palette
19         /// \return The number of colours in the palette
20         LIBRAPID_NODISCARD size_t size() const;
21
22         /// Indexing operator (const)
23         /// \param index The index of the colour to return
24         /// \return The colour at the given index
25         const ColorType &operator[](size_t index) const;
26
27         /// Indexing operator (non-const)
28         /// \param index The index of the colour to return
29         /// \return The colour at the given index
30         ColorType &operator[](size_t index);
31
32         /// Linearly interpolate between two colours
33         /// \param a First colour
34         /// \param b Second colour
35         /// \param t Interpolation factor
36         /// \return The interpolated colour
37         static ColorType merge(const ColorType &a, const ColorType &b,
38                                 float t);
39     private:
40         std::vector<ColorType> m_colors;
```

```
41     };  
42 } // namespace frac
```

3.2 Color Palette (colorPalette.cpp)

```
01 #include <fractal/fractal.hpp>  
02  
03 namespace frac {  
04     void ColorPalette::addColor(const ColorType &color) {  
05         m_colors.push_back(color);  
06         FRAC_LOG(fmt::format("Adding Color: {} {} {} {}", color.x(),  
07                               color.y(), color.z(), color.w()));  
07     }  
08  
09     size_t ColorPalette::size() const { return m_colors.size(); }  
10  
11     const ColorPalette::ColorType &ColorPalette::operator[](size_t  
12         index) const {  
13         if (index > m_colors.size())  
14             FRAC_ERROR(fmt::format(  
15                 "Index {} out of bounds for ColorPalette with size {}",  
16                 index, m_colors.size()));  
17         return m_colors[index];  
18     }  
19  
20     ColorPalette::ColorType &ColorPalette::operator[](size_t index) {  
21         if (index > m_colors.size())  
22             FRAC_ERROR(fmt::format(  
23                 "Index {} out of bounds for ColorPalette with size {}",  
24                 index, m_colors.size()));  
25         return m_colors[index];  
26     }  
27  
28     ColorPalette::ColorType ColorPalette::merge(const ColorType &a,  
29         const ColorType &b, float t) {  
30         return a + (b - a) * t;  
31     }  
32 } // namespace frac
```


3.3 Debug Logger (debug.hpp)

```
01 #pragma once
02
03 #define FRAC_LOG(message) \
04     ::frac::debugLogger.write(message, ::frac::Priority::Info, FILENAME,
05     __LINE__)
06 #define FRAC_WARN(message) \
07     ::frac::debugLogger.write(message, ::frac::Priority::Warning,
08     FILENAME, __LINE__)
09 #define FRAC_ERROR(message) \
10     ::frac::debugLogger.write(message, ::frac::Priority::Error,
11     FILENAME, __LINE__)
12
13 namespace frac {
14     // A way to specify the verbosity of the debug logger
15     enum class Priority { Info = 0, Warning = 5, Error = 10 };
16
17     /// A logger type that can write debug information to a file
18     class DebugLogger {
19     public:
20         /*
21          * Since there should only ever be a single DebugLogger
22          * instance, delete the
23          * majority of the constructors and assignment operators as they
24          * are not needed
25          */
26
27         DebugLogger() = delete;
28         DebugLogger(const DebugLogger &) = delete;
29         DebugLogger(DebugLogger &&) = delete;
30         DebugLogger &operator=(const DebugLogger &) = delete;
31         DebugLogger &operator=(DebugLogger &&) = delete;
32
33         /// Create a new DebugLogger instance from a filename
34         /// \param filename
35         explicit DebugLogger(const std::string &filename,
36                             Priority priority = Priority::Info);
37
38         /// Close the file stream on destruction
39         ~DebugLogger();
40
41         /// Set the priority level of the debugger's logs. Higher
42         /// priorities will be
43         /// logged in release mode, while lower priorities will only be
```

```

        logged in debug
38    /// mode
39    /// \param newPriority The new priority level
40    void setPriorityLevel(Priority newPriority) { m_priority =
        newPriority; }
41
42    /// Write a message to the log file
43    /// \param message The message to write
44    /// \param priority The priority of the message (see Priority)
45    /// \param filename The filename of the file that called this
        function
46    /// \param line The line number of the file that called this
        function
47    void write(const std::string &message, Priority priority,
48               const std::string &filename, int64_t line);
49
50    private:
51        std::fstream m_log;        // File stream
52        double m_startTime;        // Time at which the logger was created
53        Priority m_priority = Priority::Info; // Priority level of the
        logger
54    };
55
56    extern DebugLogger debugLogger;
57 } // namespace frac

```

3.4 Debug Logger (debug.cpp)

```

01 #include <fractal/fractal.hpp>
02
03 namespace frac {
04     DebugLogger::DebugLogger(const std::string &filename, Priority
        priority) {
05         m_log.open(filename, std::fstream::out);
06         m_startTime = lrc::now();
07
08         m_log << "=====[ FRACTAL RENDERER DEBUG LOG
            ]=====\n" << std::endl;
09     }
10
11     DebugLogger::~DebugLogger() {
12         m_log << "\n=====[ FRACTAL RENDERER DEBUG LOG
            ]=====";
13         m_log.flush();
14         m_log.close();

```

```
15     }
16
17     void DebugLogger::write(const std::string &message, Priority
        priority,
18                             const std::string &filename, int64_t line) {
19         if (static_cast<size_t>(priority) <
            static_cast<size_t>(m_priority)) return;
20
21         double time      = lrc::now();
22         constexpr size_t maxFilenameLength = 40;
23         std::string truncatedFilename;
24         std::string priorityString;
25         std::string cleanedMessage;
26
27         if (filename.size() > maxFilenameLength)
28             truncatedFilename =
29                 "... " + filename.substr(filename.size() - maxFilenameLength
                    + 3, maxFilenameLength);
30         else
31             truncatedFilename = filename;
32
33         switch (priority) {
34             case Priority::Info: priorityString = "INFO"; break;
35             case Priority::Warning: priorityString = "WARNING"; break;
36             case Priority::Error: priorityString = "ERROR"; break;
37         }
38
39         // Pad new lines with 26 spaces to align with the beginning of
            the message
40         // in the log file.
41         int64_t preambleLength = 26 + maxFilenameLength;
42         for (char c : message) {
43             cleanedMessage += c;
44             if (c == '\n') cleanedMessage += std::string(preambleLength,
                ' ');
45         }
46
47         // Use std::endl here to force-flush the buffer -- this is the
            only way
48         // to ensure that the log is written to disk in the event of a
            crash
49         m_log << fmt::format("[ {:.5f} ] {:>7} {:>{}}: {:>4} {}",
50                             time - m_startTime,
51                             priorityString,
52                             truncatedFilename,
```

```
53             maxFilenameLength,
54             line,
55             cleanedMessage)
56         << std::endl;
57     }
58
59     #if defined(LIBRAPID_DEBUG) // More reliable than NDEBUG
60         DebugLogger debugLogger("./log.txt", Priority::Info); // Log all
            messages
61     #else
62         DebugLogger debugLogger("./log.txt", Priority::Warning); // Only
            warnings and above
63     #endif
64 } // namespace frac
```

3.5 Fractal Base Class Implementation (fractal.hpp)

```
01 #pragma once
02
03 #include <cinderbox/cinderbox.hh>
04 #include <librapid>
05 #include <fstream>
06 #include <nlohmann/json.hpp>
07 #include <BS_thread_pool.hpp>
08
09 #ifndef FRACTAL_SETTINGS_PATH
10 # define FRACTAL_UI_SETTINGS_PATH FRACTAL_RENDERER_ROOT_DIR
11     "/settings/settings.json"
12 #endif
13
14 namespace lrc = librapid;
15
16 using ThreadPool = BS::thread_pool;
17 using json = nlohmann::json;
18
19 namespace frac {
20     using HighPrecision = lrc::mpf;
21     using LowPrecision = double;
22
23     using HighVec2 = lrc::Vec<HighPrecision, 2>;
24     using LowVec2 = lrc::Vec<LowPrecision, 2>;
25 } // namespace frac
26
27 #include <fractal/debug.hpp>
28 #include <fractal/colorPalette.hpp>
29 #include <fractal/openglUtils.hpp>
30 #include <fractal/renderConfig.hpp>
31 #include <fractal/genericFractal.hpp>
32 #include <fractal/mandelbrot.hpp>
33 #include <fractal/fractalRenderer.hpp>
34 #include <fractal/history.hpp>
35 #include <fractal/mainWindow.hpp>
```

3.6 Fractal Renderer Definition (fractalRenderer.hpp)

```
001 #pragma once
002
003 namespace frac {
004     class FractalRenderer {
005     public:
006         FractalRenderer() = default;
007
008         /// Construct a new renderer object from a JSON config object
009         /// \param config The JSON config object
010         explicit FractalRenderer(const json &config);
011
012         ~FractalRenderer();
013
014         /// Set the fractal renderer config
015         /// \param config JSON object
016         void setConfig(const json &config);
017
018         /// Stop the renderer gracefully and wait for all threads to
019         /// rejoin main
020         void stopRender();
021
022         /// Set the complex-valued coordinate of the top-left corner of
023         /// the fractal and
024         /// its size
025         /// \param topLeft Top-left corner
026         /// \param size Size of the fractal
027         /// \see moveFractalCenter
028         void moveFractalCorner(const lrc::Vec<HighPrecision, 2> &topLeft,
029                               const lrc::Vec<HighPrecision, 2> &size);
030
031         /// Set the complex-valued coordinate of the center of the
032         /// fractal and its size
033         /// \param center Center of the fractal
034         /// \param size Size of the fractal
035         /// \see moveFractalCorner
036         void moveFractalCenter(const lrc::Vec<HighPrecision, 2> &center,
037                                const lrc::Vec<HighPrecision, 2> &size);
038
039         /// Render the fractal into the fractal surface, and copy that
040         /// to the
041         /// fractal surface to be drawn. This will be executed on a
042         /// separate thread
043         /// in order to keep the UI updating
```

```
039     void renderFractal();
040
041     /// Render a sub-section of the fractal, defined by the \p box
042     /// variable. This is
043     /// intended to be used within the call queue to render multiple
044     /// sections in
045     /// parallel
046     /// \param box The box configuration
047     /// \param boxIndex Box ID (for updating states)
048     void renderBox(const RenderBox &box, int64_t boxIndex = -1);
049
050     /// Calculate the colour of a pixel at standard-precision. This
051     /// implements
052     /// anti-aliasing as well
053     /// \param pixPos Pixel-space coordinate
054     /// \param aliasFactor Anti-aliasing factor
055     /// \param step Step size
056     /// \param aliasStepCorrect Anti-aliasing step correction
057     /// \return Color of the pixel
058     ci::ColorA pixelColorLow(const LowVec2 &pixPos, int64_t
059         aliasFactor,
060         const LowVec2 &step, const LowVec2
061         &aliasStepCorrect);
062
063     /// Calculate the colour of a pixel at high-precision. See
064     /// pixelColorLow
065     /// \param pixPos Pixel-space coordinate
066     /// \param aliasFactor Anti-aliasing factor
067     /// \param step Step size
068     /// \param aliasStepCorrect Anti-aliasing step correction
069     /// \return Color of the pixel
070     /// \see pixelColorLow
071     ci::ColorA pixelColorHigh(const HighVec2 &pixPos, int64_t
072         aliasFactor,
073         const HighVec2 &step, const HighVec2
074         &aliasStepCorrect);
075
076     /// Update the render configuration of the internal fractal
077     /// pointer
078     void updateRenderConfig();
079
080     /// Ensure all values are using the highest precision possible
081     void updateConfigPrecision();
082
083     /// Regenerate the surfaces and resize them to fit the image size
```

```
075         void regenerateSurface();
076
077         /// Getter method for the render box time statistics
078         /// \return Statistics
079         LIBRAPID_NODISCARD RenderBoxTimeStats boxTimeStats() const;
080
081         /// Constant getter method for the render configuration
082         /// \return Render configuration
083         LIBRAPID_NODISCARD const RenderConfig &config() const;
084
085         /// Non-const getter method for the render configuration
086         /// \return Render configuration
087         LIBRAPID_NODISCARD RenderConfig &config();
088
089         /// Constant getter method for the internal render box vector
090         /// \return Render box vector
091         LIBRAPID_NODISCARD const std::vector<RenderBox> &renderBoxes()
092             const;
093
094         /// Non-const getter method for the internal render box vector
095         /// \return Render box vector
096         LIBRAPID_NODISCARD std::vector<RenderBox> &renderBoxes();
097
098         /// Constant getter method for the internal settings object
099         /// \return Settings object
100         LIBRAPID_NODISCARD const json &settings() const;
101
102         /// Non-const getter method for the internal settings object
103         /// \return Settings object
104         LIBRAPID_NODISCARD json &settings();
105
106         /// Constant getter method for the internal surface
107         /// \return Surface
108         LIBRAPID_NODISCARD const ci::Surface &surface() const;
109
110         /// Non-const getter method for the internal surface
111         /// \return Surface
112         LIBRAPID_NODISCARD ci::Surface &surface();
113
114     private:
115         RenderConfig m_renderConfig; // The settings for the fractal
116                                     // renderer
117         ci::Surface m_fractalSurface; // The surface that the fractal
118                                     // is rendered to
119         json m_settings; // The settings for the fractal
```



```
117         std::unique_ptr<Fractal> m_fractal; // The fractal to render
118         ThreadPool m_threadPool;    // Pool for render threads
119
120         std::vector<RenderBox> m_renderBoxes; // The state of each
            render box
121
122         bool m_haltRender = false; // Used to gracefully stop the render
            threads
123     };
124 } // namespace frac
```

3.7 Fractal Renderer Implementation (fractalRenderer.cpp)

```
001 #include <fractal/fractal.hpp>
002
003 namespace frac {
004     FractalRenderer::FractalRenderer(const json &config) {
005         setConfig(config); }
006     FractalRenderer::~FractalRenderer() { stopRender(); }
007
008     void FractalRenderer::setConfig(const json &config) {
009         m_settings = config;
010
011         try {
012             // Set the default precision
013             lrc::prec2(m_settings["renderConfig"]["precision"].get<int64_t>());
014
015             // Load settings from settings JSON object
016             m_renderConfig = RenderConfig {
017                 m_settings["renderConfig"]["numThreads"].get<int64_t>(),
018                 m_settings["renderConfig"]["maxIters"].get<int64_t>(),
019                 m_settings["renderConfig"]["precision"].get<int64_t>(),
020                 m_settings["renderConfig"]["bail"].get<LowPrecision>(),
021                 m_settings["renderConfig"]["antiAlias"].get<int>(),
022
023                 lrc::Vec2i(
024                     m_settings["renderConfig"]["imageSize"]["width"].get<int64_t>(),
025                     m_settings["renderConfig"]["imageSize"]["height"].get<int64_t>()),
026                 lrc::Vec2i(m_settings["renderConfig"]["boxSize"]["width"].get<int64_t>(),
027                     m_settings["renderConfig"]["boxSize"]["height"].get<int64_t>()),
028
029                 lrc::Vec<HighPrecision, 2>(
030                     m_settings["renderConfig"]["fracTopLeft"]["Re"].get<float>(),
031                     m_settings["renderConfig"]["fracTopLeft"]["Im"].get<float>()),
032                 lrc::Vec<HighPrecision, 2>(
```

```
032         m_settings["renderConfig"]["fracSize"]["Re"].get<float>(),
033         m_settings["renderConfig"]["fracSize"]["Im"].get<float>()),
034         lrc::Vec<HighPrecision, 2>(0, 0),
035
036         ColorPalette(), // Default for now -- colors added later
037
038         m_settings["renderConfig"]["draftRender"].get<bool>(),
039         m_settings["renderConfig"]["draftInc"].get<int64_t>());
040
041     m_renderConfig.originalFracSize = m_renderConfig.fracSize;
042
043     // Load the colour palette from the JSON object
044     for (const auto &color :
045         m_settings["renderConfig"]["colorPalette"]) {
046         m_renderConfig.palette.addColor(
047             ColorPalette::ColorType(color["red"].get<float>(),
048                                     color["green"].get<float>(),
049                                     color["blue"].get<float>(),
050                                     color["alpha"].get<float>()));
051     }
052
053     m_fractal = std::make_unique<Mandelbrot>(m_renderConfig);
054 } catch (std::exception &e) {
055     FRAC_LOG(fmt::format("Failed to load settings: {}"),
056             e.what());
057     stopRender();
058 }
059
060 void FractalRenderer::stopRender() {
061     m_haltRender = true;
062     m_threadPool.wait_for_tasks();
063     m_haltRender = false;
064 }
065
066 void FractalRenderer::moveFractalCorner(const
067     lrc::Vec<HighPrecision, 2> &topLeft,
068     const lrc::Vec<HighPrecision, 2>
069     &size) {
070     m_renderConfig.fracTopLeft = topLeft;
071     m_renderConfig.fracSize = size;
072     m_fractal->updateRenderConfig(m_renderConfig);
073 }
074
075 void FractalRenderer::moveFractalCenter(const
```

```
lrc::Vec<HighPrecision, 2> &center,
073                                     const lrc::Vec<HighPrecision, 2>
                                     &size) {
074     moveFractalCorner(center - size / lrc::Vec<HighPrecision, 2>(2,
        2), size);
075 }
076
077 void FractalRenderer::renderFractal() {
078     if (m_threadPool.get_tasks_queued() > 0) {
079         FRAC_WARN("Render already in progress. Halting...");
080         m_haltRender = true;
081         m_threadPool.wait_for_tasks();
082         m_haltRender = false;
083         FRAC_LOG("Render halted");
084     }
085
086     FRAC_LOG("Rendering Fractal...");
087
088     m_renderBoxes.clear();
089     m_threadPool.reset(m_renderConfig.numThreads);
090
091     // Split the render into boxes to be rendered in parallel
092     auto imageSize = m_renderConfig.imageSize;
093     auto boxSize = m_renderConfig.boxSize;
094
095     // Round number of boxes up so the full image is covered
096     auto numBoxes =
097         lrc::Vec2i(lrc::ceil(lrc::Vec2f(imageSize) /
        lrc::Vec2f(boxSize)));
098
099     m_renderBoxes.reserve(numBoxes.x() * numBoxes.y());
100
101     // Iterate over all boxes
102     for (int64_t i = 0; i < numBoxes.y(); ++i) {
103         for (int64_t j = 0; j < numBoxes.x(); ++j) {
104             lrc::Vec2i adjustedBoxSize(
105                 lrc::min(boxSize.x(), imageSize.x() - j * boxSize.x()),
106                 lrc::min(boxSize.y(), imageSize.y() - i * boxSize.y()));
107             RenderBox box {lrc::Vec2i(j, i) * boxSize,
108                           adjustedBoxSize,
109                           m_renderConfig.draftRender,
110                           m_renderConfig.draftInc,
111                           RenderBoxState::Queued};
112
113             auto prevSize = (int64_t)m_renderBoxes.size();
```

```
114
115         // Must happen before pushing to render queue
116         m_renderBoxes.emplace_back(box);
117
118         m_threadPool.push_task(
119             [this, box, prevSize]() { renderBox(box, prevSize); });
120     }
121 }
122
123     FRAC_LOG("Fractal Complete...");
124 }
125
126 void FractalRenderer::renderBox(const RenderBox &box, int64_t
    boxIndex) {
127     // Update the render box state
128     m_renderBoxes[boxIndex].state = RenderBoxState::Rendering;
129     const double start = lrc::now();
130
131     const int64_t inc = box.draftRender ? box.draftInc : 1;
132
133     HighVec2 fractalOrigin = lrc::map(
134         static_cast<HighVec2>(box.topLeft),
135         HighVec2({0, 0}),
136         static_cast<HighVec2>(m_renderConfig.imageSize),
137         m_renderConfig.fracTopLeft,
138         m_renderConfig.fracTopLeft +
            static_cast<HighVec2>(m_renderConfig.fracSize));
139
140     HighVec2 step =
141         m_renderConfig.fracSize /
            static_cast<HighVec2>(m_renderConfig.imageSize);
142
143     int64_t aliasFactor = m_renderConfig.antiAlias;
144     if (box.draftRender) aliasFactor = 1; // No anti-aliasing for
        drafts
145
146     HighPrecision scaleFactor =
147         HighPrecision(1) / static_cast<HighPrecision>(aliasFactor);
148     HighVec2 aliasStepCorrect(scaleFactor, scaleFactor);
149
150     bool blackEdges = true; // Assume edges are black to begin with
151
152     if (m_haltRender) return;
153
154     if (box.draftRender) {
```

```
155         for (int64_t py = box.topLeft.y(); py < box.topLeft.y() +
156             box.dimensions.y();
157             ++py) {
158             for (int64_t px = box.topLeft.x();
159                 px < box.topLeft.x() + box.dimensions.x();
160                 ++px) {
161                 m_fractalSurface.setPixel(lrc::Vec2i(px, py),
162                     ci::ColorA {0.2, 0, 0.2, 0.5});
163             }
164         }
165
166         // Render the top edge
167         for (int64_t px = box.topLeft.x(); px < box.topLeft.x() +
168             box.dimensions.x();
169             px += inc) {
170             // Anti-aliasing
171             auto pixPos = fractalOrigin + step * HighVec2(px -
172                 box.topLeft.x(), 0);
173
174             ci::ColorA pix;
175
176             if (m_renderConfig.precision <= 64) {
177                 pix = pixelColorLow(pixPos, aliasFactor, step,
178                     aliasStepCorrect);
179             } else {
180                 pix = pixelColorHigh(pixPos, aliasFactor, step,
181                     aliasStepCorrect);
182             }
183
184             if (blackEdges && (pix.r != 0 && pix.g != 0 && pix.b != 0)) {
185                 blackEdges = false;
186             }
187
188             m_fractalSurface.setPixel(lrc::Vec2i(px, box.topLeft.y()),
189                 pix);
190         }
191
192         if (m_haltRender) return;
193
194         // Render the right edge
195         for (int64_t py = box.topLeft.y(); py < box.topLeft.y() +
196             box.dimensions.y();
197             py += inc) {
198             // Anti-aliasing
```

```
193         auto pixPos =
194             fractalOrigin + step * HighVec2(box.dimensions.x(), py -
195                 box.topLeft.y());
196
197         ci::ColorA pix;
198
199         if (m_renderConfig.precision <= 64) {
200             pix = pixelColorLow(pixPos, aliasFactor, step,
201                 aliasStepCorrect);
202         } else {
203             pix = pixelColorHigh(pixPos, aliasFactor, step,
204                 aliasStepCorrect);
205         }
206
207         if (blackEdges && (pix.r != 0 && pix.g != 0 && pix.b != 0)) {
208             blackEdges = false;
209         }
210
211         m_fractalSurface.setPixel(
212             lrc::Vec2i(box.topLeft.x() + box.dimensions.x() - 1, py),
213             pix);
214     }
215
216     if (m_haltRender) return;
217
218     // Render the bottom edge
219     for (int64_t px = box.topLeft.x(); px < box.topLeft.x() +
220         box.dimensions.x();
221         px += inc) {
222         // Anti-aliasing
223         auto pixPos = fractalOrigin +
224             step * HighVec2(px - box.topLeft.x(),
225                 box.dimensions.y() - 1);
226
227         ci::ColorA pix;
228
229         if (m_renderConfig.precision <= 64) {
230             pix = pixelColorLow(pixPos, aliasFactor, step,
231                 aliasStepCorrect);
232         } else {
233             pix = pixelColorHigh(pixPos, aliasFactor, step,
234                 aliasStepCorrect);
235         }
236
237         if (blackEdges && (pix.r != 0 && pix.g != 0 && pix.b != 0)) {
```

```
230         blackEdges = false;
231     }
232
233     m_fractalSurface.setPixel(
234         lrc::Vec2i(px, box.topLeft.y() + box.dimensions.y() - 1),
235         pix);
236
237     if (m_haltRender) return;
238
239     // Render the left edge
240     for (int64_t py = box.topLeft.y(); py < box.topLeft.y() +
241         box.dimensions.y();
242         py += inc) {
243         // Anti-aliasing
244         auto pixPos =
245             fractalOrigin +
246             step * HighVec2(box.topLeft.x() - box.topLeft.x(), py -
247                 box.topLeft.y());
248
249         ci::ColorA pix;
250
251         if (m_renderConfig.precision <= 64) {
252             pix = pixelColorLow(pixPos, aliasFactor, step,
253                 aliasStepCorrect);
254         } else {
255             pix = pixelColorHigh(pixPos, aliasFactor, step,
256                 aliasStepCorrect);
257         }
258
259         if (blackEdges && (pix.r != 0 && pix.g != 0 && pix.b != 0)) {
260             blackEdges = false;
261         }
262
263         m_fractalSurface.setPixel(lrc::Vec2i(box.topLeft.x(), py),
264             pix);
265     }
266
267     if (blackEdges) {
268         for (int64_t py = box.topLeft.y() + 1;
269             py < box.topLeft.y() + box.dimensions.y() - 1;
270             py += inc) {
271             for (int64_t px = box.topLeft.x() + 1;
272                 px < box.topLeft.x() + box.dimensions.x() - 1;
273                 px += inc) {
```

```
269         m_fractalSurface.setPixel(lrc::Vec2i(px, py),
270                                   ci::ColorA {0, 0, 0, 1});
271     }
272 }
273 } else {
274     // Make the primary axis of iteration the x-axis to improve
    // cache
275     // efficiency and increase performance.
276     for (int64_t py = box.topLeft.y() + 1;
277         py < box.topLeft.y() + box.dimensions.y() - 1;
278         py += inc) {
279         // Quick return if required. Without this, the
280         // render threads will continue running after the
281         // application is closed, leading to weird behaviour.
282         if (m_haltRender) return;
283
284         for (int64_t px = box.topLeft.x() + 1;
285             px < box.topLeft.x() + box.dimensions.x() - 1;
286             px += inc) {
287             // Anti-aliasing
288             auto pixPos = fractalOrigin + step * HighVec2(px -
                box.topLeft.x(),
289
290
291                                     py -
292                                     box.topLeft.y());
293
294             ci::ColorA pix;
295
296             if (m_renderConfig.precision <= 64) {
297                 pix = pixelColorLow(pixPos, aliasFactor, step,
298                                     aliasStepCorrect);
299             } else {
300                 pix = pixelColorHigh(pixPos, aliasFactor, step,
301                                     aliasStepCorrect);
302             }
303
304             m_fractalSurface.setPixel(lrc::Vec2i(px, py), pix);
305         }
306     }
307 }
308
309 // Update the render box state
310 m_renderBoxes[boxIndex].state = RenderBoxState::Rendered;
311 m_renderBoxes[boxIndex].renderTime = lrc::now() - start;
```



```
309     ci::ColorA FractalRenderer::pixelColorLow(const LowVec2 &pixPos,
310                                                int64_t aliasFactor,
311                                                const LowVec2 &step,
312                                                const LowVec2
313                                                &aliasStepCorrect) {
314     ci::ColorA pix(0, 0, 0, 1);
315     for (int64_t aliasY = 0; aliasY < aliasFactor; ++aliasY) {
316         for (int64_t aliasX = 0; aliasX < aliasFactor; ++aliasX) {
317             auto pos = pixPos + step * LowVec2(aliasX, aliasY) *
318                 aliasStepCorrect;
319             auto [iters, endPoint] =
320                 m_fractal->iterCoordLow(lrc::Complex<LowPrecision>(pos.x(),
321                 pos.y()));
322             if (endPoint.real() * endPoint.real() +
323                 endPoint.imag() * endPoint.imag() <
324                 4) {
325                 pix += ci::ColorA(0, 0, 0, 1); // Probably in the set
326             } else {
327                 pix +=
328                     m_fractal->getColorLow(endPoint, iters); // Probably
329                     not in the set
330             }
331         }
332     }
333     return pix / static_cast<float>(aliasFactor * aliasFactor);
334 }
335
336 ci::ColorA FractalRenderer::pixelColorHigh(const HighVec2 &pixPos,
337                                              int64_t aliasFactor, const
338                                              HighVec2 &step,
339                                              const HighVec2
340                                              &aliasStepCorrect) {
341     ci::ColorA pix(0, 0, 0, 1);
342     for (int64_t aliasY = 0; aliasY < aliasFactor; ++aliasY) {
343         for (int64_t aliasX = 0; aliasX < aliasFactor; ++aliasX) {
344             auto pos = pixPos + step * HighVec2(aliasX, aliasY) *
345                 aliasStepCorrect;
346             auto [iters, endPoint] =
347                 m_fractal->iterCoordHigh(lrc::Complex<HighPrecision>(pos.x(),
348                 pos.y()));
```

```
345         if (endPoint.real() * endPoint.real() +
346             endPoint.imag() * endPoint.imag() <
347             4) {
348             pix += ci::ColorA(0, 0, 0, 1); // Probably in the set
349         } else {
350             pix +=
351                 m_fractal->getColorHigh(endPoint, iters); //
352                 // Probably not in the set
353         }
354     }
355
356     return pix / static_cast<float>(aliasFactor * aliasFactor);
357 }
358
359 void FractalRenderer::updateRenderConfig() {
360     m_fractal->updateRenderConfig(m_renderConfig);
361 }
362
363 void FractalRenderer::regenerateSurface() {
364     FRAC_LOG("Regenerating Surface...");
365     int64_t w = m_renderConfig.imageSize.x();
366     int64_t h = m_renderConfig.imageSize.y();
367     m_fractalSurface = ci::Surface((int32_t)w, (int32_t)h, true);
368     FRAC_LOG("Surface regenerated");
369 }
370
371 void FractalRenderer::updateConfigPrecision() {
372     int64_t prec = m_renderConfig.precision;
373     HighPrecision highPrecTopLeftX(m_renderConfig.fracTopLeft.x(),
374                                     prec);
375     HighPrecision highPrecTopLeftY(m_renderConfig.fracTopLeft.y(),
376                                     prec);
377     HighPrecision highPrecFracSizeX(m_renderConfig.fracSize.x(),
378                                     prec);
379     HighPrecision highPrecFracSizeY(m_renderConfig.fracSize.y(),
380                                     prec);
381     HighPrecision highPrecOriginalFracSizeX(m_renderConfig.originalFracSize.x(),
382                                             prec);
383     HighPrecision highPrecOriginalFracSizeY(m_renderConfig.originalFracSize.y(),
384                                             prec);
385     m_renderConfig.fracTopLeft = {highPrecTopLeftX,
```

```
        highPrecTopLeftY};
383     m_renderConfig.fracSize = {highPrecFracSizeX,
        highPrecFracSizeY};
384     m_renderConfig.originalFracSize = {highPrecOriginalFracSizeX,
385                                         highPrecOriginalFracSizeY};
386 }
387
388 RenderBoxTimeStats FractalRenderer::boxTimeStats() const {
389     double min = 1e10;
390     double max = -1e10;
391     double total = 0;
392     size_t count = 0;
393
394     for (const auto &box : m_renderBoxes) {
395         if (box.renderTime == 0) continue;
396
397         if (box.renderTime < min) min = box.renderTime;
398         if (box.renderTime > max) max = box.renderTime;
399         total += box.renderTime;
400         count += 1;
401     }
402
403     double average = total / (double)count;
404     size_t remainingBoxes = m_renderBoxes.size() - count;
405     double remainingTime =
406         ((double)remainingBoxes * average) /
407         (double)m_renderConfig.numThreads;
408
409     return {min, max, average, remainingTime};
410 }
411
412 const RenderConfig &FractalRenderer::config() const { return
    m_renderConfig; }
413
414 RenderConfig &FractalRenderer::config() { return m_renderConfig; }
415
416 const std::vector<RenderBox> &FractalRenderer::renderBoxes() const {
417     return m_renderBoxes;
418 }
419
420 std::vector<RenderBox> &FractalRenderer::renderBoxes() { return
    m_renderBoxes; }
421
422 const json &FractalRenderer::settings() const { return m_settings; }
423
424 json &FractalRenderer::settings() { return m_settings; }
425
426 const ci::Surface &FractalRenderer::surface() const { return
```

```
        m_fractalSurface; }  
423     ci::Surface &FractalRenderer::surface() { return m_fractalSurface; }  
424 } // namespace frac
```

3.8 Generic Fractal Definition (genericFractal.hpp)

```
01 #pragma once
02
03 namespace frac {
04     class Fractal {
05     public:
06         /// Constructor taking a RenderConfig object
07         /// \param config
08         explicit Fractal(const RenderConfig &config);
09         Fractal(const Fractal &) = delete;
10         Fractal(Fractal &&) = delete;
11         Fractal &operator=(const Fractal &) = delete;
12         Fractal &operator=(Fractal &&) = delete;
13         virtual ~Fractal() = default;
14
15         /// Configure a new set of options for the fractal
16         /// \param config The new RenderConfig to use
17         virtual void updateRenderConfig(const RenderConfig &config);
18
19         /// Iterate over a complex-valued coordinate and return the
20         /// value at which the
21         /// coordinate exceeds the given threshold or reaches the
22         /// desired number of
23         /// iterations. The return value also includes the number of
24         /// iterations it took
25         /// to reach the return coordinate.
26         /// \param coord The initial complex-valued coordinate
27         /// \return <iterations, resulting coordinate (low precision)>
28         virtual std::pair<int64_t, lrc::Complex<LowPrecision>>
29         iterCoordLow(const lrc::Complex<LowPrecision> &coord) const = 0;
30
31         /// See iterCoordLow(const lrc::Complex<LowPrecision> &coord)
32         /// const
33         /// \param coord The initial complex-valued coordinate
34         /// \return <iterations, resulting coordinate (high precision)>
35         /// \see iterCoordLow(const lrc::Complex<LowPrecision> &coord)
36         /// const
37         virtual std::pair<int64_t, lrc::Complex<HighPrecision>>
38         iterCoordHigh(const lrc::Complex<HighPrecision> &coord) const =
39             0;
40
41         /// Apply the colouring algorithm given the result of an
42         /// 'iterCoord' call
43         /// \param coord Resulting coordinate
```

```

37     /// \param iters Number of iterations
38     /// \return Colour of the point
39     virtual ci::ColorA getColorLow(const lrc::Complex<LowPrecision>
        &coord,
40                                     int64_t iters) const;
41
42     /// See getColorLow(const lrc::Complex<LowPrecision> &coord,
        int64_t iters) const
43     /// \param coord Resulting coordinate
44     /// \param iters Number of iterations
45     /// \return Colour of the point
46     /// \see getColorLow(const lrc::Complex<LowPrecision> &coord,
        int64_t iters) const
47     virtual ci::ColorA getColorHigh(const
        lrc::Complex<HighPrecision> &coord,
48                                     int64_t iters) const;
49
50     protected:
51         RenderConfig m_renderConfig;
52     };
53 } // namespace frac

```

3.9 Generic Fractal Implementation (genericFractal.cpp)

```

01 #include <fractal/fractal.hpp>
02
03 namespace frac {
04     Fractal::Fractal(const RenderConfig &config) :
        m_renderConfig(config) {}
05
06     void Fractal::updateRenderConfig(const RenderConfig &config) {
        m_renderConfig = config; }
07
08     ci::ColorA Fractal::getColorLow(const lrc::Complex<LowPrecision>
        &coord, int64_t iters) const {
09         using Col = ColorPalette::ColorType;
10
11         // float logZN =
            lrc::log(lrc::abs(lrc::Complex<float>(coord.real(),
            coord.imag())))) / 2;
12         // float nu = lrc::log(logZN / lrc::LN2) / lrc::LN2;
13         // float iteration = static_cast<float>(iters) + 1 - nu;
14         // const auto &palette = m_renderConfig.palette;
15         // Col color1 = palette[static_cast<size_t>(iteration) %
            palette.size()];

```

```

16     // Col color2 = palette[(static_cast<size_t>(iteration) + 1) %
    palette.size()];
17     // Col merged = ColorPalette::merge(color1, color2,
    lrc::mod(iteration, 1.0f));
18     // return {merged.x(), merged.y(), merged.z(), 1};
19
20     // Nice gradient
21     double s1 = (double)iters -
22         lrc::log2(lrc::log2((float)coord.real() *
    (float)coord.real() +
23             (float)coord.imag() *
    (float)coord.imag())) +
24         4;
25     Col color = 0.5 + 0.5 * lrc::cos(3.0 + s1 * 0.15 +
    lrc::Vec3d(0.0, 0.6, 1.0));
26     return {(float)color.x(), (float)color.y(), (float)color.z(), 1};
27
28     // Cool stepped gradients
29     // return {(iters % 10) / 10.f, 0, 0, 1};
30     // return {(iters % 11) / 11.f, (iters % 23) / 23.f, (iters %
    31) / 31.f, 1};
31     // return {(iters % 2) / 2.f, (iters % 3) / 3.f, (iters % 7) /
    7.f, 1};
32 }
33
34 ci::ColorA Fractal::getColorHigh(const lrc::Complex<HighPrecision>
    &coord,
35                                     int64_t iters) const {
36     using Col = ColorPalette::ColorType;
37
38     // float logZN =
    lrc::log(lrc::abs(lrc::Complex<float>(coord.real(),
    coord.imag())) / 2;
39     // float nu = lrc::log(logZN / lrc::LN2) / lrc::LN2;
40     // float iteration = static_cast<float>(iters) + 1 - nu;
41     // const auto &palette = m_renderConfig.palette;
42     // Col color1 = palette[static_cast<size_t>(iteration) %
    palette.size()];
43     // Col color2 = palette[(static_cast<size_t>(iteration) + 1) %
    palette.size()];
44     // Col merged = ColorPalette::merge(color1, color2,
    lrc::mod(iteration, 1.0f));
45     // return {merged.x(), merged.y(), merged.z(), 1};
46
47     // Nice gradient

```

```
48     double s1 = (double)iters -
49                 lrc::log2(lrc::log2((float)coord.real() *
50                                     (float)coord.real() +
51                                     (float)coord.imag() *
52                                     (float)coord.imag())) +
53                 4;
54     Col color = 0.5 + 0.5 * lrc::cos(3.0 + s1 * 0.15 +
55                                     lrc::Vec3d(0.0, 0.6, 1.0));
56     return {(float)color.x(), (float)color.y(), (float)color.z(), 1};
57
58     // Cool stepped gradients
59     // return {(iters % 10) / 10.f, 0, 0, 1};
60     // return {(iters % 11) / 11.f, (iters % 23) / 23.f, (iters %
61                 31) / 31.f, 1};
62     // return {(iters % 2) / 2.f, (iters % 3) / 3.f, (iters % 7) /
63                 7.f, 1};
64 }
65 } // namespace frac
```


3.10 History Definition(history.hpp)

```
001 #pragma once
002
003 namespace frac {
004     class HistoryNode {
005     public:
006         HistoryNode() = default;
007         HistoryNode(const HistoryNode &) = delete;
008         HistoryNode(HistoryNode &&) = delete;
009         HistoryNode &operator=(const HistoryNode &) = delete;
010         HistoryNode &operator=(HistoryNode &&) = delete;
011         ~HistoryNode() = default;
012
013         /// Append a new node to the end of the linked list
014         /// \param node The node to append (can contain links to other
015         /// nodes)
016         void append(HistoryNode *node);
017
018         /// Free all child nodes following this one
019         void killChildren();
020
021         /// The number of nodes in the list, iterating forwards from
022         /// this node
023         /// \param prevSize The number of nodes in the list before this
024         /// one (default to
025         /// zero) \return The number of nodes in the list
026         LIBRAPID_NODISCARD size_t sizeForward(size_t prevSize = 0) const;
027
028         /// The number of nodes in the list, iterating backwards from
029         /// this node
030         /// \param prevSize
031         /// \return The number of nodes in the list
032         /// \see sizeForward
033         LIBRAPID_NODISCARD size_t sizeBackward(size_t prevSize = 0)
034         const;
035
036         /// The next node in the linked list. This may be 'nullptr', so
037         /// always check
038         /// the value is valid
039         /// \return The next node in the linked list
040         LIBRAPID_NODISCARD HistoryNode *next() const;
041
042         /// The previous node in the linked list. See 'next()' for more
043         /// information
```

```
037     /// \return The previous node in the linked list
038     /// \see next
039     LIBRAPID_NODISCARD HistoryNode *prev() const;
040
041     /// Iterate backwards until a node with an invalid parent is
042     /// found (i.e. the
043     /// first node in the linked list)
044     LIBRAPID_NODISCARD HistoryNode *first();
045
046     /// return the last node in the linked list
047     /// \return
048     /// \see first
049     LIBRAPID_NODISCARD HistoryNode *last();
050
051     /// Update the configuration and surface members of this node
052     /// \param config New configuration
053     /// \param surface New surface
054     void set(const RenderConfig &config, const ci::Surface &surface);
055
056     /// See 'set()'
057     /// \param config New configuration
058     /// \see set
059     void setConfig(const RenderConfig &config);
060
061     /// See 'set()'
062     /// \param surface New surface
063     /// \see set
064     void setSurface(const ci::Surface &surface);
065
066     /// Getter method for the configuration instance stored
067     /// \return RenderConfig
068     LIBRAPID_NODISCARD const RenderConfig &config() const;
069
070     /// Getter method for the surface instance stored
071     /// \return ci::Surface
072     LIBRAPID_NODISCARD const ci::Surface &surface() const;
073
074     /// Non-const getter method for the configuration instance stored
075     /// \return RenderConfig
076     LIBRAPID_NODISCARD RenderConfig &config();
077
078     /// Non-const getter method for the surface instance stored
079     /// \return ci::Surface
080     LIBRAPID_NODISCARD ci::Surface &surface();
```

```
081
082     private:
083         HistoryNode *m_next = nullptr;
084         HistoryNode *m_prev = nullptr;
085
086         RenderConfig m_config;
087         ci::Surface m_surface;
088     };
089
090     class HistoryBuffer {
091     public:
092         HistoryBuffer() = default;
093         HistoryBuffer(const HistoryBuffer &) = delete;
094         HistoryBuffer(HistoryBuffer &&) = delete;
095         HistoryBuffer &operator=(const HistoryBuffer &) = delete;
096         HistoryBuffer &operator=(HistoryBuffer &&) = delete;
097
098         ~HistoryBuffer();
099
100         /// Append a new point to the history buffer
101         /// \param config The settings for the fractal renderer
102         /// \param surface A saved copy of the fractal surface
103         void append(const RenderConfig &config, const ci::Surface
104             &surface);
105
106         /// Undo the last operation
107         bool undo();
108
109         /// If possible, redo the last operation
110         bool redo();
111
112         /// Return the number of elements in the history buffer
113         /// \return Number of elements
114         LIBRAPID_NODISCARD size_t size() const;
115
116         /// Return the first buffer item (a HistoryNode pointer)
117         /// \return First item in the buffer
118         LIBRAPID_NODISCARD HistoryNode *first() const;
119
120         /// Return the last buffer item (a HistoryNode pointer)
121         /// \return Last item in the buffer
122         LIBRAPID_NODISCARD HistoryNode *last() const;
123     private:
124         HistoryNode *m_listHead = nullptr;
```

```
125         HistoryNode *m_currentNode = nullptr;
126     };
127 } // namespace frac
```

3.11 History Implementation (history.cpp)

```
001 #include <fractal/fractal.hpp>
002
003 namespace frac {
004     void HistoryNode::append(HistoryNode *list) {
005         if (m_next) {
006             m_next->append(list);
007         } else {
008             m_next = list;
009             m_next->m_prev = this;
010         }
011     }
012
013     void HistoryNode::killChildren() {
014         if (m_next) m_next->killChildren();
015         delete m_next;
016         m_next = nullptr;
017     }
018
019     size_t HistoryNode::sizeForward(size_t prevSize) const {
020         if (m_next)
021             return m_next->sizeForward(prevSize + 1);
022         else
023             return prevSize;
024     }
025
026     size_t HistoryNode::sizeBackward(size_t prevSize) const {
027         if (m_prev)
028             return m_prev->sizeBackward(prevSize + 1);
029         else
030             return prevSize;
031     }
032
033     HistoryNode *HistoryNode::next() const { return m_next; }
034     HistoryNode *HistoryNode::prev() const { return m_prev; }
035
036     HistoryNode *HistoryNode::first() {
037         if (m_prev)
038             return m_prev->first();
039         else
```

```
040         return this;
041     }
042
043     HistoryNode *HistoryNode::last() {
044         if (m_next)
045             return m_next->last();
046         else
047             return this;
048     }
049
050     void HistoryNode::set(const RenderConfig &config, const ci::Surface
051         &surface) {
052         m_config = config;
053         m_surface = surface;
054     }
055
056     void HistoryNode::setConfig(const RenderConfig &config) { m_config =
057         config; }
058
059     void HistoryNode::setSurface(const ci::Surface &surface) { m_surface
060         = surface; }
061
062     const RenderConfig &HistoryNode::config() const { return m_config; }
063     const ci::Surface &HistoryNode::surface() const { return m_surface; }
064     RenderConfig &HistoryNode::config() { return m_config; }
065     ci::Surface &HistoryNode::surface() { return m_surface; }
066
067     HistoryBuffer::~HistoryBuffer() {
068         m_listHead->killChildren();
069         // No need to delete m_currentNode, since it will be killed
070         // recursively
071         LIBRAPID_ASSERT(!m_listHead->next() && !m_listHead->prev(),
072             "HistoryBuffer is not empty");
073         delete m_listHead;
074     }
075
076     void HistoryBuffer::append(const RenderConfig &config, const
077         ci::Surface &surface) {
078         auto list = new HistoryNode;
079         list->set(config, surface);
080         if (m_listHead) {
081             m_listHead->append(list);
082             m_currentNode = m_listHead->last();
083         } else {
084             m_listHead = list;
085         }
086     }
```

```
080         m_currentNode = list;
081     }
082 }
083
084 bool HistoryBuffer::undo() {
085     if (m_currentNode->prev()) {
086         m_currentNode = m_currentNode->prev();
087         return true;
088     }
089     return false;
090 }
091
092 bool HistoryBuffer::redo() {
093     if (m_currentNode->next()) {
094         m_currentNode = m_currentNode->next();
095         return true;
096     }
097     return false;
098 }
099
100 size_t HistoryBuffer::size() const {
101     if (!m_listHead) return 0;
102     return m_listHead->sizeForward();
103 }
104
105 HistoryNode *HistoryBuffer::first() const { return
    m_listHead->first(); }
106 HistoryNode *HistoryBuffer::last() const { return
    m_listHead->last(); }
107 } // namespace frac
```

3.12 Main Window Definition (mainWindow.hpp)

```
001 #pragma once
002
003 namespace frac {
004     class MainWindow : public ci::app::App {
005     public:
006         /// Nothing passed to the constructor
007         MainWindow() = default;
008
009         void configureSettings();
010
011         /// Set up the main window, making sure it's the right size and
012         /// that the frame
013         /// rates are set correctly
014         void configureWindow();
015
016         /// Configure ImGui, setting up the style and enabling docking
017         void configureImGui();
018
019         /// Set up the window, configure ImGui and initialize the
020         /// fractal rendering
021         /// surfaces
022         void setup() override;
023
024         /// Halt all render threads and wait for them to join main
025         void stopRender();
026
027         void appendConfigToHistory();
028
029         std::vector<std::tuple<lrc::Vec2f, lrc::Vec2f, HistoryNode *>>
030         getHistoryFrameLocations() const;
031
032         void undoLastMove();
033         void redoLastMove();
034
035         // Run on shutdown
036         void cleanup() override;
037
038         /// Render the fractal to the screen (from the FractalRenderer
039         /// surface)
040         void drawFractal();
041
042         /// Outline each render box (if active) to show their current
043         /// states
```

```
040         void outlineRenderBoxes();
041
042         /// Called every frame
043         void draw() override;
044
045         /// Draw the UI
046         void drawImGui();
047
048         /// Draw the history window
049         void drawHistory();
050
051         /// Update the most recent history item with the current fractal
            configuration
052         /// and surface
053         void updateHistoryItem();
054
055         /// Move the top left corner of the fractal and set a new size
056         /// \param topLeft Top-left corner (complex coordinate)
057         /// \param size Size of the fractal (Re, Im)
058         void moveFractalCorner(const lrc::Vec<HighPrecision, 2> &topLeft,
059                               const lrc::Vec<HighPrecision, 2> &size);
060
061         /// Set the center of the fractal and the dimensions -- see
            moveFractalCorner
062         /// \param center Top-left corner
063         /// \param size Size of fractal
064         /// \see moveFractalCorner
065         void moveFractalCenter(const lrc::Vec<HighPrecision, 2> &center,
066                               const lrc::Vec<HighPrecision, 2> &size);
067
068         /// Advanced zooming method -- given pixel coordinates for the
            top left and
069         /// bottom right of the new area, perform the following:
070         /// 1. Copy existing pixels in the specified region to a buffer
071         /// 2. Regenerate the surface
072         /// 3. Copy the buffer to the fractal surface
073         /// 4. Reconfigure the fractal renderer
074         /// 5. Trigger another fractal render
075         /// \param pixTopLeft
076         /// \param pixBottomRight
077         void zoomFractal(const lrc::Vec2i &pixTopLeft, const lrc::Vec2i
            &pixBottomRight);
078
079         /// Render the fractal into the fractal surface, and copy that
            to the
```



```
080      /// fractal surface to be drawn. This will be executed on a
      separate
081      /// thread in order to keep the UI updating
082      void renderFractal(bool amendHistory = true);
083
084      /// Callback for mouse movement (this does not include mouse
      clicks or
085      /// drags) \param event The mouse event
086      void mouseMove(ci::app::MouseEvent event) override;
087
088      /// Callback for mouse clicks
089      /// \param event The mouse event
090      void mouseDown(ci::app::MouseEvent event) override;
091
092      /// Callback for mouse drags
093      /// \param event The mouse event
094      void mouseDrag(ci::app::MouseEvent event) override;
095
096      /// Callback for mouse releases
097      /// \param event The mouse event
098      void mouseUp(ci::app::MouseEvent event) override;
099
100      /// Callback for mouse wheel events
101      /// \param event The mouse event
102      void mouseWheel(ci::app::MouseEvent event) override;
103
104      /// Callback for when a key is pressed, including the modifiers
      (shift, ctrl,
105      /// etc) \param event The key event
106      void keyDown(ci::app::KeyEvent event) override;
107
108      template<typename T>
109      static lrc::Vec<T, 2> aspectCorrectedBox(const lrc::Vec<T, 2>
      &p1,
110                                              const lrc::Vec<T, 2> &p2,
111                                              float aspectRatio) {
112          lrc::Vec<T, 2> correctedBox;
113          lrc::Vec<T, 2> delta = p2 - p1;
114          if (delta.y() < delta.x() / aspectRatio)
115              correctedBox = {delta.x(), delta.x() / aspectRatio};
116          else
117              correctedBox = {delta.y() * aspectRatio, delta.y()};
118          return correctedBox;
119      }
120
```

```
121     /// Draw a zoom box at a given point. This includes a
122     /// transparent box
123     /// surrounded by a solid rectangle with a cross in the middle.
124     /// \param start
125     /// The top left corner of the box \param end The bottom right
126     /// corner of the
127     /// box
128     void drawZoomBox(const lrc::Vec2f &start, const lrc::Vec2f &end)
129     const;
130
131 private:
132     FractalRenderer m_renderer;    // The fractal renderer
133     ci::gl::Texture2dRef m_fractalTexture; // The fractal texture
134     ci::Font m_font = ci::Font("Arial", 24); // The font to use for
135     rendering text
136     lrc::Vec2i m_mousePos; // The current position of the mouse in
137     the window
138     lrc::Vec2i m_mouseDownPos; // The position of the mouse when it
139     was clicked
140     bool m_mouseDown = false; // Whether the mouse is currently down
141
142     HistoryBuffer m_history;
143     HistoryNode *m_historyNode = nullptr;
144     float m_historyScrollTarget = 0.0f;
145
146     bool m_drawingZoomBox = false;
147     bool m_showZoomBox = false;
148     bool m_moveZoomBox = false;
149     lrc::Vec2i m_zoomBoxStart;
150     lrc::Vec2i m_zoomBoxEnd;
151
152     // Values used for ImGui input fields
153     std::string m_fineMovementRe;
154     std::string m_fineMovementIm;
155     std::string m_fineMovementZoom;
156 };
157 } // namespace frac
```

3.13 Main Window Implementation (mainWindow.cpp)

```
001 #include <fractal/fractal.hpp>
002
003 namespace frac {
004     void MainWindow::configureSettings() {
005         // Load the settings file
```

```
006         FRAC_LOG(fmt::format("Loading settings from {}",
                                FRACTAL_UI_SETTINGS_PATH));
007
008         std::fstream settingsFile(FRACTAL_UI_SETTINGS_PATH,
                                std::ios::in);
009         if (settingsFile.is_open()) {
010             m_renderer.setConfig(json::parse(settingsFile));
011             m_history.append(m_renderer.config(), m_renderer.surface());
012             m_historyNode = m_history.first();
013         } else {
014             FRAC_ERROR("Failed to open settings file");
015             quit();
016         }
017
018         FRAC_LOG("Settings Configured");
019     }
020
021     void MainWindow::configureWindow() {
022         setFrameRate(-1);    // Unlimited framerate
023         ci::gl::enableVerticalSync(true); // Enable vertical sync to
                                avoid tearing
024         setWindowSize(1364, 700); // Set the initial window size
025
026         // Set up rendering settings
027         ci::gl::enableDepthWrite();
028         ci::gl::enableDepthRead();
029         ci::gl::enableDepth();
030         glDepthFunc(GL_ALWAYS);
031
032         FRAC_LOG("Window Configured");
033     }
034
035     void MainWindow::configureImGui() {
036         ImGui::Initialize();
037         ImGui::StyleColorsDark();
038         ImGui::GetIO().ConfigFlags |= ImGuiConfigFlags_DockingEnable;
039         ImGui::GetIO().FontGlobalScale = 1.0f;
040
041         FRAC_LOG("ImGui Configured");
042     }
043
044     void MainWindow::setup() {
045         FRAC_LOG("Setup Called");
046
047         configureSettings();
```

```
048     configureWindow();
049     configureImGui();
050
051     m_renderer.regenerateSurface();
052     renderFractal();
053
054     FRAC_LOG("Setup Complete");
055 }
056
057 void MainWindow::stopRender() { m_renderer.stopRender(); }
058
059 void MainWindow::appendConfigToHistory() {
060     FRAC_LOG("Appending to history");
061
062     if (m_historyNode != m_history.last()) {
063         // There is a pre-existing history, so it must be overwritten
064         m_historyNode->killChildren();
065     }
066
067     m_history.append(m_renderer.config(), m_renderer.surface());
068     m_historyNode = m_history.last();
069 }
070
071 std::vector<std::tuple<lrc::Vec2f, lrc::Vec2f, HistoryNode *>>
072 MainWindow::getHistoryFrameLocations() const {
073     std::vector<std::tuple<lrc::Vec2f, lrc::Vec2f, HistoryNode *>>
074         ret;
075
076     const json &settings = m_renderer.settings();
077     const float historyFrameWidth =
078         settings["menus"]["history"]["frameWidth"];
079     const float historyFrameSep =
080         settings["menus"]["history"]["frameSep"];
081
082     const auto windowHeight = (float)getWindowWidth();
083     const RenderConfig &config = m_renderer.config();
084     size_t historySize = m_history.size();
085     HistoryNode *node = m_history.first();
086     int64_t index = 0;
087     int64_t totalHeight = 0;
088
089     while (node) {
090         float aspect = (float)config.imageSize.x() /
091             (float)config.imageSize.y();
092         lrc::Vec2f renderSize(historyFrameWidth, historyFrameWidth /
```

```
        aspect);
089         lrc::Vec2f drawPos(windowWidth - historyFrameWidth -
            historyFrameSep,
090                             (renderSize.y() + historyFrameSep) *
091                             (float)(historySize - index - 1) +
092                             historyFrameSep);
093
094         totalHeight += (int64_t)(renderSize.y() + historyFrameSep);
095         drawPos.y(drawPos.y() + m_historyScrollTarget);
096
097         ret.emplace_back(std::tuple<lrc::Vec2f, lrc::Vec2f,
            HistoryNode *>(
098             drawPos, renderSize, node));
099
100         node = node->next();
101         index++;
102     }
103
104     return ret;
105 }
106
107 void MainWindow::undoLastMove() {
108     FRAC_LOG("Attempting to Undo...");
109     // Ensure a previous configuration actually exists
110     if (m_historyNode->prev()) {
111         FRAC_LOG("Undo successful");
112         m_historyNode = m_historyNode->prev();
113
114         // Update the render configuration
115         m_renderer.config() = m_historyNode->config();
116         renderFractal(false);
117     }
118 }
119
120 void MainWindow::redoLastMove() {
121     FRAC_LOG("Attempting to Redo...");
122     if (m_historyNode->next()) {
123         FRAC_LOG("Redo successful");
124         m_historyNode = m_historyNode->next();
125
126         // Update the render configuration
127         m_renderer.config() = m_historyNode->config();
128         renderFractal(false);
129     }
130 }
```

```
131
132     void MainWindow::cleanup() {
133         stopRender();
134         FRAC_LOG("Cleaned Up");
135     }
136
137     void MainWindow::drawFractal() {
138         m_fractalTexture =
139             ci::gl::Texture2d::create(m_renderer.surface());
140
141         const RenderConfig &config = m_renderer.config();
142         double aspect = (double)config.imageSize.x() /
143             (double)config.imageSize.y();
144         double height = getWindowHeight();
145         lrc::Vec2f renderSize(height * aspect, height);
146
147         ci::gl::color(ci::ColorA(1, 1, 1, 1));
148         ci::gl::draw(m_fractalTexture, ci::Rectf({0, 0}, renderSize));
149     }
150
151     void MainWindow::outlineRenderBoxes() {
152         const RenderConfig &config = m_renderer.config();
153         const std::vector<RenderBox> &renderBoxes =
154             m_renderer.renderBoxes();
155         for (const auto &box : renderBoxes) {
156             switch (box.state) {
157                 case RenderBoxState::None:
158                 case RenderBoxState::Rendered: continue;
159                 case RenderBoxState::Queued:
160                     ci::gl::color(ci::ColorA(0, 1, 0, 0.2));
161                     break;
162                 case RenderBoxState::Rendering:
163                     ci::gl::color(ci::ColorA(1, 1, 0, 0.2));
164                     break;
165             }
166
167             ci::ivec2 boxPos = box.topLeft;
168             ci::ivec2 boxSize = box.dimensions;
169             boxPos.y += getWindowHeight() - config.imageSize.y();
170             ci::gl::drawStrokedRect(ci::Rectf(boxPos, boxPos + boxSize),
171                                     1);
172         }
173     }
174
175     void MainWindow::draw() {
```

```
172         ci::gl::clear(ci::Color(0.2f, 0.2f, 0.2f));
173
174         drawImGui();
175         drawFractal();
176         outlineRenderBoxes();
177         drawHistory();
178
179         if (m_drawingZoomBox) {
180             // Draw an aspect-ratio corrected box
181             RenderConfig config = m_renderer.config();
182             float aspectRatio = (float)config.imageSize.x() /
183                                 (float)config.imageSize.y();
184             lrc::Vec2i correctedBox =
185                 aspectCorrectedBox(m_mouseDownPos, m_mousePos, aspectRatio);
186             auto correctedEnd = m_mouseDownPos + correctedBox;
187             drawZoomBox(m_mouseDownPos, correctedEnd);
188         }
189
190         if (m_showZoomBox) { drawZoomBox(m_zoomBoxStart, m_zoomBoxEnd); }
191     }
192
193     void MainWindow::drawImGui() {
194         // Ensure there is space for the labels in the ImGui windows
195         constexpr int64_t labelledItemWidth = -120;
196
197         RenderConfig &config = m_renderer.config();
198         const json &settings = m_renderer.settings();
199
200         // Fractal Information Window
201         json fractalInfo = settings["menus"]["fractalInfo"];
202         ImGui::SetNextWindowPos({(float)fractalInfo["posX"],
203                                 (float)fractalInfo["posY"]},
204                                 ImGuiCond_Once);
205         ImGui::SetNextWindowSize(
206             {(float)fractalInfo["width"], (float)fractalInfo["height"]},
207             ImGuiCond_Once);
208         ImGui::Begin("Fractal Info", nullptr);
209         {
210             ImGui::Text("Fractal Type: Mandelbrot");
211
212             HighPrecision re = config.fracTopLeft.x() +
213                             config.fracSize.x() / 2;
214             HighPrecision im = config.fracTopLeft.y() +
215                             config.fracSize.y() / 2;
216             HighPrecision zoom = config.originalFracSize.x() /
```

```

        config.fracSize.x();
212
213     ImGui::TextWrapped("%s", fmt::format("Re: {}", re).c_str());
214     ImGui::TextWrapped("%s", fmt::format("Im: {}", im).c_str());
215
216     std::ostringstream os;
217     os << std::fixed << std::setprecision(6) << std::scientific
        << zoom;
218     ImGui::TextWrapped("%s", fmt::format("Zoom: {}x",
        os.str()).c_str());
219
220     double maxZoomExponent = (double)config.precision /
        lrc::log2(10);
221     ImGui::TextWrapped(
222         "%s", fmt::format("Max Zoom: e+{:.3f}",
            maxZoomExponent).c_str());
223 }
224 ImGui::End();
225
226 // Fine movement window
227 json fineMovement = settings["menus"]["fineMovement"];
228 ImGui::SetNextWindowPos(
229     {(float)fineMovement["posX"], (float)fineMovement["posY"]},
        ImGuiCond_Once);
230 ImGui::SetNextWindowSize(
231     {(float)fineMovement["width"], (float)fineMovement["height"]},
        ImGuiCond_Once);
232 ImGui::Begin("Fine Movement", nullptr);
233 {
234     ImGui::InputText("Re", &m_fineMovementRe);
235     ImGui::InputText("Im", &m_fineMovementIm);
236     ImGui::InputText("Zoom", &m_fineMovementZoom);
237
238     if (ImGui::Button("Apply")) {
239         HighPrecision re, im, zoom, sizeRe, sizeIm;
240         scn::scan(m_fineMovementRe, "{}", re);
241         scn::scan(m_fineMovementIm, "{}", im);
242         scn::scan(m_fineMovementZoom, "{}", zoom);
243
244         FRAC_LOG(fmt::format("Received Real Part: {}", re));
245
246         sizeRe = config.originalFracSize.x() / zoom;
247         sizeIm = config.originalFracSize.y() / zoom;
248         moveFractalCenter(lrc::Vec<HighPrecision, 2>(re, im),
249             lrc::Vec<HighPrecision, 2>(sizeRe,

```



```
sizeIm));
250     renderFractal();
251 }
252 }
253 ImGui::End();
254
255 // Render configuration
256 json renderConfigMenu = settings["menus"]["renderConfig"];
257 ImGui::SetNextWindowPos(
258     {(float)renderConfigMenu["posX"],
259      (float)renderConfigMenu["posY"]},
259     ImGuiCond_Once);
260 ImGui::SetNextWindowSize(
261     {(float)renderConfigMenu["width"],
262      (float)renderConfigMenu["height"]},
262     ImGuiCond_Once);
263 ImGui::Begin("Render Configuration", nullptr);
264 {
265     static int64_t minThreads = 1;
266     static int64_t maxThreads =
267         std::thread::hardware_concurrency();
268     static int64_t minIters = 1;
269     static int64_t maxIters = 100000;
270     static int64_t minPrecision = 64;
271     static int64_t maxPrecision = 1024;
272     static int64_t minAntiAlias = 1;
273     static int64_t maxAntiAlias = 16;
274     static int64_t minDraftInc = 1;
275     static int64_t maxDraftInc = 4;
276
277     static int64_t newThreads = config.numThreads;
278     static int64_t newIters = config.maxIters;
279     static int64_t newPrecision = config.precision;
280     static int64_t newAntiAlias = config.antiAlias;
281     static bool newDraftRender = config.draftRender;
282     static int64_t newDraftInc = config.draftInc;
283
284     ImGui::PushItemWidth(labelledItemWidth);
285     ImGui::SliderScalar(
286         "Threads", ImGuiDataType_S64, &newThreads, &minThreads,
287         &maxThreads);
288
289     ImGui::PushItemWidth(labelledItemWidth);
290     ImGui::SliderScalar("Anti Aliasing",
291         ImGuiDataType_S64,
```

```
290             &newAntiAlias,
291             &minAntiAlias,
292             &maxAntiAlias);
293
294     ImGui::PushItemWidth(labelledItemWidth);
295     ImGui::DragScalarN(
296         "Iterations", ImGuiDataType_S64, &newIters, 1, 5,
297         &minIters, &maxIters);
298
299     ImGui::PushItemWidth(labelledItemWidth);
300     ImGui::DragScalarN("Precision",
301         ImGuiDataType_S64,
302         &newPrecision,
303         1,
304         0.1,
305         &minPrecision,
306         &maxPrecision);
307
308     if (ImGui::Button("Apply")) {
309         stopRender();
310         config.numThreads = newThreads;
311         config.maxIters = newIters;
312         config.precision = newPrecision;
313         config.antiAlias = newAntiAlias;
314         config.draftRender = newDraftRender;
315         config.draftInc = newDraftInc;
316         lrc::prec2(newPrecision);
317         m_renderer.updateRenderConfig();
318         m_renderer.updateConfigPrecision();
319         renderFractal();
320     }
321
322     ImGui::SameLine();
323     ImGui::Checkbox("Draft Mode", &newDraftRender);
324
325     if (newDraftRender) {
326         ImGui::SameLine();
327         ImGui::PushItemWidth(labelledItemWidth);
328         ImGui::SliderScalar("Draft Increment",
329             ImGuiDataType_S64,
330             &newDraftInc,
331             &minDraftInc,
332             &maxDraftInc);
333     }
```

```
334     ImGui::End();
335
336     // Render Statistics
337     json renderStatistics = settings["menus"]["renderStatistics"];
338     ImGui::SetNextWindowPos(
339         {(float)renderStatistics["posX"],
340          (float)renderStatistics["posY"]},
341         ImGuiCond_Once);
342     ImGui::SetNextWindowSize(
343         {(float)renderStatistics["width"],
344          (float)renderStatistics["height"]},
345         ImGuiCond_Once);
346
347     RenderBoxTimeStats stats = m_renderer.boxTimeStats();
348     ImGui::Begin("Render Statistics", nullptr);
349     {
350         ImGui::Text("Pixels/s (min): %s", fmt::format("{:.3f}",
351             stats.min).c_str());
352         ImGui::Text("Pixels/s (max): %s", fmt::format("{:.3f}",
353             stats.max).c_str());
354         ImGui::Text("Pixels/s (avg): %s",
355             fmt::format("{:.3f}", stats.average).c_str());
356         ImGui::Text("Estimated Time Remaining: %s",
357             lrc::formatTime(stats.remainingTime).c_str());
358     }
359     ImGui::End();
360 }
361
362 void MainWindow::drawHistory() {
363     const json &settings = m_renderer.settings();
364     const float historyFrameWidth =
365         settings["menus"]["history"]["frameWidth"];
366     const float historyFrameSep =
367         settings["menus"]["history"]["frameSep"];
368
369     const auto windowWidth = (float)getWindowWidth();
370     const auto windowHeight = (float)getWindowHeight();
371     const RenderConfig &config = m_renderer.config();
372     const std::vector<std::tuple<lrc::Vec2f, lrc::Vec2f, HistoryNode
373         *>> frames =
374         getHistoryFrameLocations();
375
376     int64_t totalHeight = 0;
377
378     // Draw a bounding box for the frames to sit within
```

```
372     float boxLeft = windowWidth - historyFrameWidth -
        historyFrameSep * 2;
373     ci::gl::color(ci::ColorA(0.15, 0.15, 0.3, 1));
374     ci::gl::drawSolidRect(ci::Rectf(boxLeft, 0, windowWidth,
        windowHeight));
375
376     for (const auto &frame : frames) {
377         const lrc::Vec2f framePos = std::get<0>(frame);
378         const lrc::Vec2f frameSize = std::get<1>(frame);
379         const HistoryNode *node = std::get<2>(frame);
380
381         auto texture = ci::gl::Texture2d::create(node->surface());
382         totalHeight += (int64_t)(frameSize.y() + historyFrameSep);
383
384         // Don't draw the frame if it's not visible on the screen
385         if (framePos.y() > windowHeight || framePos.y() +
            frameSize.y() < 0) continue;
386
387         ci::gl::color(ci::ColorA(1, 1, 1, 1));
388         ci::gl::draw(texture, ci::Rectf(framePos, framePos +
            frameSize));
389         ci::gl::color(ci::ColorA(0, 0, 0, 1));
390         glu::drawStrokedRectangle(framePos, framePos + frameSize, 3);
391
392         if (node == m_historyNode) {
393             // If this frame is selected, outline it gold
394             ci::gl::color(ci::ColorA(1, 1, 0, 1));
395             glu::drawStrokedRectangle(framePos, framePos + frameSize,
                4);
396         }
397     }
398
399     if (windowHeight < (float)totalHeight) {
400         m_historyScrollTarget =
401             lrc::clamp(m_historyScrollTarget, windowHeight -
                (float)totalHeight, 0);
402     } else {
403         m_historyScrollTarget = 0;
404     }
405 }
406
407 void MainWindow::moveFractalCorner(const lrc::Vec<HighPrecision, 2>
    &topLeft,
408                                     const lrc::Vec<HighPrecision, 2>
                                        &size) {
```

```
409         m_renderer.moveFractalCorner(topLeft, size);
410     }
411
412     void MainWindow::moveFractalCenter(const lrc::Vec<HighPrecision, 2>
        &center,
413                                         const lrc::Vec<HighPrecision, 2>
        &size) {
414         m_renderer.moveFractalCenter(center, size);
415     }
416
417     void MainWindow::zoomFractal(const lrc::Vec2i &pixTopLeft,
418                                   const lrc::Vec2i &pixBottomRight) {
419         // The vast majority of the calculations must be done at the
420         // highest
421         // precision possible. Without this, the zooming will not
422         // function
423         // correctly when the zoom factor exceeds the range of 64-bit
424         // precision.
425
426         FRAC_LOG("Moving Fractal...");
427         FRAC_LOG(fmt::format("Pixel Coordinates: {} -> {}", pixTopLeft,
428                               pixBottomRight));
429         updateHistoryItem();
430
431         RenderConfig &config = m_renderer.config();
432         ci::Surface &surface = m_renderer.surface();
433
434         // Resize the fractal area
435         HighVec2 imageSize = config.imageSize;
436         HighVec2 pixelDelta = pixBottomRight - pixTopLeft;
437
438         HighVec2 newFracPos = lrc::map(HighVec2(pixTopLeft),
439                                         HighVec2(0, 0),
440                                         imageSize,
441                                         config.fracTopLeft,
442                                         config.fracTopLeft +
443                                         config.fracSize);
444
445         HighVec2 newFracSize = lrc::map(
446             pixelDelta, HighVec2(0, 0), imageSize, HighVec2(0, 0),
447             config.fracSize);
448
449         // Copy the pixels from the selected region to the new region
450         // A temporary buffer is required here because, at some point,
451         // the loop
```

```
445         // would be writing to the same pixels it is reading from,
446         // resulting in
447         // strange visual glitches.
448         int64_t imgWidth = config.imageSize.x();
449         int64_t imgHeight = config.imageSize.y();
450         int64_t index = 0;
451         std::vector<ci::ColorA> newPixels(imgWidth * imgHeight);
452         auto mouseStartInImageLow =
453             pixTopLeft - lrc::Vec2i {0, getWindowHeight() -
454                                     config.imageSize.y()};
455         for (int64_t y = 0; y < imgHeight; ++y) {
456             for (int64_t x = 0; x < imgWidth; ++x) {
457                 int64_t pixX = lrc::map(x,
458                                         0.f,
459                                         imgWidth,
460                                         mouseStartInImageLow.x(),
461                                         mouseStartInImageLow.x() +
462                                             (float)pixelDelta.x());
463                 int64_t pixY = lrc::map(y,
464                                         0.f,
465                                         imgHeight,
466                                         mouseStartInImageLow.y(),
467                                         mouseStartInImageLow.y() +
468                                             (float)pixelDelta.y());
469
470                 newPixels[index++] = surface.getPixel({pixX, pixY});
471             }
472         }
473
474         // Write the new pixels to the surface
475         index = 0;
476         for (int64_t y = 0; y < imgHeight; ++y) {
477             for (int64_t x = 0; x < imgWidth; ++x) {
478                 surface.setPixel({x, y}, newPixels[index++]);
479             }
480         }
481
482         config.fracTopLeft = newFracPos;
483         config.fracSize = newFracSize;
484         m_renderer.updateRenderConfig();
485         renderFractal();
486     }
487
488     void MainWindow::renderFractal(bool amendHistory) {
489         m_renderer.renderFractal();
490     }
```

```
486
487     // m_history.append(m_renderer.config(), m_renderer.surface());
488     if (amendHistory) appendConfigToHistory();
489 }
490
491 void MainWindow::updateHistoryItem() {
492     // Update history buffer surface before re-rendering the fractal
493     if (m_history.size() > 0) {
494         m_history.last()->setSurface(m_renderer.surface());
495         FRAC_LOG("Writing to surface");
496     }
497 }
498
499 void MainWindow::mouseMove(ci::app::MouseEvent event) { m_mousePos =
    event.getPos(); }
500
501 void MainWindow::mouseDown(ci::app::MouseEvent event) {
502     // Don't capture mouse events if ImGui wants them
503     if (ImGui::GetIO().WantCaptureMouse) return;
504
505     m_mouseDown = true;
506     m_mouseDownPos = event.getPos();
507
508     // Ensure mouse is within the image
509     if (m_mouseDownPos.x() >= 0 &&
510         m_mouseDownPos.x() < m_renderer.config().imageSize.x() &&
511         m_mouseDownPos.y() >= 0 &&
512         m_mouseDownPos.y() < m_renderer.config().imageSize.y()) {
513         // Check if mouse is inside the box (and it is being shown)
514         if (m_showZoomBox && m_mouseDownPos.x() > m_zoomBoxStart.x()
515             &&
516             m_mouseDownPos.x() < m_zoomBoxEnd.x() &&
517             m_mouseDownPos.y() > m_zoomBoxStart.y() &&
518             m_mouseDownPos.y() < m_zoomBoxEnd.y()) {
519             m_moveZoomBox = true;
520         } else {
521             m_drawingZoomBox = true;
522             m_showZoomBox = false;
523         }
524     }
525
526     // See if mouse is in the history buffer section
527     const json &settings = m_renderer.settings();
528     const float historyFrameWidth =
529         settings["menus"]["history"]["frameWidth"];
```

```
528     const float historyFrameSep =
          settings["menus"]["history"]["frameSep"];
529     const std::vector<std::tuple<lrc::Vec2f, lrc::Vec2f, HistoryNode
          *>> frames =
530         getHistoryFrameLocations();
531     const auto windowWidth = (float)getWindowWidth();
532     const auto windowHeight = (float)getWindowHeight();
533     float boxLeft = windowWidth - historyFrameWidth -
          historyFrameSep * 2;
534     if (m_mouseDownPos.x() > boxLeft && m_mouseDownPos.x() <
          windowWidth) {
535         // Iterate over frames to see if any contain the mouse
536         for (const auto &frame : frames) {
537             const lrc::Vec2i framePos = std::get<0>(frame);
538             const lrc::Vec2i frameSize = std::get<1>(frame);
539             HistoryNode *node = std::get<2>(frame);
540
541             if (m_mouseDownPos.x() >= framePos.x() &&
542                 m_mouseDownPos.x() < framePos.x() + frameSize.x() &&
543                 m_mouseDownPos.y() >= framePos.y() &&
544                 m_mouseDownPos.y() < framePos.y() + frameSize.y()) {
545                 // Mouse was within this frame, so set it as current
546                 m_historyNode = node;
547                 m_renderer.config() = node->config();
548                 renderFractal(false); // Re-render the fractal
549             }
550         }
551     }
552 }
553
554 void MainWindow::mouseDrag(ci::app::MouseEvent event) {
555     if (ImGui::GetIO().WantCaptureMouse) return;
556
557     lrc::Vec2i delta = lrc::Vec2i(event.getPos()) - m_mousePos;
558     m_mousePos = event.getPos();
559
560     if (m_moveZoomBox) {
561         m_zoomBoxStart += delta;
562         m_zoomBoxEnd += delta;
563     }
564 }
565
566 void MainWindow::mouseUp(ci::app::MouseEvent event) {
567     if (ImGui::GetIO().WantCaptureMouse) return;
568     RenderConfig &config = m_renderer.config();
```



```
569         m_mouseDown = false;
570
571         // Resize the fractal area
572         lrc::Vec2i imageSize = config.imageSize;
573         float aspectRatio = (float)imageSize.x() / (float)imageSize.y();
574
575         lrc::Vec2f aspectCorrected =
576             aspectCorrectedBox(m_mouseDownPos, m_mousePos, aspectRatio);
577
578         // Persistent zoom area
579         if (m_drawingZoomBox) {
580             m_zoomBoxStart = m_mouseDownPos;
581             m_zoomBoxEnd = m_mouseDownPos + lrc::Vec2i(aspectCorrected);
582             m_showZoomBox = true;
583             m_drawingZoomBox = false;
584         }
585     }
586
587     void MainWindow::mouseWheel(ci::app::MouseEvent event) {
588         if (ImGui::GetIO().WantCaptureMouse) return;
589
590         const json &settings = m_renderer.settings();
591         if (m_mousePos.x() > settings["menus"]["history"]["frameWidth"])
592         {
593             m_historyScrollTarget +=
594                 event.getWheelIncrement() *
595                 settings["menus"]["history"]["scrollSpeed"].get<float>();
596         }
597     }
598
599     void MainWindow::keyDown(ci::app::KeyEvent event) {
600         const json &settings = m_renderer.settings();
601
602         if (m_showZoomBox) {
603             const int64_t scrollSpeed =
604                 settings["menus"]["history"]["scrollSpeed"];
605
606             switch (event.getCode()) {
607                 case ci::app::KeyEvent::KEY_RETURN: {
608                     zoomFractal(m_zoomBoxStart, m_zoomBoxEnd);
609                 }
610                 case ci::app::KeyEvent::KEY_ESCAPE: {
611                     m_showZoomBox = false;
612                     break;
613                 }
614             }
615         }
```

```
612         case ci::app::KeyEvent::KEY_RIGHT: {
613             m_zoomBoxStart.x(m_zoomBoxStart.x() + scrollSpeed);
614             m_zoomBoxEnd.x(m_zoomBoxEnd.x() + scrollSpeed);
615             break;
616         }
617         case ci::app::KeyEvent::KEY_LEFT: {
618             m_zoomBoxStart.x(m_zoomBoxStart.x() - scrollSpeed);
619             m_zoomBoxEnd.x(m_zoomBoxEnd.x() - scrollSpeed);
620             break;
621         }
622         case ci::app::KeyEvent::KEY_UP: {
623             m_zoomBoxStart.y(m_zoomBoxStart.y() - scrollSpeed);
624             m_zoomBoxEnd.y(m_zoomBoxEnd.y() - scrollSpeed);
625             break;
626         }
627         case ci::app::KeyEvent::KEY_DOWN: {
628             m_zoomBoxStart.y(m_zoomBoxStart.y() + scrollSpeed);
629             m_zoomBoxEnd.y(m_zoomBoxEnd.y() + scrollSpeed);
630             break;
631         }
632     }
633 }
634
635 if (event.getCode() == ci::app::KeyEvent::KEY_z &&
636     event.getModifiers() & ci::app::KeyEvent::CTRL_DOWN) {
637     if (event.getModifiers() & ci::app::KeyEvent::SHIFT_DOWN) {
638         redoLastMove();
639     } else {
640         undoLastMove();
641     }
642 }
643 }
644
645 void MainWindow::drawZoomBox(const lrc::Vec2f &start, const
646     lrc::Vec2f &end) const {
647     // Translucent inner box
648     ci::gl::color(ci::ColorA(1, 0, 0, 0.333)); // Red with alpha
649     ci::gl::drawSolidRect(ci::Rectf(start.x(), start.y(), end.x(),
650         end.y()));
651     // Small cross in the middle
652     ci::gl::color(ci::ColorA(0, 0, 1, 0.333)); // Blue with alpha
653     glu::drawCross((start + end) * 0.5f, 5.f, 2.f);
654     // Bounding box
655     ci::gl::color(ci::ColorA(1, 0, 0, 1)); // Red
656     glu::drawStrokedRectangle(start, end, 5);
```

```
655     }  
656 } // namespace frac
```

3.14 Mandelbrot Fractal Definition (mandelbrot.hpp)

```
01 #pragma once
02
03 #include <fractal/genericFractal.hpp>
04
05 namespace frac {
06     /*
07      * No need to document this file, since the class inherits from a
08      * generic fractal
09      * class and does not implement any novel functions.
10      */
11
12     class Mandelbrot : public Fractal {
13     public:
14         /// Constructor taking a RenderConfig object
15         /// \param config RenderConfig object
16         explicit Mandelbrot(const RenderConfig &config);
17         Mandelbrot(const Mandelbrot &) = delete;
18         Mandelbrot(Mandelbrot &&) = delete;
19         Mandelbrot &operator=(const Mandelbrot &) = delete;
20         Mandelbrot &operator=(Mandelbrot &&) = delete;
21
22         ~Mandelbrot() override = default;
23
24         LIBRAPID_NODISCARD std::pair<int64_t, lrc::Complex<LowPrecision>>
25         iterCoordLow(const lrc::Complex<LowPrecision> &coord) const
26             override;
27
28         LIBRAPID_NODISCARD std::pair<int64_t,
29             lrc::Complex<HighPrecision>>
30         iterCoordHigh(const lrc::Complex<HighPrecision> &coord) const
31             override;
32     };
33 } // namespace frac
```

3.15 Mandelbrot Fractal Implementation (mandelbrot.cpp)

```
01 #include <fractal/fractal.hpp>
02
03 namespace frac {
04     Mandelbrot::Mandelbrot(const RenderConfig &config) : Fractal(config)
05     {}
06
07     /*
```

```
07     * Note that, since this class will be used polymorphically with
08     other classes,
09     * these two functions must be implemented separately and cannot be
    templated, as the compiler
10     * would error when trying to identify which function to call.
    Additionally, splitting the
11     * functions in this way allows for more targeted optimisations to
    be made in some cases.
12     */
13     std::pair<int64_t, lrc::Complex<LowPrecision>>
14     Mandelbrot::iterCoordLow(const lrc::Complex<LowPrecision> &coord)
        const {
15         LowPrecision re_0 = lrc::real(coord); // Real component (initial)
16         LowPrecision im_0 = lrc::imag(coord); // Imaginary component
            (initial)
17         LowPrecision re = 0, im = 0;
18         LowPrecision tmp; // Temporary variable for use in the
            calculation
19         int64_t iteration = 0;
20
21         // Bail when larger than this
22         double bailout = Fractal::m_renderConfig.bail;
23
24         while (re * re + im * im <= bailout && iteration <
            Fractal::m_renderConfig.maxIters) {
25             tmp = re * re - im * im + re_0;
26             im = 2 * re * im + im_0;
27             re = tmp;
28             ++iteration;
29         }
30
31         return {iteration, lrc::Complex<LowPrecision>(re, im)};
32
33         // lrc::Complex<LowPrecision> tempVarThing = coord;
34         // while (lrc::abs(tempVarThing) <= bailout && iteration <
            Fractal::m_renderConfig.maxIters) {
35             // tempVarThing = lrc::pow(tempVarThing, LowPrecision(4)) +
                coord;
36             // ++iteration;
37             // }
38
39         // return {iteration, tempVarThing};
40     }
41 }
```

```
42     std::pair<int64_t, lrc::Complex<HighPrecision>>
43     Mandelbrot::iterCoordHigh(const lrc::Complex<HighPrecision> &coord)
44     {
45         HighPrecision re_0 = lrc::real(coord); // Real component
46         (initial)
47         HighPrecision im_0 = lrc::imag(coord); // Imaginary component
48         (initial)
49         HighPrecision re = 0, im = 0;
50         HighPrecision tmp; // Temporary variable for use in the
51         calculation
52         int64_t iteration = 0;
53
54         // Bail when larger than this
55         double bailout = 1 << 16;
56
57         while (re * re + im * im <= bailout && iteration <
58                Fractal::m_renderConfig.maxIters) {
59             tmp = re * re - im * im + re_0;
60             im = 2 * re * im + im_0;
61             re = tmp;
62             ++iteration;
63         }
64
65         return {iteration, lrc::Complex<HighPrecision>(re, im)};
66     }
67 } // namespace frac
```

3.16 OpenGL Utilities Definition (openglUtils.hpp)

```
01 #pragma once
02
03 namespace frac::glu {
04     /// Draw a line from p1 to p2 with a given thickness. The line has a
05     /// circle drawn at each end
06     /// to make it look nice.
07     /// \param p1 Line start
08     /// \param p2 Line end \param
09     /// thickness Line thickness
10     void drawLine(const lrc::Vec2f &p1, const lrc::Vec2f &p2, float
11         thickness = 1);
12
13     /// Draw a stroked rectangle with a given thickness -- note this
14     /// draws the EDGES of
15     /// the rectangle, and does not fill the inside \param topLeft Top
16     /// left corner of the
17     /// rectangle \param bottomRight Bottom right corner of the
18     /// rectangle \param thickness
19     /// Line thickness
20     void drawStrokedRectangle(const lrc::Vec2f &topLeft, const
21         lrc::Vec2f &bottomRight,
22         float thickness = 1);
23
24     /// Draw a cross at \p center, where each "arm" has length \p radius
25     /// and thickness
26     /// \p thickness
27     /// \param center Where to draw the cross
28     /// \param radius Radius of the cross
29     /// \param thickness Thickness of the cross
30     void drawCross(const lrc::Vec2f &center, float radius, float
31         thickness = 1);
32 } // namespace frac::glu
```

3.17 OpenGL Utilities Implementation (openglUtils.cpp)

```
01 #include <fractal/fractal.hpp>
02
03 namespace frac::glu {
04     void drawLine(const lrc::Vec2f &p1, const lrc::Vec2f &p2, float
05         thickness) {
06         ci::vec3 translation({p1.x(), p1.y(), 0});
07         float rotation = lrc::atan2(p2.y() - p1.y(), p2.x() - p1.x());
08         float lineLength = static_cast<float>((p2 - p1).mag());
```

```
08
09     ci::gl::pushMatrices();
10     ci::gl::translate(translation);
11     ci::gl::rotate(rotation);
12
13     // Line segment
14     ci::gl::drawSolidRect(ci::Rectf({0.f, -thickness / 2.f},
15                                     {lineLength, thickness / 2}));
16
17     // Draw two circles to make it look nice :)
18     ci::gl::drawSolidCircle({0, 0}, thickness / 2);
19     ci::gl::drawSolidCircle({lineLength, 0}, thickness / 2);
20
21     ci::gl::popMatrices();
22 }
23
24 void drawStrokedRectangle(const lrc::Vec2f &topLeft, const
25                          lrc::Vec2f &bottomRight,
26                          float thickness) {
27     // Draw each edge using drawLine, as it allows a thickness to be
28     // specified
29     drawLine(topLeft, {bottomRight.x(), topLeft.y()}, thickness);
30     drawLine({bottomRight.x(), topLeft.y()}, bottomRight, thickness);
31     drawLine(bottomRight, {topLeft.x(), bottomRight.y()}, thickness);
32     drawLine({topLeft.x(), bottomRight.y()}, topLeft, thickness);
33 }
34
35 void drawCross(const lrc::Vec2f &center, float radius, float
36               thickness) {
37     ci::vec3 translation({center.x(), center.y(), 0});
38     ci::gl::pushMatrices();
39     ci::gl::translate(translation);
40     ci::gl::lineWidth(thickness);
41     ci::gl::drawLine(ci::vec2(0, -radius), ci::vec2(0, radius));
42     ci::gl::drawLine(ci::vec2(-radius, 0), ci::vec2(radius, 0));
43     ci::gl::popMatrices();
44 }
45 } // namespace frac::glu
```


3.18 Render Configuration Definition (renderConfig.hpp)

```
01 #pragma once
02
03 namespace frac {
04     /// Represents the state of a render box
05     enum class RenderBoxState {
06         None, // Not yet assigned a state
07         Queued, // Queued to be rendered
08         Rendering, // Currently being rendered
09         Rendered // Rendered and ready to be written to the image
10     };
11
12     /// Stores the pixel-space coordinates of a region to render
13     struct RenderBox {
14         lrc::Vec2i topLeft;
15         lrc::Vec2i dimensions;
16         bool draftRender;
17         int64_t draftInc;
18         RenderBoxState state = RenderBoxState::None;
19         double renderTime = 0;
20     };
21
22     /// Information about the time taken to render a box
23     struct RenderBoxTimeStats {
24         double min = 0;
25         double max = 0;
26         double average = 0;
27         double remainingTime = 0;
28     };
29
30     /// Contains all the information required to define an image (not
31     /// including the
32     /// fractal type and colouring algorithm)
33     struct RenderConfig {
34         int64_t numThreads; // Number of threads to render on (max)
35         int64_t maxIters; // Largest number of iterations to allow
36         int64_t precision; // Precision of floating point types used for
37                             // arithmetic
38         LowPrecision bail; // Bailout value
39         int64_t antiAlias; // Anti-aliasing factor -- 1 = no
40                             // anti-aliasing
41
42         lrc::Vec2i imageSize; // Size of the image to render
43         lrc::Vec2i boxSize; // Size of sub-regions to render (see
```

```
        RenderBox)
41
42     lrc::Vec<HighPrecision, 2> fracTopLeft; // The fractal-space
        center of the image
43     lrc::Vec<HighPrecision, 2> fracSize; // The width and height of
        the fractal space
44     lrc::Vec<HighPrecision, 2> originalFracSize; // Original size
45
46     ColorPalette palette; // The palette to use for rendering the
        fractal
47
48     bool draftRender; // Whether to render the fractal in draft mode
49     int64_t draftInc; // Increment for draft rendering
50 };
51 } // namespace frac
```

3.19 Render Configuration Implementation (renderConfig.cpp)

```
1 #include <fractal/fractal.hpp>
2
3 namespace frac {
4
5 } // namespace frac
```

3.20 CMake File (CMakeLists.txt)

```
01 cmake_minimum_required(VERSION 3.10)
02 project(FractalRenderer)
03
04 set(CMAKE_CXX_STANDARD 17)
05
06 file(GLOB_RECURSE FRACTAL_SOURCES
07      "${CMAKE_CURRENT_SOURCE_DIR}/src/*.cpp")
08
09 # Include multiprecision floating point
10 set(LIBRAPID_USE_MULTIPREC ON)
11 set(LIBRAPID_FAST_MATH ON)
12
13 add_subdirectory(cinderbox)
14 add_subdirectory(json)
15 target_link_libraries(FractalRenderer PUBLIC cinderbox
16                        nlohmann_json::nlohmann_json)
17
18 target_include_directories(FractalRenderer PUBLIC
19                        "${CMAKE_CURRENT_SOURCE_DIR}/include")
20 target_include_directories(FractalRenderer PUBLIC
21                        "${CMAKE_CURRENT_SOURCE_DIR}/thread-pool")
22
23 target_compile_definitions(FractalRenderer PUBLIC
24                        -DFRACTAL_RENDERER_ROOT_DIR="${CMAKE_CURRENT_SOURCE_DIR}")
```

3.21 Main File (main.cpp)

```
1 #include <fractal/fractal.hpp>
2 CINDER_APP(frac::MainWindow,
3            ci::app::RendererGl(ci::app::RendererGl::Options().msaa(4)))
```

References

- [1] Catherine Soanes and Sara Hawker. *Compact Oxford English Dictionary of current English*. Oxford University Press, 2013.
- [2] Paul Bourke, Nov 2002. URL <http://paulbourke.net/fractals/mandelbrot/>.
- [3] Frederik Slijkerman. Ultra fractal: Advanced fractal software for windows and macos, Jul 2022. URL <https://www.ultrafractal.com/>.
- [4] David J Eck. URL <https://math.hws.edu/eck/index.html>.
- [5] URL <https://xaos-project.github.io/XaoSjs/>.
- [6] Fractal software. URL <https://fractalfoundation.org/resources/fractal-software/>.
- [7] Cinder Developers and Toby Davis. Pencilcaseman/cinderbox: A modified version of cinder with extra libraries for improved functionality. URL <https://github.com/Pencilcaseman/cinderbox>.
- [8] Toby Davis. LibRapid: Optimised Mathematics for C++, 1 2023. URL <https://github.com/LibRapid/librapid>.