


FEATURES 特点

- Excellent solderability and high heat resistance 绝佳的焊锡性和高温耐热性
- Excellent terminal strength construction 绝佳的端面强度结构

APPLICATIONS 应用

- Power supply for VCR, OA equipment, LCD, television set, notebook, DC to DC converters, DC to AC inverters etc.
- VCR、辦公室自動設備、液晶電視機、筆記型電腦、直流 - 直流整流器、直流 - 交流換流器等的電源供應器。

Product Identification 产品标识



A. Series

B. Dimension



A x C

C. Inductance

1R0=1.0uH, 100=10uH, 101=100uH

D. Inductance Tolerance

K=±10%, M=±20%



Series	A	B	C	D ref
CD31	3.5±0.3	3.0±0.3	1.6±0.3	1.0
CD32	3.5±0.3	3.0±0.3	2.1±0.3	1.0
CD42	4.5±0.3	4.0±0.3	2.0±0.3	1.4
CD43	4.5±0.3	4.0±0.3	3.2±0.3	1.4
CD52	5.8±0.3	5.2±0.3	2.0±0.3	1.6
CD53	5.8±0.3	5.2±0.3	3.0±0.3	1.6
CD54	5.8±0.3	5.2±0.3	4.5±0.3	1.6
CD73	7.8±0.3	7.0±0.3	3.5±0.3	2.4
CD75	7.8±0.3	7.0±0.3	5.0±0.3	2.4
CD104	10.0±0.3	9.0±0.3	4.0±0.3	3.1
CD105	10.0±0.3	9.0±0.3	5.4±0.3	3.1

Unit:mm