

Import Modules


```
In [1]: import os
import random
import numpy as np
import numpy.matlib

from skimage import io
```

Show original image

```
In [2]: original_image = io.imread('../images/before-compression/Sumatran-Tiger-Hero.jpg')

io.imshow(original_image)
io.show()
```



Get width and length from image

```
In [3]: length = original_image.shape[0]
width = original_image.shape[1]
original_image = original_image / 255

X = original_image.reshape(original_image.shape[0]*original_image.shape[1], 3)
```

Determine Cluster and Max Iteration

```
In [4]: number_of_cluster = 16
max_iters = 50
```

Function Initialize centroid

```
In [5]: def init_centroids(X, number_of_clusters):
c = random.sample(list(X), number_of_clusters)

return c
```

Determine closest centroid for each datapoint (pixel)

```
In [6]: def closest_centroids(X, c):
number_of_cluster = np.size(c,0)
idx = np.zeros((np.size(X,0),1))
arr = np.empty((np.size(X,0),1))

for i in range(0, number_of_cluster):
y = c[i]
temp = np.ones((np.size(X,0),1))*y
b = np.power(np.subtract(X,temp),2)
a = np.sum(b,axis = 1)
a = np.asarray(a)

a.resize((np.size(X,0),1))
arr = np.append(arr, a, axis=1)

arr = np.delete(arr,0,axis=1)
idx = np.argmin(arr, axis=1)

return idx
```

Determine Centroid

```
In [7]: def compute_centroids(X, idx, number_of_cluster):
n = np.size(X, 1)
centroids = np.zeros((number_of_cluster, n))

for i in range(0, number_of_cluster):
ci = idx==i
ci = ci.astype(int)
total_number = sum(ci)

ci.resize((np.size(X,0),1))

total_matrix = np.matlib.repmat(ci,1,n)
ci = np.transpose(ci)
total = np.multiply(X,total_matrix)
centroids[i] = (1 / total_number) * np.sum(total, axis=0)

return centroids
```

KMeans Clustering

```
In [8]: def run_kMean(X, initial_centroids, max_iters):
m = np.size(X, 0)
n = np.size(X, 1)
print(m)
print(n)
number_of_cluster = np.size(initial_centroids, 0)
centroids = initial_centroids
previous_centroids = centroids
idx = np.zeros((m,1))

for i in range(1,max_iters):
idx = closest_centroids(X, centroids)
centroids = compute_centroids(X, idx, number_of_cluster)

return centroids,idx
```

Generate Centroid

```
In [9]: initial_centroids = init_centroids(X, number_of_cluster)
centroids, idx = run_kMean(X, initial_centroids, max_iters)

print(np.shape(centroids))
print(np.shape(idx))
```

```
307200
3
(8, 3)
(307200,)
```

Generate Compression Image

```
In [10]: idx = closest_centroids(X, centroids)
X_recovered = centroids[idx]
X_recovered = np.reshape(X_recovered, (length, width, 3))

print(np.shape(X_recovered))
print(np.shape(X_recovered))
```

```
(480, 640, 3)
(480, 640, 3)
```

Show image compressed

```
In [11]: image_compressed = io.imsave('../images/after-compression/Sumatran-Tiger-Hero-Result.jpg', X_recovered)
```

Lossy conversion from float64 to uint8. Range [0, 1]. Convert image to uint8 prior to saving to suppress this warning.

```
In [12]: image_compressed = io.imread('../images/after-compression/Sumatran-Tiger-Hero-Result.jpg')

io.imshow(image_compressed)
io.show()
```



Image size before and after compression with KMeans

```
In [13]: size_before_compression = os.stat('../images/before-compression/Sumatran-Tiger-Hero.jpg').st_size
size_after_compression = os.stat('../images/after-compression/Sumatran-Tiger-Hero-Result.jpg').st_size

print("Size of image before running K-mean algorithm: ", size_before_compression.st_size)
print("Size of image after running K-mean algorithm: ", size_after_compression.st_size)
```

```
Size of image before running K-mean algorithm: 90.515625 KB
Size of image after running K-mean algorithm: 83.76953125 KB
```