

# Deep reinforcement learning for the board game Dominion

An assignment for the course AI tools

written by

**Peter Khiem Duc Tinh Nguyen**

Pengu20@student.sdu.dk

**Course lector:** Xiaofeng Xiong

**ECTS:** 5



The code for this project is available at

when the code is public put the github link in the curly brackets

[https://gitlab.sdu.dk/sdurobotics/medical/student-projects/2023/Peter\\_Duc\\_Bachelor\\_NLP](https://gitlab.sdu.dk/sdurobotics/medical/student-projects/2023/Peter_Duc_Bachelor_NLP)

**the Faculty of Engineering (TEK)**

University of Southern Denmark

Date of Hand In 31. of May

# Contents

---

<b>1</b>	<b>Project specification</b>	<b>1</b>
1.1	Problem constraint . . . . .	1
<b>2</b>	<b>Task: Creating a dominion engine suited for a RL agent</b>	<b>3</b>
2.0.1	General rules of the board game Dominion . . . . .	3
2.0.2	Specifications of criteria for the Dominion engine . . . . .	4
2.0.3	Finished Implementation of the Dominion Engine . . . . .	4
<b>3</b>	<b>Task: choosing and creating RL agents</b>	<b>6</b>
3.0.1	SARSA . . . . .	6
<b>4</b>	<b>Task: implementing a neural network Q-table</b>	<b>7</b>
<b>5</b>	<b>Task: Training scheme</b>	<b>8</b>
<b>6</b>	<b>evaluation</b>	<b>9</b>
<b>7</b>	<b>Discussion</b>	<b>10</b>
<b>8</b>	<b>Conclusion</b>	<b>11</b>
<b>9</b>	<b>Future work</b>	<b>12</b>

## Chapter 1

# Project specification

---

For this project, an AI agent must be designed, constructed and evaluated, based on a board game called "Dominion". The main problems posed, is the navigation and optimization of trajectories in large discrete state spaces. The aim for this project is therefore to construct a Reinforcement Learning method which can be used for large discrete spaces.

3 Different methods will be used to train a Reinforcement Learning agent to play the game Dominion. These methods will then be compared to each other as the conclusion of this paper. The structure of the entire project is shown as following: The project is divided into the following tasks:

- Create a Dominion engine that can be used to simulate games of Dominion.
- Design and create an AI agent that can play the game Dominion.
- Implement a deep learning approach for the Q-table.
- Create a training scheme for the AI agent.
- Evaluate the AI agent.
- Discuss the results of the AI agent.
- Conclude on the work.

## 1.1 Problem constraint

For this project there are some constraints which must be taken into consideration. These constraints are:

- The Dominion game can only support 2 players (The trained player, and the test player)
- The tested method are all within the category of 1-step temporal difference learning methods.
- The game normally varies for each game, as the cards present are randomized. For this project, the agent will train on a fixed set of cards.

The reason for only supporting 2 players, is that the game poses the problem of large variance due to the nature of the game. As the game already has large variance, it would be difficult to train and visualize progress, if the player had to battle more than one opponent. The reason for only evaluating methods within the category of 1-step temporal difference learning methods, is due to the limits of the time frame of the project. Furthermore, the main focus is to evaluate the differences between 3 different methods. Diverging from the specified category comparing only 3 methods, would pose too many variables to consider, if the methods yield different results. It would therefore be difficult to determine the cause of the difference in results. Is the winrate affected by the use of 10 steps instead of 1-step SARSA? Is it because of the low bias of monte carlo non-bootstrapping methods? Or is it because of the high bias of the 1-step SARSA method? These are questions that would be difficult to answer if the methods were not within the same category. For future work, more methods can be evaluated, and the category can be expanded to include more methods. The game features randomization in the game setup, in which the AI must be capable of generalizing its knowledge to other domains which are similar the learned domain. Due to the time constraint of

the project, and a lack of computational power, the game setup has been set to a fixed game setup for the AI to train on. The concept of domain variation due to randomization in the board game, will be discussed at the rules of the game.

## Chapter 2

# Task: Creating a dominion engine suited for a RL agent

---

The first step for the project is to create the board game engine which both can be used to play the game of dominion while supporting the playability from a Reinforcement Learning agent. Before going into the specifications of the criteria for the engine, the game of Dominion will be explained in short.

### 2.0.1 General rules of the board game Dominion

Each player starts with a deck of 10 cards, that are identical between players. At the start of each turn, draw 5 cards, at the end of each turn, put all cards from the hand into the discard pile. If there is not enough cards in the deck to draw all 5 cards, then shuffle the discard pile into the deck and draw until 5 cards are drawn. The main goal of the game is to reach terminal state with the most Victory points. These victory points are gained by buying victory cards.

All cards in the game is categorized into 3 different types of cards. The types are as follows:

- Action cards
- Treasure cards
- Victory cards

**Action cards:** Action cards are cards that can be played to perform an action, that manipulates the state space in some way or form. A typical example, could be the "smithy" that makes the player draw 3 cards. Based on the price of the

**Treasure cards:** These cards have assigned a currency value, which is used to buy other cards. The process of buying a card is discussed later in the rules

**Victory cards:** These cards are expensive card, which gives the player victory points. The cards hold no tactical value, other than to be bought to gain victory points.

A turn consists of an action phase, and a buy phase. The player is granted a single action that the player can do, and a single buy action, which enables the player to buy a single card. It is possible, through, action cards to gain more actions, and more buys. The cards that can be bought are shown as a shared pool of cards that are structured as piles of cards. Every pile represents all the copies of a unique card which can be bought. A typical game setup is shown in the illustration below:

Insert image of a typical game setup

The usual process is a randomization of the action card piles present. Only 10 action card piles are at play at a time, but around 25 unique action cards exists. For the sake of simplicity, the game will be played with a unique set of cards, that is fixed.

The process of buying a card in the buy phase, is done by showing the currency in hand that is enough to

buy the specified card, and then putting the bought card into the discard pile, so it can be drawn in future turns. The treasure cards used does not disappear, and will be discarded at the end of your turn as all other cards.

The game ends when the highest cost victory card pile is empty (Card is named "Province"), or when 3 piles of cards are empty. The player with the most victory points wins the game.

## 2.0.2 Specifications of criteria for the Dominion engine

The game can be found for free on the internet. Therefore, the reason for creating a new engine, is to have a more flexible engine that supports the use of an AI agent, which does not need to extract information from an image. The advantage of creating a new engine, is that the engine can be designed to ensure that it is capable of giving the entire state space of the game to the AI through a single command call. All actions can also be given to the AI as a list of integers, which the AI must choose from. For the final result of the Dominion game engine, given the nature of the information delivered, it is observed that the game is far more intuitive for the AI than it would be for a human player.

The specific criteria for the Dominion engine are as follows:

- The engine must be able to simulate a game of Dominion. (The simulation speed must ideally be faster than the real-time average game length of 20-30 minutes)
- The engine must pass a game state object to the agent player, which contains all the information about the current game state.
- All actions that can be made in the game must exclusively be run by the agent that is inserted into the game.

## 2.0.3 Finished Implementation of the Dominion Engine

The finished implementation of the Dominion engine is a python class, which can input arbitrary players and simulate the game. An illustration of the class structure is shown below:

Show illustration of the class structure.

The only constriction for the player object, is that the player object must have a function called "choose\_action" with inputs action\_list and game\_state, that returns on of the actions.

The game state is a dictionary object, which contains the following keys:

**game\_state:**

- The unique Dominion card set
- The supply amount of each card
- The type of action that can be done
- The parameter that the action needs to be executed
- The main player's state
- The adversary player's state

**player\_state:**

- Player won
- Cards in hand
- Cards in deck
- Known cards on top of deck
- Cards in discard pile
- Owned cards
- Played cards
- Action points
- Buy points
- Treasure value
- Victory points

An interesting note, is that information regarding the opponent player is partially observable. An example, is that cards in the opponent's hand is not shown, but the amount of cards in the hand is. In the same way, both the order of the cards in the opponent and the player's deck is not shown, but the amount of cards in the deck is.

Another aspect of the Dominion game, is that since the game only had to support AI agent training, then no GUI is created. This in turn also makes the game go significantly faster than a normal average game. The average game length of the engine using two agents is around 5-10 seconds, instead of 20-30 minutes. The game engine is now ready to be used to train an AI.

## Chapter 3

# Task: choosing and creating RL agents

---

For this part of the project, it has to be decided which kind of Reinforcement Learning method must be used. Due to the constraints of the assignment, it must either be a Monte Carlo based approach, or a Temporal Difference (TD) based approach. Between these two categories, it is decided that it would make more sense to focus on different Temporal Difference methods, since these offers more variety to work with. As stated earlier also, the project will focus on 1-step version of the most known TD-methods. The TD-methods that will be implemented are SARSA, Q-learning and Expected SARSA. A brief introduction to all three methods will be given in this section.

### 3.0.1 SARSA

This method is the most fundamental TD-method which will be the fundament which Q-learning and Expected SARSA will work on. SARSA is an on-policy method that introduces a concept called bootstrapping in comparison to Monte Carlo type methods. The bootstrapping concept works on updating the value function based on the estimation of the next state and action. Meaning that the value function is updated based on an estimate instead of the actual reward. This method theoretically lowers the variance of expected returns in comparison to Monte Carlo methods. The update rule for SARSA is as follows:

$$Q(S_t, A_t) \leftarrow Q(S_t, A_t) + \alpha [R_{t+1} + \gamma Q(S_{t+1}, A_{t+1}) - Q(S_t, A_t)] \quad (1)$$

Where  $Q(S_t, A_t)$  is the value function for state  $S_t$  and action  $A_t$ ,  $\alpha$  is the learning rate,  $R_{t+1}$  is the reward received after taking action  $A_t$  in state  $S_t$ ,  $\gamma$  is the discount factor,  $Q(S_{t+1}, A_{t+1})$  is the value function for the next state and action.



## Chapter 4

### **Task: implementing a neural network Q-table**

---

## Chapter 5

### **Task: Training scheme**

---

Chapter 6

## **evaluation**

---

## Chapter 7

# Discussion

---

Chapter 8

## **Conclusion**

---

## Chapter 9

# **Future work**

---

## Bibliography

---