

1 Reminder	1
1.1 Observations and Tricks	1
1.2 Bug List	1
2 Init (Linux)	1
2.1 vimrc	1
2.2 bashrc	1
3 Basic	1
3.1 Template (Using Codebook)	1
3.2 PBDS, Random	1
3.3 Debug	1
3.4 SVG Writer	2
3.5 Python	2
3.6 Stress Tests	2
4 Data Structure	2
4.1 Mo's Algorithm	2
4.2 CDQ	2
4.3 Persistent Treap	3
4.4 Wavelet Matrix	3
4.5 Range Set	4
4.6 Incremental Min Sum	4
4.7 Li Chao Tree	4
4.8 Time Segment Tree	4
4.9 Segment Tree Beats	5
4.10 Range Affine SegT: Metadata	5
4.11 Range Affine SegT	5
4.12 Range Affine SegT: Binary Search	6
5 DP	6
5.1 SOS DP	6
5.2 Divide and Conquer DP	6
5.3 Dynamic DP	6
5.4 Convex Hull Trick	6
6 Graph	6
6.1 Max Clique	6
6.2 Bellman-Ford	7
6.3 System of Difference Constraints	7
6.4 Graph Girth	7
6.5 Euler Trail	7
6.6 Vertex BCC (Round Square Tree)	7
6.7 Edge BCC	8
6.8 Kth Shortest Path	8
6.9 SCC - Tarjan	9
6.10 2SAT	9
7 Tree	9
7.1 Tree Isomorphism (Rooted Trees)	9
7.2 Tree Isomorphism (Unrooted Trees)	9
7.3 Heavy Light Decomposition	9
7.4 Virtual Tree	9
8 Matching	10
8.1 Bipartite Matching	10
8.2 Bipartite Weighted Matching	10
8.3 General Matching	10
9 Flow	10
9.1 Flow Methods	10
9.2 Dinic (Flow Decomposition)	11
9.3 ISAP	12
9.4 Bounded Max Flow	12
9.5 MCMF	12
9.6 Push-Relabel	13
9.7 Gomory-Hu Tree	13
9.8 Global Min Cut	13
10 String	13
10.1 Rolling Hash	13
10.2 KMP	13
10.3 Z Value	13
10.4 Manacher	14
10.5 Suffix Array + LCP	14
10.6 Suffix Automaton	14
10.7 Minimum Rotation	14
10.8 AC Automaton	14
10.9 AC Automaton - Dict Links	15
10.10 AC Automaton - Counting Patterns	15
10.11 AC Automaton - Pattern Position	15
11 Geometry	15
11.1 Template	15

11.2 Basic	15
11.3 Line / Segment Intersections	15
11.4 Point-Line / Segment Distance	15
11.5 Sort	15
11.6 Convex Hull	16
11.7 Triangle Centers	16
11.8 Point Inside	16
11.9 Point In Triangle	16
11.10 Vector In Polygon	16
11.11 Polygon Cut	16
11.12 Half-Plane Intersection	16
11.13 Cyclic Ternary Search	16
11.14 Circle Intersections	16
11.15 Tangents	17
11.16 Bisector	17
11.17 Minimum Enclosing Circle	17
11.18 Minkowski Sum	17
11.19 Convex Hull Distance	17
11.20 Closest Point Pair	17
11.21 Polygon-Circle Intersection	17
11.22 Union of Polygons	18
11.23 Rotating Sweep Line	18
11.24 Pick's Theorem	18
12 Math Basic	18
12.1 Basic	18
13 Number Theory	18
13.1 Mod Sum / Floor Sum	18
13.2 Mod Sqrt	18
13.3 Discrete Log (exBSGS)	19
13.4 Miller Rabin	19
13.5 Pollard Rho	19
13.6 Linear Sieve	19
13.7 Lucy (prime counting / prime sum)	19
13.8 Black (Min25 sieve)	19
13.9 Fast GCD	19
13.10 CRT	20
13.11 Extended Lucas	20
13.12 Divisor Block	20
13.13 Formulas	20
14 Polynomial	20
14.1 Generating Functions	20
14.2 NTT	21
14.3 FFT	21
14.4 FFT Mod (arbitrary modulus)	21
14.5 FWHT	21
14.6 Polynomial Operations	21
14.7 Berlekamp Massey	22
14.8 Linear Recurrence (Kitamasa)	23
14.9 Lagrange Interpolation (iota points)	23
15 Linear Algebra	23
15.1 Gauss (mod p)	23
15.2 Solve Linear Equations	23
15.3 Gauss (GF(2) / XOR basis)	23
15.4 Solve Linear Equations (GF(2))	23
15.5 Determinant	24
16 Numerical	24
16.1 Integrate (Simpson / adaptive)	24
16.2 Linear Programming	24
16.3 Simplex	24
17 Combinatorics	24
17.1 Catalan Number	24
17.2 Bertrand's Ballot Theorem	24
17.3 Burnside's Lemma	24
17.4 Binomial Identities	25
17.5 Stirling Numbers	25
17.6 Derangement / Inclusion-Exclusion	25
17.7 Pólya (necklaces)	25
18 Game Theory	25
18.1 Nim	25
18.2 Sprague-Grundy	25
19 Special Numbers	25
19.1 Fibonacci Series	25
19.2 Prime Numbers	25
19.3 Number of Divisors	25
19.4 Distinct Prime Factors	25

- 寫好的函式 (例如 `init()`、`build()`) 忘記呼叫
- 0-base / 1-base
- 線段樹改值懶標初始值不能設為 0
- DFS 的時候不小心覆寫到全域變數
- 多筆測資不能沒讀完直接 return
- vector 超級肥，小 vector 請用 array，例如矩陣快速冪
- `#define endl '\n'` 要寫在開頭 (`#define` 是 sequential 的，之前的程式碼不會被替換)
- `cin >>` 讀 double / long double 超級慢 (CF 10662I)，改讀字串再 `stod`/`stold` 或用 `scanf`

2 Init (Linux)

2.1 vimrc

```
1 syn on
2 set nu rnu cul mouse=a cin et ts=2 sw=2 sts=2 autochdir
  cb=unnamedplus
3 no ; :
4 ino {<CR> {<CR>}<Esc>ko
5 ca Hash w !cpp -fpreprocessed -dD -P \ | tr -d '[:space:]' \ |
  openssl sha256 -r \ | cut -c-6
```

```
1" Gino's .vimrc "
2"no <C-h> ^ | <C-l> $ | h b | l e | b l | e h
```

2.2 bashrc

```
1 gogo() {
2   g++ -std=c++20 -O2 "$1" && echo run && ./a.out
3 }
4 alias vig='vim -u ~/.vimrc-gino'
```

3 Basic

3.1 Template (Using Codebook)

```
1 // CRyptogRapher
2 #define SZ(c) ((int)(c).size())
3 // kactl
4 #define sz(x) (int)(x).size()
5 #define rep(i, a, b) for(int i=(a); i<(b); i++)
6 using ll = long long;
7 using vi = vector<int>;
8 using pii = pair<int, int>;
9 // ckiseki
10 #define all(x) begin(x), end(x)
11 #define pb emplace_back
12 #define REP(i, l, r) for (int i=(l); i<=(r); ++i)
13 const ll LINF = 1e18;
14 template<class A, class B> bool chmin(A& a, B& b) {
15   return b < a ? a = b, 1 : 0;
16 }
```

3.2 PBDS, Random

```
1 #include <bits/extc++.h>
2 using namespace __gnu_pbds;
3 // map
4 tree<int, int, less<>, rb_tree_tag,
  tree_order_statistics_node_update> tr;
5 tr.order_of_key(element);
6 tr.find_by_order(rank);
7 // set
8 tree<int, null_type, less<>, rb_tree_tag,
  tree_order_statistics_node_update> tr;
9 tr.order_of_key(element);
10 tr.find_by_order(rank);
11 // priority queue
12 __gnu_pbds::priority_queue<int, less<int>> big_q;
13 __gnu_pbds::priority_queue<int, greater<int>> small_q;
14 ql.join(q2); // join
15
16 mt19937
  gen(chrono::steady_clock::now().time_since_epoch().count());
17 uniform_int_distribution<int>(a, b)(rng) // [a, b]
18 uniform_real_distribution<double>(a, b)(rng) // (a, b)
19 shuffle(v.begin(), v.end(), gen);
```

3.3 Debug

```
1 #define debug(...) cerr << "\x1b[33m" # __VA_ARGS__ " :
  \x1b[0m", \
2   [ ](auto&&... a){ ((cerr << a << ' '), ...) }
  ( __VA_ARGS__ ), cerr << '\n'
3 #define output(...) \
4   [ ](auto&&... a){ ((cout << a << ' '), ...) }
  ( __VA_ARGS__ ), cout << '\n'
5 int v = 42;
6 format("{:b}", v); // "101010"
7 format("{:#b}", v); // "0b101010"
8 format("{:x}", v); // "0x2a"
9 format("{:X}", v); // "0X2A"
10 int x = 7;
11 format("{:05d}", x); // "00007"
12 format("{:>5}", x); // " 7"
13 format("{:<5}", x); // "7 "
```

1 Reminder

1.1 Observations and Tricks

- Contribution Technique
- 二分圖/Spanning Tree/DFS Tree
- 行、列操作互相獨立
- 奇偶性
- 當 s, t 遞增並且 $t = f(s)$ ，對 s 二分搜不好做，可以改成對 t 二分搜，再算 $f(t)$
- 啟發式合併
- Permutation Normalization (做一些平移對齊兩個 permutation)
- 枚舉 $a_1 \sim a_n$ 再枚舉 $a_n \sim a_1$ 可以包在一個迴圈
- 兩個凸型函數相加還是凸型函數，相減不一定
- 一個區間的 $\text{mex} = k$ ，表示這個區間包含 $0 \sim k-1$ 所有數字，並且「 U -區間」的最小值 $= k$ 。

1.2 Bug List

- 沒開 long long
- 陣列戳出界／陣列開不夠大

```

14 format("{: ^5}", x); // " 7 "
15 format("{: *^5}", x); // "***7***"
16 double pi = 3.1415926535;
17 format("{: .2f}", pi); // "3.14"

```

3.4 SVG Writer

```

1 // Author: ckiseki
2 class SVG {
3     void p(string_view s) { o << s; }
4     void p(string_view s, auto v, auto... vs) {
5         auto i = s.find('$');
6         o << s.substr(0, i) << v, p(s.substr(i + 1), vs...);
7     }
8     ofstream o; string c = "red";
9 public:
10    SVG(auto f, auto x1, auto y1, auto x2, auto y2) : o(f) {
11        p("<svg xmlns='http://www.w3.org/2000/svg' "
12          "viewBox='$ $ $ $'>\n"
13          "<style>{*stroke-width:0.5%;}</style>\n",
14          x1, -y2, x2 - x1, y2 - y1); }
15    ~SVG() { p("</svg>\n"); }
16    void color(string nc) { c = nc; }
17    void line(auto x1, auto y1, auto x2, auto y2) {
18        p("<line x1='$' y1='$' x2='$' y2='$' stroke='$'>\n",
19          x1, -y1, x2, -y2, c); }
20    void circle(auto x, auto y, auto r) {
21        p("<circle cx='$' cy='$' r='$' stroke='$' "
22          "fill='none'>\n", x, -y, r, c); }
23    void text(auto x, auto y, string s, int w = 12) {
24        p("<text x='$' y='$' font-size='$px'>\n",
25          x, -y, w, s); }
26 };

```

```

1 SVG svg("out.svg", -200, -200, 200, 200);
2 svg.color("lightgray"); // ↓ drawing x-y plane
3 svg.line(-200, 0, 200, 0); svg.line(0, -200, 0, 200);
4 svg.color("blue"); svg.line(10, 10, 80, 80);
5 svg.color("red"); svg.circle(50, 50, 1);

```

3.5 Python

b16508

```

1 import sys
2 input = sys.stdin.readline
3 readStr = lambda: input().rstrip('\r\n')
4 readInt = lambda: int(input())
5 readInts = lambda: list(map(int, input().split()))
6 from decimal import *
7 getcontext().prec = 50 # precision
8 x = Decimal(str(x))
9 y = Decimal("6.7")
10 x *= y
11 print(x.quantize(Decimal("0.000001"),
12                  rounding=ROUND_HALF_EVEN))
13 # ROUND_CEILING : To INF (2.9 -> 3, -2.1 -> -2)
14 # ROUND_FLOOR : To -INF (2.1 -> 2, -2.9 -> -3)
15 # ROUND_HALF_EVEN: To nearest even (2.5 -> 2, 3.5 -> 4)
16 # ROUND_HALF_UP : Half away from 0 (2.5 -> 3, -2.5 -> -3)
17 # ROUND_HALF_DOWN: Half towards 0 (2.5 -> 2, -2.5 -> -2)
18 # ROUND_UP : Away from 0 (2.1 -> 3, -2.1 -> -3)
19 # ROUND_DOWN : Truncate to 0 (2.9 -> 2, -2.9 -> -2)
20 # <Default>: ROUND_HALF_EVEN
21 # <Standard School Math>: ROUND_HALF_UP

```

3.6 Stress Tests

```

1 from random import *
2 n = randint(1, 10)
3 arr = list(randint(1, 20) for i in range(n))
4 print(*arr)
5 # permutation / non-repetitive sequence
6 perm = sample(range(1, n + 1), n)
7 arr = sample(range(1, 10000 + 1), n)
8 # string
9 from string import *
10 s = "".join(choices(ascii_lowercase, k=n))
11 t = "".join(choices(ascii_lowercase[:3], k=n)) # (a|b|c)*
12 u = "".join(choices(ascii_lowercase + ascii_uppercase +
13                    digits, k=n))
14 # palindrome
15 half = "".join(choices(ascii_lowercase, k=(n + 1) // 2))
16 palindrome = half + (half[-2::-1] if n % 2 else half[:-1])
17 # ===== tree =====
18 n = 30
19 ## shallow tree
20 edges = [(randint(1, u - 1), u) for u in range(2, n + 1)]
21 ## deep tree
22 ## (suggested k: 2 ~ 5 or int(sqrt(n)) or 2n/D (D is
23    expected depth))
24 from math import *
25 k = int(sqrt(n))
26 edges = [(randint(max(1, u - k), u - 1), u) for u in range(2, n
27    + 1)]
28 for e in edges:

```

```

26     print(*e)
27 edges = [(1, i) for i in range(2, n + 1)] ## star
28 edges = [(i, i + 1) for i in range(1, n)] ## chain
29 edges = [(i // 2, i) for i in range(2, n + 1)] ## complete
    binary tree
30 # ===== graph =====
31 # not necessarily connected, no multi-edge or self-loop
32 n = 10
33 density = 0.3 # graph density (0.0 ~ 1.0)
34 edges = [(i, j) for i in range(1, n + 1) for j in range(i + 1,
35    n + 1) if random() < density]
36 ## connected, no multi-edge or self-loop
37 n, extra_edges = 10, 5
38 edges = set()
39 ##### ... generate spanning tree with codes above
40 while len(edges) < n - 1 + extra_edges:
41     u, v = randint(1, n), randint(1, n)
42     if u != v:
43         edges.add((min(u, v), max(u, v)))
44 edges = list(edges)
45 ## DAG
46 perm = sample(range(1, n + 1), n)
47 edges = []
48 for _ in range(m):
49     i, j = sorted(sample(range(n), 2))
50     edges.append((perm[i], perm[j]))
51 ## Bipartite Graph
52 n1, n2 = 6, 7
53 left, right = list(range(1, n1 + 1)), list(range(n1 + 1,
54    n1 + n2 + 1))
55 edges = [(choice(left), choice(right)) for _ in range(m)]

```

```

1 g++ -std=c++20 -o buggy $1
2 g++ -std=c++20 -o ac ac.cpp
3 for i in {1..100}; do
4     echo "TEST $i"
5     python3 gen.py > in
6     ./ac < in > oa
7     ./buggy < in > ob
8     if ! diff -q oa ob; then
9         cat in <(echo "=== AC") oa <(echo "=== WA") ob
10        break
11    fi
12 done

```

4 Data Structure

4.1 Mo's Algorithm

5308dd

```

1 // segments are 0-based
2 int B = max(1, (int)sqrt(n));
3 sort(Q.begin(), Q.end(), [&](const auto& a, const auto& b) {
4     if (a[0]/B != b[0]/B) return a[0]/B < b[0]/B;
5     return (a[0]/B & 1) ? a[1] < b[1] : a[1] > b[1];
6 });
7 ll cur = 0; // current answer
8 int pl = 0, pr = -1;
9 for (auto& qi : Q) {
10    // get (l, r, qid) from qi
11    while (pl < l) del(pl++); while (pl > l) add(--pl);
12    while (pr < r) add(++pr); while (pr > r) del(pr--);
13    ans[qid] = cur;
14 }

```

4.2 CDQ

e1864b

```

1 // sorted by x; type 0 = update (weight w), 1 = query
2 // query: ans[id] = sum of w over updates with x' <= x,
3 // y' <= y, z' <= z (< if strict[dim]). 值域 [1, mxc]
4 // Dependency: 值域 BIT
5 struct Info { int x, y, z, type; ll w; int id; };
6 struct CDQ {
7     static bool cy(const Info& p, const Info& q)
8     { return p.y < q.y; }
9     vector<Info> a; int n; array<bool, 3> strict;
10    vector<ll> ans; BIT bit;
11    void dfs(int l, int r) { if (r - l <= 1) return;
12        int m = (l + r) / 2, i = l;
13        dfs(l, m);
14        vector<Info> t(a.begin() + m, a.begin() + r);
15        ranges::sort(t, cy);
16        for (auto& q : t) {
17            for (; i < m && a[i].y < q.y + !strict[1]; i++)
18                if (!a[i].type) bit.upd(a[i].z, a[i].w);
19            if (q.type)
20                ans[q.id] += bit.qry(q.z - strict[2]);
21        }
22        for (int k = l; k < i; k++)
23            if (!a[k].type) bit.upd(a[k].z, -a[k].w);
24        dfs(m, r);
25        inplace_merge(a.begin() + l, a.begin() + m,
26            a.begin() + r, cy);

```

```

27 }
28 CDQ(vector<Info> _a, int mxc, array<bool, 3> _s = {}):
29     a(_a), n(a.size()), strict(_s) {
30     ans.assign(n, 0); bit.init(mxc);
31     auto key = [&](Info& p) { return
32         make_tuple(p.x, p.type != strict[0], p.y, p.z); };
33     ranges::sort(a, {}, key); dfs(0, n);
34 }
35 };

```

4.3 Persistent Treap

5f64da

```

1 // Author: Ian
2 struct node {
3     node *l, *r;
4     char c; int v, sz;
5     node(char x = '$'): c(x), v(mt()), sz(1) {
6         l = r = nullptr;
7     }
8     node(node* p) { *this = *p; }
9     void pull() {
10         sz = 1;
11         for (auto i : {l, r})
12             if (i) sz += i->sz;
13     }
14 } arr[maxn], *ptr = arr;
15 inline int size(node* p) { return p ? p->sz : 0; }
16 node* merge(node* a, node* b) {
17     if (!a || !b) return a ? a : b;
18     if (a->v < b->v) {
19         node* ret = new(ptr++) node(a);
20         ret->r = merge(ret->r, b); ret->pull();
21         return ret;
22     }
23     else {
24         node* ret = new(ptr++) node(b);
25         ret->l = merge(a, ret->l); ret->pull();
26         return ret;
27     }
28 }
29 P<node*> split(node* p, int k) {
30     if (!p) return {nullptr, nullptr};
31     if (k >= size(p->l) + 1) {
32         auto [a, b] = split(p->r, k - size(p->l) - 1);
33         node* ret = new(ptr++) node(p);
34         ret->r = a; ret->pull();
35         return {ret, b};
36     }
37     else {
38         auto [a, b] = split(p->l, k);
39         node* ret = new(ptr++) node(p);
40         ret->l = b; ret->pull();
41         return {a, ret};
42     }
43 }

```

4.4 Wavelet Matrix

d6d983

```

1 // KACTL (Kopricky). values in [0, sigma). all ranges [l, r)
2 // rank(v, l, r): #v in [l, r); quantile(k, l, r): k-th smallest
3 // rangefreq(l, r, a, b): #x in [l, r) with a <= x < b; rangemin:
4 // min such x or -1
5 struct BitRank {
6     // block manages bit by bit in rows
7     std::vector<unsigned long long> block;
8     std::vector<unsigned int> count;
9     BitRank() {}
10    // bit vector length
11    void resize(const unsigned int num) {
12        block.resize(((num + 1) >> 6) + 1, 0);
13        count.resize(block.size(), 0);
14    }
15    // set bit at position i
16    void set(const unsigned int i, const unsigned long long
17    val) {
18        block[i >> 6] |= (val << (i & 63));
19    }
20    void build() {
21        for (unsigned int i = 1; i < block.size(); i++) {
22            count[i] = count[i - 1] + __builtin_popcountll(block[i
23            - 1]);
24        }
25        // number of 1s in [0, i)
26        unsigned int rank1(const unsigned int i) const {
27            return count[i >> 6] +
28            & 63)) - 1ULL);
29        // number of 1s in [i, j)
30        unsigned int rank1(const unsigned int i, const unsigned
31        int j) const {

```

```

30         return rank1(j) - rank1(i);
31     }
32     // number of 0s in [0, i)
33     unsigned int rank0(const unsigned int i) const { return i
34     - rank1(i); }
35     // number of 0s in [i, j)
36     unsigned int rank0(const unsigned int i, const unsigned
37     int j) const {
38         return rank0(j) - rank0(i);
39     }
40 }
41 class WaveletMatrix {
42 private:
43     unsigned int height;
44     std::vector<BitRank> B;
45     std::vector<int> pos;
46 public:
47     WaveletMatrix() {}
48     WaveletMatrix(std::vector<int> vec)
49         : WaveletMatrix(vec, *std::max_element(vec.begin(),
50         vec.end()) + 1) {}
51     // sigma: alphabet size (for strings), number of distinct
52     // values for number sequences
53     WaveletMatrix(std::vector<int> vec, const unsigned int
54     sigma) {
55         init(vec, sigma);
56     }
57     void init(std::vector<int> &vec, const unsigned int sigma)
58     {
59         height = (sigma == 1) ? 1 : (64 - __builtin_clzll(sigma
60         - 1));
61         B.resize(height), pos.resize(height);
62         for (unsigned int i = 0; i < height; ++i) {
63             B[i].resize(vec.size());
64             for (unsigned int j = 0; j < vec.size(); ++j) {
65                 B[i].set(j, get(vec[j], height - i - 1));
66             }
67             B[i].build();
68             auto it = stable_partition(vec.begin(), vec.end(), [&
69             (int c) {
70                 return !get(c, height - i - 1);
71             });
72             pos[i] = it - vec.begin();
73         }
74     }
75     int get(const int val, const int i) { return val >> i &
76     1; }
77     // frequency of val in [l, r)
78     int rank(const int val, const int l, const int r) {
79         return rank(val, r) - rank(val, l);
80     }
81     // frequency of val in [0, i)
82     int rank(int val, int i) {
83         int p = 0;
84         for (unsigned int j = 0; j < height; ++j) {
85             if (get(val, height - j - 1)) {
86                 p = pos[j] + B[j].rank1(p);
87                 i = pos[j] + B[j].rank1(i);
88             } else {
89                 p = B[j].rank0(p);
90                 i = B[j].rank0(i);
91             }
92         }
93         return i - p;
94     }
95     // k-th smallest in [l, r)
96     int quantile(int k, int l, int r) {
97         int res = 0;
98         for (unsigned int i = 0; i < height; ++i) {
99             const int j = B[i].rank0(l, r);
100             if (j > k) {
101                 l = B[i].rank0(l);
102                 r = B[i].rank0(r);
103             } else {
104                 l = pos[i] + B[i].rank1(l);
105                 r = pos[i] + B[i].rank1(r);
106                 k -= j;
107                 res |= (1 << (height - i - 1));
108             }
109         }
110         return res;
111     }
112     int rangefreq(const int i, const int j, const int a, const
113     int b, const int l,
114     const int r, const int x) {

```

```

110 if (i == j || r <= a || b <= l) return 0;
111 const int mid = (l + r) >> 1;
112 if (a <= l && r <= b) {
113     return j - i;
114 } else {
115     const int left =
116         rangefreq(B[x].rank0(i), B[x].rank0(j), a, b, l,
117             mid, x + 1);
118     const int right = rangefreq(pos[x] + B[x].rank1(i),
119             pos[x] + B[x].rank1(j), a,
120             b, mid, r, x + 1);
121     return left + right;
122 }
123 // number of values in [l,r) with values in range [a, b)
124 int rangefreq(const int l, const int r, const int a, const
125     int b) {
126     return rangefreq(l, r, a, b, 0, 1 << height, 0);
127 }
128 int rangemin(const int i, const int j, const int a, const
129     int b, const int l,
130     const int r, const int x, const int val) {
131     if (i == j || r <= a || b <= l) return -1;
132     if (r - l == 1) return val;
133     const int mid = (l + r) >> 1;
134     const int res =
135         rangemin(B[x].rank0(i), B[x].rank0(j), a, b, l, mid,
136             x + 1, val);
137     if (res < 0)
138         return rangemin(pos[x] + B[x].rank1(i), pos[x] +
139             B[x].rank1(j), a, b, mid,
140             r, x + 1, val + (1 << (height - x -
141                 1)));
142     else
143         return res;
144 }
145 // minimum value that exists in [l,r) within value range
146 [a,b), returns -1 if none exists
147 int rangemin(int l, int r, int a, int b) {
148     return rangemin(l, r, a, b, 0, 1 << height, 0, 0);
149 }
150 }
151 }
152 }
153 }

```

4.5 Range Set

a2366a

```

1 // std abs. disjoint half-open ranges [l, r) in a set.
2 // split(l,r): remove & return all pieces covering [l,r)
3 // (cuts at l, r)
4 // insert(l,r): add [l,r) (must be disjoint from S), merges
5 // neighbours
6 struct RangeSet { // [l, r)
7     set<pii> S;
8     void cut(int x) {
9         auto it = S.lower_bound({x + 1, -1});
10        if (it == S.begin()) return;
11        auto [l, r] = *prev(it);
12        if (l >= x || x >= r) return;
13        S.erase(prev(it));
14        S.insert({l, x});
15        S.insert({x, r});
16    }
17    vector<pii> split(int l, int r) {
18        // remove and return ranges in [l, r)
19        cut(l), cut(r);
20        vector<pii> res;
21        while (true) {
22            auto it = S.lower_bound({l, -1});
23            if (it == S.end() || r <= it->first) break;
24            res.pb(*it), S.erase(it);
25        }
26        return res;
27    }
28    void insert(int l, int r) {
29        // add a range [l, r), [l, r) not in S
30        auto it = S.lower_bound({l, r});
31        if (it != S.begin() && prev(it)->second == l)
32            l = prev(it)->first, S.erase(prev(it));
33        if (it != S.end() && r == it->first)
34            r = it->second, S.erase(it);
35        S.insert({l, r});
36    }
37    bool count(int x) {
38        auto it = S.lower_bound({x + 1, -1});
39        return it != S.begin() && prev(it)->first <= x
40            && x < prev(it)->second;
41    }
42 }
43 }

```

4.6 Incremental Min Sum

b3e8ac

```

1 // std abs. multiset with insert/erase; sum = sum of the cap
2 // smallest
3 // elements; enlarge() increases cap by 1. O(log n) each.

```

```

3 struct IncrementalMinSum {
4     multiset<int, greater<int>> in;
5     multiset<int> out;
6     ll sum; int cap;
7     IncrementalMinSum() : sum(0), cap(0) {}
8     void enlarge() {
9         if (!out.empty()) {
10             int mx = *out.begin();
11             sum += mx, in.insert(mx), out.erase(out.begin());
12         }
13         cap++;
14     }
15     void insert(int x) {
16         if (!cap) {
17             out.insert(x);
18             return;
19         }
20         if (in.size() < cap) {
21             in.insert(x), sum += x;
22             return;
23         }
24         int mx = *in.begin();
25         if (x < mx) {
26             sum -= mx, out.insert(mx), in.erase(in.begin());
27             sum += x, in.insert(x);
28         } else {
29             out.insert(x);
30         }
31     }
32     void erase(int x) {
33         if (out.find(x) != out.end()) {
34             out.erase(out.lower_bound(x));
35         } else {
36             in.erase(in.lower_bound(x)), sum -= x;
37             if (!out.empty()) {
38                 int mx = *out.begin();
39                 sum += mx, out.erase(out.begin()), in.insert(mx);
40             }
41         }
42     }
43 };

```

4.7 Li Chao Tree

110f70

```

1 // Author: Ian
2 // insert(L): add line L(ax+b) in [0, maxn)
3 // insertseg(L, ql, qr): add segment L in [ql, qr)
4 // query(x): find maximum L at x
5 using T=long long;
6 const int maxn = 1e5+5;
7 const T MN = -1e15;
8 struct line {
9     T a, b;
10    line(T a=0, T b=MN): a(a), b(b) {}
11    T operator()(T x) {return a * x + b;}
12 } arr[(maxn+1)<<3];
13 bool operator<(line a, line b) {
14     return a.a < b.a || (a.a == b.a && a.b < b.b); }
15 #define m ((l+r)>>1)
16 void insert(line x, int i=1, int l=0, int r=maxn) {
17     if (r-l == 1) {
18         if (x(l) > arr[i](l)) arr[i] = x;
19         return; }
20     line a = max(arr[i], x), b = min(arr[i], x);
21     if (a(m) > b(m))
22         arr[i] = a, insert(b, i<<1, l, m);
23     else
24         arr[i] = b, insert(a, i<<1, m, r);
25 }
26 void insertseg(line x, int ql, int qr,
27     int i=1, int l=0, int r=maxn) {
28     if (qr<=l || r<=ql || ql>=qr) return;
29     if (ql<=l && r<=qr) { insert(x, i, l, r); return; }
30     insertseg(x, ql, qr, i<<1, l, m);
31     insertseg(x, ql, qr, i<<1, m, r);
32 }
33 T query(T x, int i=1, int l=0, int r=maxn) {
34     if (x<l || r<=x) return MN;
35     if (r-l == 1) return arr[i](x);
36     return max({arr[i](x),
37         query(x, i<<1, l, m), query(x, i<<1, m, r)});
38 }
39 #undef m

```

4.8 Time Segment Tree

e8ac31

```

1 // Author: Ian
2 struct Op; // reversible operation
3 const int maxn = 2e5 + 5;
4 vector<Op> arr[(maxn + 1) << 2];
5 #define m ((l + r) >> 1)

```

```

6 void insert(int ql, int qr, Op x, int i=1, int l=0, int r=maxn) {
7     if (qr <= l || r <= ql) return;
8     if (ql <= l && r <= qr) { arr[i].push_back(x); return; }
9     if (qr <= m) insert(ql, qr, x, i << 1, l, m);
10    else if (m <= ql) insert(ql, qr, x, i << 1 | 1, m, r);
11    else {
12        insert(ql, qr, x, i << 1, l, m);
13        insert(ql, qr, x, i << 1 | 1, m, r);
14    }
15}
16 void traversal(vector<int>& ans, int i=1, int l=0, int r=maxn) {
17     int opcnt = 0;
18     for (auto val : arr[i])
19         if (DO_SOMETHING(val)) opcnt++;
20     if (r - l == 1) ans[l] = CALC_ANS();
21     else {
22         traversal(ans, i << 1, l, m);
23         traversal(ans, i << 1 | 1, m, r);
24     }
25     while (opcnt--) UNDO_SOMETHING();
26     arr[i].clear();
27 }
28 #undef m

```

4.9 Segment Tree Beats

d7946d

```

1 // Author: Ian, https://judge.yosupo.jp/submission/400861
2 const int maxn=2e5+5;
3 const ll MX = 1e18+5;
4 const ll MN = -MX;
5 #define m ((l+r)>>1)
6 struct node {
7     ll sum, inc;
8     ll mn, smn; int mnc;
9     ll mx, smx; int mxc;
10    node(ll x=0): sum(x), inc(0),
11        mn(x), smn(MX), mnc(1),
12        mx(x), smx(MN), mxc(1) {}
13    void pull(int i);
14    void push(int i, int l, int r);
15} a[(maxn+1)<<2];
16 void node::pull(int i) {
17     sum = a[i<<1].sum+a[i<<1|1].sum;
18     if (a[i<<1].mn == a[i<<1|1].mn) {
19         mn = a[i<<1].mn;
20         smn = min(a[i<<1].smn, a[i<<1|1].smn);
21         mnc = a[i<<1].mnc+a[i<<1|1].mnc;
22     } else {
23         if (a[i<<1].mn < a[i<<1|1].mn) {
24             mn = a[i<<1].mn;
25             smn = min(a[i<<1].smn, a[i<<1|1].smn);
26             mnc = a[i<<1].mnc;
27         } else {
28             mn = a[i<<1|1].mn;
29             smn = min(a[i<<1|1].smn, a[i<<1].smn);
30             mnc = a[i<<1|1].mnc;
31         }
32     }
33     if (a[i<<1].mx == a[i<<1|1].mx) {
34         mx = a[i<<1].mx;
35         smx = max(a[i<<1].smx, a[i<<1|1].smx);
36         mxc = a[i<<1].mxc+a[i<<1|1].mxc;
37     } else {
38         if (a[i<<1].mx > a[i<<1|1].mx) {
39             mx = a[i<<1].mx;
40             smx = max(a[i<<1].smx, a[i<<1|1].smx);
41             mxc = a[i<<1].mxc;
42         } else {
43             mx = a[i<<1|1].mx;
44             smx = max(a[i<<1|1].smx, a[i<<1].smx);
45             mxc = a[i<<1|1].mxc;
46         }
47     }
48 }
49 void updmn(int i, int len, ll v) {
50     a[i].sum += (v-a[i].mn)*a[i].mnc; a[i].mn = v;
51     if (len==1 || v>=a[i].mx)
52         a[i].mx = v, a[i].smx = MN;
53     else if (v>a[i].smx)
54         a[i].smx = v;
55 }
56 void updmx(int i, int len, ll v) {
57     a[i].sum -= (a[i].mx-v)*a[i].mxc; a[i].mx = v;
58     if (len==1 || v<=a[i].mn)
59         a[i].mn = v, a[i].smn = MX;
60     else if (v<a[i].smn)
61         a[i].smn = v;
62 }
63 void node::push(int i, int l, int r) {
64     if (r-l==1) return;
65     pair<int, int> ch[] = {{i<<1, m-l}, {i<<1|1, r-m}};
66     if (inc!=0) for (auto [j, len]: ch) {
67         a[j].sum += inc*len, a[j].inc += inc;

```

```

68         a[j].mx += inc, a[j].smx += inc;
69         a[j].mn += inc, a[j].smn += inc;
70     } inc = 0;
71     for (auto [j, len]: ch) {
72         if (a[j].mn < mn) updmn(j, len, mn);
73         if (a[j].mx > mx) updmx(j, len, mx);
74     }
75 void build(vector<ll>& v, int i=1, int l=0, int r=maxn) {
76     if ((int)v.size()<=l) return;
77     if (r-l==1) { a[i] = node(v[l]); return; }
78     build(v, i<<1, l, m);
79     build(v, i<<1|1, m, r);
80     a[i].pull(i);
81 }
82 void chmin(int ql, int qr, ll v, int i=1, int l=0, int r=maxn) {
83     if (qr<=l || r<=ql || a[i].mx<=v) return;
84     if (ql<=l && r<=qr && a[i].smx<v) { updmx(i, r-l, v); return; }
85     a[i].push(i, l, r);
86     chmin(ql, qr, v, i<<1, l, m);
87     chmin(ql, qr, v, i<<1|1, m, r);
88     a[i].pull(i);
89 }
90 void chmax(int ql, int qr, ll v, int i=1, int l=0, int r=maxn) {
91     if (qr<=l || r<=ql || a[i].mn>=v) return;
92     if (ql<=l && r<=qr && a[i].smn>v) { updmn(i, r-l, v); return; }
93     a[i].push(i, l, r);
94     chmax(ql, qr, v, i<<1, l, m);
95     chmax(ql, qr, v, i<<1|1, m, r);
96     a[i].pull(i);
97 }
98 void inc(int ql, int qr, ll v, int i=1, int l=0, int r=maxn) {
99     if (qr<=l || r<=ql) return;
100    if (ql<=l && r<=qr) {
101        a[i].sum += v*(r-l);
102        a[i].mx += v, a[i].smx += v;
103        a[i].mn += v, a[i].smn += v;
104        a[i].inc += v;
105        return;
106    }
107    a[i].push(i, l, r);
108    inc(ql, qr, v, i<<1, l, m);
109    inc(ql, qr, v, i<<1|1, m, r);
110    a[i].pull(i);
111 }
112 ll qsum(int ql, int qr, int i=1, int l=0, int r=maxn) {
113     if (qr<=l || r<=ql) return 0;
114     if (ql<=l && r<=qr) return a[i].sum;
115     a[i].push(i, l, r);
116     return qsum(ql, qr, i<<1, l, m)+qsum(ql, qr, i<<1|1, m, r);
117 }
118 #undef m

```

4.10 Range Affine SegT: Metadata

32a905

```

1 // Author: Gino, Range Affine Segment Tree
2 // Maintain b*a[i]+c, support range modifications of b, c
3 // ===== RANGE MAX/MIN =====
4 struct S { ll mx; };
5 struct T { ll b, c; }; // bx + c, b >= 0
6 inline S op(S a, S b) { return {max(a.mx, b.mx)}; }
7 inline S e() { return {LLONG_MIN}; } // min: LLONG_MAX
8 inline S mapping(T f, S x) {
9     if (x.mx == LLONG_MIN) return x; // keep -inf
10    return {f.b * x.mx + f.c};
11 }
12 inline T composition(T f, T g) {
13     return {f.b * g.b, f.b * g.c + f.c};
14 }
15 inline T id() { return {1, 0}; }
16 // ===== RANGE SUM =====
17 struct S { ll x, len; };
18 struct T { ll b, c; }; // bx + c
19 inline S op(S a, S b) { return {
20     (a.x + b.x) % mod,
21     a.len + b.len,
22 }; }
23 inline S e() { return {0, 0}; }
24 inline S mapping(T f, S x) { return {
25     (f.b * x.x + f.c * x.len) % mod,
26     x.len,
27 }; }
28 inline T composition(T f, T g) { return {
29     fb(gb*x + gc) + fc = (fb*gb)x + (fb*gc + fc)
30     (f.b * g.b) % mod,
31     (f.b * g.c + f.c) % mod,
32 }; }
33 inline T id() { return {1, 0}; }

```

4.11 Range Affine SegT

a2785d

```

1 #define mid ((l + r) >> 1)
2 #define cl (i<<1)
3 #define cr (i<<1|1)

```

```

4 class SegT {
5     int n; vector<S> a, t; vector<T> lz;
6     inline void pull(int i) { t[i] = op(t[cl], t[cr]); }
7     inline void apply(int i, T tag) {
8         t[i] = mapping(tag, t[i]);
9         lz[i] = composition(tag, lz[i]);
10    }
11    inline void push(int i) {
12        apply(cl, lz[i]); apply(cr, lz[i]);
13        lz[i] = id();
14    }
15    void build(int l, int r, int i) {
16        if (l == r) { t[i] = a[l]; return; } ///! a[l], not a[i]
17        build(l, mid, cl); build(mid+1, r, cr); pull(i);
18    }
19    int ql, qr; T tag;
20    void upd(int l, int r, int i) {
21        if (qr < l || r < ql) return;
22        if (ql <= l && r <= qr) { apply(i, tag); return; }
23        push(i); upd(l, mid, cl); upd(mid+1, r, cr); pull(i);
24    }
25    S qry(int l, int r, int i) {
26        if (qr < l || r < ql) return e();
27        if (ql <= l && r <= qr) return t[i];
28        push(i); return op(qry(l, mid, cl), qry(mid+1, r, cr));
29    }
30 public:
31     SegT(vector<S>& a):
32         n(a.size()), a(a), t(n<<2), lz(n<<2, id()) {
33         build(0, n - 1, 1);
34     }
35     void update(int l, int r, T tag) { // [l, r)
36         ql = l, qr = r - 1, this->tag = tag;
37         upd(0, n - 1, 1);
38     }
39     S query(int l, int r) { // [l, r)
40         ql = l, qr = r - 1;
41         return qry(0, n - 1, 1);
42     };
43 #undef mid
44 #undef cl
45 #undef cr

```

4.12 Range Affine SegT: Binary Search

658c18

```

1 // Add-on: paste inside SegT (before #undef mid/cl/cr).
2 // g: bool(S), monotone along the range, g(e()) must be true.
3 // e.g. first r with sum[l, r) >= k:
4 // max_right(l, [&](S s) { return s.x < k; }) (n if none)
5 // private:
6 template <class G> int mr(int l, int r, int i, S& acc, G g) {
7     if (r < ql) return -1;
8     if (ql <= l) { S s = op(acc, t[i]);
9         if (g(s)) { acc = s; return -1; }
10        if (l == r) return l; }
11    push(i);
12    int res = mr(l, mid, cl, acc, g);
13    return res != -1 ? res : mr(mid+1, r, cr, acc, g);
14 }
15 template <class G> int ml(int l, int r, int i, S& acc, G g) {
16     if (qr < l) return -1;
17     if (r <= ql) { S s = op(t[i], acc);
18         if (g(s)) { acc = s; return -1; }
19         if (l == r) return l + 1; }
20    push(i);
21    int res = ml(mid+1, r, cr, acc, g);
22    return res != -1 ? res : ml(l, mid, cl, acc, g);
23 }
24 // public:
25 // max r in [l, n] s.t. g(op(a[l..r))) true
26 template <class G> int max_right(int l, G g) {
27     ql = l; S acc = e(); int r = mr(0, n - 1, 1, acc, g);
28     return r == -1 ? n : r;
29 }
30 // min l in [0, r] s.t. g(op(a[l..r))) true
31 template <class G> int min_left(int r, G g) {
32     qr = r - 1; S acc = e(); int l = ml(0, n - 1, 1, acc, g);
33     return l == -1 ? 0 : l;
34 }

```

5 DP

5.1 SOS DP

d1c8c0

```

1 // Author: Gino
2 // Function: Solve problems that enumerates subsets of
3 // subsets (3^n => n*2^n)
4 for (int msk = 0; msk < (1<<n); msk++) {

```

```

4     for (int i = 1; i <= n; i++) {
5         if (msk & (1<<(i - 1))) {
6             dp[msk][i] = dp[msk][i - 1] + dp[msk ^ (1<<(i - 1))][i - 1];
7         } else {
8             dp[msk][i] = dp[msk][i - 1];
9         }

```

5.2 Divide and Conquer DP

7f9218

```

1 /* Author: Simon Lindholm (License: CC0)
2 * Description: Given $a[i] = \min_{lo(i) \le k < hi(i)} (f(i, k))$ where the (minimal)
3 * optimal $k$ increases with $i$, computes $a[i]$ for $i = L..R-1$.
4 * Time: $O((N + (hi-lo)) \log N)$ */
5 struct DP { // Modify at will:
6     int lo(int ind) { return 0; }
7     int hi(int ind) { return ind; }
8     ll f(int ind, int k) { return dp[ind][k]; }
9     void store(int ind, int k, ll v) { res[ind] = pii(k, v); }
10    void rec(int L, int R, int LO, int HI) {
11        if (L >= R) return;
12        int mid = (L + R) >> 1;
13        pair<ll, int> best(LLONG_MAX, LO);
14        rep(k, max(LO, lo(mid)), min(HI, hi(mid)))
15            best = min(best, make_pair(f(mid, k), k));
16        store(mid, best.second, best.first);
17        rec(L, mid, LO, best.second+1);
18        rec(mid+1, R, best.second, HI);
19    }
20    void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
21 };

```

5.3 Dynamic DP

- 適用情境： $dp_i = M_i \cdot dp_{i-1} \Rightarrow dp_i = M_i M_{i-1} \cdots M_1 dp_0$
- 當 M_i 需要動態修改，且 M_i 是廣義矩陣乘法：

$$C_{ij} = \bigoplus_k A_{ik} \otimes B_{kj}$$

- 滿足 $(\oplus, \otimes)$ 是半環 ($\otimes$ 對 $\oplus$ 有分配律、 $\otimes$ 和 $\oplus$ 有結合律、 $\oplus$ 有交換律)
- 此時便可用線段樹維護 $M_n M_{n-1} \cdots M_1$ 的乘積。線段樹上的 pos 是 M_{pos} ，但 pull 時要 $\text{st}[\text{idx}] = \text{mul}(\text{st}[\text{cr}], \text{st}[\text{cl}])$

5.4 Convex Hull Trick

28a4d4

```

1 /**
2 * Author: Simon Lindholm (License: CC0, Source: own work)
3 * Container where you can add lines of the form kx+m,
4 * and query maximum values at points x.
5 * Useful for dynamic programming ('convex hull trick').
6 * Time: $O(\log N)$, Status: stress-tested */
7 struct Line {
8     mutable ll k, m, p;
9     bool operator<(const Line& o) const { return k < o.k; }
10    bool operator<(ll x) const { return p < x; }
11 };
12 struct LineContainer : multiset<Line, less<>> {
13     // (for doubles, use inf = 1/.0, div(a,b) = a/b)
14     static const ll inf = LLONG_MAX;
15     ll div(ll a, ll b) { // floored division
16         return a / b - ((a ^ b) < 0 && a % b); }
17     bool isect(iterator x, iterator y) {
18         if (y == end()) return x->p = inf, 0;
19         if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
20         else x->p = div(y->m - x->m, x->k - y->k);
21         return x->p >= y->p;
22     }
23     void add(ll k, ll m) {
24         auto z = insert({k, m, 0}), y = z++, x = y;
25         while (isect(y, z)) z = erase(z);
26         if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
27         while ((y = x) != begin() && (--x)->p >= y->p)
28             isect(x, erase(y));
29     }
30     ll query(ll x) {
31         auto l = *lower_bound(x);
32         return l.k * x + l.m;
33     };

```

6 Graph

6.1 Max Clique

3ea3ee

```

1 // max N = 64
2 typedef unsigned long long ll;
3 struct MaxClique {
4     ll nb[ N ], n, ans;
5     void init( ll _n ) {
6         n = _n;
7         for (int i = 0; i < n; i++) nb[ i ] = 0LLU;

```

```

8 }
9 void add_edge( ll _u , ll _v ){
10     nb[ _u ] |= ( 1LLU << _v );
11     nb[ _v ] |= ( 1LLU << _u );
12 }
13 void B( ll r , ll p , ll x , ll cnt , ll res ){
14     if( cnt + res < ans ) return;
15     if( p == 0LLU && x == 0LLU ){
16         if( cnt > ans ) ans = cnt;
17         return;
18     }
19     ll y = p | x; y &= -y;
20     ll q = p & ( ~nb[ int( log2( y ) ) ] );
21     while( q ){
22         ll i = int( log2( q & (-q) ) );
23         B( r | ( 1LLU << i ) , p & nb[ i ] , x & nb[ i ]
24             , cnt + 1LLU , __builtin_popcountll( p &
25                 nb[ i ] ) );
26         q &= ~( 1LLU << i );
27         p &= ~( 1LLU << i );
28         x |= ( 1LLU << i );
29     }
30 }
31 int solve(){
32     ans = 0;
33     ll _set = 0;
34     if( n < 64 ) _set = ( 1LLU << n ) - 1;
35     else{
36         for( ll i = 0 ; i < n ; i ++ ) _set |= ( 1LLU << i );
37     }
38     B( 0LLU , _set , 0LLU , 0LLU , n );
39     return ans;
40 }
41 }maxClique;

```

6.2 Bellman-Ford

841372

```

1 // Author: Gino
2 // n, m = #(vertices), #(edges), and vertices are 1-based
3 // 1. BellmanFord bf(G, n, m);
4 // 2-1: bf.calcDis(s);
5 // => bf.dis[u] := shortest dis from s to u
6 // => bf.dis[u] := LINF (s can't reach u)
7 // => bf.dis[u] := -LINF (dis[u] can be arbitrary small)
8 // 2-2: bf.findNegCycle();
9 // => false (if no neg cycle)
10 // => true (has neg cycle & gives an example: bf.neg_cycle)
11 // Time: O(VE), Space: O(V + E)
12 const ll LINF = 4e18;
13 struct BellmanFord {
14     const vector<vector<pair<int, ll>>& G;
15     int n, m; // #(vertices), #(edges)
16     BellmanFord(const auto& G, int n, int m):G(G), n(n), m(m) {}
17     vector<ll> dis; vector<int> nth_relax, pa;
18     void run_bf(const auto& src) {
19         dis.assign(n+1, LINF);
20         nth_relax.assign(n+1, 0); pa.assign(n+1, -1);
21         for (auto& s : src) dis[s] = 0;
22         for (int rlx = 1; rlx <= n; rlx++) {
23             for (int u = 1; u <= n; u++) {
24                 if (dis[u] == LINF) continue; // !important
25                 for (auto& [v, w] : G[u]) {
26                     if (dis[v] > dis[u] + w) {
27                         dis[v] = dis[u] + w; pa[v] = u;
28                         if (rlx == n) nth_relax[v] = 1;
29                     }
30                 }
31             }
32             // 5 brackets
33         }
34         void calcDis(int s) {
35             run_bf(vector<int>{s}); queue<int> q;
36             for (int u=1; u<=n; u++) if (nth_relax[u]) q.push(u);
37             while (!q.empty()) { int u = q.front(); q.pop();
38                 for (auto& [v, w] : G[u]) {
39                     if (!nth_relax[v]) {
40                         nth_relax[v] = 1; q.push(v);
41                     }
42                 }
43             }
44             for (int u=1; u<=n; u++) if (nth_relax[u]) dis[u] = -LINF;
45         }
46     }
47     vector<int> neg_cycle;
48     bool findNegCycle() {
49         auto src = views::iota(1, n + 1); run_bf(src);
50         auto it = ranges::find_if(src,
51             [&](int s){ return nth_relax[s]; });
52         if (it == src.end()) return false;
53         int ptr = *it; for (int i=0; i<n; i++) ptr = pa[ptr];
54         neg_cycle.clear(); int cur = ptr;
55         while (true) {
56             neg_cycle.emplace_back(cur);
57             if (cur == ptr && neg_cycle.size() > 1) break;
58             cur = pa[cur];
59         }
60         ranges::reverse(neg_cycle); return true;
61     }
62 }

```

54 } };

6.3 System of Difference Constraints

```

1 vector<vector<pair<int, ll>>> G;
2 void add(int u, int v, ll w) { G[u].push_back({v, w}); }

```

- $x_u - x_v \leq c \Rightarrow \text{add}(v, u, c)$
- $x_u - x_v \geq c \Rightarrow \text{add}(u, v, -c)$
- $x_u - x_v = c \Rightarrow \text{add}(v, u, c), \text{add}(u, v, -c)$
- $x_u \geq c \Rightarrow \text{add super vertex } x_0 = 0, \text{ then } x_u - x_0 \geq c \Rightarrow \text{add}(u, 0, -c)$
- Don't forget non-negative constraints for every variable if specified implicitly.
- Interval sum $\Rightarrow$ Use prefix sum to transform into differential constraints. Don't forget $S_{i+1} - S_i \geq 0$ if x_i needs to be non-negative.
- $x_u/x_v \leq c \Rightarrow \log x_u - \log x_v \leq \log c$

6.4 Graph Girth

Run BFS for every node, when encountered non-BFS-tree edge, update answer (min cycle length) with $\text{dis}[u] + \text{dis}[v] + 1$. Time $O(VE)$.

6.5 Euler Trail

ee23d4

```

1 // Author: kactl (Simon Lindholm), wrapped by Gino
2 // Vertices are 1-based, Edge ID are 0-based
3 // 1. EulerWalk euler(n, true(directed) / false(undirected));
4 // 2. euler.addEdge(u, v);
5 // 3. int result = euler.solve();
6 // => -1: nothing (euler.path, euler.path_edges = {})
7 // => 1: Euler trail,
8 // => 2: Euler circuit
9 //     euler.path = {u_1, ..., u_{m+1}}
10 //     euler.path_edges = {e_1, ..., e_m}
11 // Time: O(V + E), Space: O(V + E)
12 // Test: V, E <= 2e5, 99ms
13 struct EulerWalk {
14     int n, m = 0; bool dir;
15     vector<vector<pii>> G; vi deg;
16     EulerWalk(int n, bool dir) :
17         n(n), dir(dir), G(n+1), deg(n+1) {}
18     void addEdge(int u, int v) {
19         G[u].push_back({v, m});
20         if (!dir) G[v].push_back({u, m});
21         deg[u]++, deg[v] += dir ? -1 : 1; m++;
22     }
23     vi path, path_edges;
24     void walk(int src) {
25         path.clear(); path_edges.clear();
26         vi its(n+1), visE(m);
27         function<void(int, int)> dfs = [&](int u, int e_in) {
28             while (its[u] < sz(G[u])) {
29                 auto [v, e] = G[u][its[u]++];
30                 if (visE[e]) continue;
31                 visE[e] = 1;
32                 dfs(v, e);
33             }
34             path.push_back(u);
35             if (e_in != -1) path_edges.push_back(e_in);
36         };
37         dfs(src, -1);
38         if (sz(path) != m + 1) {
39             path.clear(); path_edges.clear(); return;
40         }
41         ranges::reverse(path); ranges::reverse(path_edges);
42     }
43     int solve() {
44         int s = -1, odd = 0, src = 0, dst = 0;
45         for (int u = 1; u <= n; u++) {
46             if (!dir && (deg[u] & 1)) odd++, s = u;
47             if (dir && deg[u] == 1) s = u, src++;
48             if (dir && deg[u] == -1) dst++;
49             if (dir && abs(deg[u]) > 1) return -1;
50         }
51         if (!dir && odd != 0 && odd != 2) return -1;
52         if (dir && !((src == 0 && dst == 0) || (src == 1 && dst == 1))) return -1;
53         if (s == -1) for (int u = 1; u <= n; u++)
54             if (!G[u].empty()) { s = u; break; }
55         if (s == -1) s = 1;
56         walk(s);
57         return path.empty() ? -1 :
58             path.front() == path.back() ? 2 : 1;
59     }
60 };

```

6.6 Vertex BCC (Round Square Tree)

21bcde

```

1 // Author: Ian, https://judge.yosupo.jp/submission/399308
2 // Vertex BCC (Round Square Tree) 0-based; Edge ID 0-based
3 // 1. BCC bcc(n); // n = #(vertices)
4 // 2. bcc.add_edge(u, v);

```

```

5// 3. bcc.build();
6// => bcc[id]: vertices in bcc `id` (square node n+id in T)
7// => T[id]: tree adjacency; square nodes are n..n+ncnt-1
8// => is_cut(x): whether x is a cut vertex
9// => bcc_id(u, v): square node containing tree-edge (u, v)
10 struct BCC {
11     int n, m, t, ncnt;
12     vector<vector<pii>> G;
13     vector<vector<int>> T, bcc;
14     vector<int> dep, low, pa2, dep2, s;
15     void add_edge(int u, int v) {
16         G[u].eb(v, m), G[v].eb(u, m++);
17     }
18     void dfs(int x, int f) {
19         if (~dep[x]) return;
20         dep[x] = low[x] = t++;
21         s.push_back(x);
22         for (auto [y, e]: G[x]) if (e != f) {
23             if (dep[y] == -1) {
24                 dfs(y, e), low[x] = min(low[x], low[y]);
25                 if (low[y] >= dep[x]) {
26                     int id = n + ncnt++; p;
27                     bcc.resize(bcc.size()+1);
28                     do {
29                         p = s.back(), s.pop_back();
30                         T[id].push_back(p), T[p].push_back(id);
31                         bcc.back().push_back(p);
32                     } while (p != y);
33                     T[id].push_back(x), T[x].push_back(id);
34                     bcc.back().push_back(x);
35                 } else low[x] = min(low[x], dep[y]);
36             }
37         }
38         void dfs2(int x, int p) {
39             dep2[x] = ~p ? dep2[p] + 1 : 0, pa2[x] = p;
40             for (auto y: T[x]) if (y != p) dfs2(y, x);
41         }
42         bool is_cut(int x) { return (int)T[x].size() != 1; }
43         int bcc_id(int u, int v) {
44             return pa2[dep2[u] < dep2[v] ? v : u] - n;
45         }
46         void build() {
47             for (int i = 0; i < n; i++) if (dep[i] == -1) {
48                 if (G[i].empty()) { // isolated vertex: singleton bcc
49                     dep[i] = low[i] = t++;
50                     int id = n + ncnt++;
51                     bcc.push_back({i});
52                     T[id].push_back(i), T[i].push_back(id);
53                 } else dfs(i, -1);
54             }
55             dfs2(i, -1);
56         }
57         BCC(int n): n(n), m(0), t(0), ncnt(0), G(n), T(2*n),
58         dep(n, -1), low(n), pa2(2*n), dep2(2*n) {}
59 };

```

6.7 Edge BCC

e56b23

```

1// Author: Ian, https://judge.yosupo.jp/submission/399295
2// Edge BCC, 0-based; Edge ID 0-based
3// 1. EBCC ebcc(n); // n = #vertices
4// 2. ebcc.add_edge(u, v);
5// 3. ebcc.build();
6// => bcc[i]: each edge bcc
7// => bccn[x]: in which bcc is x
8// => isbr[e]: whether edge e is a bridge
9 struct EBCC {
10     int n, m, t, ncnt;
11     vector<vector<pii>> G;
12     vector<vector<int>> bcc;
13     vector<bool> isbr;
14     vector<int> dep, low, bccn, s;
15     EBCC(int n): n(n), m(0), t(0), ncnt(0), G(n),
16     dep(n, -1), low(n), bccn(n) {}
17     void add_edge(int u, int v) {
18         G[u].eb(v, m), G[v].eb(u, m++);
19     }
20     void dfs(int x, int f) {
21         if (~dep[x]) return;
22         dep[x] = low[x] = t++;
23         s.push_back(x);
24         for (auto [y, e]: G[x]) if (e != f) {
25             if (dep[y] == -1) {
26                 dfs(y, e), low[x] = min(low[x], low[y]);
27             } else
28                 low[x] = min(low[x], dep[y]);
29         }
30         if (dep[x] == low[x]) {
31             if (~f) isbr[f] = true;
32             bcc.resize(bcc.size()+1);
33             int p; do {
34                 bccn[p = s.back()] = ncnt;
35                 s.pop_back();
36                 bcc.back().push_back(p);
37             } while (p != x); ncnt++;
38         }
39     }
40 }

```

```

38 void build() {
39     isbr.assign(m, false);
40     for (int i=0; i<n; i++) dfs(i, -1);
41 }

```

6.8 Kth Shortest Path

15319c

```

1// time: O(|E| lg |E|+|V| lg |V|+K)
2// memory: O(|E| lg |E|+|V|)
3 struct KSP { // 1-base
4     struct nd {
5         int u, v; ll d;
6         nd(int ui=0, int vi=0, ll di=INF) { u=ui; v=vi; d=di; }
7     };
8     struct heap { nd* edge; int dep; heap* chd[4]; };
9     static int cmp(heap* a, heap* b) {
10         return a->edge->d > b->edge->d;
11     }
12     struct node {
13         int v; ll d; heap* H; nd* E;
14         node() {}
15         node(ll _d, int _v, nd* _E) { d=_d; v=_v; E=_E; }
16         node(heap* _H, ll _d) { H=_H; d=_d; }
17         friend bool operator<(node a, node b) {
18             return a.d > b.d;
19         }
20     };
21     int n, k, s, t, dst[N]; nd *nxt[N];
22     vector<nd*> g[N], rg[N]; heap *nullNd, *head[N];
23     void init(int _n, int _k, int _s, int _t) {
24         n=_n; k=_k; s=_s; t=_t;
25         for (int i=1; i<=n; i++) {
26             g[i].clear(); rg[i].clear();
27             nxt[i]=NULL; head[i]=NULL; dst[i]=-1;
28         }
29     }
30     void addEdge(int ui, int vi, ll di) {
31         nd* e=new nd(ui, vi, di);
32         g[ui].push_back(e); rg[vi].push_back(e);
33     }
34     queue<int> dfsQ;
35     void dijkstra() {
36         while (dfsQ.size()) dfsQ.pop();
37         priority_queue<node> Q; Q.push(node(0, t, NULL));
38         while (!Q.empty()) {
39             node p=Q.top(); Q.pop(); if (dst[p.v] != -1) continue;
40             dst[p.v]=p.d; nxt[p.v]=p.E; dfsQ.push(p.v);
41             for (auto e: rg[p.v]) Q.push(node(p.d+e->d, e->u, e));
42         }
43     }
44     heap* merge(heap* curNd, heap* newNd) {
45         if (curNd==nullNd) return newNd;
46         heap* root=new heap; memcpy(root, curNd, sizeof(heap));
47         if (newNd->edge->d < curNd->edge->d) {
48             root->edge=newNd->edge;
49             root->chd[2]=newNd->chd[2];
50             root->chd[3]=newNd->chd[3];
51             newNd->edge=curNd->edge;
52             newNd->chd[2]=curNd->chd[2];
53             newNd->chd[3]=curNd->chd[3];
54         }
55         if (root->chd[0]->dep < root->chd[1]->dep)
56             root->chd[0]=merge(root->chd[0], newNd);
57         else root->chd[1]=merge(root->chd[1], newNd);
58         root->dep=max(root->chd[0]->dep,
59                     root->chd[1]->dep)+1;
60         return root;
61     }
62     vector<heap*> V;
63     void build() {
64         nullNd=new heap; nullNd->dep=0; nullNd->edge=new nd;
65         fill(nullNd->chd, nullNd->chd+4, nullNd);
66         while (not dfsQ.empty()) {
67             int u=dfsQ.front(); dfsQ.pop();
68             if (!nxt[u]) head[u]=nullNd;
69             else head[u]=head[nxt[u]->v];
70             V.clear();
71             for (auto& e: g[u]) {
72                 int v=e->v;
73                 if (dst[v] == -1) continue;
74                 e->d+=dst[v]-dst[u];
75                 if (nxt[u] != e) {
76                     heap* p=new heap; fill(p->chd, p->chd+4, nullNd);
77                     p->dep=1; p->edge=e; V.push_back(p);
78                 }
79             }
80         }
81         if (V.empty()) continue;
82         make_heap(V.begin(), V.end(), cmp);
83         #define L(X) ((X<<1)+1)
84         #define R(X) ((X<<1)+2)
85         for (size_t i=0; i<V.size(); i++) {
86             if (L(i)<V.size()) V[i]->chd[2]=V[L(i)];
87             else V[i]->chd[2]=nullNd;
88             if (R(i)<V.size()) V[i]->chd[3]=V[R(i)];
89         }
90     }

```

```

84     else V[i] -> chd[3] = nullNd;
85 }
86 head[u] = merge(head[u], V.front());
87 } }
88 vector<ll> ans;
89 void first_K() {
90     ans.clear(); priority_queue<node> Q;
91     if (dst[s] == -1) return;
92     ans.push_back(dst[s]);
93     if (head[s] != nullNd)
94         Q.push(node(head[s], dst[s] + head[s] -> edge -> d));
95     for (int _ = 1; < k and not Q.empty(); _++) {
96         node p = Q.top(); Q.pop(); ans.push_back(p.d);
97         if (head[p.H -> edge -> v] != nullNd) {
98             q.H = head[p.H -> edge -> v]; q.d = p.d + q.H -> edge -> d;
99             Q.push(q);
100         }
101         for (int i = 0; i < 4; i++)
102             if (p.H -> chd[i] != nullNd) {
103                 q.H = p.H -> chd[i];
104                 q.d = p.d + p.H -> edge -> d + p.H -> chd[i] -> edge -> d;
105                 Q.push(q);
106             } } }
107 void solve() { // ans[i] stores the i-th shortest path
108     dijkstra(); build();
109     first_K(); // ans.size() might less than k
110 }
111 } solver;

```

6.9 SCC - Tarjan

56df66

```

1 // Author: Ian, https://judge.yosupo.jp/submission/399291
2 // Tarjan SCC, 0-based
3 // 1. SCC scc(n); // n = #(vertices)
4 // 2. Fill in adj list G
5 // 3. scc.build()
6 // => scc[i]: each scc
7 // => sccn[x]: in which scc is x
8 struct SCC {
9     const int inf = 1e9+5;
10    int n, t, ncnt;
11    vector<vector<int>> G, scc;
12    vector<bool> ins;
13    vector<int> sccn, dfn, low, s;
14    SCC(int n): n(n), t(0), ncnt(0), G(n),
15        ins(n, false), sccn(n, dfn(n, -1), low(n, inf) {}
16    void dfs(int x) {
17        if (~dfn[x]) return;
18        dfn[x] = low[x] = t++;
19        s.push_back(x), ins[x] = true;
20        for (auto i: G[x])
21            if (dfs(i), ins[i])
22                low[x] = min(low[x], low[i]);
23        if (dfn[x] == low[x]) {
24            scc.resize(scc.size()+1);
25            int p; do {
26                ins[p = s.back()] = false;
27                s.pop_back(); sccn[p] = ncnt;
28                scc.back().push_back(p);
29            } while (p != x); ncnt++;
30        }
31    }
32    void build() { for (int i=0; i<n; i++) dfs(i); }
33 };

```

6.10 2SAT

8d59f5

```

1 // Author: Ian, CRYPTOGRAPHER
2 struct TwoSAT: SCC {
3     TwoSAT(int n): SCC(2*n) {}
4     void add_disjunction(int a, int na, int b, int nb) {
5         a = 2*a^na, b = 2*b^nb;
6         G[a^1].push_back(b);
7         G[b^1].push_back(a);
8     }
9     vector<int> solve() {
10        build(); vector<int> assignment(n/2, 0);
11        for (int i=0; i<n/2; i++) {
12            if (sccn[2*i] == sccn[2*i^1]) return {};
13            assignment[i] = sccn[2*i] > sccn[2*i^1];
14        } return assignment;
15    };
16 // a -> b: (a, 0, b, 1) not both a, b: (a, 0, b, 0)
17 // a and b: (a, 1, a, 1), (b, 1, b, 1)
18 // a or b: (a, 1, b, 1) a xor b: (a, 1, b, 1), (a, 0, b, 0)
19 // a == b: (a, 0, b, 1), (a, 1, b, 0)
20 // force a = v: (a, v, a, v)
21 // solve(): assignment[i] = value of var i, {} if invalid

```

7 Tree

7.1 Tree Isomorphism (Rooted Trees)

a615bc

```

1 // Author: Gino
2 // Checks if 2 rooted trees are isomorphic
3 // Time: O(V log V)
4 // vector<vector<int>> G1, G2;
5 // int root_1, root_2;
6 map<vector<int>, int> dict;
7 int encode(const auto& G, int u, int pa = -1) {
8     vector<int> codes;
9     for (auto& v : G[u])
10         if (v != pa)
11             codes.emplace_back(encode(G, v, u));
12     ranges::sort(codes);
13     auto [it, _] = dict.try_emplace(codes, dict.size());
14     return it -> second;
15 }
16 bool isomorphic() {
17     dict.clear(); dict[{}] = 0;
18     return encode(G1, root_1) == encode(G2, root_2);
19 }

```

7.2 Tree Isomorphism (Unrooted Trees)

Find the centroid(s) of T_1, T_2 .Case 1: T_1, T_2 have different number of centroids $\rightarrow$ NOCase 2: T_1 has centroid c_1, T_2 has centroid c_2 $\rightarrow$ rooted_isomorphic(c_1, c_2)Case 3: T_1 has centroids c_1, c'_1, T_2 has centroids c_2, c'_2 $\rightarrow$ rooted_isomorphic(c_1, c_2) || rooted_isomorphic(c'_1, c'_2)

7.3 Heavy Light Decomposition

16d094

```

1 // Author: Ian, https://judge.yosupo.jp/submission/399317
2 void segbuild(vector<int>&v);
3 void segmodify(int p, int k);
4 int segquery(int ql, int qr);
5 // Insert [ql, qr] segment tree here
6 template<class T=int> struct HLD {
7     int n, cnt;
8     vector<int> d, f, sz, son, top, dfn;
9     HLD(int n): n(n), cnt(0), d(n, 0), f(n, 0), sz(n, 1),
10         son(n, -1), top(n, 0), dfn(n, -1) {}
11     void dfs1(int x, int p) {
12         for (auto i: e[x]) if (i != p) {
13             d[i] = d[x]+1, f[i] = x;
14             dfs1(i, x), sz[x] += sz[i];
15             if (son[x] == -1 || sz[son[x]] < sz[i])
16                 son[x] = i;
17         }
18     }
19     void dfs2(int x, int t) {
20         dfn[x] = cnt++, top[x] = t;
21         if (son[x] == -1) return;
22         dfs2(son[x], t);
23         for (auto i: e[x])
24             if (!~dfn[i]) dfs2(i, i);
25     }
26     void build(const vector<T>&v) {
27         dfs1(0, 0); dfs2(0, 0);
28         vector<T> dfnv(v.size());
29         for (int i=0; i<n; i++)
30             dfnv[dfn[i]] = v[i];
31         segbuild(dfnv);
32     }
33     void modify(int p, T v) { segmodify(dfn[p], v); }
34     T query(int a, int b) {
35         auto aggr = [](int x, int y) { return max(x, y); };
36         T ret = 0;
37         while (top[a] != top[b]) {
38             if (d[top[a]] > d[top[b]]) swap(a, b);
39             ret = aggr(ret, segquery(dfn[top[b]], dfn[b]+1));
40             b = f[top[b]];
41         }
42         if (dfn[a] > dfn[b]) swap(a, b);
43         return aggr(ret, segquery(dfn[a], dfn[b]+1));
44     };
45 };

```

7.4 Virtual Tree

5a0bd4

```

1 // Author: std_abs
2 // need lca, in, out
3 vector<pii> virtual_tree(vector<int>&v) {
4     auto cmp = [&](int x, int y) { return in[x] < in[y]; };
5     sort(all(v), cmp);
6     for (int i = 1; i < sz(v); ++i)
7         v.pb(lca(v[i-1], v[i]));
8     sort(all(v), cmp);
9     v.resize(unique(all(v)) - v.begin());
10    vector<int> stk(1, v[0]);
11    vector<pii> res;
12    for (int i = 1; i < sz(v); ++i) {
13        int x = v[i];

```

```

14 while (out[stk.back()] < out[x]) stk.pop_back();
15 res.emplace_back(stk.back(), x), stk.pb(x);
16 }
17 return res;
18 }

```

8 Matching

8.1 Bipartite Matching

e0a92e

```

1 // Author: Gino
2 // Function: Max Bipartite Matching in  $O(V \sqrt{E})$ 
3 //> hk.init(nx, ny) -> hk.add(x, y (+nx))
4 //> hk.max_matching(): the matching plan stores in mx, my
5 //> hk.min_vertex_cover(): vertex cover plan stores in vcover
6 // (!) vertices are 0-based: X = [0, nx), Y = [ny, nx+ny)
7 #define pb emplace_back
8 struct HopcroftKarp {
9     int n, nx, ny; vector<vector<int>> G; vector<int> mx, my;
10     HopcroftKarp(int nx, int ny): nx(nx), ny(ny), n(nx + ny) {
11         G.assign(n, vector<int>()); }
12     void add(int x, int y) { G[x].pb(y); G[y].pb(x); }
13     int max_matching() {
14         vector<int> dis, vis;
15         mx.assign(n, -1); my.assign(n, -1);
16         function<bool(int)> dfs = [&](int x) {
17             vis[x] = 1;
18             for (int y : G[x]) { int p = my[y];
19                 if (p == -1 ||
20                     (dis[p] == dis[x] + 1 && !vis[p] && dfs(p)))
21                     return mx[x] = y, my[y] = x, true;
22             }
23             return false;
24         };
25         while (true) {
26             dis.assign(n, -1);
27             queue<int> q;
28             for (int x = 0; x < nx; x++)
29                 if (mx[x] == -1) dis[x] = 0, q.push(x);
30             while (!q.empty()) {
31                 int x = q.front(); q.pop();
32                 for (int y : G[x])
33                     if (my[y] != -1 && dis[my[y]] == -1)
34                         dis[my[y]] = dis[x] + 1, q.push(my[y]);
35             }
36             vis.assign(n, 0);
37             bool found = false;
38             for (int x = 0; x < nx; x++)
39                 if (mx[x] == -1 && dfs(x)) found = true;
40             if (!found) break;
41         }
42         int ans = 0;
43         for (int x = 0; x < nx; x++) if (mx[x] != -1) ans++;
44         return ans;
45     }
46     vector<int> vcover;
47     int min_vertex_cover() {
48         int ans = max_matching(); vector<int> vis(n, 0);
49         function<void(int)> dfs = [&](int x) {
50             vis[x] = true;
51             for (int y : G[x]) {
52                 if (y == mx[x] || my[y] == -1 || vis[y]) continue;
53                 vis[y] = true;
54                 dfs(my[y]);
55             }
56             for (int x = 0; x < nx; x++) if (mx[x] == -1) dfs(x);
57             vcover.clear();
58             for (int x=0; x < nx; x++) if (!vis[x]) vcover.pb(x);
59             for (int y=nx; y < nx+ny; y++) if (vis[y]) vcover.pb(y);
60             return ans;
61         };

```

8.2 Bipartite Weighted Matching

5b976c

```

1 // Author: ckiseki, n = #(left vertices) = #(right vertices)
2 // left, right vertices labeled 1 ~ n separately
3 // 1. build 1-based matrix G of size (n + 1) * (n + 1)
4 // G[u][v] := weight between (left u, right v)
5 // <!-- if not need perfect matching
6 // ==> set weights of all negative edges to 0
7 // 2. construct (solve at same time): KM km(n, G);
8 // ==> km.ans (max perfect weight sum)
9 // ==> km.fl[u] (left u -> right v)
10 // ==> km.fr[v] (right v -> left u)
11 // Time:  $O(V^3)$ , Space:  $O(V^2)$ , Test:  $V \leq 500$ , 243ms
12 struct KM { // maximize, test @ UOJ 80
13     int n, l, r; ll ans; // fl and fr are the match
14     vector<ll> hl, hr; vector<int> fl, fr, pre, q;
15     void bfs(const auto &w, int s) {
16         vector<int> vl(n + 1), vr(n + 1);
17         vector<ll> slk(n + 1, LINF);
18         l = r = 0; vr[q[r++]] = s = true;

```

```

19 auto check = [&](int x) -> bool {
20     if (vl[x] || slk[x] > 0) return true;
21     vl[x] = true; slk[x] = LINF;
22     if (fl[x] != -1) return (vr[q[r++]] = fl[x]) = true;
23     while (x != -1) swap(x, fr[fl[x] = pre[x]]);
24     return false;
25 };
26 while (true) {
27     while (l < r)
28         for (int x = 1, y = q[l++]; x <= n; ++x) if (!vl[x])
29             if (ll val = hl[x] + hr[y] - w[x][y]; val < slk[x]) {
30                 slk[x] = val;
31                 if (pre[x] = y, !check(x)) return;
32             }
33     ll d = LINF;
34     for (int x = 1; x <= n; ++x) d = min(d, slk[x]);
35     for (int x = 1; x <= n; ++x)
36         vl[x] ? hl[x] += d : slk[x] -= d;
37     for (int x = 1; x <= n; ++x) if (vr[x]) hr[x] -= d;
38     for (int x = 1; x <= n; ++x) if (!check(x)) return;
39 }
40 KM(int n_, const auto &w) : n(n_), ans(0),
41     hl(n+1, hr(n+1), fl(n+1, -1), fr(fl), pre(n+1), q(n+1) {
42     for (int i = 1; i <= n; ++i) {
43         hl[i] = -LINF;
44         for (int j=1; j<=n; ++j) hl[i]=max(hl[i], (ll)w[i][j]);
45     }
46     for (int i = 1; i <= n; ++i) bfs(w, i);
47     for (int i = 1; i <= n; ++i) ans += w[i][fl[i]];
48 }
49 };

```

8.3 General Matching

6e783c

```

1 // Author: ckiseki
2 // 0. build 1-based graph vector<vector<int>> G(n + 1);
3 // 1. construct (solve at same time):
4 // GeneralMatching M(G, n); ==> M.ans
5 // status: M.match[x] (== -1 if not matched, 1 <= x <= n)
6 // Time:  $O(V^3)$ , Space:  $O(V + E)$ , Test:  $V \leq 500$ , 11ms
7 struct GeneralMatching {
8     queue<int> q; int ans, n;
9     vector<int> fa, s, v, pre, match;
10     int Find(int u) {
11         return u == fa[u] ? u : fa[u] = Find(fa[u]); }
12     int LCA(int x, int y) {
13         static int tk = 0; tk++; x = Find(x); y = Find(y);
14         for (; swap(x, y)) if (x != 0) {
15             if (v[x] == tk) return x;
16             v[x] = tk;
17             x = Find(pre[match[x]]);
18         }
19     void Blossom(int x, int y, int l) {
20         for (; Find(x) != l; x = pre[y]) {
21             pre[x] = y, y = match[x];
22             if (s[y] == 1) q.push(y), s[y] = 0;
23             for (int z : {x, y}) if (fa[z] == z) fa[z] = l;
24         }
25     bool Bfs(auto &g, int r) {
26         iota(all(fa), 0); ranges::fill(s, -1);
27         q = queue<int>(); q.push(r); s[r] = 0;
28         for (; !q.empty(); q.pop()) {
29             for (int x = q.front(); int u : g[x])
30                 if (s[u] == -1) {
31                     if (pre[u] = x, s[u] = 1, match[u] == 0) {
32                         for (int a = u, b = x, last;
33                             b != 0; a = last, b = pre[a])
34                             last = match[b], match[b] = a, match[a] = b;
35                         return true;
36                     }
37                     q.push(match[u]); s[match[u]] = 0;
38                 }
39             else if (!s[u] && Find(u) != Find(x)) {
40                 int l = LCA(u, x);
41                 Blossom(x, u, l); Blossom(u, x, l);
42             }
43         }
44         return false;
45     }
46     GeneralMatching(auto &g, int n_) : ans(0), n(n_),
47         fa(n+1), s(n+1), v(n+1), pre(n+1, 0), match(n+1, 0) {
48         for (int x = 1; x <= n; ++x)
49             if (match[x] == 0) ans += Bfs(g, x);
50         for (int x = 1; x <= n; ++x)
51             if (match[x] == 0) match[x] = -1;
52     };

```

9 Flow

9.1 Flow Methods

9516b6

```

1 // Author: CRyptographeR (some modified by Gino)
2 Maximize  $c^T x$  subject to  $Ax \leq b, x \geq 0$ ;

```

```

3 with the corresponding symmetric dual problem,
4 Minimize  $b^T y$  subject to  $A^T y \geq c, y \geq 0$ .
5 Maximize  $c^T x$  subject to  $Ax \leq b$ ;
6 with the corresponding asymmetric dual problem,
7 Minimize  $b^T y$  subject to  $A^T y = c, y \geq 0$ .
8 Maximize  $\sum x$  subject to  $x_i + x_j \leq A_{ij}, x \geq 0$ ;
9 => Maximize  $\sum x$  subject to  $x_i + x_j \leq A_{ij}$ ;
10 => Minimize  $A^T y = \sum A_{ij} y_{ij}$  subject to for all  $v$ ,
     $\sum_{i=v \text{ or } j=v} y_{ij} = 1, y_{ij} \geq 0$ 
11 => possible optimal solution:  $y_{ij} = \{0, 0.5, 1\}$ 
12 =>  $y' = 2y$ :  $\sum_{i=v \text{ or } j=v} y'_{ij} = 2, y'_{ij} = \{0, 1, 2\}$ 
13 => Minimum Bipartite perfect matching/2 ( $V_1=X, V_2=Y, E=A$ )
14 General Graph:
15  $|Max Ind. Set| + |Min Vertex Cover| = |V|$ 
16  $|Max Ind. Edge Set| + |Min Edge Cover| = |V|$ 
17 Bipartite Graph:
18  $|Max Ind. Set| = |Min Edge Cover|$ 
19  $|Max Ind. Edge Set| = |Min Vertex Cover|$ 
20 To reconstruct the minimum vertex cover, dfs from each
21 unmatched vertex on the left side and with unused edges
22 only. Equivalently, dfs from source with unused edges
23 only and without visiting sink. Then, a vertex is
24 chosen iff. it is on the left side and without visited
25 or on the right side and visited through dfs.
26 Minimum Weighted Bipartite Edge Cover:
27 Construct new bipartite graph with  $n+m$  vertices on each
    side:
28 for each vertex  $u$ , duplicate a vertex  $u'$  on the other side
29 for each edge  $(u,v,w)$ , add edges  $(u,v,w)$  and  $(v',u',w)$ 
30 for each vertex  $u$ , add edge  $(u,u',2w)$  where  $w$  is min edge
    connects to  $u$ 
31 then the answer is the minimum perfect matching of the new
    graph (KM)
32 Maximum density subgraph ( $\sum W_e + \sum W_v$ ) /  $|V|$ 
33 Binary search on answer:
34 For a fixed  $D$ , construct a Max flow model as follow:
35 Let  $S$  be Sum of all weight (or inf)
36 1. from source to each node with cap =  $S$ 
37 2. For each  $(u,v,w)$  in  $E$ ,  $(u \rightarrow v, \text{cap}=w), (v \rightarrow u, \text{cap}=w)$ 
38 3. For each node  $v$ , from  $v$  to sink with cap =  $S + 2 * D - \text{deg}[v]$ 
    where  $\text{deg}[v] = \sum \text{weight of edge associated with } v$ 
39 where  $\text{deg}[v] = \sum \text{weight of edge associated with } v$ 
40 If  $\text{maxflow} < S * |V|$ ,  $D$  is an answer.
41 Requiring subgraph: all vertex can be reached from source
    with
42 edge whose cap  $> 0$ .
43 Maximum closed subgraph
44 1. connect source with positive weighted
    vertex(capacity=weight)
45 2. connect sink with negative weighted vertex(capacity=-
    weight)
46 3. make capacity of the original edges = inf
47 4. ans = sum(positive weighted vertex weight) - (max flow)
48 (Node-disjoint) Min DAG Path Cover (用最少路徑覆蓋所有點)
49 Node disjoint: 拆出來的路徑不能共用同一個點
50 將一個點  $u$  裂成  $u_+$  和  $u_-$ , 代表進入和出去
51 對於一條邊  $(u, v)$  建邊  $u_- \Rightarrow v_+$ 
52 1.  $+$ 點們和  $-$ 點們形成一張二分圖
53 2. 最差的答案是  $n$ , 代表每個點自己一個點就是一條路徑
54 3. 只要一組  $(u_-, v_+)$  匹配成功那對應到的答案恰好會  $-1$ 
55 >>> ans =  $n - \text{這張二分圖的最大匹配}$ 
56 General DAG Path Cover
57 跟 Node-disjoint 版本差在點可以被很多條路共用
58 建邊方式 Node-disjoint 差別在條件比較鬆
59 Node-disjoint:  $u_- \Rightarrow v_+$  只能在  $(u, v)$  有邊時建
60 General:  $u_- \Rightarrow v_+$  在  $u$  能走到  $v$  的時候就建
61 Dilworth Theorem
62 反鏈: 一些節點的集合, 滿足這些節點互相無法抵達
63 最大反鏈 = 最小 General DAG Path Cover
64 Min Cut reconstruction (after running max flow  $s \rightarrow t$ ):
65 From  $s$ , BFS/DFS through residual edges with remaining
66 capacity  $> 0$ , marking reached vertices as visited.
67 The cut set is every original edge  $(u, v)$  with  $u$  visited
68 and  $v$  not visited; its capacity sum equals the max flow.
69 Bipartite Matching reconstruction (after running max flow
70 on source  $\rightarrow X \rightarrow Y \rightarrow \text{sink model}$ ):
71 For each edge  $(x, y)$  between the  $X$ -side and  $Y$ -side, it is
72 part of the matching iff. its residual capacity is 0
73 (i.e. it is saturated).
74 Max/Min Flow with Lower Bound (Circulation Problem):
75 1. Construct super source  $S$  and super sink  $T$ .
76 2. For each edge  $(x, y, l, u)$ , connect  $x \rightarrow y$  with capacity
     $u - l$ .
77 3. For each vertex  $v$ , let  $\text{in}(v) = (\text{sum of incoming lower}$ 
    bounds)
78  $- (\text{sum of outgoing lower bounds})$ .
79 4. If  $\text{in}(v) > 0$ , connect  $S \rightarrow v$  with capacity  $\text{in}(v)$ ;
80 otherwise connect  $v \rightarrow T$  with capacity  $-\text{in}(v)$ .

```

```

81 To maximize: connect  $t \rightarrow s$  with capacity inf (skip this
    edge
82 for a pure circulation problem), let  $f = \text{maxflow}(S, T)$ .
83 If
84  $f \neq \text{sum of in}(v)$  over all  $\text{in}(v) > 0$ , no solution exists.
85 Otherwise  $\text{maxflow}(s, t)$  (found after adding  $t \rightarrow s$ ) is
    the answer.
86 To minimize: let  $f = \text{maxflow}(S, T)$  (without any  $s \rightarrow t$  edge
    yet).
87 Then connect  $t \rightarrow s$  with capacity inf and let  $f'$  be the
    extra
88 flow pushed from  $S$  to  $T$ . If  $f + f' \neq \text{sum of in}(v)$  over
    all
89  $\text{in}(v) > 0$ , no solution exists. Otherwise  $f'$  is the
    answer.
90 5. The flow on each original edge  $e$  is  $l_e + f_e$ , where  $f_e$ 
    is
    e's flow in the constructed graph.

```

9.2 Dinic (Flow Decomposition)

8d8937

```

1 // Function: Max Flow + Flow Decomposition,  $O(V^2 E)$ 
2 // init  $\rightarrow$  addEdge; vertices 0-based
3 // >>> flow() := return max flow
4 // >>> flow_decomposition() := return max flow + store
    decomposition in flow.D
5 struct Dinic{
6     static const int MXN=10000;
7     struct Edge{ int v,c,r,C; bool fw; };
8     int n,s,t,level[MXN]; vector<Edge> G[MXN];
9     void init(int _n,int _s,int _t){
10         n=_n; s=_s; t=_t;
11         for (int i=0; i<n; i++) G[i].clear();
12     void addEdge(int u,int v,int c){
13         G[u].push_back({v,c,(int)G[v].size(),c,true});
14         G[v].push_back({u,0,(int)G[u].size()-1,0,false});
15     bool BFS(){
16         for (int i=0; i<n; i++) level[i]=-1;
17         queue<int> que; que.push(s); level[s]=0;
18         while(!que.empty()){
19             int u=que.front(); que.pop();
20             for (auto &it:G[u]){
21                 if(it.c>0&&level[it.v]==-1){
22                     level[it.v]=level[u]+1; que.push(it.v);
23                 }
24             }
25         }
26         return level[t]!=-1;
27     int DFS(int u,int nf){
28         if(u==t) return nf;
29         int res=0;
30         for (auto &it:G[u]){
31             if(it.c>0&&level[it.v]==level[u]+1){
32                 int tf=DFS(it.v,min(nf,it.c));
33                 res+=tf; nf-=tf; it.c-=tf;
34                 G[it.v][it.r].c+=tf;
35                 if(nf==0) return res;
36             }
37         }
38         if(!res) level[u]=-1;
39         return res;
40     int flow(int res=0){
41         while(BFS()) res+=DFS(s,2147483647);
42         return res;
43     } // reset: do nothing
44     vector<pair<int, vector<int>>> D; // (flow amount, [path
    p1 ... pk])
45     int flow_decomposition(){
46         int mxflow = flow();
47         vector<vector<Edge>> fG(n); // graph with forward edges
48         for (int u = 0; u < n; u++) {
49             for (auto &e : G[u]) {
50                 if (e.fw && e.c - e.c > 0)
51                     fG[u].push_back({e.v, e.C - e.c, e.r, e.C, e.fw});
52             }
53         }
54         vector<int> vis(n, 0);
55         function<int(int, int)> dfs = [&](int u, int cur) {
56             if (u == t) {
57                 D.back().second.push_back(u);
58                 return cur;
59             }
60             vis[u] = 1;
61             for (auto &e : fG[u]) {
62                 if (e.c > 0 && !vis[e.v]) {
63                     int ans = dfs(e.v, min(cur, e.c));
64                     if (ans > 0) {
65                         e.c -= ans;
66                         D.back().second.push_back(u);
67                         return ans;
68                     }
69                 }
70             }
71             return 0;
72         };
73         D.clear();
74         int quota = mxflow;
75         while (quota > 0) {
76             D.emplace_back(0, vector<int>());

```

```

69     fill(vis.begin(), vis.end(), 0);
70     int f = dfs(s, 2147483647);
71     if (f == 0) break;
72     reverse(D.back().second.begin(),
73            D.back().second.end());
74     D.back().first = f, quota -= f;
75 }
76 return mxflow; }
77 }flow;

```

9.3 ISAP

647ff0

```

1// Author: CryptoGRapheR
2// 1-based: vertices are numbered 1 ~ n
3// 1. flow.init(n, s, t);
4// n = #vertices, s, t = source, sink
5// 2. flow.addEdge(u, v, c); // u, v in [1, n]
6// 3. call: int ans = flow.flow();
7// => ans = max flow value from s to t
8// Time: O(V^2 * E) worst case, usually much faster in
   practice
9static const int MAXV=50010;
10static const int INF =1000000;
11struct Maxflow{
12    struct Edge{
13        int v,c,r;
14        Edge(int _v,int _c,int _r):v(_v),c(_c),r(_r){}
15    };
16    int s,t; vector<Edge> G[MAXV];
17    int iter[MAXV],d[MAXV],gap[MAXV],tot;
18    void init(int n,int _s,int _t){
19        tot=n,s=_s,t=_t;
20        for(int i=1;i<=tot;i++){
21            G[i].clear(); iter[i]=d[i]=gap[i]=0;
22        }
23    }
24    void addEdge(int u,int v,int c){
25        G[u].push_back(Edge(v,c,SZ(G[v])));
26        G[v].push_back(Edge(u,0,SZ(G[u])-1));
27    }
28    int DFS(int p,int flow){
29        if(p==t) return flow;
30        for(int &i=iter[p];i<SZ(G[p]);i++){
31            Edge &e=G[p][i];
32            if(e.c>0&&d[p]==d[e.v]+1){
33                int f=DFS(e.v,min(flow,e.c));
34                if(f){ e.c-=f; G[e.v][e.r].c+=f; return f; }
35            }
36        }
37        if(--gap[d[p]]==0) d[s]=tot;
38        else{ d[p]++; iter[p]=0; ++gap[d[p]]; }
39        return 0;
40    }
41    int flow(){
42        int res=0;
43        for(res=0,gap[0]=tot;d[s]<tot;res+=DFS(s,INF));
44        return res;
45    }
46    void reset(){
47        for(int i=1;i<=tot;i++) iter[i]=d[i]=gap[i]=0;
48    }
49 }flow;

```

9.4 Bounded Max Flow

aaf309

```

1// Author: CryptoGRapheR
2// Max flow with lower/upper bound on edges (source-sink
   version)
3// <!-- 1-based: original vertices are numbered 1 ~ n.
4// Super source, sink: n+1, n+2 respectively.
5// <!-- dependency: ISAP.cpp
6// 1. n = #vertices (1 ~ n), m = #edges
7// s, t = original source, sink (both in [1, n])
8// 2. l[i], r[i] := edge i goes from l[i] -> r[i] (l[i],
   r[i] in [1, n])
9// 3. a[i], b[i] := flow on edge i must lie in [a[i], b[i]]
10// 4. int ans = solve(n, m, s, t);
11// => ans == -1 : no feasible flow exists
12// => ans : feasible max flow value
13// <!-- N, M must be large enough for original graph + 2
   super nodes
14// Time: O(V^2 E), Space: O(V + E)
15int in[N], out[N], l[M], r[M], a[M], b[M];
16int solve(int n, int m, int s, int t){
17    flow.init(n+2, n+1, n+2); // super source = n+1, super
   sink = n+2
18    for(int i = 0; i < m; i++){
19        in[r[i]] += a[i]; out[l[i]] += a[i];
20        flow.addEdge(l[i], r[i], b[i] - a[i]);
21        // flow from l[i] to r[i] must lie in [a[i], b[i]]
22    }
23    int nd = 0;

```

```

24    for(int i = 1; i <= n; i++){
25        if(in[i] < out[i]){
26            flow.addEdge(i, flow.t, out[i] - in[i]);
27            nd += out[i] - in[i];
28        }
29        if(out[i] < in[i])
30            flow.addEdge(flow.s, i, in[i] - out[i]);
31    }
32    flow.addEdge(t, s, INF); // original sink -> source
33    if(flow.flow() != nd) return -1; // infeasible
34    int ans = flow.G[s].back().c; // t->s edge's current flow
   = feasible flow s->t
35    flow.G[s].back().c = flow.G[t].back().c = 0;
36    for(size_t i = 0; i < flow.G[flow.s].size(); i++){
37        Maxflow::Edge &e = flow.G[flow.s][i];
38        flow.G[flow.s][i].c = 0; flow.G[e.v][e.r].c = 0;
39    }
40    for(size_t i = 0; i < flow.G[flow.t].size(); i++){
41        Maxflow::Edge &e = flow.G[flow.t][i];
42        flow.G[flow.t][i].c = 0; flow.G[e.v][e.r].c = 0;
43    }
44    flow.addEdge(flow.s, s, INF); flow.addEdge(t, flow.t,
   INF);
45    flow.reset(); // keeps G[] intact, only resets search
   state
46    return ans + flow.flow();
47 }

```

9.5 MCMF

b4675d

```

1// Author: CryptoGRapheR
2// MCMF (supports negative edges without negative cycles)
3// <!-- 1-based: vertices are numbered 1 ~ n.
4// 1. MCMF.init(n); // n = #vertices (1 ~ n)
5// 2. MCMF.add(u, v, cap, cost);
6// 3. auto [max_flow, min_cost] = MCMF.flow(s, t); // s, t
   in [1, n]
7// Time: O(F * E), Space: O(V + E)
8typedef int Tcost;
9const int MAXV = 20010;
10const int INFf = 1000000;
11const Tcost INFc = 1e9;
12struct MCMF {
13    struct Edge{
14        int v, cap;
15        Tcost w;
16        int rev;
17        bool fw;
18        Edge(){}
19        Edge(int t2, int t3, Tcost t4, int t5, bool t6)
   : v(t2), cap(t3), w(t4), rev(t5), fw(t6) {}
20    };
21    int V, s, t;
22    vector<Edge> G[MAXV];
23    void init(int n){
24        V = n;
25        for(int i = 0; i <= V; i++) G[i].clear();
26    }
27    void add(int a, int b, int cap, Tcost w){
28        G[a].push_back(Edge(b, cap, w, (int)G[b].size(), true));
29        G[b].push_back(Edge(a, 0, -w, (int)G[a].size()-1,
   false));
30    }
31    Tcost d[MAXV];
32    int id[MAXV], mom[MAXV];
33    bool inqu[MAXV];
34    queue<int> q;
35    pair<int, Tcost> flow(int _s, int _t){
36        s = _s, t = _t;
37        int mxflow = 0, Tcost mnc = 0;
38        while(1){
39            fill(d, d+V, INFc); // need to use type cast
40            fill(inqu, inqu+V, 0);
41            fill(mom, mom+V, -1);
42            mom[s] = s;
43            d[s] = 0;
44            q.push(s); inqu[s] = 1;
45            while(q.size()){
46                int u = q.front(); q.pop();
47                inqu[u] = 0;
48                for(int i = 0; i < (int) G[u].size(); i++){
49                    Edge &e = G[u][i];
50                    int v = e.v;
51                    if(e.cap > 0 && d[v] > d[u]+e.w){
52                        d[v] = d[u]+e.w;
53                        mom[v] = u;
54                        id[v] = i;
55                        if(!inqu[v]) q.push(v), inqu[v] = 1;
56                    }
57                }
58            }
59        }

```

```

60     if(mom[t] == -1) break ;
61     int df = INFF;
62     for(int u = t; u != s; u = mom[u])
63         df = min(df, G[mom[u]][id[u]].cap);
64     for(int u = t; u != s; u = mom[u]){
65         Edge &e = G[mom[u]][id[u]];
66         e.cap -= df;
67         G[e.v][e.rev].cap += df;
68     }
69     mxf += df;
70     mnc += df*d[t];
71 }
72 return make_pair(mxf, mnc);
73 }
74 };

```

9.6 Push-Relabel

f50218

```

1// Author: Simon Lindholm (kactl)
2// 0-based: vertices are numbered 0 ~ n-1
3// 1. PushRelabel pr(n); // n = #vertices
4// 2. pr.addEdge(u, v, c); // u, v in [0, n-1]
5// 3. ll ans = pr.calc(s, t);
6// => ans = max flow value from s to t
7// To obtain actual flow:
8// for (int u = 0; u < n; u++)
9//     for (auto& e : pr.g[u])
10//         if (e.f > 0) => (u, e.dest, e.f)
11// Time:  $O(V^2 * \sqrt{E})$ , better on dense graph
12 struct PushRelabel {
13     struct Edge { int dest, back; ll f, c; };
14     vector<vector<Edge>> g;
15     vector<ll> ec;
16     vector<Edge*> cur;
17     vector<vi> hs; vi H;
18     PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}
19     void addEdge(int s, int t, ll cap, ll rcap=0) {
20         if (s == t) return;
21         g[s].push_back({t, sz(g[t]), 0, cap});
22         g[t].push_back({s, sz(g[s])-1, 0, rcap});
23     }
24     void addFlow(Edge& e, ll f) {
25         Edge &back = g[e.dest][e.back];
26         if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
27         e.f += f; e.c -= f; ec[e.dest] += f;
28         back.f -= f; back.c += f; ec[back.dest] -= f;
29     }
30     ll calc(int s, int t) {
31         int v = sz(g); H[s] = v; ec[t] = 1;
32         vi co(2*v); co[0] = v-1;
33         rep(i, 0, v) cur[i] = g[i].data();
34         for (Edge& e : g[s]) addFlow(e, e.c);
35         for (int hi = 0; ) {
36             while (hs[hi].empty()) if (!hi--) return -ec[s];
37             int u = hs[hi].back(); hs[hi].pop_back();
38             while (ec[u] > 0) // discharge u
39                 if (cur[u] == g[u].data() + sz(g[u])) {
40                     H[u] = 1e9;
41                     for (Edge& e : g[u]) if (e.c && H[u] >
42                         H[e.dest]+1)
43                         H[u] = H[e.dest]+1, cur[u] = &e;
44                     if (++co[H[u]], !--co[hi] && hi < v)
45                         rep(i, 0, v) if (hi < H[i] && H[i] < v)
46                             --co[H[i]], H[i] = v + 1;
47                     hi = H[u];
48                 } else if (cur[u]->c && H[u] == H[cur[u]->dest]+1)
49                     addFlow(*cur[u], min(ec[u], cur[u]->c));
50                 else ++cur[u];
51             }
52         }
53         bool leftOfMinCut(int a) { return H[a] >= sz(g); }

```

9.7 Gomory-Hu Tree

3777d4

```

1// Author: chilli, Takanori MAEHARA (kactl)
2// <!> Dependency: PushRelabel.cpp
3// Given a list of edges representing an undirected flow
graph,
4// returns edges of the Gomory-Hu tree.
5// maxflow / mincut of (u, v) => min edge from u to v on
Gomory-Hu tree
6// Time:  $O(V) * O(\text{PushRelabel})$ 
7 typedef array<ll, 3> Edge; // (u, v, w)
8 vector<Edge> gomoryHu(int N, vector<Edge> ed) {
9     vector<Edge> tree;
10     vi par(N);
11     rep(i, 1, N) {
12         PushRelabel D(N); // Dinic also works
13         for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
14         tree.push_back({i, par[i], D.calc(i, par[i])});
15         rep(j, i+1, N)

```

```

16         if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
17     }
18     return tree;
19 }

```

9.8 Global Min Cut

a0d6c2

```

1// Author: ckiseki
2// 1-based: vertices are numbered 1 ~ n
3// 1. vector<vector<ll>> G(n+1, vector<ll>(n+1, 0));
4// 2. add_edge(G, u, v, c); // add undirected edge u-v with
weight c, u,v in [1,n]
5// 3. ll ans = mincut(G, n); // n = #vertices
6// => ans = global min cut value
7// Time:  $O(V^3)$ 
8 void add_edge(auto &w, int u, int v, int c) {
9     w[u][v] += c; w[v][u] += c; }
10 auto phase(const auto &w, int n, vector<int> id) {
11     vector<ll> g(n+1); int s = -1, t = -1;
12     while (!id.empty()) {
13         int c = -1;
14         for (int i : id) if (c == -1 || g[i] > g[c]) c = i;
15         s = t; t = c;
16         id.erase(ranges::find(id, c));
17         for (int i : id) g[i] += w[c][i];
18     } return tuple{s, t, g[t]};
19 }
20 ll mincut(auto w, int n) {
21     ll cut = numeric_limits<ll>::max();
22     vector<int> id(n); iota(all(id), 1);
23     for (int i = 0; i < n - 1; ++i) {
24         auto [s, t, gt] = phase(w, n, id);
25         id.erase(ranges::find(id, t));
26         cut = min(cut, gt);
27         for (int j = 1; j <= n; ++j)
28             w[s][j] += w[t][j], w[j][s] += w[j][t];
29     } return cut;
30 }

```

10 String

10.1 Rolling Hash

bb1f6e

```

1// Author: ckiseki (Modified by Gino)
2// Usage: RH<Sigma, Mod> Hs(s);
3// If no modifications needed, replace BIT with prefix sum
4 template <ll P = 127, ll Q = 1051762951>
5 class RH {
6     int n; vector<ll> p, inv, d, bit;
7     ll add(ll a, ll b) { return a+b >= Q ? a+b-Q : a+b; }
8     ll sub(ll a, ll b) { return a-b < 0 ? a-b+Q : a-b; }
9     ll mul(ll a, ll b) { return (__int128)a * b % Q; }
10    ll pw(ll a, ll x) {
11        ll r = 1; for (; x; a = mul(a, a), x >>= 1)
12            if (x & 1) r = mul(r, a);
13        return r;
14    }
15    void bit_add(int i, ll x) {
16        for (; i <= n; i += i&-i) bit[i] = add(bit[i], x); }
17    ll bit_qry(int i) {
18        for (ll s = 0; i; i -= i&-i) s = add(s, bit[i]);
19        return s; }
20 public:
21     RH(const auto &s) : n(s.size()),
22         p(n+1, 1), inv(n+1, 1), d(n+1), bit(n+1) {
23         ll iv = pw(P, Q - 2);
24         for (int i = 1; i <= n; i++) {
25             p[i] = mul(p[i-1], P); inv[i] = mul(inv[i-1], iv);
26             d[i] = mul(s[i-1], p[i]); bit_add(i, d[i]);
27         }
28         void update(int i, char c) {
29             ll x=mul(c, p[i]); bit_add(i, sub(x, d[i])); d[i]=x; }
30         ll query(int l, int r) {
31             return mul(sub(bit_qry(r), bit_qry(l-1)), inv[l]); }

```

10.2 KMP

47ace9

```

1// Author: Gino
2 vector<int> kmp(auto s) { int n=s.size(); vector<int> f(n,0);
3     for (int i = 1, ptr = 0; i < n; i++) {
4         while (ptr && s[i] != s[ptr]) ptr = f[ptr-1];
5         if (s[i] == s[ptr]) ptr++; f[i] = ptr;
6     } return f;
7 }

```

10.3 Z Value

20d446

```

1// Author: std_abs
2 vector<int> Z(auto s) { int n=s.size(); vector<int> Z(n);
3     for (int i = 0, l = 0, r = 0; i < n; ++i) {
4         Z[i] = max(min(Z[i-l], r-i), 0);
5         while (i+Z[i] < n && s[Z[i]] == s[i+Z[i]])
6             l = i, r = i+Z[i], Z[i]++;
7     } return Z;

```

```

8}
10.4 Manacher 846756
1// Author: std_abs
2// return array Z (length == 2N - 1)
3// Example: s = "aaaa"
4//   a       a       a
5// Z_0 Z_1 Z_2 Z_3 Z_4 Z_5 Z_6
6// 1   2   3   4   3   2   1
7// The corresponding palindrome s[l..r]:
8// l = (i - Z[i] + 1) / 2
9// r = (i + Z[i] - 1) / 2
10vector<int> manacher(auto tmp) {
11    vector<int> s(1, -1);
12    for (auto c : tmp) s.push_back(c), s.push_back(-1);
13    int l = 0, r = 0, n = (int)s.size();
14    vector<int> Z(n);
15    for (int i = 0; i < n; ++i) {
16        Z[i] = r > i ? min(Z[2 * l - i], r - i) : 1;
17        while (i - Z[i] >= 0 && i + Z[i] < n &&
18            s[i + Z[i]] == s[i - Z[i]]) Z[i]++;
19        if (Z[i] + i > r) l = i, r = Z[i] + i;
20    }
21    for (int i = 0; i < n; ++i)
22        Z[i] = (Z[i] - (i & 1)) / 2 * 2 + (i & 1);
23    return vector<int>(Z.begin() + 1, Z.end() - 1);
24}

```

```

10.5 Suffix Array + LCP 15b646
1// Author: std_abs
2// Tested @yosupo, N <= 5e5, 123ms
3const int N = 5e5 + 10;
4int sa[N], tmp[2][N], c[N], rk[N], lcp[N];
5void buildSA(string s) {
6    int *x = tmp[0], *y = tmp[1], m = 256, n = s.size();
7    for (int i = 0; i < m; ++i) c[i] = 0;
8    for (int i = 0; i < n; ++i) c[x[i]]++;
9    for (int i = 1; i < m; ++i) c[i] += c[i - 1];
10   for (int i = n - 1; ~i; --i) sa[--c[x[i]]] = i;
11   for (int k = 1; k < n; k <= 1) {
12       for (int i = 0; i < n; ++i) c[i] = 0;
13       for (int i = 0; i < n; ++i) c[x[i]]++;
14       for (int i = 1; i < m; ++i) c[i] += c[i - 1];
15       int p = 0;
16       for (int i = n - k; i < n; ++i) y[p++] = i;
17       for (int i = 0; i < n; ++i) if (sa[i] >= k)
18           y[p++] = sa[i] - k;
19       for (int i = n - 1; ~i; --i)
20           sa[--c[x[y[i]]]] = y[i];
21       y[sa[0]] = p = 0;
22       for (int i = 1; i < n; ++i) {
23           int a = sa[i], b = sa[i - 1];
24           p += !(x[a] == x[b] && a + k < n && b + k < n && x[a + k] == x[b + k]);
25           y[sa[i]] = p;
26       }
27       if (n == p + 1) break;
28       swap(x, y), m = p + 1;
29   }
30   void buildLCP(string s) {
31       // lcp[i] = LCP(sa[i - 1], sa[i])
32       // lcp(i, j) = query_lcp_min [rk[i] + 1, rk[j] + 1)
33       int n = s.length(), x = 0;
34       for (int i = 0; i < n; ++i) rk[sa[i]] = i;
35       for (int i = 0; i < n; ++i) {
36           if (!rk[i]) lcp[rk[i]] = 0;
37           else { if (x) x--;
38               int p = sa[rk[i] - 1];
39               while (x + i < n && x + p < n && s[x + i] == s[x + p]) x++;
40               lcp[rk[i]] = x;
41           }
42       }
43   }

```

```

10.6 Suffix Automaton 322a41
1// Author: std_abs
2// state (i.e. node) -> all substr with the same endpos
3// those substrs' length in range [len(link) + 1, len]
4// state i's endpos set -> union of pos[i] over the subtree
   of i in the suffix link tree
5// link[i] -> longest suffix with different endpos set
   (suffix link tree edge)
6// len[i] -> length longest suffix of state i
7// pos[i] -> an example end position of state i (1-based)
8// cnt[i] -> size of endpos set of state i, built by
   build_cnt() (tree DP)
9const int N = 5e5 + 10, C = 26;
10struct SAM {
11    int ch[2*N][C], len[2*N], link[2*N], pos[2*N], cnt[2*N], _id;
12    SAM() { reset(); }
13    void reset() { _id = 0, newnode(), link[0] = -1; }
14    int newnode() {
15        fill_n(ch[_id], C, 0);

```

```

16        len[_id] = link[_id] = pos[_id] = cnt[_id] = 0;
17        return _id++;
18    }
19    void build(string s) {
20        int last = 0; for (int i = 0; i < (int)s.size(); i++) {
21            char c = s[i]; int cur = newnode();
22            len[cur] = len[last] + 1, pos[cur] = i + 1;
23            int p = last;
24            while (~p && !ch[p][c - 'a'])
25                ch[p][c - 'a'] = cur, p = link[p];
26            if (p == -1) link[cur] = 0;
27            else { // conflict: p --> q, p --> cur
28                int q = ch[p][c - 'a'];
29                if (len[p] + 1 == len[q]) { // q is suffix of cur
30                    link[cur] = q;
31                } else { // we need auxiliary state
32                    int nxt = newnode();
33                    len[nxt] = len[p] + 1, link[nxt] = link[q];
34                    pos[nxt] = 0;
35                    for (int j = 0; j < C; j++)
36                        ch[nxt][j] = ch[q][j];
37                    while (~p && ch[p][c - 'a'] == q)
38                        ch[p][c - 'a'] = nxt, p = link[p];
39                    link[q] = link[cur] = nxt;
40                }
41                cnt[cur]++, last = cur;
42            }
43        }
44        void build_cnt() {
45            vector<int> p(_id); iota(all(p), 0); sort(all(p),
46                [&](int i, int j){ return len[i] > len[j]; });
47            for (int i = 0; i < _id; ++i) if (link[p[i]] != -1)
48                cnt[link[p[i]]] += cnt[p[i]];
49        }
50        bool match(string s) {
51            int p = 0; for (auto& c : s) {
52                if (!ch[p][c - 'a']) return false;
53                p = ch[p][c - 'a'];
54            } return true; }

```

10.7 Minimum Rotation

ae667e

```

1// Author: std_abs
2string rotate(auto s){ int n=s.size(), i=0, j=1;
3    string t = s + s;
4    while (i < n && j < n) {
5        int k = 0; while (k < n && t[i + k] == t[j + k]) ++k;
6        if (t[i + k] <= t[j + k]) j += k + 1; else i += k + 1;
7        if (i == j) ++j;
8    } return t.substr((i < n ? i : j), n);
9}

```

10.8 AC Automaton

dc83a2

```

1// Author: std_abs (slightly modified by Gino)
2// Recap: fail[s] = s 在 trie 上 (也就是某個 pattern 的前綴
   的最長 proper 後綴
3// N := sum(length of all patterns) + 1
4// 1. ac.insert(pat) -> end-node id recorded in ac.pid
5// 2. ac.build_fail()
6// 3. run text: ptr = to[ptr][c-'a'] each char;
   accumulate on your own arrays
7// - pull: rep(i ac.order_cnt-1 ~ 0) val[fail[x]] += val[x]
8// - push: rep(i 0 ~ ac.order_cnt-1) val[x] += val[fail[x]]
9// Tested @yosupo, N <= 1e6, 323ms on building AC
10const int N = 1e6 + 5, C = 26;
11struct AC {
12    int ch[N][C], to[N][C], fail[N], _id, order[N], order_cnt;
13    int np; vector<int> pid; // pattern ID on trie
14    // order[r] := which trie node has BFS order r
15    // fail link tree: (parent) fail[i] <-- i (child)
16    void reset() { _id = np = order_cnt = 0, pid.clear(),
17        newnode(); }
18    int newnode() {
19        fill_n(ch[_id], C, 0), fill_n(to[_id], C, 0);
20        fail[_id] = 0; return _id++;
21    }
22    AC() { reset(); }
23    void insert(string s) {
24        int ptr = 0; for (char c : s) {
25            if (!ch[ptr][c - 'a']) ch[ptr][c - 'a'] = newnode();
26            ptr = ch[ptr][c - 'a'];
27        } np++; pid.emplace_back(ptr);
28    }
29    void build_fail() {
30        queue<int> q; order_cnt = 0;
31        for (int i = 0; i < C; ++i) if (ch[0][i])
32            q.push(ch[0][i]), to[0][i] = ch[0][i];
33        while (!q.empty()) {
34            int u = q.front(); q.pop(); order[order_cnt++] = u;
35            for (int i = 0; i < C; ++i) {
36                if (!ch[u][i]) to[u][i] = to[fail[u]][i];

```

```

38     else { int v = ch[u][i], k = fail[u];
39           while (k && !ch[k][i]) k = fail[k];
40           if (ch[k][i]) k = ch[k][i];
41           fail[v] = k, to[u][i] = v;
42           q.push(v);
43     } } }
44 } ac;

```

10.9 AC Automaton - Dict Links

009582

```

1// Author: Gino, paste this in `struct AC {...}`
2// 3 Modifications to the original AC Automaton:
3// int np; vector<int> pid; bool is_pattern[N];
4// fail[_id] = 0, is_pattern[_id] = false; return _id++;
5// np++; pid.emplace_back(ptr); is_pattern[ptr] = true;
6int dict[N];
7void build_dict() { // call this after build_fail()!
8    for (int i = 0; i < order_cnt; i++) {
9        int u = order[i], f = fail[u];
10       dict[u] = is_pattern[f] ? f : dict[f];
11    } }

```

10.10 AC Automaton - Counting Patterns

05fa55

```

1// Author: Gino, paste this in `struct AC {...}`
2ll val[N];
3void count_patterns(string& text, vector<string>& patterns){
4    for (auto& p : patterns) insert(p); build_fail();
5    ranges::fill(val, 0LL);
6    int ptr = 0; for (auto& c : text) {
7        ptr = to[ptr][c - 'a']; val[ptr]++;
8    }
9    for (int x : span(order, order_cnt) | views::reverse)
10       val[fail[x]] += val[x];
11    for (auto& i : pid) cout << val[i] << endl;
12}

```

10.11 AC Automaton - Pattern Position

輸出每個 pattern 在 text 中第一次出現的位置，若不存在則輸出 -1。
走 AC 自動機時 if (val[ptr] == -1) val[ptr] = i; 接著 pull DP
if (val[x] == -1) continue;
if (val[fail[x]] == -1) val[fail[x]] = val[x];
else val[fail[x]] = min(val[fail[x]], val[x]);

11 Geometry

11.1 Template

de6583

```

1using T = long long; // or double
2const double eps = 1e-8;
3int sgn(T x) { return (x > eps) - (x < -eps); }
4struct Pt {
5    T x = 0, y = 0;
6    Pt operator+(Pt a) const { return {x + a.x, y + a.y}; }
7    Pt operator-(Pt a) const { return {x - a.x, y - a.y}; }
8    Pt operator*(T k) const { return {x * k, y * k}; }
9    Pt operator/(T k) const { return {x / k, y / k}; }
10   T operator*(Pt a) const { return x * a.x + y * a.y; }
11   T operator^(Pt a) const { return x * a.y - y * a.x; }
12   bool operator<(Pt a) const
13   { return tie(x, y) < tie(a.x, a.y); }
14   bool operator==(Pt a) const
15   { return !sgn(x - a.x) && !sgn(y - a.y); }
16   //friend ostream& operator<<(ostream& o, Pt a)
17   //{ return o << "(" << a.x << ", " << a.y << ")"; }
18};
19struct Line { Pt a, b; }; // a -> b
20T abs2(Pt a) { return a * a; }
21double abs(Pt a) { return sqrt(abs2(a)); }
22int ori(Pt o, Pt a, Pt b) // 1: CCW, -1: CW, 0: collinear
23{ return sgn((a - o) ^ (b - o)); }

```

11.2 Basic

b94994

```

1struct Cir { Pt o; double r; };
2// ----- 極角排序 -----
3int ud(Pt a) // 0: upper half (incl. +x axis), 1: lower
4{ return !sgn(a.y) ? sgn(a.x) < 0 : a.y < 0; }
5bool cmp(Pt a, Pt b) // polar angle in [0, 2PI),
6{ return ud(a) == ud(b) ? sgn(a ^ b) > 0 : ud(a) < ud(b); }
7ranges::sort(p, [&](Pt a, Pt b){return cmp(a - o, b - o);});
8// -----
9bool sameVec(Pt a, Pt b, int d)//d=0: parallel, d=1: same dir
10{ return !sgn(a ^ b) && sgn(a * b) > d * 2 - 2; }
11bool sameVec(Line a, Line b, int d)
12{ return sameVec(a.b - a.a, b.b - b.a, d); }
13Pt rot90(Pt a) { return {-a.y, a.x}; } // CCW
14Pt ref(Pt a) { return ud(a) ? Pt(-a.x, -a.y) : a; }
15T dbarea(vector<Pt>& p) { // doubled signed area, CCW > 0
16    T res = 0; for (int i = 0; i < sz(p); i++)
17        res += p[i] ^ p[(i+1) % sz(p)];
18    return res; }
19bool onseg(Pt p, Pt a, Pt b) // p on segment ab?
20{ return !ori(p, a, b) && sgn((a - p) * (b - p)) <= 0; }
21// ---- T = double ----

```

```

22const double PI = acos(-1);
23double normalize(double x) { // to [0, 2pi)
24    while (x < -eps) x += PI * 2;
25    while (x > PI * 2 + eps) x -= PI * 2;
26    return x; }
27double theta(Pt a) { return normalize(atan2(a.y, a.x)); }
28Pt unit(Pt a) { return a / abs(a); }
29Pt rot(Pt a, double o) { // CCW
30    double c = cos(o), s = sin(o);
31    return Pt(c * a.x - s * a.y, s * a.x + c * a.y); }
32Pt projVec(Pt a, Pt b, Pt c) // vector ac proj to ab
33{ return (b - a) * ((c - a) * (b - a)) / abs2(b - a); }
34Pt projPt(Pt a, Pt b, Pt c) // point c proj to ab
35{ return projVec(a, b, c) + a; }

```

11.3 Line / Segment Intersections

471854

```

1// m=0: segment, m=1: ray from l.a to l.b, m=2: line
2bool banana(Line ls, int ms, Line lt, int mt, int strict) {
3    auto on = [&](Line l, int m, Pt p) {
4        if (ori(l.a, l.b, p) != 0) return false;
5        if (m && abs2(l.a - p) > abs2(l.b - p)) return true;
6        return m == 2 || sgn((p - l.a) * (p - l.b)) <= -strict;
7    };
8    if (sameVec(ls, lt, 0)) {
9        return on(ls, ms, lt.a) || on(ls, ms, lt.b) ||
10       on(lt, mt, ls.a) || on(lt, mt, ls.b);
11    }
12    auto good = [&](Line l, int m, Line o) {
13        if (m && abs((l.a - o.a) ^ (l.a - o.b)) >
14            abs((l.b - o.a) ^ (l.b - o.b))) return true;
15        return m == 2 ||
16            ori(l.a, o.a, o.b) * ori(l.b, o.a, o.b) == -1;
17    };
18    if (good(ls, ms, lt) && good(lt, mt, ls)) return 1;
19    if (!strict) {
20        if (mt != 2 && on(ls, ms, lt.a)) return 1;
21        if (mt == 0 && on(ls, ms, lt.b)) return 1;
22        if (ms != 2 && on(lt, mt, ls.a)) return 1;
23        if (ms == 0 && on(lt, mt, ls.b)) return 1;
24    }
25    return 0;
26}
27// becareful when two lines are parallel
28auto bananaPoint(Line a, Line b) {
29    auto abc = (a.b - a.a) ^ (b.a - a.a);
30    auto abd = (a.b - a.a) ^ (b.b - a.a);
31    return make_pair(b.b * abc - b.a * abd, abc - abd);
32}

```

11.4 Point-Line / Segment Distance

6b5619

```

1// T = double
2double pointLineDist(Pt p, Line L)
3{ return fabs(((L.b - L.a) ^ (p - L.a)) / abs(L.b - L.a)); }
4double pointSegDist(Pt p, Pt a, Pt b) {
5    if (a == b) return abs(p - a);
6    if (sgn((b - a) * (p - a)) >= 0 &&
7        sgn((a - b) * (p - b)) >= 0)
8        return pointLineDist(p, {a, b});
9    return min(abs(p - a), abs(p - b));
10}

```

11.5 Sort

59d0a3

```

1// Dependency: cmp(), btwAngle()
2// cmp in Basic: polar angle sort
3// all points are on line ab. closer to a: front
4bool cmpLine(Pt s, Pt t, Pt a, Pt b) {
5    Pt v = a - b;
6    if (sgn(v.x)) return sgn(s.x - t.x) == sgn(v.x);
7    return sgn(s.y - t.y) == sgn(v.y);
8}
9// intersect points polar angle sort, deno: positive
10bool cmpFractionPolar(pair<Pt, ll> o,
11    pair<Pt, ll> s, pair<Pt, ll> t) {
12    Pt u = s.first * o.second - o.first * s.second;
13    Pt v = t.first * o.second - o.first * t.second;
14    return cmp(u, v);
15}
16struct Seg {
17    Pt a, b; // a.x < b.x
18    bool operator<(const Seg& o) const {
19        if (a == o.a) return ori(o.b, a, b) == 1;
20        if (a.x <= o.a.x) return ori(o.a, a, b) == 1;
21        return ori(a, o.a, o.b) == -1;
22    };
23}
24struct PolarSeg {
25    Pt a, b; // ori(Pt(0, 0), a, b) > 0
26    bool operator<(const PolarSeg& o) const {
27        if (a == o.a) return ori(o.b, a, b) == -1;
28        if (btwAngle(Pt(0, 0), a, b, o.a, 0))
29            return ori(o.a, a, b) == -1;

```

```

29     return ori(a, o.a, o.b) == 1;
30 } };
31 struct Arc {
32     // contain(a, b): circle a inside circle b
33     Cir c; int id, s; // 0 -> up, 1 -> down
34     bool operator<(const Arc& b) const {
35         if (id == b.id) return s < b.s;
36         if (contain(c, b.c)) return b.s == 1;
37         if (contain(b.c, c)) return s == 0;
38         if (c.o.y == b.c.o.y) return id < b.id;
39         return c.o.y > b.c.o.y;
40 } };

```

11.6 Convex Hull

788ba8

```

1 auto convexHull(vector<Pt> pts) {
2     sort(all(pts)); vector<Pt> ans = {pts[0]};
3     for (int t = 0; t < 2; t++, reverse(all(pts))) {
4         for (int i = 1, m = sz(ans); i < sz(pts); i++) {
5             while (sz(ans) > m &&
6                 ori(ans[sz(ans) - 2], ans.back(), pts[i]) <= 0)
7                 ans.pop_back();
8             ans.pb(pts[i]); } }
9     if (sz(ans) > 1) ans.pop_back(); return ans; }

```

11.7 Triangle Centers

12240b

```

1 // T = double
2 Pt circenter(Pt a, Pt b, Pt c) { // r = abs(o - a)
3     b = b - a, c = c - a; double m = 2 * (b^c);
4     Pt o = {(abs2(b) * c.y - abs2(c) * b.y) / m,
5             (abs2(c) * b.x - abs2(b) * c.x) / m};
6     return o + a;
7 }
8 Pt incenter(Pt a, Pt b, Pt c) { // r = 2 * area / s
9     double x = abs(b - c), y = abs(c - a);
10    double z = abs(a - b), s = x + y + z;
11    return (a*x + b*y + c*z) / s;
12 }
13 Pt centroid(Pt a, Pt b, Pt c) { return (a + b + c) / 3; }
14 Pt orthocenter(Pt a, Pt b, Pt c) {
15     return centroid(a, b, c) * 3 - circenter(a, b, c) * 2;
16 }

```

11.8 Point Inside

670564

```

1 // get edge index: check (0, a), (0, b) first
2 // then after binary search, check (a, b)
3 bool inConvex(vector<Pt>& C, Pt p, bool strict = true) {
4     // only works when no three points are collinear
5     int a = 1, b = sz(C) - 1, r = !strict;
6     if (sz(C) == 0) return false;
7     if (sz(C) < 3) return r && onseg(p, C[0], C.back());
8     if (ori(C[0], C[a], C[b]) > 0) swap(a, b);
9     if (ori(C[0], C[a], p) >= r ||
10         ori(C[0], C[b], p) <= -r) return false;
11     while (abs(a - b) > 1) {
12         int c = (a + b) / 2;
13         (ori(C[0], C[c], p) > 0 ? b : a) = c;
14     }
15     return ori(C[a], C[b], p) < r;
16 }
17 // need onseg(), -1: out, 0: edge, 1: in
18 int inPoly(vector<Pt> poly, Pt o, int strict) {
19     int cnt = 0;
20     for (int i = 0; i < sz(poly); i++) {
21         Pt a = poly[i], b = poly[(i + 1) % sz(poly)];
22         if (onseg(o, a, b)) return !strict;
23         cnt ^= ((o.y < a.y) - (o.y < b.y)) * ori(o, a, b) > 0;
24     }
25     return cnt ? 1 : -1;
26 }
27 // relation of q with circumcircle; T = long long
28 bool inCC(array<Pt, 3> p, Pt q) {
29     __int128 det = 0;
30     for (int i = 0; i < 3; i++)
31         det += __int128(abs2(p[i]) - abs2(q)) *
32             ((p[(i + 1) % 3] - q) ^ (p[(i + 2) % 3] - q));
33     return det > 0; // in: >0, on: =0, out: <0
34 }

```

11.9 Point In Triangle

0eabd1

```

1 // number of p with a < p < b and ori(p, a, b) < 0
2 int under(Pt a, Pt b) {}
3 // number of points with a < p < b and ori(p, a, b) = 0
4 int edge(Pt a, Pt b) {}
5 // check if this number is calculated
6 bool check(Pt p) {}
7 // number of points that strictly inside the triangle
8 int inTri(array<Pt, 3> arr) {
9     sort(all(arr)); auto [a, b, c] = arr; intx = ori(b, a, c);
10    if (x == 0) return 0;
11    if (x == 1) return under(a, b) + under(b, c) -
12        under(a, c) - edge(a, c);

```

```

13     return under(a, c) - under(a, b) -
14         under(b, c) - edge(a, b) - edge(b, c) - check(b);
15 }

```

11.10 Vector In Polygon

970582

```

1 // ori(a, b, c) >= 0, valid: "strict" angle from a-b to a-c
2 bool btwAngle(Pt a, Pt b, Pt c, Pt p, int strict) {
3     return ori(a, b, p) >= strict &&
4         ori(a, p, c) >= strict;
5 }
6 // whether vector{cur, p} is in order prv, cur, nxt
7 bool inside(Pt prv, Pt cur, Pt nxt, Pt p, int strict) {
8     if (ori(cur, nxt, prv) >= 0)
9         return btwAngle(cur, nxt, prv, p, strict);
10    return !btwAngle(cur, prv, nxt, p, !strict);
11 }

```

11.11 Polygon Cut

21751d

```

1 // Dependency: bananaPoint(); T = double
2 // Cut a convex polygon with line (s -> e), keep right side
3 vector<Pt> polyCut(vector<Pt> poly, Pt s, Pt e) {
4     vector<Pt> res; for (int i = 0; i < sz(poly); i++) {
5         Pt cur = poly[i], prv = i ? poly[i - 1] : poly.back();
6         bool side = ori(s, e, cur) < 0;
7         if (side != (ori(s, e, prv) < 0)) {
8             auto [p, d] = bananaPoint({s, e}, {cur, prv});
9             res.pb(p / d);
10            if (side) res.pb(cur);
11        } return res;
12 }

```

11.12 Half-Plane Intersection

1cf136

```

1 // Dependency: sameVec(), cmp(); T = long long
2 /* Having solution, check size > 2 */
3 /* --^-- Line.a --^-- Line.b --^-- */
4 auto halfPlaneIntersection(vector<Line> arr) {
5     auto areaPair = [&](Line a, Line b) {
6         return make_pair((a.b - a.a) ^ (b.a - a.a),
7                         (a.b - a.a) ^ (b.b - a.a));
8     };
9     auto isin = [&](Line l0, Line l1, Line l2) {
10        // Check inter(l1, l2) strictly in l0
11        auto [a02X, a02Y] = areaPair(l0, l2);
12        auto [a12X, a12Y] = areaPair(l1, l2);
13        if (a12X - a12Y < 0) a12X *= -1, a12Y *= -1;
14        return ((__int128)a02Y * a12X -
15                (__int128)a02X * a12Y > 0; // C^4
16    };
17    sort(all(arr), [&](Line a, Line b) {
18        if (sameVec(a, b, 1))
19            return ori(a.a, a.b, b.b) < 0;
20        return cmp(a.b - a.a, b.b - b.a);
21    });
22    deque<Line> dq(1, arr[0]);
23    auto popBack = [&](int t, Line p) {
24        while (sz(dq) >= t &&
25            !isin(p, dq[sz(dq) - 2], dq.back()))
26            dq.pop_back();
27    };
28    auto popFront = [&](int t, Line p) {
29        while (sz(dq) >= t && !isin(p, dq[0], dq[1]))
30            dq.pop_front();
31    };
32    for (auto p : arr) if (!sameVec(dq.back(), p, 1))
33        popBack(2, p), popFront(2, p), dq.pb(p);
34    popBack(3, dq[0]), popFront(3, dq.back());
35    return vector<Line>(all(dq));
36 }

```

11.13 Cyclic Ternary Search

d1b304

```

1 /* bool pred(int a, int b);
2 f(0) ~ f(n - 1) is a cyclic-shift U-function
3 return idx s.t. pred(x, idx) is false forall x*/
4 int cycTsearch(int n, auto pred) {
5     if (n == 1) return 0;
6     int l = 0, r = n; bool rv = pred(1, 0);
7     while (r - l > 1) {
8         int m = (l + r) / 2;
9         if (pred(0, m) ? rv : pred(m, (m + 1) % n)) r = m;
10        else l = m;
11    } return pred(l, r % n) ? l : r % n;
12 }

```

11.14 Circle Intersections

8f97aa

```

1 // Dependency: cycTsearch(); T = double for circles
2 vector<Pt> circleLineIntersect(Cir c, Line l) {
3     Pt p = l.a + (l.b - l.a) *
4         ((c.o - l.a) * (l.b - l.a)) / abs2(l.b - l.a);
5     double s = (l.b - l.a) ^ (c.o - l.a);
6     double h2 = c.r * c.r - s * s / abs2(l.b - l.a);
7     if (sgn(h2) == -1) return {};

```

```

8  if (sgn(h2) == 0) return {p};
9  Pt h = (l.b - l.a) / abs(l.b - l.a) * sqrt(h2);
10 return {p - h, p + h};
11}
12// covered area of c1: arc from res[0] to res[1], CCW
13vector<Pt> circlesIntersect(Cir c1, Cir c2) {
14  double d2 = abs2(c1.o - c2.o), d = sqrt(d2);
15  if (d < max(c1.r, c2.r) - min(c1.r, c2.r) ||
16      d > c1.r + c2.r) return {};
17  Pt u = (c1.o + c2.o) / 2 +
18      (c1.o - c2.o) *
19      ((c2.r * c2.r - c1.r * c1.r) / (2 * d2));
20  double A = sqrt((c1.r + c2.r + d) *
21      (c1.r - c2.r + d) * (c1.r + c2.r - d) *
22      (-c1.r + c2.r + d));
23  Pt v = rot90(c2.o - c1.o) * A / (2 * d2);
24  if (sgn(v.x) == 0 && sgn(v.y) == 0) return {u};
25  return {u - v, u + v};
26}
27vector<pii> convexLineIntersect(vector<Pt>& C, Line la) {
28  auto dis = [&](int p) {
29      return (la.b - la.a) ^ (C[p] - la.a);
30  };
31  auto gao = [&](int s) {
32      return cycTsearch(sz(C), [&](int i, int j) {
33          return sgn(dis(i) - dis(j)) == s;
34      });
35  };
36  int x = gao(1), y = gao(-1), n = sz(C);
37  if (sgn(dis(x)) < 0 || sgn(dis(y)) > 0) return {};
38  if (sgn(dis(x)) == 0 || sgn(dis(y)) == 0) {
39      int v = ((sgn(dis(x)) == 0 ? x : y) + n - 1) % n;
40      vector<pii> vec;
41      for (int i = 0; i < 3; i++, v = (v + 1) % n)
42          if (sgn(dis(v)) == 0) vec.emplace_back(v, v);
43      return vec;
44  }
45  auto get = [&](int l, int r, int s) {
46      while ((l + 1) % n != r) {
47          int m = ((l + r + (l < r ? 0 : n)) / 2) % n;
48          (sgn(dis(m)) == s ? l : r) = m;
49      }
50      if (sgn(dis(r)) == 0) return pii(r, r);
51      return pii(l, r);
52  };
53  return {get(x, y, 1), get(y, x, -1)};
54}

```

11.15 Tangents

7d0503

```

1// Dependency: cycTsearch(); T = double for circle tangents
2auto circlePointTangent(Cir c, Pt p) {
3  vector<Line> res;
4  double dSq = abs2(p - c.o);
5  if (sgn(dSq - c.r * c.r) == 0) {
6      res.push_back({p, p + rot90(p - c.o)});
7  } else if (dSq > c.r * c.r) {
8      double s = dSq - c.r * c.r;
9      Pt v = p + (c.o - p) * s / dSq;
10     Pt u = rot90(c.o - p) * sqrt(s) * c.r / dSq;
11     res.push_back({p, v + u});
12     res.push_back({p, v - u});
13 }
14 return res;
15}
16auto circlesTangent(Cir c1, Cir c2, int sign1) {
17 // sign1 = 1 for outer tang, -1 for inter tang
18 vector<Line> res;
19 double dSq = abs2(c1.o - c2.o);
20 if (sgn(dSq) == 0) return res;
21 double d = sqrt(dSq);
22 Pt v = (c2.o - c1.o) / d;
23 double c = (c1.r - sign1 * c2.r) / d;
24 if (c * c > 1) return res;
25 double h = sqrt(max(0.0, 1.0 - c * c));
26 for (int sign2 = 1; sign2 >= -1; sign2 -= 2) {
27     Pt n = Pt(v.x * c - sign2 * h * v.y,
28         v.y * c + sign2 * h * v.x);
29     Pt p1 = c1.o + n * c1.r;
30     Pt p2 = c2.o + n * (c2.r * sign1);
31     if (sgn(p1.x - p2.x) == 0 &&
32         sgn(p1.y - p2.y) == 0)
33         p2 = p1 + rot90(c2.o - c1.o);
34     res.push_back({p1, p2});
35 }
36 return res;
37}
38/* The point should be strictly out of hull
39   return arbitrary point on the tangent line */
40pii pointConvexTangent(vector<Pt>& C, Pt p) {

```

```

41 auto gao = [&](int s) {
42     return cycTsearch(sz(C), [&](int x, int y) {
43         return ori(p, C[x], C[y]) == s;
44     });
45 };
46 return pii(gao(1), gao(-1));
47 // return (a, b), ori(p, C[a], C[b]) >= 0

```

11.16 Bisector

a45c44

```

1Pt bisector(Pt a, Pt b, Pt c) { Pt s = b-a, t = c-a;
2  t = t * abs(s) / abs(t); return s + t; }

```

11.17 Minimum Enclosing Circle

cd2fc9

```

1// Dependency: circenter(); T = double
2Cir minEnclosingCircle(vector<Pt> p) {
3  auto seed = chrono::steady_clock::now().
4      time_since_epoch().count();
5  shuffle(all(p), mt19937(seed));
6  double r = 0.0; Pt cent = p[0];
7  for (int i = 1; i < sz(p); i++) {
8      if (abs2(cent - p[i]) <= r) continue;
9      cent = p[i]; r = 0.0;
10     for (int j = 0; j < i; j++) {
11         if (abs2(cent - p[j]) <= r) continue;
12         cent = (p[i] + p[j]) / 2; r = abs2(p[j] - cent);
13         for (int k = 0; k < j; k++) {
14             if (abs2(cent - p[k]) <= r) continue;
15             cent = circenter(p[i], p[j], p[k]);
16             r = abs2(p[k] - cent);
17         }
18     }
19     return {cent, sqrt(r)};

```

11.18 Minkowski Sum

133299

```

1// Dependency: convexHull()
2auto minkowski(vector<Pt> a, vector<Pt> b) {
3  a = convexHull(a), b = convexHull(b);
4  int n = sz(a), m = sz(b);
5  vector<Pt> c = {a[0] + b[0]}, s1, s2;
6  for (int i = 0; i < n; i++) s1.pb(a[(i+1) % n] - a[i]);
7  for (int i = 0; i < m; i++) s2.pb(b[(i+1) % m] - b[i]);
8  for (int p1 = 0, p2 = 0; p1 < n || p2 < m; )
9      if (p2 == m ||
10         (p1 < n && sgn(s1[p1] ^ s2[p2]) >= 0))
11         c.pb(c.back() + s1[p1++]);
12     else
13         c.pb(c.back() + s2[p2++]);
14  return convexHull(c);
15}

```

11.19 Convex Hull Distance

987fcf

```

1// Dependency: minkowski(), inConvex(), pointSegDist()
2// T = double
3double convexHullDist(vector<Pt> A, vector<Pt> B) {
4  Pt O(0, 0); for (auto& p : B) p = 0 - p;
5  auto C = minkowski(A, B);
6  if (inConvex(C, O)) return 0;
7  double ans = pointSegDist(O, C.back(), C[0]);
8  for (int i = 0; i + 1 < sz(C); i++)
9      ans = min(ans, pointSegDist(O, C[i], C[i + 1]));
10 return ans;

```

11.20 Closest Point Pair

45eca8

```

1// returns {min squared dist, {i, j}}, n >= 2, |coord| < 1e9
2pair<T, pair<int, int>> closestPair(vector<Pt> p) {
3  vector<int> id(sz(p)); iota(all(id), 0);
4  sort(all(id),
5      [&](int a, int b) { return p[a].y < p[b].y; });
6  set<pair<Pt, int>> s; // (point, id)
7  pair<T, pair<int, int>> best = {(T)9e18, {-1, -1}};
8  int l = 0; for (int i : id) {
9      if (!best.first) break;
10     T d = sqrtl(best.first) + is_integral_v<T>;
11     while (p[id[l]].y <= p[i].y - d)
12         s.erase({p[id[l]], id[l]}), l++;
13     auto lo = s.lower_bound({p[i] - Pt{d, 0}, 0});
14     auto hi = s.upper_bound({p[i] + Pt{d, 0}, sz(p)});
15     for (; lo != hi; lo++) {
16         auto [q, j] = *lo;
17         best = min(best,
18             {abs2(q - p[i]), {min(i, j), max(i, j)}});
19     } s.insert({p[i], i});
20 } return best;
21}

```

11.21 Polygon-Circle Intersection

51ecf1

```

1// T = double
2double areaSector(Pt pa, Pt pb, double r) {
3  if (abs(pa) < abs(pb)) swap(pa, pb);
4  if (abs(pb) < eps) return 0;
5  double S, h, t;
6  double a = abs(pb), b = abs(pa), c = abs(pb - pa);

```

```

7 double cosB = pb * (pb - pa) / a / c;
8 double B = acos(cosB);
9 double cosC = pa * pb / a / b, C = acos(cosC);
10 if (a > r) {
11     S = C / 2 * r * r;
12     h = a * b * sin(C) / c;
13     if (h < r && B < PI / 2)
14         S -= acos(h / r) * r * r - h * sqrt(r * r - h * h);
15 } else if (b > r) {
16     t = PI - B - asin(sin(B) / r * a);
17     S = 0.5 * a * r * sin(t) + (C - t) / 2 * r * r;
18 } else {
19     S = 0.5 * sin(C) * a * b;
20 }
21 return S;
22 }
23 double areaPolyCircle(vector<Pt> poly, Pt 0, double r) {
24     double S = 0;
25     int n = sz(poly);
26     for (int i = 0; i < n; i++)
27         S += areaSector(poly[i] - 0,
28             poly[(i + 1) % n] - 0, r) *
29             ori(0, poly[i], poly[(i + 1) % n]);
30     return fabs(S);
31 }

```

11.22 Union of Polygons f5b117

// Author: Gino, simple polygons any orientation, $O((\sum n)^2)$
// T = ll: exact ($|coord| \leq 1e9$); T = double: also works

```

3 double polysUnionArea(vector<vector<Pt>> poly) {
4     struct Fr { T p, q; }; // p / q, q > 0
5     auto lt = [](Fr a, Fr b) {
6         // return ( (__int128)a.p * b.q < (__int128)b.p * a.q; // if T
6         // == long long
7         return a.p * b.q < b.p * a.q;
8     };
9     auto val = [&](Fr a) { // clamp to [0, 1], to double
10         if (lt(a, {0, 1})) return 0.;
11         if (lt({1, 1}, a)) return 1.;
12         return (double)a.p / a.q;
13     };
14     auto get = [&](int i, int e) {
15         return poly[i][(e + 1) % sz(poly[i])];
16     };
17     for (auto& p : poly)
18         if (dbarea(p) < 0) reverse(all(p));
19     double sum = 0;
20     for (int i = 0; i < sz(poly); i++)
21         for (int e = 0; e < sz(poly[i]); e++) {
22             Pt s = poly[i][e], t = get(i, e);
23             vector<pair<Fr, int>> c = {{{0, 1}, 0}, {{1, 1}, 0}};
24             for (int j = 0; j < sz(poly); j++) {
25                 if (i == j) continue;
26                 for (int f = 0; f < sz(poly[j]); f++) {
27                     Pt a = poly[j][f], b = get(j, f);
28                     int ta = ori(s, t, a), tb = ori(s, t, b);
29                     if (!ta && !tb) {
30                         if (j < i && sgn((b-a) * (t-s)) > 0) {
31                             T d = abs2(t-s);
32                             c.pb({Fr{(a-s) * (t-s), d}, 1});
33                             c.pb({Fr{(b-s) * (t-s), d}, -1});
34                         }
35                     } else if ((ta >= 0) != (tb >= 0)) {
36                         T x = (b-a) ^ (s-a), y = (b-a) ^ (t-a);
37                         if (x < y) x = -x, y = -y;
38                         c.pb({Fr{x, x-y}, ta >= 0 ? 1 : -1});
39                     }
40                 }
41             }
42             sort(all(c), [&](auto& u, auto& v) {
43                 return lt(u.first, v.first); });
44             double z = val(c[0].first), r = 0;
45             for (int k = 1, d = c[0].second; k < sz(c); k++) {
46                 double w = val(c[k].first);
47                 if (!d) r += w - z;
48                 d += c[k].second, z = w;
49             }
50             sum += (s^t) * r;
51         }
52     return sum / 2;
53 }

```

11.23 Rotating Sweep Line 3b614c

```

1 // Dependency: ref()
2 struct Event {
3     Pt d; int u, v;
4     bool operator<(const Event& o) const {
5         return sgn(d ^ o.d) > 0;
6     };

```

```

7 void rotatingSweepLine(vector<Pt> pts) {
8     int n = sz(pts);
9     vector<int> ord(n), pos(n); vector<Event> e;
10    for (int i = 0; i < n; i++)
11        for (int j = i + 1; j < n; j++)
12            e.push_back({ref(pts[i] - pts[j]), i, j});
13    sort(all(e)); iota(all(ord), 0);
14    sort(all(ord), [&](int i, int j) {
15        return sgn(pts[i].y - pts[j].y) == 0 ?
16            pts[i].x < pts[j].x : pts[i].y < pts[j].y;
17    });
18    for (int i = 0; i < n; i++) pos[ord[i]] = i;
19    auto makeReverse = [](auto v) {
20        sort(all(v));
21        v.resize(unique(all(v)) - v.begin());
22        vector<pii> segs;
23        for (int i = 0, j = 0; i < sz(v); i = j) {
24            for (; j < sz(v) && v[j] - v[i] <= j - i; j++);
25            segs.emplace_back(v[i], v[j - 1] + 1 + 1);
26        }
27        return segs;
28    };
29    for (int i = 0, j = 0; i < sz(e); i = j) {
30        vector<int> tmp;
31        for (; j < sz(e) && !e[i] < e[j]; j++)
32            tmp.pb(min(pos[e[j].u], pos[e[j].v]));
33        for (auto [l, r] : makeReverse(tmp)) {
34            reverse(ord.begin() + l, ord.begin() + r);
35            for (int t = l; t < r; t++) pos[ord[t]] = t;
36            // update value here
37        }

```

11.24 Pick's Theorem

Consider a polygon which vertices are all lattice points.
Let i = number of points inside the polygon.
Let b = number of points on the boundary of the polygon.
Then we have the following formula:

$$\text{Area} = i + b/2 - 1$$

12 Math Basic

12.1 Basic 8881cf

```

1 const ll mod = 998244353;
2 ll add(ll a, ll b) { return (a += b) >= mod ? a - mod : a; }
3 ll sub(ll a, ll b) { return (a -= b) < 0 ? a + mod : a; }
4 ll mul(ll a, ll b) { return (__int128)a * b % mod; }
5 ll Pow(ll b, ll e) { ll r = 1;
6     for (; e >= 1; b = mul(b, b)) if (e & 1) r = mul(r, b);
7     return r;
8 }

```

13 Number Theory

13.1 Mod Sum / Floor Sum c72030

```

1 // modSum(to, c, k, m) sums (k*i+c) mod m for i < to.
2 // divSum computes the corresponding sum of floor((k*i+c)/m).
3 // Both run in  $O(\log m)$ .
4 using ull = unsigned long long;
5
6 ull sumsq(ull to) { return to / 2 * ((to - 1) | 1); }
7
8 ull divSum(ull to, ull c, ull k, ull m) {
9     ull res = k / m * sumsq(to) + c / m * to;
10    k %= m;
11    c %= m;
12    if (!k) return res;
13    ull to2 = (to * k + c) / m;
14    return res + (to - 1) * to2
15        - divSum(to2, m - 1 - c, m, k);
16 }
17
18 ll modSum(ull to, ll c, ll k, ll m) {
19     c = ((c % m) + m) % m;
20     k = ((k % m) + m) % m;
21     return to * c + k * sumsq(to) - m * divSum(to, c, k, m);
22 }

```

13.2 Mod Sqrt 79b959

```

1 // sqrtMod(a, p) finds x with  $x^2 = a \pmod{p}$ , p prime
2 // 2 Roots: (x, p - x), returns the smaller one
3 // (Tonelli-Shanks)  $O(\log^2 p)$ , usually  $O(\log p)$ .
4 // Pow(b, e, p):  $b^e \pmod{p}$ 
5 ll sqrtMod(ll a, ll p) { a = (a % p + p) % p;
6     if (p == 2) return a;
7     if (a == 0) return 0;
8     if (Pow(a, (p - 1) / 2, p) != 1) return -1;
9     if (p % 4 == 3) {
10         ll x = Pow(a, (p + 1) / 4, p); return min(x, p - x); }
11     ll s = p - 1, n = 2;

```

```

12 int r = 0, m;
13 while (s % 2 == 0) r++, s /= 2;
14 while (Pow(n, (p - 1) / 2, p) != p - 1) n++;
15 ll x = Pow(a, (s + 1) / 2, p);
16 ll b = Pow(a, s, p), g = Pow(n, s, p);
17 for (; r = m) {
18     ll t = b;
19     for (m = 0; m < r && t != 1; m++) t = t * t % p;
20     if (m == 0) return min(x, p - x);
21     ll gs = Pow(g, 1LL << (r - m - 1), p);
22     g = gs * gs % p;
23     x = x * gs % p;
24     b = b * g % p;
25 }

```

13.3 Discrete Log (exBSGS)

f4ee37

```

1 // Find the smallest N s.t. X^N = Y (mod P)
2 #define rep(i,a,b) for (int i = a; i <= b; i++)
3 ll Log(ll X, ll Y, ll P) { // X, Y, P any
4     X %= P, Y %= P; ll D = 1; int add = 0;
5     while (true) {
6         const auto g = gcd(X, P);
7         if (g == 1) break;
8         if (D == Y) return add;
9         if (Y % g != 0) return -1;
10        Y /= g, P /= g, add++;
11        D = D * (X / g) % P;
12    }
13    const ll B = sqrtl(P) + 1;
14    unordered_map<ll, int> mp;
15    for (ll i = 0, cur = Y; i <= B; i++) {
16        mp[cur] = i;
17        cur = cur * X % P;
18    }
19    ll step = 1;
20    rep(i, 1, B) step = step * X % P;
21    for (ll p = 1, cur = D; p <= B; p++) {
22        cur = cur * step % P;
23        if (mp.contains(cur)) {
24            return B * p - mp[cur] + add;
25        }
26    }
27    return -1;

```

13.4 Miller Rabin

bd7351

```

1 // isPrime(n): deterministic for n < 2^63; 1e6 calls ~0.25s
2 // mul(a, b, p): (__int128)a * b % p;
3 // Pow(b, e, p): b^e mod p
4 bool isPrime(ll n) {
5     if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
6     ll A[] = {2, 325, 9375, 28178, 450775, 9780504,
7               1795265022};
8     ll s = __builtin_ctzll(n - 1), d = n >> s;
9     for (ll a : A) {
10        ll p = Pow(a % n, d, n), i = s;
11        while (p != 1 && p != n - 1 && a % n && i--)
12            p = mul(p, p, n);
13        if (p != n - 1 && i != s) return 0;
14    }
15    return 1;

```

13.5 Pollard Rho

ebf488

```

1 // factorization(x): sorted (p, e) with x = prod p^e, x < 2^62
2 // needs: MillerRabin. Avg time per x (-02, worst = semiprime):
3 // x~1e9: 0.003ms | x~1e12: 0.004ms, semi 0.012ms
4 // x~1e18: 0.016ms, semi 0.33ms (~3000 semiprimes / s)
5 ll pollard(ll n) {
6     ll x = 0, y = 0, t = 30, prd = 2, i = 1, q;
7     auto f = [&](ll x) { return mul(x, x, n) + i; };
8     while (t++ % 40 || gcd(prd, n) == 1) {
9         if (x == y) x = ++i, y = f(x);
10        if ((q = mul(prd, abs(x - y), n))) prd = q;
11        x = f(x), y = f(f(y));
12    }
13    return gcd(prd, n);
14 }
15 vector<pair<ll, int>> factorization(ll x) {
16     map<ll, int> cnt;
17     auto rec = [&](auto&& self, ll x) -> void {
18         if (x == 1) return;
19         if (isPrime(x)) { cnt[x]++; return; }
20         ll d = pollard(x);
21         self(self, d), self(self, x / d);
22     };
23     rec(rec, x);
24     return {all(cnt)};
25 }

```

13.6 Linear Sieve

$O(n)$, each i crossed out once by its least prime p :

```

for i in 2..n:
    if lpf[i] == 0: lpf[i] = i, primes.pb(i), f[i] = f(p)
    for p in primes:
        if p > lpf[i] or i * p > n: break
        lpf[i*p] = p
        f[i*p] = (i % p ? f[i] * f[p] : <recurrence>)

```

Recurrence for ip when $p \mid i$ (let $i = p^k m, p \nmid m$):

- $\varphi(ip) = \varphi(i) \cdot p, \mu(ip) = 0, \sigma_0(ip) = \sigma_0(i) \cdot \frac{k+2}{k+1}$
- General: keep $pw[i] = p^k; f(ip) = f(\frac{i}{pw[i]}) \cdot f(pw[i] \cdot p)$
- $\varphi(ip) = \varphi(i) \cdot (p - [p \nmid i])$ (one formula for both cases)

Euler phi table alone (no primes): $O(n \log \log n)$

for i : $\phi[i] = i$; for p prime: for $j = p, 2p, \dots$: $\phi[j] -= \phi[j] / p$

13.7 Lucy (prime counting / prime sum)

1df76c

```

1 template<class T, class F>
2 pair<vector<T>, vector<T>> Lucy(const i64 N, const F f) {
3     const i64 sqrtN = sqrtl(N);
4     vector<T> Sl(sqrtN + 1);
5     vector<T> Sh(sqrtN + 1);
6     for (int i = 1; i <= sqrtN; i++) {
7         Sl[i] = f(i) - 1;
8         Sh[i] = f(f64(N) / i) - 1;
9     }
10    for (const int &p : primes) {
11        const i64 pp = i64(p) * p;
12        if (pp > N) break;
13        const int R = min(sqrtN, N / pp);
14        const int M = sqrtN / p;
15        const auto pi = Sl[p - 1];
16        const auto fp = Sl[p] - Sl[p - 1];
17        for (int i = 1; i <= M; i++) Sh[i] -= fp * (Sh[i * p] - pi);
18        for (int i = M + 1; i <= R; i++) Sh[i] -= fp * (Sl[N / (f64(i) * p)] - pi);
19        for (int i = sqrtN; i >= pp; i--) Sl[i] -= fp * (Sl[i / p] - pi);
20    }
21    return {Sl, Sh};
22 }

```

13.8 Black (Min25 sieve)

a652c9

```

1 template<class T, class F1, class F2>
2 T Black(const i64 N, const F1 f_prime, const F2 f_k) {
3     const i64 sqrtN = sqrtl(N);
4     const int np = int(size(primes));
5     T res = 1 + f_prime(N);
6     function<void(i64, i64, i64, T, T)> rec = [&](i64 t, i64 i, i64 c, T ft, T fu) {
7         const auto f_next = fu * f_k(primes[i], c + 1);
8         res += f_next + ft * (f_prime(f64(N) / t) - f_prime(primes[i]));
9         const i64 lim = sqrtl(f64(N) / t);
10        if (primes[i] <= lim) {
11            rec(t * primes[i], i, c + 1, f_next, fu);
12        }
13        for (int j = i + 1; j < np; j++) {
14            if (primes[j] > lim) break;
15            rec(t * primes[j], j, 1, ft * f_k(primes[j], 1), ft);
16        }
17    };
18    for (int i = 0; i < np; i++) {
19        if (primes[i] <= sqrtN) {
20            rec(primes[i], i, 1, f_k(primes[i], 1), 1);
21        }
22    }
23    return res;
24 }

```

13.9 Fast GCD

d55d7c

```

1 // O(1) gcd(x, y) for 1 <= x, y <= n after O(n) init.
2 // Use when ~1e7+ gcd queries on values <= n (e.g. sum of
3 // gcd(a[i], a[j]), gcd-convolution); else std::gcd is fine.
4 // Usage: GCD<N, SQRT> G; (global) G.init(n); G.fastGCD(x, y)
5 // N > n, SQRT > sqrt(n). Memory 20 bytes * N.
6 // -02: n=1e6 init 17ms, 20MB; n=1e7 init 0.2s, 200MB.
7 // 1e7 random queries: 0.2s (std::gcd 0.6-0.7s, ~3x).
8 template <size_t N, size_t SQRT>
9 struct GCD {
10     int sq, minp[N], gcd_table[SQRT][SQRT];
11     vector<int> primes;
12     array<int, 3> fac[N];
13     void init(const int n) {
14         sq = int(sqrt(n));
15         for (int i = 0; i <= sq; ++i)

```

```

16 gcd_table[0][i] = gcd_table[i][0] = i;
17 for (int i = 1; i <= sq; ++i)
18   for (int j = 1; j <= i; ++j)
19     gcd_table[i][j] = gcd_table[j][i] = gcd_table[j][i %
j];
20 for (int i = 1; i <= n; ++i)
21   minp[i] = i;
22 fac[1] = {1, 1, 1};
23 for (int i = 2; i <= n; ++i) {
24   if (minp[i] == i) {
25     primes.push_back(i);
26     fac[i] = {1, 1, i};
27   }
28   for (const int &p : primes) {
29     if (i * p > n) break;
30     const int j = i * p;
31     minp[j] = p;
32     fac[j] = fac[i];
33     fac[j][0] *= p;
34     ranges::sort(fac[j]);
35     if (i % p == 0) break;
36   } }
37 int fastGCD(int x, int y) {
38   int g = 1;
39   for (const int &f : fac[x]) {
40     int c = 1;
41     if (f <= sq) c = gcd_table[f][y % f];
42     else if (y % f == 0) c = f;
43     y /= c; g *= c;
44   }
45   return g;
46 }

```

13.10 CRT

255819

```

1 // Solves  $x = a \pmod m$ ,  $x = b \pmod n$ .
2 //  $m, n$  need not be coprime; asserts if no solution.
3 // Needs  $m \cdot n < 2^{62}$ -ish; extgcd returns  $a \cdot x + b \cdot y = g$ .
4 ll extgcd(ll a, ll b, ll& x, ll& y) {
5   if (!b) return x = 1, y = 0, a;
6   ll g = extgcd(b, a % b, y, x);
7   return y -= a / b * x, g;
8 }
9
10 ll crt(ll a, ll m, ll b, ll n) {
11   if (n > m) swap(a, b), swap(m, n);
12   ll x, y, g = extgcd(m, n, x, y);
13   assert((a - b) % g == 0);
14   x = (b - a) % n * x % n / g * m + a;
15   return x < 0 ? x + m * n / g : x;
16 }

```

13.11 Extended Lucas

e73902

```

1 typedef long long ll;
2 void exgcd(ll a, ll b, ll& x, ll& y) {
3   if (!b)
4     x = 1, y = 0;
5   else
6     exgcd(b, a % b, y, x), y -= a / b * x;
7 }
8 ll inv(ll a, ll p) {
9   ll x, y;
10  exgcd(a, p, x, y);
11  return (x + p) % p;
12 }
13 ll qpow(ll a, ll b, ll p) {
14   ll r = 1;
15   for (; b >= 1; a = a * a % p)
16     if (b & 1) r = r * a % p;
17   return r;
18 }
19 ll CRT(int n, ll* a, ll* m) {
20   ll M = 1, p = 0;
21   for (int i = 1; i <= n; ++i) M = M * m[i];
22   for (int i = 1; i <= n; ++i) {
23     ll w = M / m[i], x, y;
24     exgcd(w, m[i], x, y);
25     p = (p + a[i] * w * x % M) % M;
26   }
27   return (p % M + M) % M;
28 }
29 ll calc(ll n, ll x, ll P) {
30   if (!n) return 1;
31   ll s = 1;
32   for (ll i = 1; i <= P; i++)
33     if (i % x) s = s * i % P;
34   s = qpow(s, n / P, P);
35   for (ll i = n / P * P + 1; i <= n; i++)
36     if (i % x) s = i % P * s % P;
37   return s * calc(n / x, x, P) % P;

```

```

38 }
39 ll multilucas(ll n, ll m, ll x, ll P) {
40   if (n < m) return 0;
41   int cnt = 0;
42   for (ll i = n; i; i /= x) cnt += i / x;
43   for (ll i = m; i; i /= x) cnt -= i / x;
44   for (ll i = n - m; i; i /= x) cnt -= i / x;
45   return qpow(x, cnt, P) % P * calc(n, x, P) % P *
46     inv(calc(m, x, P), P) % P *
47     inv(calc(n - m, x, P), P) % P;
48 }
49 ll exlucas(ll n, ll m, ll P) {
50   int cnt = 0;
51   ll p[20], a[20];
52   for (ll i = 2; i * i <= P; i++) {
53     if (P % i == 0) {
54       p[++cnt] = 1;
55       while (P % i == 0) p[cnt] = p[cnt] * i, P /= i;
56       a[cnt] = multilucas(n, m, i, p[cnt]);
57     }
58   }
59   if (P > 1) p[++cnt] = P, a[cnt] = multilucas(n, m, P, P);
60   return CRT(cnt, a, p);
61 }

```

13.12 Divisor Block

b5dde6

```

1 // calls  $f(l, r, q)$  for each maximal  $[l, r]$  with  $\text{floor}(n/i) = q$ 
2 void divisorBlock(ll n, auto f) {
3   for (ll l = 1, r, q; l <= n; l = r + 1) {
4     q = n / l, r = n / q;
5     f(l, r, q);
6   }
7   /* Example: sum of  $\text{floor}(n/i)$ ,  $i$  from 1 to  $n$ 
8   ll ans = 0;
9   divisorBlock(n, [&](ll l, ll r, ll q) {
10     ans += q * (r - l + 1);
11   }); */

```

13.13 Formulas

- Pisano Period: 任何線性遞迴 (比如費氏數列) 模任何一個數字 M 都會循環, 找循環節 $\pi(M)$ 先質因數分解 $M = \prod p_i^{e_i}$, 然後 $\pi(M) = \text{lcm}(\pi(p_i^{e_i}))$
- Inversion: $aa^{-1} \equiv 1 \pmod m$, exists iff $\gcd(a, m) = 1$. Linear: $a^{-1} \equiv (m - \lfloor \frac{m}{a} \rfloor) \times (m \bmod a)^{-1} \pmod m$
- Fermat: $a^p \equiv a \pmod p$; Euler: $a^{\varphi(n)} \equiv 1 \pmod n$ if $\gcd(a, n) = 1$. Not coprime: 分解 $n = \prod p_i^{e_i}$, 對每個 $p_i^{e_i}$ 分開看 (互質: Euler / 不互質: 指數 $\geq e_i$ 直接是 0), 最後 CRT 合併. Also $a^b \equiv a^{b \bmod \varphi(n) + \varphi(n)} \pmod n$ for $b \geq \log_2 n$.
- Wilson: $(p-1)! \equiv -1 \pmod p$
- $\varphi(n) = n \prod_{p|n} (1 - \frac{1}{p})$, $\sum_{d|n} \varphi(d) = n$
- Divisor function: $n = \prod p_i^{a_i}$, $\sigma_x(n) = \prod \frac{p_i^{(a_i+1)x} - 1}{p_i^x - 1}$ ($x \neq 0$), $\sigma_0(n) = \prod (a_i + 1)$
- CRT (coprime): $M = \prod m_i$, $M_i = \frac{M}{m_i}$, $x = \sum a_i M_i (M_i^{-1} \bmod m_i) \pmod M$
General: $x = m_1 p + a_1 = m_2 q + a_2 \Rightarrow m_1 p - m_2 q = a_2 - a_1$, solve by extgcd, answer mod $\text{lcm}(m_1, m_2)$
- Avoiding overflow: $ca \bmod cb = c(a \bmod b)$
- Dirichlet convolution: $(f * g)(n) = \sum_{d|n} f(d)g(\frac{n}{d})$. $\varepsilon(n) = [n = 1]$, $1(n) = 1$, $id(n) = n$; $\mu * 1 = \varepsilon$, $\varphi = \mu * id$, $id = \varphi * 1$, $\sigma_0 = 1 * 1$, $\sigma_1 = id * 1$
- $[\gcd(a, b) = 1] = \sum_{d|\gcd(a, b)} \mu(d)$; Möbius inversion: $f = g * 1 \Leftrightarrow g = f * \mu$
- $\sum_{i=1}^n \sum_{j=1}^m [\gcd(i, j) = 1] = \sum_d \mu(d) \lfloor \frac{n}{d} \rfloor \lfloor \frac{m}{d} \rfloor$ (divisor block, $O(\sqrt{n})$ per query)
- Legendre: $v_p(n!) = \sum_{k \geq 1} \lfloor \frac{n}{p^k} \rfloor = \frac{n - s_p(n)}{p-1}$, s_p = digit sum in base p
- Lucas (p prime): $\binom{n}{m} \equiv \prod_i \binom{n_i}{m_i} \pmod p$ over base- p digits; Kummer: $v_p\left(\binom{n}{m}\right)$ = number of carries adding $m + (n - m)$ in base p

14 Polynomial

14.1 Generating Functions

OGF $A(x) = \sum a_i x^i$; $A(rx) \Rightarrow r^n a_n$; $AB \Rightarrow \sum_i a_i b_{n-i}$; $A^k \Rightarrow \sum_{i_1+\dots+i_k=n} a_{i_1} \dots a_{i_k}$; $xA'(x) \Rightarrow na_n$; $\frac{A(x)}{1-x} \Rightarrow \sum_{i \leq n} a_i$.
EGF $A(x) = \sum a_i \frac{x^i}{i!}$; $A^{(k)}(x) \Rightarrow a_{n+k}$; $AB \Rightarrow \sum_i \binom{n}{i} a_i b_{n-i}$; $A^k \Rightarrow \sum_{i_1+\dots+i_k=n} a_{i_1} \dots a_{i_k}$; $xA' \Rightarrow na_n$.
 $(1+x)^n = \sum \binom{n}{i} x^i$, $\frac{1}{(1-x)^n} = \sum \binom{i+n-1}{n-1} x^i$, $\frac{1}{1-x} = \sum x^i$,
 $e^x = \sum \frac{x^i}{i!}$, $-\ln(1-x) = \sum_{i \geq 1} \frac{x^i}{i}$
Catalan $C(x) = \frac{1-\sqrt{1-4x}}{2x}$; Fibonacci $\frac{x}{1-x-x^2}$; $\sum_i ix^i = \frac{x}{(1-x)^2}$; partitions $\prod_k \frac{1}{1-x^k}$.

14.2 NTT

b4c099

```

1 // mod 998244353, Requirement: ModBasic.cpp
2 const int N = 1 << 20, G = 3;
3 using Poly = vector<ll>;
4
5 struct NTT {
6     ll w[N];
7     NTT() {
8         ll dw = Pow(G, (mod - 1) / N);
9         w[0] = 1;
10        for (int i = 1; i < N; i++)
11            w[i] = mul(w[i - 1], dw);
12    }
13    void operator()(Poly& a, bool inv = false) {
14        int n = sz(a);
15        for (int j = 1, x = 0; j < n - 1; j++) {
16            for (int k = n >> 1; (x ^ k) < k; k >>= 1);
17            if (j < x) swap(a[x], a[j]);
18        }
19        for (int L = 2; L <= n; L <= 1) {
20            int dx = N / L, dl = L >> 1;
21            for (int i = 0; i < n; i += L)
22                for (int j = i, x = 0; j < i + dl; j++, x += dx) {
23                    ll tmp = mul(a[j + dl], w[x]);
24                    a[j + dl] = sub(a[j], tmp);
25                    a[j] = add(a[j], tmp);
26                }
27        }
28        if (inv) {
29            reverse(1 + all(a));
30            ll invn = Pow(n, mod - 2);
31            for (ll& x : a) x = mul(x, invn);
32        }
33    } ntt;
34    // polyMul: a*b truncated to bound terms, O(n log n).
35    // Result length must be <= N.
36    Poly polyMul(Poly a, Poly b, int bound = N) {
37        int m = sz(a) + sz(b) - 1, n = 1;
38        while (n < m) n <= 1;
39        a.resize(n), b.resize(n);
40        ntt(a), ntt(b);
41        for (int i = 0; i < n; i++) a[i] = mul(a[i], b[i]);
42        ntt(a, true);
43        a.resize(min(m, bound));
44        return a;
45    }
46    // NTT primes & primitive roots (p = c * 2^k + 1)
47    // max convolution length (|a|+|b|-1) = 2^k
48    // Prime = c * 2^k + 1
49    // 7681 = 15 * 2^9 + 1
50    // 12289 = 3 * 2^12 + 1
51    // 40961 = 5 * 2^13 + 1
52    // 65537 = 1 * 2^16 + 1
53    // 786433 = 3 * 2^18 + 1
54    // 5767169 = 11 * 2^19 + 1
55    // 7340033 = 7 * 2^20 + 1
56    // 23068673 = 11 * 2^21 + 1
57    // 104857601 = 25 * 2^22 + 1
58    // 985661441 = 235 * 2^22 + 1
59    // 998244353 = 119 * 2^23 + 1
60    // 2810183681 = 335 * 2^23 + 1
61    // 167772161 = 5 * 2^25 + 1
62    // 1107296257 = 33 * 2^25 + 1
63    // 469762049 = 7 * 2^26 + 1
64    // 2885681153 = 43 * 2^26 + 1
65    // 2013265921 = 15 * 2^27 + 1
66    // 605028353 = 577 * 2^20 + 1
67    // 2061584302081 = 15 * 2^37 + 1
68    // 2748779069441 = 5 * 2^39 + 1
69    // 1945555039024054273 = 27 * 2^56 + 1
70    // 72057594037927936

```

14.3 FFT

a6c438

```

1 // Rounding is safe if
2 // (sum a[i]^2 + sum b[i]^2) log2(N) < 9e14.
3 // In practice, 1e16 or higher often works.
4 using C = complex<double>;
5 using vd = vector<double>;
6
7 void fft(vector<C>& a) {
8     int n = sz(a), L = 31 - __builtin_clz(n);
9     static vector<complex<long double>> R(2, 1);
10    static vector<C> rt(2, 1);
11    for (static int k = 2; k < n; k *= 2) {
12        R.resize(n), rt.resize(n);
13        auto x = polar(1.0L, acos(-1.0L) / k);
14        for (int i = k; i < 2 * k; i++)
15            rt[i] = R[i] = i & 1 ? R[i / 2] * x : R[i / 2];
16    }

```

```

17 vi rev(n);
18 for (int i = 0; i < n; i++)
19     rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
20 for (int i = 0; i < n; i++)
21     if (i < rev[i]) swap(a[i], a[rev[i]]);
22 for (int k = 1; k < n; k *= 2)
23     for (int i = 0; i < n; i += 2 * k)
24         for (int j = 0; j < k; j++) {
25             auto* x = (double*)&rt[j + k];
26             auto* y = (double*)&a[i + j + k];
27             C z(x[0] * y[0] - x[1] * y[1],
28                x[0] * y[1] + x[1] * y[0]);
29             a[i + j + k] = a[i + j] - z;
30             a[i + j] += z;
31         }
32 }
33
34 vd convFFT(const vd& a, const vd& b) {
35     if (a.empty() || b.empty()) return {};
36     vd res(sz(a) + sz(b) - 1);
37     int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
38     vector<C> in(n), out(n);
39     copy(all(a), begin(in));
40     for (int i = 0; i < sz(b); i++) in[i].imag(b[i]);
41     fft(in);
42     for (C& x : in) x *= x;
43     for (int i = 0; i < n; i++)
44         out[i] = in[-i & (n - 1)] - conj(in[i]);
45     fft(out);
46     for (int i = 0; i < sz(res); i++)
47         res[i] = imag(out[i]) / (4 * n);
48     return res;
49 }

```

14.4 FFT Mod (arbitrary modulus)

185078

```

1 // Higher precision FFT convolution modulo M.
2 // Safe when N log2(N) M < 8.6e14.
3 // Inputs are in [0,M), with M < 2^31-ish.
4 // needs: FFT
5 vector<ll> convMod(const vector<ll>& a,
6                    const vector<ll>& b, ll M) {
7     if (a.empty() || b.empty()) return {};
8     vector<ll> res(sz(a) + sz(b) - 1);
9     int B = 32 - __builtin_clz(sz(res)), n = 1 << B;
10    int cut = int(sqrt(M));
11    vector<C> L(n), R(n), outs(n), outl(n);
12    for (int i = 0; i < sz(a); i++)
13        L[i] = C((int)(a[i] / cut), (int)(a[i] % cut));
14    for (int i = 0; i < sz(b); i++)
15        R[i] = C((int)(b[i] / cut), (int)(b[i] % cut));
16    fft(L), fft(R);
17    for (int i = 0; i < n; i++) {
18        int j = -i & (n - 1);
19        outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
20        outs[j] = (L[i] - conj(L[j])) * R[i]
21            / (2.0 * n * C(0, 1));
22    }
23    fft(outl), fft(outs);
24    for (int i = 0; i < sz(res); i++) {
25        ll av = ll(real(outl[i]) + .5);
26        ll cv = ll(imag(outs[i]) + .5);
27        ll bv = ll(imag(outl[i]) + .5) + ll(real(outs[i]) + .5);
28        res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
29    }
30    return res;
31 }

```

14.5 FWHT

8e386a

```

1 using Poly = vector<ll>;
2
3 // op: 0 = AND, 1 = OR, 2 = XOR; inv = inverse transform
4 // conv: fwt(a,op), fwt(b,op), a[i] = mul(a[i], b[i]),
5 // fwt(a,op,1) => a is the answer
6 void fwt(vector<ll>& a, int op, bool inv = false) {
7     int n = a.size(); ll i2 = (mod + 1) / 2;
8     for (int s = 1; s < n; s <= 1)
9         for (int i = 0; i < n; i += s << 1)
10            for (int j = i; j < i + s; j++) {
11                ll &x = a[j], &y = a[j + s];
12                if (op == 0) x = inv ? sub(x, y) : add(x, y);
13                else if (op == 1) y = inv ? sub(y, x) : add(y, x);
14                else {
15                    tie(x, y) = pair(add(x, y), sub(x, y));
16                    if (inv) x = mul(x, i2), y = mul(y, i2);
17                }
18            }
19 }

```

14.6 Polynomial Operations

b9f6d5

1 // needs: NTT

```

2// needs: ModSqrt
3// polyInv(a): inverse modulo x^n, a[0] != 0.
4Poly polyInv(Poly a) {
5    int n = sz(a);
6    Poly res(1, Pow(a[0], mod - 2));
7    for (int m = 1; m < n; m <= 1) {
8        if (n < m * 2) a.resize(m * 2);
9        Poly v1(a.begin(), a.begin() + m * 2), v2 = res;
10       v1.resize(m * 4), v2.resize(m * 4);
11       ntt(v1), ntt(v2);
12       for (int i = 0; i < m * 4; i++)
13           v1[i] = mul(mul(v1[i], v2[i]), v2[i]);
14       ntt(v1, true);
15       res.resize(m * 2);
16       for (int i = 0; i < m; i++) res[i] = add(res[i],
17           res[i]);
18       for (int i = 0; i < m * 2; i++)
19           res[i] = sub(res[i], v1[i]);
20   }
21   res.resize(n);
22   return res;
23 }
24// polyDiv(a,b): a = bQ + R, b.back() != 0.
25pair<Poly, Poly> polyDiv(Poly a, Poly b) {
26    int n = sz(a), m = sz(b), k = n - m + 1;
27    if (n < m) return {{0}, a};
28    Poly ra = a, rb = b;
29    reverse(all(ra)), ra.resize(k);
30    reverse(all(rb)), rb.resize(k);
31    Poly q = polyMul(ra, polyInv(rb), k);
32    reverse(all(q));
33    Poly res = polyMul(b, q), r(m - 1);
34    for (int i = 0; i < m - 1; i++) r[i] = sub(a[i], res[i]);
35    return {q, r};
36 }
37
38// polySqrt(a): square root modulo x^n; asserts if a[0]
39// not a residue.
40Poly polySqrt(Poly a) {
41    if (a.empty()) return {0};
42    int n = sz(a), m = 0;
43    while (m < n && a[m] == 0) m++;
44    if (m == n) return Poly(n);
45    if (m & 1) return {-1};
46    a.erase(a.begin(), a.begin() + m);
47    ll z = sqrtMod(a[0], mod);
48    Poly q(1, z);
49    ll inv2 = (mod + 1) / 2;
50    for (int k = 1; k < n - m + 1; k <= 1) {
51        if (n - m < k * 2) a.resize(k * 2);
52        q.resize(k * 2);
53        Poly f2 = polyMul(q, q, k * 2);
54        for (int i = 0; i < k * 2; i++) f2[i] = sub(f2[i],
55            a[i]);
56        f2 = polyMul(f2, polyInv(q), k * 2);
57        for (int i = 0; i < k * 2; i++)
58            q[i] = sub(q[i], mul(f2[i], inv2));
59    }
60    q.resize(n - m);
61    Poly res(n);
62    for (int i = 0; i < sz(q); i++) res[i + m / 2] = q[i];
63    return res;
64 }
65Poly deriv(Poly a) {
66    int n = sz(a);
67    Poly res(max(0, n - 1));
68    for (int i = 0; i < n - 1; i++)
69        res[i] = mul(a[i + 1], i + 1);
70    return res;
71 }
72
73Poly integ(Poly a) {
74    int n = sz(a);
75    Poly res(n + 1);
76    for (int i = 0; i < n; i++)
77        res[i + 1] = mul(a[i], Pow(i + 1, mod - 2));
78    return res;
79 }
80
81// polyLn(a): formal logarithm, a[0] = 1.
82Poly polyLn(Poly a) {
83    int n = sz(a);
84    if (n == 1) return {0};
85    Poly d = deriv(a);
86    a.pop_back();
87    return integ(polyMul(d, polyInv(a), n - 1));
88 }

```

```

89
90// polyExp(a): formal exponential, a[0] = 0.
91Poly polyExp(Poly a) {
92    int n = sz(a);
93    Poly q(1, 1);
94    a[0] = add(a[0], 1);
95    for (int m = 1; m < n; m <= 1) {
96        if (n < m * 2) a.resize(m * 2);
97        Poly g(a.begin(), a.begin() + m * 2), h = q;
98        h.resize(m * 2), h = polyLn(h);
99        for (int i = 0; i < m * 2; i++) g[i] = sub(g[i], h[i]);
100       q = polyMul(g, q, m * 2);
101   }
102   q.resize(n);
103   return q;
104 }
105
106Poly polyPow(Poly a, ll k) {
107    int n = sz(a), m = 0;
108    Poly ans(n);
109    if (!k) return ans[0] = 1, ans;
110    while (m < n && a[m] == 0) m++;
111    if (k && m && (k >= n || k * m >= n)) return ans;
112    if (m == n) return ans[0] = 1, ans;
113    int lead = m * k;
114    Poly b(a.begin() + m, a.end());
115    ll base = Pow(b[0], k), inv = Pow(b[0], mod - 2);
116    for (int i = 0; i < n - m; i++) b[i] = mul(b[i], inv);
117    b = polyLn(b);
118    for (ll& x : b) x = mul(x, k % mod);
119    b = polyExp(b);
120    for (int i = lead; i < n; i++)
121        ans[i] = mul(b[i - lead], base);
122    return ans;
123 }
124
125vector<ll> evaluate(Poly a, vector<ll> x) {
126    if (x.empty()) return {};
127    int n = sz(x);
128    vector<Poly> up(n * 2);
129    for (int i = 0; i < n; i++) up[i + n] = {sub(0, x[i]), 1};
130    for (int i = n - 1; i > 0; i--)
131        up[i] = polyMul(up[i * 2], up[i * 2 + 1]);
132    vector<Poly> down(n * 2);
133    down[1] = polyDiv(a, up[1]).second;
134    for (int i = 2; i < n * 2; i++)
135        down[i] = polyDiv(down[i >> 1], up[i]).second;
136    vector<ll> y(n);
137    for (int i = 0; i < n; i++) y[i] = down[i + n][0];
138    return y;
139 }
140
141Poly interpolate(vector<ll> x, vector<ll> y) {
142    int n = sz(x);
143    vector<Poly> up(n * 2);
144    for (int i = 0; i < n; i++) up[i + n] = {sub(0, x[i]), 1};
145    for (int i = n - 1; i > 0; i--)
146        up[i] = polyMul(up[i * 2], up[i * 2 + 1]);
147    Poly a = evaluate(deriv(up[1]), x);
148    for (int i = 0; i < n; i++)
149        a[i] = mul(y[i], Pow(a[i], mod - 2));
150    vector<Poly> down(n * 2);
151    for (int i = 0; i < n; i++) down[i + n] = {a[i]};
152    for (int i = n - 1; i > 0; i--) {
153        Poly lhs = polyMul(down[i * 2], up[i * 2 + 1]);
154        Poly rhs = polyMul(down[i * 2 + 1], up[i * 2]);
155        down[i].resize(sz(lhs));
156        for (int j = 0; j < sz(lhs); j++)
157            down[i][j] = add(lhs[j], rhs[j]);
158    }
159    return down[1];
160 }

```

14.7 Berlekamp Massey

b65456

```

1// Returns c with s[i] = \sum c[j] * s[i-1-j].
2// 0(n^2); you should provide at least 2k samples for order
3// k.
4// Require: ModBasic.cpp
5using Poly = vector<ll>;
6Poly berlekampMassey(Poly s) {
7    int n = s.size(), L = 0, m = 0;
8    Poly C(n), B(n), T;
9    C[0] = B[0] = 1; ll b = 1;
10   for (int i = 0; i < n; i++) {
11       m++; ll d = s[i] % mod;
12       for (int j = 1; j <= L; j++)
13           d = add(d, mul(C[j], s[i - j]));
14       if (!d) continue;
15       T = C;

```

```

15 ll coef = mul(d, Pow(b, mod - 2));
16 for (int j = m; j < n; j++)
17   C[j] = sub(C[j], mul(coef, B[j - m]));
18 if (2 * L > i) continue;
19 L = i + 1 - L;
20 B = T, b = d, m = 0;
21 }
22 C.resize(L + 1);
23 C.erase(C.begin());
24 for (ll& x : C) x = x ? mod - x : 0;
25 return C;
26 }
27 /* Example: Fibonacci
28 Poly s = {0, 1, 1, 2, 3, 5, 8, 13};
29 Poly c = berlekampMassey(s); // c = {1, 1}, k = 2
30 ll ans = linearRec(s, c, (ll)1e18); // find fib(1e18) */

```

14.8 Linear Recurrence (Kitamasa)

496400

```

1 // k-th term of a recurrence in O(n^2 log k)
2 // S[i] = \sum C[j] * S[i-1-j]
3 // Example: linearRec({0,1},{1,1},k) returns Fib(k).
4 // Require: ModBasic.cpp
5 using Poly = vector<ll>;
6 ll linearRec(Poly S, Poly C, ll k) {
7   int n = C.size();
8   auto combine = [&](Poly a, Poly b) {
9     Poly res(n * 2 + 1);
10    for (int i = 0; i <= n; i++)
11      for (int j = 0; j <= n; j++)
12        res[i + j] = add(res[i + j], mul(a[i], b[j]));
13    for (int i = 2 * n; i > n; i--)
14      for (int j = 0; j < n; j++)
15        res[i - 1 - j] = add(res[i - 1 - j],
16                             mul(res[i], C[j]));
17    res.resize(n + 1);
18    return res;
19  };
20 Poly pol(n + 1, e(pol));
21 pol[0] = e[1] = 1;
22 for (++k; k; k /= 2) {
23   if (k % 2) pol = combine(pol, e);
24   e = combine(e, e);
25 }
26 ll res = 0;
27 for (int i = 0; i < n; i++)
28   res = add(res, mul(pol[i + 1], S[i]));
29 return res;
30 }

```

14.9 Lagrange Interpolation (iota points)

8075cc

```

1 Mint lagrange_iota(const vector<Mint> &f, const int c) {
2   const int n = int(size(f));
3   if (c < n) {
4     return f[c];
5   }
6   vector<Mint> fac(n), ifac(n);
7   fac[0] = 1;
8   for (int i = 1; i < n; i++) fac[i] = fac[i - 1] * i;
9   ifac[n - 1] = fac[n - 1].inv();
10  for (int i = n - 1; i >= 1; i--) ifac[i - 1] = ifac[i] *
11  i;
12  vector<Mint> g(n);
13  for (int i = 0; i < n; i++) {
14    g[i] = f[i] * ifac[i] * ifac[n - 1 - i];
15    if ((n - 1 - i) & 1) g[i] *= -1;
16  }
17  vector<Mint> lp(n + 1), rp(n + 1);
18  lp[0] = rp[n] = 1;
19  for (int i = 0; i < n; i++) lp[i + 1] = lp[i] * Mint(c -
20  i);
21  for (int i = n - 1; i >= 0; i--) rp[i] = rp[i + 1] *
22  Mint(c - i);
23  Mint ans = 0;
24  for (int i = 0; i < n; i++) ans += g[i] * lp[i] * rp[i +
25  1];
26  return ans;
27 }

```

15 Linear Algebra

15.1 Gauss (mod p)

dad24a

```

1 // In-place RREF over Z_mod (mod prime); returns {rank,
2 det}.
3 // det is valid only when A is square.
4 // Values must be normalized.
5 pair<int, ll> gauss(vector<vector<ll>>& A) {
6   int n = A.size(), m = A[0].size();
7   int rank = 0; ll det = 1;
8   for (int c = 0; c < m && rank < n; c++) {
9     int piv = rank;
10    while (piv < n && !A[piv][c]) piv++;

```

```

10    if (piv == n) { det = 0; continue; }
11    if (piv != rank) {
12      swap(A[piv], A[rank]);
13      det = sub(0, det);
14    }
15    ll inv = Pow(A[rank][c], mod - 2);
16    det = mul(det, A[rank][c]);
17    for (ll& x : A[rank]) x = mul(x, inv);
18    for (int i = 0; i < n; i++) if (i != rank && A[i][c]) {
19      ll f = A[i][c];
20      for (int j = c; j < m; j++)
21        A[i][j] = sub(A[i][j], mul(f, A[rank][j]));
22    }
23    rank++;
24  }
25  return {rank, det};
26 }

```

15.2 Solve Linear Equations

07cff4

```

1 // Author: Gino
2 // solve(Augmented Matrix), nullity == -1 if no solution
3 struct Solution {
4   int nullity; vector<ll> xp; vector<vector<ll>> basis;
5 };
6 Solution solve(vector<vector<ll>>& A) { // augmented matrix
7   int n = A.size(), m = A[0].size() - 1;
8   auto [rank, det] = gauss(A);
9   for (int i = 0; i < n; i++) if (A[i][m] != 0) {
10     if (ranges::all_of(A[i] | views::take(m),
11                        [](ll x) { return x == 0; }))
12       return {-1, {}, {}};
13   }
14   Solution sol;
15   vector<int> pcol(rank); // pivot columns
16   vector<bool> isp(m, false); // is the column a pivot?
17   for (int i = 0; i < rank; i++) {
18     auto it = ranges::find(A[i], 1);
19     pcol[i] = ranges::distance(A[i].begin(), it);
20     isp[pcol[i]] = true;
21   }
22   sol.nullity = m - rank;
23   sol.xp.assign(m, 0);
24   for (int i = 0; i < rank; i++) sol.xp[pcol[i]] = A[i][m];
25   for (int j = 0; j < m; j++) if (!isp[j]) {
26     vector<ll> d(m, 0); d[j] = 1;
27     for (int i = 0; i < rank; i++) d[pcol[i]] = sub(0, A[i]
28 [j]);
29     sol.basis.push_back(d);
30   }
31   return sol;

```

15.3 Gauss (GF(2) / XOR basis)

c8d703

```

1 // In-place RREF over GF(2); rows are bitsets, m = #columns.
2 // Returns {rank, det}; det is valid only when A is square.
3 // For an XOR basis, run it and read the nonzero rows.
4 const int N = 1000;
5 using bs = bitset<N>;
6 pair<int, int> gaussBinary(vector<bs>& A, int m) {
7   int n = A.size(), rank = 0;
8   for (int c = 0; c < m && rank < n; c++) {
9     int piv = rank;
10    while (piv < n && !A[piv][c]) piv++;
11    if (piv == n) continue;
12    swap(A[piv], A[rank]);
13    for (int i = 0; i < n; i++)
14      if (i != rank && A[i][c]) A[i] ^= A[rank];
15    rank++;
16  }
17  return {rank, n == m && rank == n};
18 }

```

15.4 Solve Linear Equations (GF(2))

7324a9

```

1 // solveBinary(A, m): A is augmented (column m is b),
2 // m = #variables. nullity == -1 if no solution.
3 struct BinSolution { int nullity; bs xp; vector<bs>
4 basis; };
5 BinSolution solveBinary(vector<bs>& A, int m) {
6   int n = A.size();
7   auto [rank, det] = gaussBinary(A, m + 1);
8   for (int i = 0; i < n; i++) // row: 0 ... 0 | 1
9     if ((int)A[i].Find_first() == m) return {-1, {}, {}};
10  BinSolution sol{m - rank, {}, {}};
11  vector<int> pcol(rank); // pivot columns
12  bs isp; // is the column a pivot?
13  for (int i = 0; i < rank; i++) {
14    pcol[i] = A[i].Find_first();
15    isp[pcol[i]] = 1; sol.xp[pcol[i]] = A[i][m];
16  }
17  for (int j = 0; j < m; j++) if (!isp[j]) {

```

```

17     bs d; d[j] = 1;
18     for (int i = 0; i < rank; i++) d[pcol[i]] = A[i][j];
19     sol.basis.push_back(d);
20 }
21 return sol;
22 }

```

15.5 Determinant

- Row swap: $-\det$; $k\vec{r}_i$: $k\det$; $\vec{r}_i + k\vec{r}_j$: unchanged; $\det(A^T) = \det(A)$, $\det(AB) = \det(A)\det(B)$.
- Matrix-tree: number of spanning trees = any cofactor of Laplacian $D - A$. Directed (arborescences rooted at r): delete row/col r of $D_{in} - A$.
- Cayley: n^{n-2} labeled trees; forests of k rooted trees on given roots: kn^{n-k-1} .

16 Numerical

16.1 Integrate (Simpson / adaptive)

6fe0fe

```

1// Simpson integration has fourth-order error
2// in the step size.
3template<class F>
4double simpsonPart(double a, double b, F& f) {
5    double c = (a + b) / 2;
6    return (f(a) + 4 * f(c) + f(b)) * (b - a) / 6;
7}
8
9template<class F>
10double simpson(double a, double b, F f, int n = 1000) {
11    double h = (b - a) / (2 * n);
12    double v = f(a) + f(b);
13    for (int i = 1; i < 2 * n; i++)
14        v += f(a + i*h) * (i&1 ? 4 : 2);
15    return v * h / 3;
16}
17
18// Adaptive Simpson integration to absolute error eps.
19template<class F>
20double adaptiveSimpson(F& f, double a, double b,
21    double eps, double whole) {
22    double c = (a + b) / 2;
23    double left = simpsonPart(a, c, f);
24    double right = simpsonPart(c, b, f);
25    double sum = left + right;
26    if (abs(sum - whole) <= 15 * eps ||
27        abs(b - a) < 1e-10)
28        return sum + (sum - whole) / 15;
29    return adaptiveSimpson(f, a, c, eps / 2, left) +
30        adaptiveSimpson(f, c, b, eps / 2, right);
31}
32
33template<class F>
34double quad(double a, double b, F f, double eps = 1e-8) {
35    return adaptiveSimpson(f, a, b, eps, simpsonPart(a, b,
36    f));
37}

```

16.2 Linear Programming

Standard form: $\max c^T x$ s.t. $Ax \leq b, x \geq 0$. Dual: $\min b^T y$ s.t. $A^T y \geq c, y \geq 0$; optima equal (strong duality). Complementary slackness: $\bar{x}_i, \bar{y}_j$ optimal iff for all i : $\bar{x}_i = 0$ or $\sum_j A_{ji} \bar{y}_j = c_i$, and for all j : $\bar{y}_j = 0$ or $\sum_i A_{ji} \bar{x}_i = b_j$. To standard form: minimize $\Rightarrow$ negate c ; $\geq$ row $\Rightarrow$ negate row; $=$ row $\Rightarrow$ both $\leq$ and $\geq$; free $x_i \Rightarrow x_i - x_i'$.

16.3 Simplex

66d762

```

1// Maximize c^T x subject to Ax <= b, x >= 0.
2// Returns -inf if infeasible, inf if unbounded.
3// Otherwise returns the maximum value and stores x.
4// Numerical stability is not guaranteed.
5using T = double;
6using vd = vector<T>;
7using vvd = vector<vd>;
8
9const T eps = 1e-8;
10const T inf = numeric_limits<T>::infinity();
11
12struct LPSolver {
13    int m, n;
14    vi N, B;
15    vvd D;
16
17    LPSolver(const vvd& A, const vd& b, const vd& c)
18        : m(sz(b)), n(sz(c)), N(n + 1), B(m),
19        D(m + 2, vd(n + 2)) {
20        for (int i = 0; i < m; i++)
21            for (int j = 0; j < n; j++) D[i][j] = A[i][j];
22        for (int i = 0; i < m; i++) {
23            B[i] = n + i;
24            D[i][n] = -1;
25            D[i][n + 1] = b[i];

```

```

26    }
27    for (int j = 0; j < n; j++) D[m][j] = -c[j];
28    N[n] = -1;
29    D[m + 1][n] = 1;
30 }
31
32 void pivot(int r, int s) {
33     T* a = D[r].data();
34     T inv = 1 / a[s];
35     for (int i = 0; i < m + 2; i++) if (i != r &&
36         abs(D[i][s]) > eps) {
37         T* b = D[i].data();
38         T inv2 = b[s] * inv;
39         for (int j = 0; j < n + 2; j++) b[j] -= a[j] * inv2;
40         b[s] = a[s] * inv2;
41     }
42     for (int j = 0; j < n + 2; j++)
43         if (j != s) D[r][j] *= inv;
44     for (int i = 0; i < m + 2; i++)
45         if (i != r) D[i][s] *= -inv;
46     D[r][s] = inv;
47     swap(B[r], N[s]);
48 }
49
50 bool simplex(int phase) {
51     int x = m + phase - 1;
52     for (;;) {
53         int s = -1;
54         for (int j = 0; j <= n; j++) {
55             if (N[j] == -phase) continue;
56             if (s == -1 || pair(D[x][j], N[j]) <
57                 pair(D[x][s], N[s])) s = j;
58         }
59         if (D[x][s] >= -eps) return true;
60         int r = -1;
61         for (int i = 0; i < m; i++) {
62             if (D[i][s] <= eps) continue;
63             if (r == -1 || pair(D[i][n + 1] / D[i][s], B[i]) <
64                 pair(D[r][n + 1] / D[r][s], B[r])) r = i;
65         }
66         if (r == -1) return false;
67         pivot(r, s);
68     }
69 }
70
71 T solve(vd& x) {
72     int r = 0;
73     for (int i = 1; i < m; i++)
74         if (D[i][n + 1] < D[r][n + 1]) r = i;
75     if (D[r][n + 1] < -eps) {
76         pivot(r, n);
77         if (!simplex(2) || D[m + 1][n + 1] < -eps) return -
78         inf;
79     }
80     for (int i = 0; i < m; i++) if (B[i] == -1) {
81         int s = 0;
82         for (int j = 1; j <= n; j++)
83             if (s == 0 || pair(D[i][j], N[j]) <
84                 pair(D[i][s], N[s])) s = j;
85         pivot(i, s);
86     }
87     bool ok = simplex(1);
88     x = vd(n);
89     for (int i = 0; i < m; i++)
90         if (B[i] < n) x[B[i]] = D[i][n + 1];
91     return ok ? D[m][n + 1] : inf;
92 }

```

17 Combinatorics

17.1 Catalan Number

$$C_0 = 1, C_n = \sum_{i=0}^{n-1} C_i C_{n-1-i}, C_n = C_n^{2n} - C_{n-1}^{2n}$$

0	1	1	2	5
4	14	42	132	429
8	1430	4862	16796	58786
12	208012	742900	2674440	9694845

17.2 Bertrand's Ballot Theorem

- A always $> B$: $C(p+q, p) - 2C(p+q-1, p)$
- A always $\geq B$: $C(p+q, p) \times \frac{p+1-q}{p+1}$

17.3 Burnside's Lemma

Let X be the original set.

Let G be the group of operations acting on X .

Let X^g be the set of x not affected by g .
Let X/G be the set of orbits. Then the following equation holds:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

17.4 Binomial Identities

- Vandermonde: $\sum_k \binom{m}{k} \binom{n}{r-k} = \binom{m+n}{r}$; $\sum_k \binom{n}{k}^2 = \binom{2n}{n}$;
- Hockey stick: $\sum_{i=r}^n \binom{i}{r} = \binom{n+1}{r+1}$; $\sum_k k \binom{n}{k} = n2^{n-1}$; $\binom{n}{k} = \frac{n}{k} \binom{n-1}{k-1}$
- Stars and bars: $x_1 + \dots + x_k = n, x_i \geq 0$: $\binom{n+k-1}{k-1}$
- Catalan: $C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1}$; paths from $(0, 0)$ to (a, b) never above $y = x$ ($a \geq b$): $\binom{a+b}{b} - \binom{a+b}{b-1}$

17.5 Stirling Numbers

- 1st kind (permutations of n with k cycles): $c(n, k) = c(n-1, k-1) + (n-1)c(n-1, k)$; $\sum_k c(n, k)x^k = x(x+1)\dots(x+n-1)$
- 2nd kind (partitions of n into k nonempty sets): $S(n, k) = S(n-1, k-1) + kS(n-1, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$ (a convolution, one row in $O(n \log n)$)
- $x^n = \sum_k S(n, k)x^k$, $x^k = x(x-1)\dots(x-k+1)$; Bell $B_n = \sum_k S(n, k)$
- Surjections $n \rightarrow k$: $k!S(n, k)$

17.6 Derangement / Inclusion-Exclusion

- $D_n = (n-1)(D_{n-1} + D_{n-2}) = nD_{n-1} + (-1)^n = n! \sum_{k=0}^n \frac{(-1)^k}{k!}$;
 $D_0 = 1, D_1 = 0, D_2 = 1, D_3 = 2, D_4 = 9, D_5 = 44$
- $|\cup A_i| = \sum_{\emptyset \neq S} (-1)^{|S|+1} |\cap_{i \in S} A_i|$; “exactly k of n properties”:
 $\sum_{j \geq k} (-1)^{j-k} \binom{j}{k} N_j$ where N_j = sum over j -subsets of $| \cap |$
- Binomial inversion: $f(n) = \sum_k \binom{n}{k} g(k) \Leftrightarrow g(n) = \sum_k (-1)^{n-k} \binom{n}{k} f(k)$

17.7 Pólya (necklaces)

- Colorings of n -cycle with m colors under rotation: $\frac{1}{n} \sum_{d|n} \varphi(d) m^{\frac{n}{d}}$;
with reflection too (n odd): add $nm^{\frac{n+1}{2}}$, (n even): add $\frac{n}{2}(m^{\frac{n}{2}} + m^{\frac{n}{2}+1})$,
then divide by $2n$ instead of n .

18 Game Theory

18.1 Nim

- n piles $a_1, \dots, a_n$; 兩人輪流選一堆拿走 ≥ 1 顆，拿不了的人輸 (normal play)。
- 先手必勝 $\Leftrightarrow X = a_1 \oplus \dots \oplus a_n \neq 0$ 。必勝走法：找一堆 a_i 使 $a_i \oplus X < a_i$ (即 a_i 在 X 最高位為 1)，拿成 $a_i \oplus X$ ，讓 XOR 歸零。
- Misère (拿到最後一顆的人輸)：若所有 $a_i \leq 1$ 則勝負相反 (堆數為偶數先手勝)，否則判定同 normal。
- 變形：每次最多拿 k 顆 $\Rightarrow$ 用 $a_i \bmod (k+1)$ 代入；Staircase Nim：只看奇數階的 XOR。

18.2 Sprague-Grundy

- $SG(s) = \text{mex}\{SG(t_1), SG(t_2), \dots\}$ t_i 為對 s 做一步操作後的狀態；終止態 $SG = 0$ (mex = 最小未出現的非負整數)。
- $SG(s) \neq 0 \Leftrightarrow$ 先手必勝；必勝走法：走到任一 $SG(t) = 0$ 的 t 。
- 多個獨立子遊戲同時進行 (每步只能動一個)： $SG = \oplus SG(s_i)$ ；Nim 一堆 a 就是 $SG = a$ 。
- 一步可把一局分裂成多局 (如 Kayles)： t 的 SG 是各分裂部分的 XOR，再取 mex。
- 狀態小時直接打表 $O(|S| \cdot \text{moves})$ ，大狀態先打表找週期／規律。

19 Special Numbers

19.1 Fibonacci Series

1	1	1	2	3
5	5	8	13	21
9	34	55	89	144
13	233	377	610	987
17	1597	2584	4181	6765
21	10946	17711	28657	46368
25	75025	121393	196418	317811
29	514229	832040	1346269	2178309
33	3524578	5702887	9227465	14930352

$$f(45) \approx 10^9, f(88) \approx 10^{18}$$

19.2 Prime Numbers

- $\pi(n) \equiv$ Number of primes $\leq n \approx \frac{n}{(\ln n)-1}$
 $\pi(100) = 25, \pi(200) = 46$
 $\pi(500) = 95, \pi(1000) = 168$

$$\begin{aligned}\pi(2000) &= 303, \pi(4000) = 550 \\ \pi(10^4) &= 1229, \pi(10^5) = 9592 \\ \pi(10^6) &= 78498, \pi(10^7) = 664579\end{aligned}$$

19.3 Number of Divisors

- If $n = \prod p_i^{a_i}$, then $\tau(n) = \prod (a_i + 1)$
- Maximum $\tau(n)$ for $n \leq 10^k$:

k	$\max \tau(n)$	k	$\max \tau(n)$	k	$\max \tau(n)$
3	32	9	1344	15	26880
4	64	10	2304	16	41472
5	128	11	4032	17	64512
6	240	12	6720	18	103680
7	448	13	10752		
8	768	14	17280		

- Useful bounds: $n \leq 10^6 \Rightarrow \tau(n) \leq 240$
 $n \leq 10^9 \Rightarrow \tau(n) \leq 1344$
 $n \leq 10^{12} \Rightarrow \tau(n) \leq 6720$
 $n \leq 10^{15} \Rightarrow \tau(n) \leq 26880$
 $n \leq 10^{18} \Rightarrow \tau(n) \leq 103680$

19.4 Distinct Prime Factors

- Let $\omega(n)$ = number of distinct prime factors.
- Minimum number with k distinct prime factors is the product of the first k primes.
 - $2 \cdot 3 \cdot 5 \cdot 7 \cdot 11 \cdot 13 \cdot 17 \cdot 19 = 9699690$
 - $2 \cdot 3 \cdot \dots \cdot 23 = 223092870$
 - $2 \cdot 3 \cdot \dots \cdot 29 = 6469693230$
 - $n \leq 10^9 \Rightarrow \omega(n) \leq 9, n \leq 10^{18} \Rightarrow \omega(n) \leq 15$
- Number of square-free divisors = $2^{\omega(n)}$
 - $n \leq 10^9 \Rightarrow \leq 512, n \leq 10^{18} \Rightarrow \leq 32768$

