HW4 PBT

CIS 1200

PBT FOR MUTABLE STRUCTURES

Here we have defined an interface for a mutable notebook type

```
module type NOTEBOOK = sig

  type notebook

  val empty : unit -> notebook

  val write : notebook -> string -> unit

  val append : notebook -> string -> unit

  val read : notebook -> string

  val clear : notebook -> unit

  end
```

PBT FOR MUTABLE STRUCTURES

What are some properties we could test for the notebook?

```
module type NOTEBOOK = sig

  type notebook

  val empty : unit -> notebook

  val write : notebook -> string -> unit

  val append : notebook -> string -> unit

  val read : notebook -> string

  val clear : notebook -> unit

  end
```

PBT FOR MUTABLE STRUCTURES

What are some properties we could test for the notebook?

```
module type NOTEBOOK = sig

  type notebook

  val empty : unit -> notebook

  val write : notebook -> string -> unit

  val append : notebook -> string -> unit

  val read : notebook -> string

  val clear : notebook -> unit

  end
```

PBT FOR MUTABLE STRUCTURES

What are some properties we could test for the notebook?

```
let write_read (n: notebook) (s: string) : bool =
    (write n s; read n) = s

let append_read (n: notebook) (s: string) : bool =
    let data = read n in
    (append n s; read n) = data ^ s

let read_clear (n: notebook) : bool =
    clear n; read n = ""
```