

ECE 251C Project Proposal

Pengluo Wang, Nathan Godwin

The fast development of the Internet has made it possible to distribute digital data. In order to protect the copyright of the data, a watermark is frequently used in digital media such as audio, images and video. Here in our project, we will focus on implementing an algorithm to produce an imperceptible, robust watermark with high resistance to image alterations. These algorithms use the discrete wavelet transform to embed the copyright image in the wavelet domain into the host image without significant alterations to the appearance of the host image. Additional transformations in the wavelet domain such as SVD or fractional fourier transforms may be applied in order to improve watermark embedding.

We will use the LENA image of size 512x512 with 256 gray level as the host image and the binary COPYRIGHT image of size 20x50 as the watermark image. Since most of the researches are focused on grayscale image, we will also try to implement the algorithm on RGB images if time permits.

Results will be evaluated on the basis of image quality and quality of recovered watermark using metrics such as PSNR and correlation to the original host image. Additionally, the embedded image will be corrupted using a variety of methods such as cropping, blurring, and compression.



Fig 1. Test images. (left: LENA, right: COPYRIGHT)

References:

- [1] M. Barni, F. Bartolini and A. Piva, "Improved wavelet-based watermarking through pixel-wise masking," in IEEE Transactions on Image Processing, vol. 10, no. 5, pp. 783-791, May 2001.
- [2] D. Kundur and D. Hatzinakos, "Digital watermarking using multiresolution wavelet decomposition," Proceedings of the 1998 IEEE International Conference on Acoustics, Speech and Signal Processing, ICASSP '98 (Cat. No.98CH36181), Seattle, WA, USA, 1998, pp. 2969-2972 vol.5.
- [3] D. Kundur and D. Hatzinakos, "A robust digital image watermarking method using wavelet-based fusion," Proceedings of International Conference on Image Processing, Santa Barbara, CA, 1997, pp. 544-547 vol.1.

- [4] Peter Meerwald, Andreas Uhl, "Survey of wavelet-domain watermarking algorithms," Proc. SPIE 4314, Security and Watermarking of Multimedia Contents III, (1 August 2001)
- [5] C. Lai and C. Tsai, "Digital Image Watermarking Using Discrete Wavelet Transform and Singular Value Decomposition," in IEEE Transactions on Instrumentation and Measurement, vol. 59, no. 11, pp. 3060-3063, Nov. 2010.
- [6] Elshazly, Ehab H., Ashour, Mahmoud A., El-Rabaie, El-sayed M., Abbas, Alaa M.,Kazemian, H.: An efficient fractional fourier transform approach for digital image watermarking. In: Proceeding of National Radio Science Conference NRSC (2012)
- [7] Elshazly EH, Faragallah OS, Abbas AM, Ashour MA, El-Rabaie E-S M, Kazemian H, Alshebeii SA, Fathi E, Hala Abd El-Samie, Elsayed Hala S. Robust and secure fractional wavelet image watermarking. Signal, Image and Video Processing, DOI: 10.1007/s11760-014- 0684-x, 2014.
- [8] Pujara, C.; Bhardwaj, A.; Gadre, V.M.; Khire, S. Secure watermarking in fractional wavelet domains. IETE J. Res. 2007, 53, 573–580