



PB706

Slim BLE Tracking Tag

PB706 is a cutting-edge tag harnessing a Bluetooth crowdsourcing network to globally track objects, all without the need for a SIM card. Featuring a sleek 2mm-thick body akin to a credit card in size, the device boasts tempered glass on both sides and a sandblasted, anodized aerospace-grade aluminum alloy frame, combining strength with texture. Its small form factor makes it effortlessly portable in backpacks, wallets (purses), or luggage tags. Powered by a high-capacity disposable lithium battery, PB706 ensures up to two years of reliable and uninterrupted usage.



Wallet Tracking & Protection



Luggage Tracking



Backpack Tracking



Compact Size

The unit is ultra-slim, measuring only 2mm thick, ensuring portability in virtually any object for tracking purposes.



Global Connectivity

Bluetooth connectivity enables usage of the device anywhere in the world at no additional cost, ensuring seamless tracking regardless of location.



Long Service Life

The internal battery can power the PB706 BLE tag for up to 24 months, ensuring extended usage without the need for frequent replacement.



Audible Finding

With just one tap, you can locate the tracked object with the assistance of an audible guide sound, simplifying the retrieval process.



Movement History

Access the movement history of the tracked object, which can be replayed conveniently on a designated app or URL, providing insights into past locations and routes.



Security Fence

Receive immediate notifications if the tracked object moves beyond your preset virtual boundary, enhancing security and enabling prompt action.



Superb Quality

Featuring a tempered glass surface and metal frame, the PB706 offers exceptional durability and aesthetics, representing a perfect blend of strength and texture.

Standard Configuration

Connectivity	BLE (15–20m)
Battery	540mAh Li-MnO2 battery
Service life	24 months
Button	1 * Power button
Buzzer	60dB
Scenarios	Audible alarm, Geofence entry & exit alert, Movement history
Certification	CE, FCC, RoHS
Operating temperature	–20 °C to +60 °C
Device dimensions	84,5 x 54,4 x 2,0mm
Device weight	16g

Standard Packing

PB706 unit	1
------------	---