

# XXX YYY/AAA/BBB

## Interface Design Description

### Abstract

This document describes a [ppp] protocol with [sss] payload security and [eee] payload encoding variant of the [XXX] service.

## Contents

<b>1</b>	<b>Overview</b>	<b>3</b>
<b>2</b>	<b>Service Operations</b>	<b>4</b>
2.1	operation <a href="#">Register</a>	4
2.2	operation <a href="#">Unregister</a>	5
2.3	operation <a href="#">Query</a>	5
2.4	operation <a href="#">Echo</a>	7
<b>3</b>	<b>Data Models</b>	<b>8</b>
3.1	struct <a href="#">Error</a>	8
3.2	struct <a href="#">ServiceRegistryRequest</a>	8
3.3	struct <a href="#">ServiceRegistryUnregisterRequest</a>	8
3.4	struct <a href="#">ServiceQueryForm</a>	8
3.5	struct <a href="#">Metadata</a>	8
3.6	Primitives	9
<b>4</b>	<b>Revision History</b>	<b>11</b>
4.1	Amendments	11
4.2	Quality Assurance	11

# 1 Overview

This document describes the [XXX] service interface, which provides [brief description of the service interface].  
It's implemented using protocol, encoding as stated in below table:

Profile ype	Type	Version
Transfer protocol	HTTP	1.1
Data encryption	TLS	1.3
Encoding	e.g. JSON	RFC 8259 [?]
Compression	N/A	-
Semantics	e.g. SensML	RFC 9100 [?]
Ontology	N/A	-

Table 1: Communication and semantics details used for the [XXX] service interface

This document provides the Interface Design Description IDD to the [XXX] – *Service Description* document. For further details about how this service is meant to be used, please consult that document.

The rest of this document describes how to realize the [XXX] service interface in detail. Both in terms of its operations (Section 2) and its information model (Section 3).

«IDD» ServiceDiscovery_HTTP	
flow properties	
^inout HTTP : ServiceDiscovery_HTTP	
^inout CoAP : ServiceDiscovery_CoAP	
^inout MQTT : ServiceDiscovery_MQTT	
values	
Security : SecurityKind = CERTIFICATE	
CertificateLevel : CertificateKind = CoreService	
Protocol : ProtocolKind = HTTP 1.1	
Encoding : EncodingKind = JSON	
operations	
Register( ServiceRegistryRequest : ServiceRegistryRequest )(method==POST,subURL==/serviceregistry/register)	
Unregister( ServiceRegistryForm : ServiceRegistryRequest ) : StatusCodeKind(method==POST,subURL==/serviceregistry/unregister)	
Echo() : StatusCodeKind(method==GET,subURL==/serviceRegistry/echo)	
Query( ServiceQueryForm : ServiceQueryForm, ServiceQueryList : ServiceQueryList )(method==POST,subURL==/serviceregistry/query)	

Figure 1: SysML model of the ServiceDiscovery interface, its operations, datamodels and implementation.

## 2 Service Operations

The interfaces of the [XXX] service, its operations, data models and implementation are provided below. An SysML service overview is found in Figure 1. A SysML overview of the operation datamodels is found in Figure 2.

In particular, each subsection first names the [ppp] protocol method and path used to call the function, after which it names an abstract function from the Service Discovery Register SD document, as well as input and output types.

All operations in this section respond with the status code 201 Created if called successfully. The error codes are, 400 Bad Request if request is malformed, 401 Unauthorized if improper client side certificate is provided, 500 Internal Server Error if Service Registry is unavailable.

All interfaces to be described as provided by the following examples

### 2.1 POST /serviceregistry/register

**Operation:** Register()  
**Input:** ServiceRegistryRequest  
**Output:** Void or Error

Called to register a service offered by the caller system, as exemplified in Listing 1.

```
1 POST /serviceregistry/register HTTP/1.1
2
3 {
4   "endOfValidity": "2020-12-05 12:00:00",
5   "interfaces": [
6     "HTTP-SECURE-JSON"
7   ],
8   "metadata": {
9     "unit": "celsius"
10  },
11  "providerSystem": {
12    "address": "192.168.0.101",
13    "authenticationInfo": "public key of the client certificate",
14    "port": 8080,
15    "systemName": "exampleprovider"
16  },
17  "secure": "TOKEN",
18  "serviceDefinition": "temperature",
19  "serviceUri": "/",
20  "version": 1
21 }
```

Listing 1: A [Register](#) invocation.

```
1 {
2   "id": 14,
3   "serviceDefinition": {
4     "id": 13,
5     "serviceDefinition": "temperature",
6     "createdAt": "2020-12-01 11:59:10",
7     "updatedAt": "2020-12-01 11:59:10"
8   },
9   "provider": {
10    "id": 4,
11    "systemName": "exampleprovider",
12    "address": "192.168.0.101",
13    "port": 8080,
14    "authenticationInfo": "public key of the client certificate",
15    "createdAt": "2020-12-01 11:59:10",
16    "updatedAt": "2020-12-01 11:59:10"
17  },
18  "serviceUri": "/",
19  "endOfValidity": "2020-12-05 12:00:00",
20  "secure": "TOKEN",
21  "metadata": {
22    "unit": "celsius"
23  },
24  "version": 1,
25  "interfaces": [
26    {
27      "id": 1,
28      "interfaceName": "HTTP-SECURE-JSON",
29      "createdAt": "2019-10-07 04:29:51",
30      "updatedAt": "2019-10-07 04:29:51"
31    }
32  ],
33  "createdAt": "2020-12-01 11:59:10",
34  "updatedAt": "2020-12-01 11:59:10"
35 }
```

Listing 2: A [Register](#) response. Every Object contains an id.

**2.2 DELETE /serviceregistry/unregister**  
**?address={address}**  
**&port={port}**  
**&service\_definition={service\_definition}**  
**&system\_name={system\_name}**  
**Operation:** [Unregister\(\)](#)  
**Input:** ServiceRegistryUnregisterRequest  
**Output:** Void **or** Error

Called to unregister a service offered by the caller system, as exemplified in Listing 3.

```
1 DELETE /serviceregistry/unregister?address=10.0.0.0&port=8080&service_definition=temperature&
   system_name=mytemperaturesensor HTTP/1.1
2 Accept: application/json
```

Listing 3: An [Unregister](#) invocation.



## 2.3 POST /serviceregistry/query

**Operation:** Query()

**Input:** ServiceQueryForm

**Output:** Array<ServiceRegistryRequest> or Error

Called to query a service offered by a core system, as exemplified in Listing 4.

```
1 POST /serviceregistry/query HTTP/1.1
2
3 {
4   "interfaceRequirements": [
5     "HTTP-SECURE_JSON"
6   ],
7   "maxVersionRequirement": 1,
8   "metadataRequirements": {
9     "additionalProp1": "string",
10    "additionalProp2": "string",
11    "additionalProp3": "string"
12  },
13   "minVersionRequirement": 1,
14   "pingProviders": true,
15   "securityRequirements": [
16     "CERTIFICATE"
17   ],
18   "serviceDefinitionRequirement": "orchestration-service",
19   "versionRequirement": 1
20 }
```

Listing 4: A Query invocation.

```
1 {
2   "serviceQueryData": [
3     {
4       "id": 0,
5       "serviceDefinition": {
6         "id": 0,
7         "serviceDefinition": "string",
8         "createdAt": "string",
9         "updatedAt": "string"
10      },
11      "provider": {
12        "id": 0,
13        "systemName": "string",
14        "address": "string",
15        "port": 0,
16        "authenticationInfo": "string",
17        "createdAt": "string",
18        "updatedAt": "string"
19      },
20      "serviceUri": "string",
21      "endOfValidity": "string",
22      "secure": "NOT_SECURE",
23      "metadata": {
24        "additionalProp1": "string",
25        "additionalProp2": "string",
26        "additionalProp3": "string"
27      },
28      "version": 0,
29      "interfaces": [
30        {
31          "id": 0,
32          "interfaceName": "string",
33          "createdAt": "string",
34          "updatedAt": "string"
35        }
36      ]
37    }
38  ]
39 }
```

```
36     ],  
37     "createdAt": "string",  
38     "updatedAt": "string"  
39   }  
40 ],  
41 "unfilteredHits": 0  
42 }
```

Listing 5: A [Query](#) response. Every Object contains an id.

## 2.4 GET /serviceregistry/echo

Operation: [Echo\(\)](#)

Output: [StatusCodeKind](#)

Called to check the core systems availability, as exemplified in Listing 6.

```
1 GET /serviceregistry/echo HTTP/1.1  
2  
3 200 OK
```

Listing 6: An [Echo](#) invocation response.

## 3 Data Models

Below is the preferred approach to data model description. The example used is from the ServiceRegistry system

Here, all data objects that can be part of the service calls associated with this service are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is meant to denote a JSON Object that must contain certain fields, or names, with values conforming to explicitly named types. As a complement to the primary types defined in this section, there is also a list of secondary types in Section 3.6, which are used to represent things like hashes, identifiers and texts.

### 3.1 struct Error

Indicates how some service operation failed.

Object Field	Value Type	Description
"code"	ErrorCode	String or number indicating what went wrong.
"text"	String	An optional human-readable description of the error.

### 3.2 struct ServiceRegistryRequest

This structure is used to register a service offering into the Service Registry.

Object Field	Value Type	Description
"endofValidity"	DateTime	Service is available until this UTC timestamp.
"interfaces"	Array<Interface>	List of interfaces the service supports.
"metadata"	Metadata	Metadata
"providerSystem"	Name	Name of the provider system.
"secure"	SecureType	Type of security the service uses.
"serviceDefinition"	Name	Service Definition.
"serviceUri"	URI	URI of the service.
"version"	Version	Version of the service.

### 3.3 struct ServiceRegistryUnregisterRequest

Identifies a requested Unregister call. As the fields of this type occur only as query parameters in the [Unregister](#) function, there is no need for it to be representable as a JSON Object. This subsection exists only for the sake of completeness.

### 3.4 struct ServiceQueryForm

This structure is used to query a service from the Service Registry.

### 3.5 struct Metadata

A JSON Object which maps String key-value pairs.



Object Field	Value Type	Description
"interfaceRequirements"	Array<Interface>	List of the required interfaces.
"maxVersionRequirement"	Version	Maximum version.
"minVersionRequirement"	Version	Minimum version.
"metadataRequirements"	Metadata	Metadata.
"pingProviders".	Boolean	Checks the availability of the providers if true
"securityRequirements"	SecureType	Type of security.
"serviceDefinitionRequirement"	Name	Service Definition.
"versionRequirement"	Version	Version of the service.

### 3.6 Primitives

As all messages are encoded using the JSON format [?], the following primitive constructs, part of that standard, become available. Note that the official standard is defined in terms of parsing rules, while this list only concerns syntactic information. Furthermore, the **Object** and **Array** types are given optional generic type parameters, which are used in this document to signify when pair values or elements are expected to conform to certain types.

JSON Type	Description
Value	Any out of Object, Array, String, Number, Boolean or Null.
Object<A>	An unordered collection of [String: Value] pairs, where each Value conforms to type A.
Array<A>	An ordered collection of Value elements, where each element conforms to type A.
String	An arbitrary UTF-8 string.
Number	Any IEEE 754 binary64 floating point number [?], except for <i>+Inf</i> , <i>-Inf</i> and <i>NaN</i> .
Boolean	One out of <code>true</code> or <code>false</code> .
Null	Must be <code>null</code> .

The **Void** type is used to indicate no value at all.

With these primitives now available, we proceed to define all the types specified in the Service Discovery Register SD document without a direct equivalent among the JSON types. Concretely, we define the Service Discovery Register SD primitives either as *aliases* or *structs*. An *alias* is a renaming of an existing type, but with some further details about how it is intended to be used. Structs are described in the beginning of the parent section. The types are listed by name in alphabetical order.

#### 3.6.1 alias DateTime = String

Pinpoints a moment in time in the format of "YYYY-MM-DD HH:mm:ss", where "YYYY" denotes year (4 digits), "MM" denotes month starting from 01, "DD" denotes day starting from 01, "HH" denotes hour in the 24-hour format (00-23), "MM" denotes minute (00-59), "SS" denotes second (00-59). " " is used as separator between the date and the time. An example of a valid date/time string is "2020-12-05 12:00:00"

#### 3.6.2 alias ErrorCode = String or Number

Any of the following strings or numbers:

String	Number	Description
"BadDateTime"	1001	A date-time value in the received message does not follow the expected format.
"Expired"	1002	The expiration time ("endOfValidity") is in the past.

These are, of course, only possible examples.



ARROWHEAD

Document title  
**XXX YYY/AAA/BBB**  
Date  
**2022-04-07**

Version  
**4.4.1**  
Status  
**RELEASE**  
Page  
**10 (12)**

### 3.6.3 **alias** id = Number

An identifier generated for each Object that enables to distinguish them and later to refer to a specific Object.

### 3.6.4 **alias** Interface = String

A String that describes an interface in *Protocol-SecurityType-MimeType* format. *SecurityType* can be *SECURE* or *INSECURE*. *Protocol* and *MimeType* can be anything. An example of a valid interface is: "HTTPS-SECURE-JSON" or "HTTP-INSECURE-SENML".

### 3.6.5 **alias** Name = String

A String that is meant to be short (less than a few tens of characters) and both human and machine-readable.

### 3.6.6 **alias** SecureType = String

A String that describes the security type. Possible values are *NOT\_SECURE* or *CERTIFICATE* or *TOKEN*.

### 3.6.7 **alias** URI = String

A String that represents the URL subpath where the offered service is reachable, starting with a slash ("/"). An example of a valid URI is "/temperature".

### 3.6.8 **alias** Version = Number

A Number that represents the version of the service. An example of a valid version is: 1.



ARROWHEAD

Document title  
**XXX YYY/AAA/BBB**  
Date  
**2022-04-07**

Version  
**4.4.1**  
Status  
**RELEASE**  
Page  
**11 (12)**

## 4 Revision History

### 4.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2020-12-05	4.4.1		Szvetlin Tanyi
2	2021-07-14	4.4.1	Minor edits	Jerker Delsing
3	2022-01-17	4.4.1	Minor edits	Jerker Delsing

### 4.2 Quality Assurance

No.	Date	Version	Approved by
1	2022-01-17	4.4.1	Jerker Delsing




Figure 2: A SysML models of the datamodel used by the ServiceDiscovery interface operations.