
 SOMAIYA VIDYAVIHAR UNIVERSITY K J Somaiya College of Engineering	K. J. Somaiya College of Engineering, Mumbai-77 (A Constituent College of Somaiya Vidyavihar University) Department of Science and Humanities	
---	---	---

Name: Shreyans Tatiya

Batch: C5_3

Roll No.: 16010123325 (53)

Experiment / assignment / tutorial No.

Grade: AA / AB / BB / BC / CC / CD / DD

Signature of the Staff In-charge with date

TITLE: File handling in Python

AIM: Write a program to demonstrate File handling mechanism in Python

Expected OUTCOME of Experiment: To demonstrate File Handling in python

Resource Needed: Python IDE

Theory:

Python File Handling

Till now, we were taking the input from the console and writing it back to the console to interact with the user.

Sometimes, it is not enough to only display the data on the console. The data to be displayed may be very large, and only a limited amount of data can be displayed on the console since the memory is volatile, it is impossible to recover the programmatically generated data again and again.

The file handling plays an important role when the data needs to be stored permanently into the file. A file is a named location on disk to store related information. We can access the stored information (non-volatile) after the program termination.



The file-handling implementation is slightly lengthy or complicated in the other programming language, but it is easier and shorter in Python.

File operation can be done in the following order:

Open a file

Read or write - Performing operation

Close the file

 SOMAIYA VIDYAVIHAR UNIVERSITY K J Somaiya College of Engineering	K. J. Somaiya College of Engineering, Mumbai-77 (A Constituent College of Somaiya Vidyavihar University) Department of Science and Humanities	
---	---	---

Opening a file:



Python provides an open() function that accepts two arguments, file name and access mode in which the file is accessed. The function returns a file object which can be used to perform various operations like reading, writing, etc.

Syntax:

file object = open(<file-name>, <access-mode>, <buffering>)

The files can be accessed using various modes like read, write, or append. The following are the details about the access mode to open a file.

SN	Access mode	Description
1	r	It opens the file to read-only mode. The file pointer exists at the beginning. The file is by default open in this mode if no access mode is passed.
2	rb	It opens the file to read-only in binary format. The file pointer exists at the beginning of the file.
3	r+	It opens the file to read and write both. The file pointer exists at the beginning of the file.
4	rb+	It opens the file to read and write both in binary format. The file pointer exists at the beginning of the file.
5	w	It opens the file to write only. It overwrites the file if previously exists or creates a new one if no file exists with the same name. The file pointer exists at the beginning of the file.
6	wb	It opens the file to write only in binary format. It overwrites the file if it exists previously or creates a new one if no file exists. The file pointer exists at the beginning of the file.
7	w+	It opens the file to write and read both. It is different from r+ in the sense that it overwrites the previous file if one exists whereas r+ doesn't overwrite the previously written file. It creates a new file if no file exists. The file pointer exists at the beginning of the file.
8	wb+	It opens the file to write and read both in binary format. The file pointer exists at the beginning of the file.
9	a	It opens the file in the append mode. The file pointer exists at the end of the previously written file if exists any. It creates a new file if no file exists with the same name.
10	ab	It opens the file in the append mode in binary format. The pointer exists at the end of the previously written file. It creates a new file in binary format if no file exists with the same name.
11	a+	It opens a file to append and read both. The file pointer remains at the end of the file if a file exists. It creates a new file if no file exists with the same name.
12	ab+	It opens a file to append and read both in binary format. The file pointer remains at the end of the file.

 SOMAIYA VIDYAVIHAR UNIVERSITY K J Somaiya College of Engineering	K. J. Somaiya College of Engineering, Mumbai-77 (A Constituent College of Somaiya Vidyavihar University) Department of Science and Humanities	
---	---	---

Example:

```
#opens the file file.txt in read mode
fileptr = open("file.txt","r")
if fileptr:
    print("file is opened successfully")
```

Output:

```
<class '_io.TextIOWrapper'>
file is opened successfully
```

Problem Definition:

In the above code, we have passed filename as a first argument and opened file in read mode as we mentioned r as the second argument. The fileptr holds the file object and if the file is opened successfully, it will execute the print statement.

The close() method:

Once all the operations are done on the file, we must close it through our Python script using the close() method. Any unwritten information gets destroyed once the close() method is called on a file object.

We can perform any operation on the file externally using the file system which is the currently opened in Python; hence it is good practice to close the file once all the operations are done.

The syntax to use the close() method is given below.

Syntax:

```
fileobject.close()
```

Example:



```
try:
    fileptr = open("file.txt")
    # perform file operations
finally:
    fileptr.close()
```

Reading and Writing Files

The file object provides a set of access methods to make our lives easier. We would see how to use read() and write() methods to read and write files.

The write() Method

The write() method writes any string to an open file. It is important to note that Python strings can have binary data and not just text.

 SOMAIYA VIDYAVIHAR UNIVERSITY K J Somaiya College of Engineering	K. J. Somaiya College of Engineering, Mumbai-77 (A Constituent College of Somaiya Vidyavihar University) Department of Science and Humanities	
---	---	---

The write() method does not add a newline character ('\n') to the end of the string

Syntax:

```
fileObject.write(string)
```

Example:

```
# Open a file
fo = open("foo.txt", "wb")
fo.write( "Python is a great language.\nYeah its great!!\n")

# Close opened file
fo.close()
```

The above method would create foo.txt file and would write given content in that file and finally it would close that file. If you would open this file, it would have following content.

Output:

```
Python is a great language.
Yeah its great!!
```

The read() Method

The read() method reads a string from an open file. It is important to note that Python strings can have binary data. apart from text data.

Syntax:

```
fileObject.read([count])
```

Here, passed parameter is the number of bytes to be read from the opened file. This method starts reading from the beginning of the file and if count is missing, then it tries to read as much as possible, maybe until the end of file.

Example:



```
# Open a file
fo = open("foo.txt", "r+")
str = fo.read(10);
print "Read String is : ", str
# Close opened file
fo.close()
```

Output

```
Read String is : Python is
```

File Positions

The tell() method tells you the current position within the file; in other words, the next read or write will occur at that many bytes from the beginning of the file.

 SOMAIYA VIDYAVIHAR UNIVERSITY K J Somaiya College of Engineering	K. J. Somaiya College of Engineering, Mumbai-77 (A Constituent College of Somaiya Vidyavihar University) Department of Science and Humanities	
---	---	---

The seek(offset[, from]) method changes the current file position. The offset argument indicates the number of bytes to be moved. The from argument specifies the reference position from where the bytes are to be moved.

If from is set to 0, it means use the beginning of the file as the reference position and 1 means use the current position as the reference position and if it is set to 2 then the end of the file would be taken as the reference position.

Example:

```
# Open a file
fo = open("foo.txt", "r+")
str = fo.read(10)
print "Read String is : ", str

# Check current position
position = fo.tell()
print "Current file position : ", position

# Reposition pointer at the beginning once again
position = fo.seek(0, 0);
str = fo.read(10)
print "Again read String is : ", str
# Close opened file
fo.close()
```

Renaming and Deleting Files

Python os module provides methods that help you perform file-processing operations, such as renaming and deleting files.

To use this module you need to import it first and then you can call any related functions.

The rename() Method

The rename() method takes two arguments, the current filename and the new filename.

Syntax:

```
os.rename(current_file_name, new_file_name)
```

Example:

Following is the example to rename an existing file test1.txt –

```
import os
```

```
# Rename a file from test1.txt to test2.txt
```

```
os.rename( "test1.txt", "test2.txt" )
```

The remove() Method

You can use the remove() method to delete files by supplying the name of the file to be deleted as the argument.

Syntax:

```
os.remove(file_name)
```

Example:

Following is the example to delete an existing file test2.txt –

```
import os
```

```
# Delete file test2.txt
os.remove("text2.txt")
```

Problem Definition:

Write a program to create a file employeeedetails.txt"which stores the Employee details by adding their Employee Id,Name and Department into it using following format:

EmpId	Name	Department
1601001	Abc	Computer
1601003	Xyz	IT

Obtain the details for EmpId from the user.

Books/ Journals/ Websites referred:

1. Reema Thareja, Python Programming: Using Problem Solving Approach, Oxford University Press, First Edition 2017, India
2. Sheetal Taneja and Naveen Kumar, Python Programming: A modular Approach, Pearson India, Second Edition 2018,India

Implementation details:

```
PPLAB6.py > ...
1  def write_employee_details_to_file(file_name, employee_id, name, department):
2      with open(file_name, 'a') as file:
3          file.write(f"{employee_id}           {name}           {department}\n")
4
5  employee_details = [
6      {'id': '1601001', 'name': 'Shrey', 'department': 'Computer'},
7      {'id': '1601003', 'name': 'Yerhs', 'department': 'IT'}
8  ]
9
10 for employee in employee_details:
11     write_employee_details_to_file('employee_details.txt', employee['id'], employee['name'], employee['department'])
12
```

Output(s):

```
employee_details.txt X
employee_details.txt
1  1601001           Shrey           Computer
2  1601003           Yerhs           IT
3
```

Conclusion:

Learned the concept of File handling and practiced various functions for file handling and solved the given problem statement by writing a program. Successfully implemented the new concepts in the given program

Post Lab Questions:

1. Write a program that prompt the user for a file name and then read and prints the contents of the requested file in the upper case.

Ans:

Implementation:

```
PPLAB6_!! > ...
1  name=input("Enter file name: ") #Taking file name
2  try :
3      fp=open(name,'r') # Trying to open file
4      print("\n\n")
5      for line in fp: #For each loop for every line
6          print(line.upper()) #Converting to upper case and printing
7      fp.close() #closing file object
8  except:
9      print("The file does not exist! Kindly check again")
10 # Exception when file is not available
```

Output:

```
PS C:\Users\Shrey\OneDrive\Desktop\Python KJ\Practice> & C:\Python39\python.exe C:\Python39\Scripts\py PPLAB6_!!
Enter file name: employeedetails.txt

1601001          SHREY          COMPUTER
1601003          YERHS          IT

PS C:\Users\Shrey\OneDrive\Desktop\Python KJ\Practice>
```





```
PS C:\Users\Shrey\OneDrive\Desktop\Python KJ\Practice> & C:/OneDrive/Desktop/Python KJ/Practice/PPLAB6_!!"
Enter file name: oyemetro.txt
The file does not exist! Kindly check again
PS C:\Users\Shrey\OneDrive\Desktop\Python KJ\Practice> |
```

2. Why is it advised to close a file after we are done with the read and write operations? What will happen if we do not close it? Will some error message be flashed?

Ans: When you open a file for reading, it is good practice to close the file because it is open with the file object and your program is using resources to keep the file open in the memory. Imagine opening 10 chrome tabs vs opening one chrome tab at a time, your computer will be more responsive in the 2nd case because of the fact that it is a less resourceful task as compared to the first one.

Additionally, when you open a file for writing. The file close does an implicit flush which writes to the file on disk. Basically, your write operations will change a hidden buffer. At some cadence, the buffer is written to the file on disk. If your program does not close the file, some of the data that you thought was written to the file on disk was not actually written.

It's good practice to close files if no further use is required. Python automatically closes a file when the reference object of a file is reassigned to another file. Python programming language will not give you runtime error for not closing a file. But it's good programming practice to close the file after opening it.

 <p>SOMAIYA VIDYAVIHAR UNIVERSITY K J Somaiya College of Engineering</p>	<p>K. J. Somaiya College of Engineering, Mumbai-77 (A Constituent College of Somaiya Vidyavihar University) Department of Science and Humanities</p>	
--	--	---

Date: _____

Signature of faculty in-charge