



K. J. Somaiya College of Engineering, Mumbai-77
(A Constituent College of Somaiya Vidyavihar University)
Department of Computer Engineering

Topic: Backtracking

Theory: In many applications of the backtrack method, the desired solution is expressible as an n -tuple (x_1, \dots, x_n) , where the x_i are chosen from some finite set S_i . Often the problem to be solved calls for finding one vector that maximizes (or minimizes or satisfies) a *criterion function* $P(x_1, \dots, x_n)$. Sometimes it seeks all vectors that satisfy P . For example, sorting the array of integers in $a[1 : n]$ is a problem whose solution is expressible by an n -tuple, where x_i is the index in a of the i th smallest element. The criterion function P is the inequality $a[x_i] \leq a[x_{i+1}]$ for $1 \leq i < n$. The set S_i is finite and includes the integers 1 through n . Though sorting is not usually one of the problems solved by backtracking, it is one example of a familiar problem whose solution can be formulated as an n -tuple.

Control abstraction:

```
void Backtrack( int k )
```

```
// This is a schema that describes the backtracking process //using recursion. On entering, the first k-1 values x[1], x[2], //..., x[k-1] of the solution vector x[1:n] have been //assigned. x[] and n are global.
```

```
{
    for (each x[k] such that x[k] ∈ T(x[1], ..., x[k-1]))
    {
        if (Bk (x[1], x[2], ..., x[k]))
        {
            if (x[1], x[2], ..., x[k] is a path to an answer node)
                output x[1:k];

            if (k < n) Backtrack(k+1);
        }
    }
}
```



K. J. Somaiya College of Engineering, Mumbai-77
(A Constituent College of Somaiya Vidyavihar University)
Department of Computer Engineering

Batch: E-2 Roll No.: 16010123325

Experiment No. __8__

Grade: AA / AB / BB / BC / CC / CD /DD

Signature of the Staff In-charge with date

Title: Study, Implementation, and Analysis of Graph Coloring Problem.

Objective: To learn the Backtracking strategy of problem solving for Graph Coloring Problem.

CO to be achieved:

CO 2 Analyze and solve problems for divide and conquer strategy, greedy method, dynamic programming approach and backtracking and branch & bound policies.

Books/ Journals/ Websites referred:

1. Ellis horowitz, Sarataj Sahni, S.Rajsekaran," Fundamentals of computer algorithm", University Press
2. T.H.Cormen ,C.E.Leiserson,R.L.Rivest and C.Stein," Introduction to algorithmtms",2nd Edition ,MIT press/McGraw Hill,2001

Pre Lab/ Prior Concepts:

Data structures, Concepts of algorithm analysis

Historical Profile:The Graph Coloring Problem is a classical problem in graph theory and combinatorics with origins rooted in practical applications and mathematical curiosity. It has a rich history, spanning over two centuries, and remains a vibrant area of research due to its theoretical significance and real-world applications.

Origins and Early History

Map Coloring and the Four Color Theorem (1852):The problem of graph coloring originated from an attempt to color regions on maps so that no two adjacent regions share the same color. In 1852, Francis Guthrie, a British mathematician, conjectured the Four Color Theorem, stating that four colors are sufficient to color any map in a plane.

Graph Representation of Maps:In 1879, Arthur Cayley formulated the map coloring problem in terms of graph theory, representing regions of a map as vertices and adjacency as edges.

New Concepts to be learned:



K. J. Somaiya College of Engineering, Mumbai-77

(A Constituent College of Somaiya Vidyavihar University)

Department of Computer Engineering

Application of algorithmic design strategy to any problem, Backtracking method of problem solving Vs other methods of problem solving problem sum of subset and its applications.

Algorithm:

Backtracking Algorithm

The backtracking approach finds the optimal solution by trying all possible color assignments.

Steps:

- 1. Try assigning each vertex a color from 1 to k, where k is the number of colors.**
- 2. Backtrack if an assignment leads to a conflict (two adjacent vertices having the same color).**
- 3. Continue until all vertices are colored or all possibilities are exhausted.**

Implementation(Code):

```
import java.util.Scanner;

public class GraphColoring {

    int V;
    int[] color;

    public GraphColoring(int v) {
        V = v;
        color = new int[V];
    }

    boolean isSafe(int v, int[][] graph, int[] color, int c) {
        for (int i = 0; i < V; i++)
            if (graph[v][i] == 1 && color[i] == c)
                return false;
        return true;
    }

    boolean graphColoringUtil(int[][] graph, int m, int v) {
        if (v == V)
            return true;

        for (int c = 1; c <= m; c++) {
            if (isSafe(v, graph, color, c)) {
                color[v] = c;
                if (graphColoringUtil(graph, m, v + 1))
                    return true;
                color[v] = 0;
            }
        }
        return false;
    }
}
```



K. J. Somaiya College of Engineering, Mumbai-77
(A Constituent College of Somaiya Vidyavihar University)
Department of Computer Engineering

```
        color[v] = c;
        if (graphColoringUtil(graph, m, v + 1))
            return true;
        color[v] = 0;
    }
}
return false;
}

boolean graphColoring(int[][] graph, int m) {
    if (!graphColoringUtil(graph, m, 0)) {
        System.out.println("Solution does not exist");
        return false;
    }

    System.out.println("Color assignment:");
    for (int i = 0; i < V; i++)
        System.out.println("Vertex " + i + " → Color " + color[i]);
    return true;
}

public static void main(String[] args) {
    Scanner sc = new Scanner(System.in);

    System.out.print("Enter number of vertices: ");
    int v = sc.nextInt();

    int[][] graph = new int[v][v];
    System.out.println("Enter adjacency matrix:");
    for (int i = 0; i < v; i++) {
        for (int j = 0; j < v; j++) {
            graph[i][j] = sc.nextInt();
        }
    }

    System.out.print("Enter number of colors: ");
    int m = sc.nextInt();

    GraphColoring gc = new GraphColoring(v);
    gc.graphColoring(graph, m);
}
}
```




K. J. Somaiya College of Engineering, Mumbai-77
(A Constituent College of Somaiya Vidyavihar University)
Department of Computer Engineering

Output:

```
Enter number of vertices: 7
Enter adjacency matrix:
0 1 0 0 1 1 1
1 0 1 1 0 0 0
0 1 0 1 0 0 1
0 1 1 0 1 0 0
1 0 0 1 0 1 1
1 0 0 0 1 0 1
1 0 1 0 1 1 0
Enter number of colors: 4
Color assignment:
Vertex 0 → Color 1
Vertex 1 → Color 2
Vertex 2 → Color 1
Vertex 3 → Color 3
Vertex 4 → Color 2
Vertex 5 → Color 3
Vertex 6 → Color 4
```

Example sum of subset Problem along with state space tree:



Analysis of Backtracking solution for :

Time Complexity : $O(k^n)$

k = number of colours

n = number of vertices



K. J. Somaiya College of Engineering, Mumbai-77
(A Constituent College of Somaiya Vidyavihar University)
Department of Computer Engineering

Conclusion:

The above experiment highlights graph colouring using backtracking method, by efficient use of pruning to find the optimal approach.