



The picture can't be displayed.

Chapter 15 : Concurrency Control

Database System Concepts, 6th Ed.

©Silberschatz, Korth and Sudarshan

See www.db-book.com for conditions on re-use



Chapter 15: Concurrency Control

- Lock-Based Protocols
- Timestamp-Based Protocols
- Validation-Based Protocols
- Multiple Granularity
- Multiversion Schemes
- Insert and Delete Operations
- Concurrency in Index Structures



Lock-Based Protocols

- A lock is a mechanism to control concurrent access to a data item
- Data items can be locked in two modes :
 1. *exclusive (X) mode*. Data item can be both read as well as written. X-lock is requested using **lock-X** instruction.
 2. *shared (S) mode*. Data item can only be read. S-lock is requested using **lock-S** instruction.
- Lock requests are made to concurrency-control manager. Transaction can proceed only after request is granted.



Lock-Based Protocols (Cont.)

■ Lock-compatibility matrix

	S	X
S	true	false
X	false	false

- A transaction may be granted a lock on an item if the requested lock is compatible with locks already held on the item by other transactions
- Any number of transactions can hold shared locks on an item,
 - but if any transaction holds an exclusive on the item no other transaction may hold any lock on the item.
- If a lock cannot be granted, the requesting transaction is made to wait till all incompatible locks held by other transactions have been released. The lock is then granted.



Lock-Based Protocols (Cont.)

- Example of a transaction performing locking:

```
 $T_2$ : lock-S( $A$ );  
      read ( $A$ );  
      unlock( $A$ );  
      lock-S( $B$ );  
      read ( $B$ );  
      unlock( $B$ );  
      display( $A+B$ )
```

- Locking as above is not sufficient to guarantee serializability — if A and B get updated in-between the read of A and B , the displayed sum would be wrong.
- A **locking protocol** is a set of rules followed by all transactions while requesting and releasing locks. Locking protocols restrict the set of possible schedules.



Pitfalls of Lock-Based Protocols

- Consider the partial schedule

T_3	T_4
lock-x (B)	
read (B)	
$B := B - 50$	
write (B)	
	lock-s (A)
	read (A)
	lock-s (B)
lock-x (A)	

- Neither T_3 nor T_4 can make progress — executing **lock-S**(B) causes T_4 to wait for T_3 to release its lock on B , while executing **lock-X**(A) causes T_3 to wait for T_4 to release its lock on A .
- Such a situation is called a **deadlock**.
 - To handle a deadlock one of T_3 or T_4 must be rolled back and its locks released.



Pitfalls of Lock-Based Protocols (Cont.)

- The potential for deadlock exists in most locking protocols. Deadlocks are a necessary evil.
- **Starvation** is also possible if concurrency control manager is badly designed. For example:
 - A transaction may be waiting for an X-lock on an item, while a sequence of other transactions request and are granted an S-lock on the same item.
 - The same transaction is repeatedly rolled back due to deadlocks.
- Concurrency control manager can be designed to prevent starvation.



The Two-Phase Locking Protocol

- This is a protocol which ensures conflict-serializable schedules.
- Phase 1: Growing Phase
 - transaction may obtain locks
 - transaction may not release locks
- Phase 2: Shrinking Phase
 - transaction may release locks
 - transaction may not obtain locks
- The protocol assures serializability. It can be proved that the transactions can be serialized in the order of their **lock points** (i.e. the point where a transaction acquired its final lock).



The Two-Phase Locking Protocol (Cont.)

- Two-phase locking *does not* ensure freedom from deadlocks
- Cascading roll-back is possible under two-phase locking. To avoid this, follow a modified protocol called **strict two-phase locking**. Here a transaction must hold all its exclusive locks till it commits/aborts.
- **Rigorous two-phase locking** is even stricter: here *all* locks are held till commit/abort. In this protocol transactions can be serialized in the order in which they commit.



Quiz Time

Quiz Q1: Consider the following locking schedule

T1

lock-X(A)

unlock-X(A)

lock-S(B)

unlock-S(B)

(1) the schedule is two phase

(3) the schedule is cascade free

(2) the schedule is recoverable

(4) none of the above



Lock Conversions

- Two-phase locking with lock conversions:
 - First Phase:
 - can acquire a lock-S on item
 - can acquire a lock-X on item
 - can convert a lock-S to a lock-X (upgrade)
 - Second Phase:
 - can release a lock-S
 - can release a lock-X
 - can convert a lock-X to a lock-S (downgrade)
- This protocol assures serializability. But still relies on the programmer to insert the various locking instructions.



Automatic Acquisition of Locks

- A transaction T_i issues the standard read/write instruction, without explicit locking calls.
- The operation **read**(D) is processed as:
 - if T_i has a lock on D
 - then
 - read(D)
 - else begin
 - if necessary wait until no other transaction has a **lock-X** on D
 - grant T_i a **lock-S** on D ;
 - read(D)
 - end



Automatic Acquisition of Locks (Cont.)

- **write(D)** is processed as:
 - if** T_i has a **lock-X** on D
 - then**
 - write(D)
 - else begin**
 - if necessary wait until no other trans. has any lock on D ,
 - if T_i has a **lock-S** on D
 - then**
 - upgrade** lock on D to **lock-X**
 - else**
 - grant T_i a **lock-X** on D
 - write(D)
 - end;**
 - All locks are released after commit or abort



Implementation of Locking

- A **lock manager** can be implemented as a separate process to which transactions send lock and unlock requests
- The lock manager replies to a lock request by sending a lock grant messages (or a message asking the transaction to roll back, in case of a deadlock)
- The requesting transaction waits until its request is answered
- The lock manager maintains a data-structure called a **lock table** to record granted locks and pending requests
- The lock table is usually implemented as an in-memory hash table indexed on the name of the data item being locked




Deadlock Handling

- System is deadlocked if there is a set of transactions such that every transaction in the set is waiting for another transaction in the set.
- **Deadlock prevention** protocols ensure that the system will *never* enter into a deadlock state. Some prevention strategies :
 - Require that each transaction locks all its data items before it begins execution (predeclaration).
 - Impose partial ordering of all data items and require that a transaction can lock data items only in the order specified by the partial order (graph-based protocol).
 - Deadlock prevention by ordering usually ensured by careful programming of transactions




Deadlock Detection

- **Deadlock detection** algorithms used to detect deadlocks



Wait-for graph without a cycle



Wait-for graph with a cycle



Deadlock Recovery

- When deadlock is detected :
 - Some transaction will have to rolled back (made a victim) to break deadlock. Select that transaction as victim that will incur minimum cost.
 - Rollback -- determine how far to roll back transaction
 - ▶ **Total rollback**: Abort the transaction and then restart it.
 - ▶ More effective to roll back transaction only as far as necessary to break deadlock.
 - Starvation happens if same transaction is always chosen as victim. Include the number of rollbacks in the cost factor to avoid starvation



Quiz Time

Quiz Q2: Consider the following locking schedule

<u>T1</u>	T2
lock-S(A)	
	lock-S(B)
lock-X(B)	
	lock-A(B)

- (1) the schedule is not two phase (2) the schedule is deadlocked
(3) the schedule is not deadlocked (4) none of the above



Locking Extensions

■ Multiple granularity locking:

- idea: instead of getting separate locks on each record
 - ▶ lock an entire page explicitly, implicitly locking all records in the page, or
 - ▶ lock an entire relation, implicitly locking all records in the relation
- See book for details of multiple-granularity locking



Timestamp-Based Protocols

- Each transaction is issued a timestamp when it enters the system. If an old transaction T_i has time-stamp $TS(T_i)$, a new transaction T_j is assigned time-stamp $TS(T_j)$ such that $TS(T_i) < TS(T_j)$.
- The protocol manages concurrent execution such that the time-stamps determine the serializability order.
- In order to assure such behavior, the protocol maintains for each data Q two timestamp values:
 - **W-timestamp**(Q) is the largest time-stamp of any transaction that executed **write**(Q) successfully.
 - **R-timestamp**(Q) is the largest time-stamp of any transaction that executed **read**(Q) successfully.



Timestamp-Based Protocols (Cont.)

- The timestamp ordering protocol ensures that any conflicting **read** and **write** operations are executed in timestamp order.
- Suppose a transaction T_i issues a **read**(Q)
 1. If $TS(T_i) \leq \mathbf{W}$ -timestamp(Q), then T_i needs to read a value of Q that was already overwritten.
 - Hence, the **read** operation is rejected, and T_i is rolled back.
 2. If $TS(T_i) \geq \mathbf{W}$ -timestamp(Q), then the **read** operation is executed, and R-timestamp(Q) is set to **max**(R-timestamp(Q), $TS(T_i)$).



Timestamp-Based Protocols (Cont.)

- Suppose that transaction T_i issues **write**(Q).
 1. If $TS(T_i) < R\text{-timestamp}(Q)$, then the value of Q that T_i is producing was needed previously, and the system assumed that that value would never be produced.
 - Hence, the **write** operation is rejected, and T_i is rolled back.
 2. If $TS(T_i) < W\text{-timestamp}(Q)$, then T_i is attempting to write an obsolete value of Q .
 - Hence, this **write** operation is rejected, and T_i is rolled back.
 3. Otherwise, the **write** operation is executed, and $W\text{-timestamp}(Q)$ is set to $TS(T_i)$.



Example Use of the Protocol


A partial schedule for several data items for transactions with timestamps 1, 2, 3, 4, 5

T_1	T_2	T_3	T_4	T_5
				read (X)
read (Y)	read (Y)	write (Y) write (Z)		
	read (Z) abort			read (Z)
read (X)		write (W) abort	read (W)	
				write (Y) write (Z)



Correctness of Timestamp-Ordering Protocol

- The timestamp-ordering protocol guarantees serializability since all the arcs in the precedence graph are of the form:



Thus, there will be no cycles in the precedence graph

- Timestamp protocol ensures freedom from deadlock as no transaction ever waits.
- But the schedule may not be cascade-free, and may not even be recoverable.



Recoverability and Cascade Freedom

- Problem with timestamp-ordering protocol:
 - Suppose T_i aborts, but T_j has read a data item written by T_i
 - Then T_j must abort; if T_j had been allowed to commit earlier, the schedule is not recoverable.
 - Further, any transaction that has read a data item written by T_j must abort
 - This can lead to cascading rollback --- that is, a chain of rollbacks
- **Solution 1:**
 - A transaction is structured such that its writes are all performed at the end of its processing
 - All writes of a transaction form an atomic action; no transaction may execute while a transaction is being written
 - A transaction that aborts is restarted with a new timestamp
- **Solution 2:** Limited form of locking: wait for data to be committed before reading it
- **Solution 3:** Use commit dependencies to ensure recoverability



Validation-Based Protocols

- Execution of transaction T_i is done in three phases.
 1. **Read and execution phase:** Transaction T_i writes only to temporary local variables
 2. **Validation phase:** Transaction T_i performs a ``validation test'' to determine if local variables can be written without violating serializability.
 3. **Write phase:** If T_i is validated, the updates are applied to the database; otherwise, T_i is rolled back.
- The three phases of concurrently executing transactions can be interleaved, but each transaction must go through the three phases in that order.
 - Assume for simplicity that the validation and write phase occur together, atomically and serially
 - ▶ I.e., only one transaction executes validation/write at a time.
- Also called as **optimistic concurrency control** since transaction executes fully in the hope that all will go well during validation



Validation-Based Protocols (Cont.)

- Validation is based on timestamps, but with two timestamps:
 - start time
 - validation time
- Details in book