



# PYTHON FOR COMPUTATIONAL PROBLEM SOLVING

## Dictionaries in python

---

**Prof. Sindhu R Pai**

PCPS Theory Anchor - 2024

Department of Computer Science and Engineering

# PYTHON FOR COMPUTATIONAL PROBLEM SOLVING

## Dictionary

---



## Dictionary

- Dictionary is a data structure that **organizes data into key and value pairs**
- Every value has a **certain unique key mapped** to it
- It is **mutable** (values can be changed after creation)

## Dictionary Creation

```
>>> phonebook={} # Creation of empty dictionary
```

```
>>> phonebook={"Johan":938477565} # Dictionary with one key-value pair
```

```
>>> phonebook={"Johan":938477565,"Jill":938547565} # Dictionary with two key-value pair
```

## PYTHON FOR COMPUTATIONAL PROBLEM SOLVING

### Dictionary

---



To access values in the dictionary, we use the keys like so:

```
>>> eng2french={ 1:'un',  
                 2:'deux',  
                 3:'trios',  
                 4:'quatre',  
                 5:'cinq }  
  
>>> print(eng2french[2]) #will give you 'deux'
```

## PYTHON FOR COMPUTATIONAL PROBLEM SOLVING

### Dictionary

---



- Each **key is of any immutable type** associated with a single value.

```
>>> d={1:"one",2:"two",3:"three",4:"four"}
```

```
>>> d1={[1,2]:"hello"}
```

```
Traceback (most recent call last): File "<stdin>", line 1, in  
<module> TypeError: unhashable type: 'list'
```

- The **values can be of any type**.

```
>>> d={1:"one", 2:[23,33] , 3:"three", 4:"four"}
```

## PYTHON FOR COMPUTATIONAL PROBLEM SOLVING

### Dictionary

---



- If you assign a value to a key, then later in the same dictionary have the same key assigned to a new value, the **previous value will be overwritten.**

```
>>> d={1:"one",2:"two",3:"three"}
```

```
>>> d={1:"one",2:"two",3:"three",1:"five"}
```

```
>>> d
```

```
{1: 'five', 2: 'two', 3: 'three'}
```

## PYTHON FOR COMPUTATIONAL PROBLEM SOLVING

### Dictionary

---



- The items (key-value pair) in dictionary are unordered, which means that the order isn't decided by the programmer but rather the interpreter.
- The ordering is based on a concept called “**hashing**” .

```
>>> d={'w':11,'a':33,'e':44}
```

```
>>> f= {'e':44,'w':11,'a':33}
```

```
>>> print(d==f)
```

```
True
```

# PYTHON FOR COMPUTATIONAL PROBLEM SOLVING

## Dictionary

---



### Common operations on dictionaries

- `len()`
- `min()`
- `max()`

**Note:** Dictionaries do not support '+' and '\*' operations

## Dictionary Functions

- **get()**: returns the value for a given key, if present.

```
>>> print(phonebook.get('Jill'))
```

```
938547565
```

- **items(...)**

D.items() -> a set-like object providing a view on D's items.

```
>>> phonebook.items()
```

```
dict_items([('Johan', 938477565), ('Jill', 938547565)])
```



## PYTHON FOR COMPUTATIONAL PROBLEM SOLVING

### Dictionary

---



- **keys(...)**

D.keys() -> a set-like object providing a view on D's keys.

```
>>> phonebook.keys()
```

```
dict_keys(['Johan', 'Jill'])
```

- **pop(...)**

D.pop(key) -> v, remove specified key and return the corresponding value. If

key is not found, otherwise KeyError is raised.

```
>>> phonebook.pop('Jill')
```

```
938547565
```

## PYTHON FOR COMPUTATIONAL PROBLEM SOLVING

### Dictionary

---



- **popitem(...)**

D.popitem() -> (k, v); remove and return some (key, value) pair as a 2-tuple, but raise KeyError if D is empty.

```
>>> person = {'name': 'Phill', 'age': 22, 'salary': 3500.0}
```

```
>>> result = person.popitem()
```

```
>>> print('Return Value = ', result)
```

```
Return Value = ('salary', 3500.0)
```

```
>>> print('person = ', person)
```

```
person = {'name': 'Phill', 'age': 22}
```

## PYTHON FOR COMPUTATIONAL PROBLEM SOLVING

### Dictionary

---



- **setdefault(...)**

D.setdefault(key,value) -> if the key is in the dictionary, returns its value. If the key is not present, insert the key with a specified value and returns that same value.

```
>>> person = {'name': 'Phil', 'age': 22}
```

```
>>> phone = person.setdefault('phone', 90909090)
```

```
>>> print('person = ',person)
```

```
>>> print('phone = ',phone)
```

#### **Output:**

```
person = {'name': 'Phil', 'age': 22, 'phone': 90909090}
```

```
phone = 90909090
```

## PYTHON FOR COMPUTATIONAL PROBLEM SOLVING

### Dictionary

---



- **update(...)**

D.update() -> updates content of D with key-value pairs from a dictionary/iterable that it is given

```
>>> marks = {'Physics':67, 'Maths':87}
```

```
>>> internal_marks = {'Practical':48}
```

```
>>> marks.update( [('Chemistry', 90), ('Python', 100)] )
```

```
>>> marks.update(internal_marks)
```

```
>>> print(marks)
```

```
{'Physics': 67, 'Maths': 87, 'Chemistry': 90, 'Python': 100, 'Practical': 48}
```

- **values(...)**

D.values() -> returns a view object that displays a list of all the values in the dictionary.

```
>>> marks = {'Physics':67, 'Maths':87}
```

```
>>> print(marks.values())
```

```
dict_values([67, 87])
```

# PYTHON FOR COMPUTATIONAL PROBLEM SOLVING

## Dictionary

---



### Use of for and while loops for dictionary

#### 1. for loop

Ex: (1) `dict = {'a': 'pencil', 'b': 'eraser', 'c': 'sharpner'}`

`for key, value in dict.items():`

`print(key, value)`

Ex: (2) `dict = {'a': 'juice', 'b': 'grill', 'c': 'corn'}`

`for key in dict:`

`print(key, dict[key])`

### Use of for and while loops for dictionary

#### 2. while loop

```
Ex:  books={"learning python": "Mark Lutz", "think python": "Allen B. Downey",  
          "Fluent Python": "Luciano Ramalho"}  
  
key=list(books) #converts keys into a list  
  
i=0  
  
while i<len(key):  
    print(key[i],":",books[key[i]])  
    i+=1
```



## THANK YOU

---

Department of Computer Science and Engineering

Dr. Shylaja S S, Director, CCBBD & CDSAML, PESU

Prof. Sindhu R Pai – [sindhurpai@pes.edu](mailto:sindhurpai@pes.edu)

Prof. Chitra G M

Prof. Mohan Kumar AV