Some Helper Function:

Softmax Function:

```
import numpy as np

def softmax(z):
    """
    Compute the softmax probabilities for a given input matrix.

    Parameters:
    z (numpy.ndarray): Logits (raw scores) of shape (m, n), where
                       - m is the number of samples.
                       - n is the number of classes.

    Returns:
    numpy.ndarray: Softmax probability matrix of shape (m, n), where
                   each row sums to 1 and represents the probability
                   distribution over classes.

    Notes:
    - The input to softmax is typically computed as: z = XW + b.
    - Uses numerical stabilization by subtracting the max value per row.
    """
    # Step 1: Subtract the max of each row for numerical stability (prevents overflow in exp)
    z_shifted = z - np.max(z, axis=1, keepdims=True)
    # Step 2: Compute exponentials
    exp_z = np.exp(z_shifted)
    # Step 3: Divide each element by the sum of its row so each row sums to 1
    return exp_z / np.sum(exp_z, axis=1, keepdims=True)
```

Softmax Test Case:

This test case checks that each row in the resulting softmax probabilities sums to 1, which is the fundamental property of softmax.

```
# Example test case

z_test = np.array([[2.0, 1.0, 0.1], [1.0, 1.0, 1.0]])
softmax_output = softmax(z_test)

# Verify if the sum of probabilities for each row is 1 using assert
row_sums = np.sum(softmax_output, axis=1)

# Assert that the sum of each row is 1
assert np.allclose(row_sums, 1), f"Test failed: Row sums are {row_sums}"

print("Softmax function passed the test case!")
```

```
---------------------------------------------------------------------------
NameError                                 Traceback (most recent call last)
/tmp/ipykernel_387/2716791688.py in <cell line: 0>()
      3
      4 z_test = np.array([[2.0, 1.0, 0.1], [1.0, 1.0, 1.0]])
----> 5 softmax_output = softmax(z_test)
      6
      7 # Verify if the sum of probabilities for each row is 1 using assert

NameError: name 'softmax' is not defined
```

Prediction Function:

```
def predict_softmax(X, W, b):
    """
    Predict the class labels for a set of samples using the trained softmax model.

    Parameters:
```

```
    X (numpy.ndarray): Feature matrix of shape (n, d), where n is the number of samples and d is the number of features.
    W (numpy.ndarray): Weight matrix of shape (d, c), where c is the number of classes.
    b (numpy.ndarray): Bias vector of shape (c,).

    Returns:
    numpy.ndarray: Predicted class labels of shape (n,), where each value is the index of the predicted class.
    """
    z = np.dot(X, W) + b          # Compute logits: shape (n, c)
    y_pred = softmax(z)            # Compute probabilities: shape (n, c)
    predicted_classes = np.argmax(y_pred, axis=1)
    return predicted_classes
```

Test Function for Prediction Function:

The test function ensures that the predicted class labels have the same number of elements as the input samples, verifying that the model produces a valid output shape.

```
# Define test case
X_test = np.array([[0.2, 0.8], [0.5, 0.5], [0.9, 0.1]])
W_test = np.array([[0.4, 0.2, 0.1], [0.3, 0.7, 0.5]])
b_test = np.array([0.1, 0.2, 0.3])  # Bias (3 classes)

y_pred_test = predict_softmax(X_test, W_test, b_test)

# Validate output shape
assert y_pred_test.shape == (3,), f"Test failed: Expected shape (3,), got {y_pred_test.shape}"

# Print the predicted labels
print("Predicted class labels:", y_pred_test)
```

```
Predicted class labels: [1 1 0]
```

Loss Function:

```
def loss_softmax(y_pred, y):
    """
    Compute the cross-entropy loss.

    Parameters:
    y_pred (numpy.ndarray): Predicted probabilities of shape (n, c) or (c,).
    y (numpy.ndarray): True labels (one-hot encoded) of shape (n, c) or (c,).

    Returns:
    float: Cross-entropy loss.
    """
    epsilon = 1e-12
    y_pred = np.clip(y_pred, epsilon, 1.0 - epsilon)
    n = y.shape[0]
    loss = -np.sum(y * np.log(y_pred)) / n
    return loss
```

Test case for Loss Function:

This test case Compares loss for correct vs. incorrect predictions.

- Expects low loss for correct predictions.
- Expects high loss for incorrect predictions.

```
import numpy as np


y_true_correct = np.array([[1, 0, 0], [0, 1, 0], [0, 0, 1]])
y_pred_correct = np.array([[0.9, 0.05, 0.05],
                           [0.1, 0.85, 0.05],
                           [0.05, 0.1, 0.85]])

y_pred_incorrect = np.array([[0.05, 0.05, 0.9],
                             [0.1, 0.05, 0.85],
```

```
                                [0.85, 0.1, 0.05]])


loss_correct = loss_softmax(y_pred_correct, y_true_correct)
loss_incorrect = loss_softmax(y_pred_incorrect, y_true_correct)


assert loss_correct < loss_incorrect, f"Test failed: Expected loss_correct < loss_incorrect, but got {loss_correct:.4f} >= {loss_

print(f"Cross-Entropy Loss (Correct Predictions): {loss_correct:.4f}")
print(f"Cross-Entropy Loss (Incorrect Predictions): {loss_incorrect:.4f}")
```

```
Cross-Entropy Loss (Correct Predictions): 0.4304
Cross-Entropy Loss (Incorrect Predictions): 8.9872
```

Cost Function:

```
def cost_softmax(X, y, W, b):
    """
    Compute the average softmax regression cost (cross-entropy loss) over all samples.

    Parameters:
    X (numpy.ndarray): Feature matrix of shape (n, d).
    y (numpy.ndarray): True labels (one-hot encoded) of shape (n, c).
    W (numpy.ndarray): Weight matrix of shape (d, c).
    b (numpy.ndarray): Bias vector of shape (c,).

    Returns:
    float: Average softmax cost (cross-entropy loss) over all samples.
    """
    n = X.shape[0]
    z = np.dot(X, W) + b
    y_pred = softmax(z)
    total_loss = loss_softmax(y_pred, y) * n
    return total_loss / n
```

Test Case for Cost Function:

The test case assures that the cost for the incorrect prediction should be higher than for the correct prediction, confirming that the cost function behaves as expected.

```
import numpy as np


X_correct = np.array([[1.0, 0.0], [0.0, 1.0]])
y_correct = np.array([[1, 0], [0, 1]])
W_correct = np.array([[5.0, -2.0], [-3.0, 5.0]])
b_correct = np.array([0.1, 0.1])

X_incorrect = np.array([[0.1, 0.9], [0.8, 0.2]])
y_incorrect = np.array([[1, 0], [0, 1]])
W_incorrect = np.array([[0.1, 2.0], [1.5, 0.3]])
b_incorrect = np.array([0.5, 0.6])


cost_correct = cost_softmax(X_correct, y_correct, W_correct, b_correct)


cost_incorrect = cost_softmax(X_incorrect, y_incorrect, W_incorrect, b_incorrect)


assert cost_incorrect > cost_correct, f"Test failed: Incorrect cost {cost_incorrect} is not greater than correct cost {cost_corre

print("Cost for correct prediction:", cost_correct)
print("Cost for incorrect prediction:", cost_incorrect)

print("Test passed!")
```

```
Cost for correct prediction: 0.0006234364133349324
Cost for incorrect prediction: 0.29930861359446115
Test passed!
```

Computing Gradients:

```
def compute_gradient_softmax(X, y, W, b):
    """
    Compute the gradients of the cost function with respect to weights and biases.

    Parameters:
    X (numpy.ndarray): Feature matrix of shape (n, d).
    y (numpy.ndarray): True labels (one-hot encoded) of shape (n, c).
    W (numpy.ndarray): Weight matrix of shape (d, c).
    b (numpy.ndarray): Bias vector of shape (c,).

    Returns:
    tuple: Gradients with respect to weights (d, c) and biases (c,).
    """
    n, d = X.shape
    z = np.dot(X, W) + b
    y_pred = softmax(z)


    grad_W = np.dot(X.T, (y_pred - y)) / n

    grad_b = np.sum(y_pred - y, axis=0) / n

    return grad_W, grad_b
```

Test case for compute_gradient function:

The test checks if the gradients from the function are close enough to the manually computed gradients using np.allclose, which accounts for potential floating-point discrepancies.

```
import numpy as np

X_test = np.array([[0.2, 0.8], [0.5, 0.5], [0.9, 0.1]])
y_test = np.array([[1, 0, 0], [0, 1, 0], [0, 0, 1]])

# Define weight matrix and bias vector
W_test = np.array([[0.4, 0.2, 0.1], [0.3, 0.7, 0.5]])
b_test = np.array([0.1, 0.2, 0.3])  # Bias (3 classes)

grad_W, grad_b = compute_gradient_softmax(X_test, y_test, W_test, b_test)

z_test = np.dot(X_test, W_test) + b_test
y_pred_test = softmax(z_test)

# Compute the manually computed gradients
grad_W_manual = np.dot(X_test.T, (y_pred_test - y_test)) / X_test.shape[0]
grad_b_manual = np.sum(y_pred_test - y_test, axis=0) / X_test.shape[0]

# Assert that the gradients computed by the function match the manually computed gradients
assert np.allclose(grad_W, grad_W_manual), f"Test failed: Gradients w.r.t. W are not equal.\nExpected: {grad_W_manual}\nGot: {gra
assert np.allclose(grad_b, grad_b_manual), f"Test failed: Gradients w.r.t. b are not equal.\nExpected: {grad_b_manual}\nGot: {gra

print("Gradient w.r.t. W:", grad_W)
print("Gradient w.r.t. b:", grad_b)

print("Test passed!")
```

```
Gradient w.r.t. W: [[ 0.1031051   0.01805685 -0.12116196]
 [-0.13600547  0.00679023  0.12921524]]
Gradient w.r.t. b: [-0.03290036  0.02484708  0.00805328]
Test passed!
```

Implementing Gradient Descent:

```
def gradient_descent_softmax(X, y, W, b, alpha, n_iter, show_cost=False):
    """
    Perform gradient descent to optimize the weights and biases.
```

```
    Parameters:
    X (numpy.ndarray): Feature matrix of shape (n, d).
    y (numpy.ndarray): True labels (one-hot encoded) of shape (n, c).
    W (numpy.ndarray): Weight matrix of shape (d, c).
    b (numpy.ndarray): Bias vector of shape (c,).
    alpha (float): Learning rate.
    n_iter (int): Number of iterations.
    show_cost (bool): Whether to display the cost at intervals.

    Returns:
    tuple: Optimized weights, biases, and cost history.
    """
    cost_history = []

    for i in range(n_iter):
        # Compute gradients
        grad_W, grad_b = compute_gradient_softmax(X, y, W, b)

        # Update weights and biases using gradient descent rule
        W -= alpha * grad_W
        b -= alpha * grad_b

        # Compute and store the cost at each iteration
        cost = cost_softmax(X, y, W, b)
        cost_history.append(cost)

        # Print cost at regular intervals
        if show_cost and (i % 100 == 0 or i == n_iter - 1):
            print(f"Iteration {i}: Cost = {cost:.6f}")

    return W, b, cost_history
```

Preparing Dataset:

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from sklearn.model_selection import train_test_split

def load_and_prepare_mnist(csv_file, test_size=0.2, random_state=42):
    """
    Reads the MNIST CSV file, splits data into train/test sets, and plots one image per class.

    Arguments:
    csv_file (str)       : Path to the CSV file containing MNIST data.
    test_size (float)    : Proportion of the data to use as the test set (default: 0.2).
    random_state (int)   : Random seed for reproducibility (default: 42).

    Returns:
    X_train, X_test, y_train, y_test : Split dataset.
    """

    # Load dataset
    df = pd.read_csv(csv_file)

    # Separate labels and features
    y = df.iloc[:, 0].values
    X = df.iloc[:, 1:].values

    X = X / 255.0

    # Split data into train and test sets
    X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=test_size, random_state=random_state)

    # Plot one sample image per class
    plot_sample_images(X, y)

    return X_train, X_test, y_train, y_test

def plot_sample_images(X, y):
    """
    Plots one sample image for each digit class (0-9).
```

```
    Arguments:
    X (np.ndarray): Feature matrix containing pixel values.
    y (np.ndarray): Labels corresponding to images.
    """

    plt.figure(figsize=(10, 4))
    unique_classes = np.unique(y)

    for i, digit in enumerate(unique_classes):
        index = np.where(y == digit)[0][0]
        image = X[index].reshape(28, 28)

        plt.subplot(2, 5, i + 1)
        plt.imshow(image, cmap='gray')
        plt.title(f"Digit: {digit}")
        plt.axis('off')

    plt.tight_layout()
    plt.show()
```

```
# following the same ERM / Softmax Regression framework from the tutorial slides.

import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder, OneHotEncoder

# ---- Load Iris dataset ----
df = pd.read_csv('Iris.csv')
print('Dataset Preview:')
print(df.head())
print('\nDataset Info:')
print(df.info())

X = df.iloc[:, 1:-1].values
y_raw = df.iloc[:, -1].values


label_encoder = LabelEncoder()
y_encoded = label_encoder.fit_transform(y_raw)

ohe = OneHotEncoder(sparse_output=False)
y_one_hot = ohe.fit_transform(y_encoded.reshape(-1, 1))


X = (X - X.mean(axis=0)) / X.std(axis=0)

X_train, X_test, y_train, y_test = train_test_split(
    X, y_one_hot, test_size=0.2, random_state=42, stratify=y_one_hot
)

print('\nUnique classes:', np.unique(y_encoded))
print('Class names:', label_encoder.classes_)
print('\nShapes:')
print('X_train:', X_train.shape, ' y_train:', y_train.shape)
print('X_test: ', X_test.shape,  ' y_test: ', y_test.shape)
```



A Quick debugging Step:

```
# Assert that X and y have matching lengths
assert len(X_train) == len(y_train), f"Error: X and y have different lengths! X={len(X_train)}, y={len(y_train)}"
print("Move forward: Dimension of Feture Matrix X and label vector y matched.")
```

```
Move forward: Dimension of Feture Matrix X and label vector y matched.
```

Train the Model:

```
print(f"Training data shape: {X_train.shape}")
print(f"Test data shape: {X_test.shape}")
```

```
Training data shape: (48000, 784)
Test data shape: (12000, 784)
```

```
from sklearn.preprocessing import OneHotEncoder

d = X_train.shape[1]   # Number of features
c = y_train.shape[1]   # Number of classes

np.random.seed(42)
W = np.random.randn(d, c) * 0.01
b = np.zeros(c)

alpha = 0.1
n_iter = 1000

W_opt, b_opt, cost_history = gradient_descent_softmax(X_train, y_train, W, b, alpha, n_iter, show_cost=True)

plt.figure(figsize=(8, 4))
plt.plot(cost_history, color='steelblue')
plt.title('Cost Function vs. Iterations')
plt.xlabel('Iterations')
plt.ylabel('Cost (Cross-Entropy Loss)')
plt.grid(True)
plt.tight_layout()
plt.show()
```

```
Iteration 0: Cost = 2.184323
Iteration 100: Cost = 0.606876
Iteration 200: Cost = 0.489345
Iteration 300: Cost = 0.440811
Iteration 400: Cost = 0.412778
Iteration 500: Cost = 0.393941
Iteration 600: Cost = 0.380141
Iteration 700: Cost = 0.369450
Iteration 800: Cost = 0.360837
Iteration 900: Cost = 0.353697
Iteration 999: Cost = 0.347700
```



Evaluating the Model:

```
import numpy as np
import matplotlib.pyplot as plt
from sklearn.metrics import confusion_matrix, precision_score, recall_score, f1_score

# Evaluation Function
def evaluate_classification(y_true, y_pred):
    """
    Evaluate classification performance using confusion matrix, precision, recall, and F1-score.

    Parameters:
    y_true (numpy.ndarray): True labels
    y_pred (numpy.ndarray): Predicted labels

    Returns:
    tuple: Confusion matrix, precision, recall, F1 score
    """
    # Compute confusion matrix
    cm = confusion_matrix(y_true, y_pred)

    # Compute precision, recall, and F1-score
    precision = precision_score(y_true, y_pred, average='weighted')
    recall = recall_score(y_true, y_pred, average='weighted')
    f1 = f1_score(y_true, y_pred, average='weighted')

    return cm, precision, recall, f1
```

```
# Predict on the test set
y_pred_test = predict_softmax(X_test, W_opt, b_opt)

# Evaluate accuracy
y_test_labels = np.argmax(y_test, axis=1)  # True labels in numeric form

# Evaluate the model
cm, precision, recall, f1 = evaluate_classification(y_test_labels, y_pred_test)
```

```
# Print the evaluation metrics
print("\nConfusion Matrix:")
print(cm)
print(f"Precision: {precision:.2f}")
print(f"Recall: {recall:.2f}")
print(f"F1-Score: {f1:.2f}")

# Visualizing the Confusion Matrix
fig, ax = plt.subplots(figsize=(12, 12))
cax = ax.imshow(cm, cmap='Blues')  # Use a color map for better visualization

# Dynamic number of classes
num_classes = cm.shape[0]
ax.set_xticks(range(num_classes))
ax.set_yticks(range(num_classes))
ax.set_xticklabels([f'Predicted {i}' for i in range(num_classes)])
ax.set_yticklabels([f'Actual {i}' for i in range(num_classes)])

# Add labels to each cell in the confusion matrix
for i in range(cm.shape[0]):
    for j in range(cm.shape[1]):
        ax.text(j, i, cm[i, j], ha='center', va='center', color='white' if cm[i, j] > np.max(cm) / 2 else 'black')

# Add grid lines and axis labels
ax.grid(False)
plt.title('Confusion Matrix', fontsize=14)
plt.xlabel('Predicted Label', fontsize=12)
plt.ylabel('Actual Label', fontsize=12)

# Adjust layout
plt.tight_layout()
plt.colorbar(cax)
plt.show()
```

```
Confusion Matrix:
[[1127    0    5    2    3   11    9    2   13    3]
 [   0 1277    7   10    1    5    1    4   16    1]
 [   1   16 1027   15   20    4   26   24   34    7]
 [   8    6   33 1050    1   54    9    8   29   21]
 [   1    5    7    1 1094    0   10    4    3   51]
 [  22   14   13   44   11  925   14    7   40   14]
 [   7    2   10    1   11   15 1119    2   10    0]
 [   7   27   23    4   15    3    0 1183    7   30]
 [   9   27   13   36    9   31   13    7 1000   15]
 [   8    6   10   18   44    9    0   38   10 1051]]
Precision: 0.90
Recall: 0.90
F1-Score: 0.90
```



Linear Seperability and Logistic Regression:

```
# ============================================================
# Linear Separability and Logistic Regression
# ============================================================
# Softmax / Logistic Regression assumes that classes are linearly
# separable in the feature space — i.e. a hyperplane can separate them.
# Below we visualise the first two features of the Iris dataset
# to show which pairs of classes are (nearly) linearly separable.

import matplotlib.pyplot as plt
import numpy as np

# Use original (non-normalised) features for easier interpretation
df_plot = pd.read_csv('Iris.csv')
X_plot = df_plot.iloc[:, 1:-1].values
y_plot = label_encoder.transform(df_plot.iloc[:, -1].values)
class_names = label_encoder.classes_

feature_pairs = [(0, 1), (2, 3), (0, 2)]
feature_labels = ['Sepal Length', 'Sepal Width', 'Petal Length', 'Petal Width']
colors = ['tomato', 'steelblue', 'seagreen']

fig, axes = plt.subplots(1, 3, figsize=(15, 4))

for ax, (f1, f2) in zip(axes, feature_pairs):
    for cls in range(3):
        mask = y_plot == cls
        ax.scatter(X_plot[mask, f1], X_plot[mask, f2],
                   label=class_names[cls], color=colors[cls], alpha=0.7, edgecolors='k', linewidths=0.4)
    ax.set_xlabel(feature_labels[f1])
    ax.set_ylabel(feature_labels[f2])
    ax.set_title(f'{feature_labels[f1]} vs {feature_labels[f2]}')
    ax.legend(fontsize=8)
    ax.grid(True, alpha=0.3)

plt.suptitle('Iris Dataset — Linear Separability Check\n'
             '(Setosa is linearly separable; Versicolor/Virginica overlap slightly)',
             fontsize=11)
plt.tight_layout()
```