

Video

Summarization

Team 11





01

Introduction

Here we take a look at what we aim to achieve

02

Assumptions

Here we can see assumption we used in our work

03

Algorithms

We Can Take A look at our Algorithm Choices

04

Examples


A Video Summarized by All Our Chosen Algorithms

05

Conclusion


We have a look at what we achieved and concluded

INTRODUCTION




Out Approach





Introduction

Our work focuses on the summarization of videos using extractive summarization methods by first transcribing them then applying a user chosen Natural Language Processing algorithm to get the final summary which can be chosen using our application.



Assumptions



Prerequisites and assumptions



Our Assumptions

Summarization Method

There are two main types of summarization: Abstractive and Extractive. Here our aim is to generate a summary from already provided keywords, so extractive summarization is used.




Language Used

Videos are in the English Language.
Algorithms are unfazed by accents.

Algorithms

Our Chosen Algorithms



Algorithms

Pure NLTK

Algorithm using only nltk library's tokenizers

Gensim

Algorithm using gensim library's TextRank based Algo

Luhn

Algorithm using sumy library's Luhn Heuristic Algo

LexRank

Algorithm using sumy library's LexRank based Algo

KL-Sum

Algorithm using sumy library's KL-Sum based Algo

Naïve Reduction

Algorithm using sumy library's Normal Reduction Algo



Let's Dive in

Brief discription of all our implemented Video
Summarization Algorithms

Pure NLTK Algorithm

The Algorithm employs a straightforward approach by assigning importance scores to sentences based on the frequency of non-stop words.

```
def summarizeNLTKPure(text):
    from nltk.corpus import stopwords
    from nltk.tokenize import word_tokenize, sent_tokenize
    stopwords = set(stopwords.words("english"))
    words = word_tokenize(text)

    freqTable = dict()
    for word in words:
        word = word.lower()
        if word in stopwords:
            continue
        if word in freqTable:
            freqTable[word] += 1
        else:
            freqTable[word] = 1

    sentences = sent_tokenize(text)
    sentenceValue = dict()
    for sentence in sentences:
        for word, freq in freqTable.items():
            if word in sentence.lower():
                if sentence in sentenceValue:
                    sentenceValue[sentence] += freq
                else:
                    sentenceValue[sentence] = freq

    sumValues = 0
    for sentence in sentenceValue:
        sumValues += sentenceValue[sentence]
    average = int(sumValues / len(sentenceValue))

    Summary = ''
    for sentence in sentences:
        if (sentence in sentenceValue) and (sentenceValue[sentence] > (1.2 * average)):
            Summary += " " + sentence

    print(Summary)
    return Summary
```


Gensim Algorithm

Summarization is done by representing words or sentences as points on a graph connected by relationships. Each point gets an initial score, and through a process of refining and ranking based on connections, the algorithm identifies the most important words or sentences

```
def summarizeGensim(text, compressionRatio):  
    from gensim.summarization import summarize  
    summary = summarize(text, ratio=compressionRatio)  
    print(summary)  
    return summary
```

Luhn Heuristic Algorithm

Summarization is done by giving importance to words that appear frequently. It uses a method called TF-IDF to weigh words and scores sentences based on concentration of important words. The scoring considers the number of important words in a sentence and their placement.

```
def summarizeLuhn(text, compressionRatio):
    from sumy.parsers.plaintext import PlaintextParser
    from sumy.nlp.tokenizers import Tokenizer
    from sumy.summarizers.luhn import LuhnSummarizer
    parser = PlaintextParser.from_string(text, Tokenizer('english'))
    CompressedSentenceCount = round(len(parser.tokenize_sentences(text))*compressionRatio)

    luhnSummarizer = LuhnSummarizer()
    luhnSummarizerSummary = luhnSummarizer(parser.document, CompressedSentenceCount)
    summaryLUHN = ' '.join([str(sentence) for sentence in luhnSummarizerSummary])
    print(f"{summaryLUHN}\n")
    return summaryLUHN
```


LexRank Algorithm

Summarization is done by measuring sentence importance based on how similar they are to others. and calculating scores using a method called power iteration.

```
def summarizeLexRank(text, compressionRatio):  
    from sumy.parsers.plaintext import PlaintextParser  
    from sumy.nlp.tokenizers import Tokenizer  
    from sumy.summarizers.lex_rank import LexRankSummarizer  
    parser = PlaintextParser.from_string(text, Tokenizer('english'))  
    CompressedSentenceCount = round(len(parser.tokenize_sentences(text))*compressionRatio)  
  
    lexRankSummarizer = LexRankSummarizer()  
    lexRankSummarizerSummary = lexRankSummarizer(parser.document, CompressedSentenceCount)  
    summaryLEX = ' '.join([str(sentence) for sentence in lexRankSummarizerSummary])  
    print(f"{summaryLEX}\n")  
    return summaryLEX
```

KL-Sum Algorithm

Summarization is done by trying to preserve the original document's word distribution. It uses KL Divergence to measure differences between distribution in summary and original and only chooses sentences that minimizes the difference

```
def summarizeKLSum(text, compressionRatio):  
    from sumy.parsers.plaintext import PlaintextParser  
    from sumy.nlp.tokenizers import Tokenizer  
    from sumy.summarizers.kl import KLSummarizer  
    parser = PlaintextParser.from_string(text, Tokenizer('english'))  
    CompressedSentenceCount = round(len(parser.tokenize_sentences(text))*compressionRatio)  
  
    klSummarizer = KLSummarizer()  
    klSummarizer = klSummarizer(parser.document, CompressedSentenceCount)  
    summaryKL = ' '.join([str(sentence) for sentence in klSummarizer])  
    print(f"{summaryKL}\n")  
    return summaryKL
```


Naïve Reduction Algorithm

Summarization is done by rating sentences based on similarity between it and other sentence by counting common words, it then converts rating to weight and finally, selecting sentences with the highest to add to summary.


```
def summarizeKLSum(text, compressionRatio):
    from sumy.parsers.plaintext import PlaintextParser
    from sumy.nlp.tokenizers import Tokenizer
    from sumy.summarizers.reduction import ReductionSummarizer
    parser = PlaintextParser.from_string(text, Tokenizer('english'))
    CompressedSentenceCount = round(len(parser.tokenize_sentences(text))*compressionRatio)

    reductionSummarizer = ReductionSummarizer()
    reductionSummarizerSummary = reductionSummarizer(parser.document, CompressedSentenceCount)
    summaryReduction = ' '.join([str(sentence) for sentence in reductionSummarizerSummary])
    print(f"{summaryReduction}\n")
    return summaryReduction
```

Examples



A video that has been summarized using all of the
different summarization methods



Original Video



Pure NLTK



Gensim



Luhn Heuristic



LexRank



KL-Sum





Naïve Reduction



Conclusion

What we achieved




Our Conclusion

We focused on crafting an extractive summarization app, leveraging a curated selection of algorithms that includes NLTK, Gensim TextRank, Luhn's Heuristic, LexRank, KL-Sum, and Naïve Reduction. This approach prioritizes fidelity to the source material.

Python served as the backbone, accompanied by Gensim, Sumy, json, pyqt5, nltk, whisper, pydub, and moviepy all encapsulated in a meticulously crafted GUI using pyqt5 that fosters simplicity and user engagement.

In conclusion, our work contributes to the ongoing evolution of video summarization.

A black horizontal bar representing a window frame, containing three small pink circles on the left side.

Thanks

Do you have any questions?

