

Ben-Gurion University of the Negev

Engineering sciences

Software and Information Systems Engineering

Physical Informed Machine Learning

למידת מכונה מבוססת פיזיקה

Daniella Kapustyan , Shay Milner, Daniel Peri

Prof. Mark Last

2024

Summary

The aviation industry relies heavily on accurate and efficient simulation models for tasks such as pilot training, aircraft design, and operational planning. Traditional simulation methods, grounded in physics-based models, provide high accuracy but are computationally intensive, often leading to extended processing times that hinder real-time applications. Recent advancements in machine learning, particularly in Physics-Informed Machine Learning (PIML), offer a promising alternative by integrating physical laws into data-driven models. This paper explores the application of PIML, specifically through Physics-Informed Neural Networks (PINNs), to enhance the prediction of aircraft movement in flight simulations. Our study presents a comprehensive approach that combines LSTM models with physical constraints to improve simulations' predictive accuracy and computational efficiency. Through rigorous experimentation, our results demonstrate a significant reduction in Mean Squared Error (MSE) by 25% to 50% compared to traditional models, along with enhanced physical consistency in trajectory predictions. Despite these advancements, challenges remain in multi-feature prediction and data quality, underscoring the need for further refinement. The findings of this research contribute to the evolving field of aerospace simulation and highlight the potential of PIML in reducing computational demands while maintaining high predictive accuracy. Future work will focus on real-time implementation, model scalability, and the exploration of additional features and architectures that can further advance aircraft simulation technology.

תקציר

תעשיית התעופה מסתמכת במידה רבה על מודלים מדויקים ויעילים של סימולציות לצורכי הכשרת טייסים, תכנון מטוסים ותכנון מבצעי. שיטות הסימולציה המסורתיות, המבוססות על מודלים פיזיקליים, מספקות דיוק גבוה אך דורשות משאבים חישוביים משמעותיים, מה שמוביל לעיתים קרובות לזמני עיבוד ממושכים שמקשים על יישומים בזמן אמת. ההתקדמות האחרונה בלמידת מכונה, ובפרט בתחום למידת מכונה מבוססת פיזיקה (PIML), מציעה חלופה מבטיחה על ידי שילוב חוקים פיזיקליים במודלים מבוססי נתונים. מאמר זה בוחן את היישום של PIML במיוחד באמצעות רשתות נוירונים מבוססות פיזיקה (PINNs) לשיפור חיזוי תנועת מטוסים בסימולציות טיסה. המחקר שלנו מציג גישה מקיפה שמשלבת מודלים של LSTM עם אילוצים פיזיקליים במטרה לשפר את דיוק ויעילות החישובים של הסימולציות. תוצאות הניסויים שלנו מראות ירידה משמעותית בשגיאה הריבועית הממוצעת (MSE) בשיעור של 25% עד 50% בהשוואה למודלים מסורתיים, יחד עם עקביות פיזיקלית משופרת בתחזיות המסלולים. על אף ההתקדמות, נותרו אתגרים בחיזוי של מספר מאפיינים בזמנית ובאיכות הנתונים, מה שמדגיש את הצורך בשיפור נוסף. ממצאי המחקר תורמים להתפתחות תחום הסימולציה האווירית ומדגישים את הפוטנציאל של PIML בהפחתת הדרישות החישוביות תוך שמירה על דיוק תחזיתי גבוה. מחקר עתידי יכול להתמקד ביישום בזמן אמת, בהגדלת היכולת להרחיב את המודלים ובחקר תכונות וארכיטקטורות נוספות לצורך קידום נוסף של טכנולוגיית הסימולציה האווירית.

Table of Contents

Summary	2
תקציר	2
Introduction	4
<i>Background</i>	4
<i>Motivation</i>	5
<i>Existing Situation</i>	5
<i>Gaps</i>	5
<i>Proposed Method</i>	6
<i>Main Findings</i>	7
<i>Document Structure</i>	7
Literature review	8
Objective	17
Methodology	18
<i>Data Collection and Preprocessing</i>	18
<i>Physics-Informed Neural Network (PINN) Design</i>	18
<i>Model Input and Output</i>	19
<i>Training Process</i>	19
Experiments	20
Results	22
Conclusions and Summary	24
<i>Challenges</i>	25
<i>Future Work</i>	25
Bibliography	26
Appendices	27

Introduction

Background

The aviation industry has long depended on simulation for various critical aspects, including pilot training, aircraft design, and operational planning. Traditionally, these simulations are based on physics-driven models that replicate the complex dynamics of flight, such as aerodynamics, propulsion, and control systems. These models rely on well-established physical laws and equations, such as Newton's laws of motion and the Navier-Stokes equations, to simulate the behavior of an aircraft under different conditions.

Despite their accuracy, these physics-based models are computationally intensive, requiring significant processing power and time to simulate complex scenarios accurately. For example, simulating the flight dynamics of an aircraft in turbulent conditions or during emergency maneuvers can take hours or even days on high-performance computing systems. This creates a bottleneck, particularly in situations that demand real-time or near-real-time responses, such as live training simulations or in-flight decision support systems.

In recent years, advancements in machine learning, particularly in deep learning and recurrent neural networks like Long Short-Term Memory (LSTM) networks, have opened new possibilities for the aviation industry. These models excel in handling time-series data and can learn complex patterns and dependencies from historical data. However, traditional machine learning models often lack an understanding of the underlying physical laws governing the system they are modeling, which can lead to inaccuracies, especially in extrapolating to unseen scenarios.

Physics-Informed Machine Learning (PIML) seeks to address this limitation by incorporating physical principles directly into the learning process. By embedding physics-based constraints and knowledge into the machine learning models, PIML combines the strengths of both data-driven and physics-based approaches. This hybrid method allows for the development of models that are not only computationally efficient but also physically accurate, offering a promising solution to the challenges faced by the aviation simulation industry.

Motivation

The aviation simulation industry is increasingly focused on real-time and accurate simulations of aircraft movements, crucial for training, safety assessments, and operational planning. Traditional simulation methods, which heavily rely on physics-based models, require substantial computational resources, leading to high costs and extended processing times. Our project aims to address these challenges by integrating Physics-Informed Machine Learning (PIML) techniques, specifically using Long Short-Term Memory (LSTM) models, to predict aircraft trajectories. By incorporating physical laws into the machine learning framework, we can reduce reliance on resource-intensive simulations while maintaining or improving predictive accuracy, ultimately saving time and resources.

Existing Situation

Currently, flight simulations rely heavily on complex mathematical models and physical computations to predict aircraft behavior. These methods, while accurate, are computationally expensive and require substantial processing power, particularly when simulating large-scale scenarios or real-time operations. The necessity for high accuracy often results in extensive simulation times, which can delay decision-making processes and increase operational costs. Furthermore, as the demand for more detailed and realistic simulations grows, the limitations of traditional methods become more apparent, highlighting the need for innovative solutions that can provide the same level of precision with fewer resources.

Gaps

The traditional reliance on purely physics-based models presents a growing challenge as the demand for faster and more detailed simulations increases. The gap between the need for real-time, accurate simulations and the computational resources required is widening. While Physics-Informed Machine Learning (PIML) offers a promising solution by integrating physical laws with machine learning models like LSTM, this approach is still under-explored in the context of aviation. Research indicates that while LSTM models excel in time series prediction, their application in PIML for aviation is in its initial stage. By effectively bridging this gap, we can achieve significant advancements in simulation efficiency, reduce costs, and enhance decision-making processes in the aviation industry.

Proposed Method

Our proposed method integrates Physics-Informed Neural Networks (PINNs) with traditional machine learning techniques to address the challenges and advance the state of aircraft movement prediction. The core of this approach involves several key components.

Firstly, the PINN model is designed to leverage both historical flight data and physical laws governing aircraft dynamics. By incorporating these physical principles into the neural network's loss function, the model is guided to produce predictions that align more closely with real-world physics. This approach not only enhances the accuracy of the predictions but also ensures their physical consistency.

To train and test the model, we utilize data extracted from the X-Plane 12 flight simulator, consisting of five simulated flights, each lasting 15 minutes. These flights vary in control inputs but maintain consistency in the aircraft used (Cessna Skyhawk), as well as the airfield, time of day, and weather conditions. Each flight provides 660 features, including altitude, speed, and aircraft orientation (pitch, yaw, roll), sampled at a rate of 10 times per second, resulting in approximately 7,800 entries per feature. From this dataset, 18 basic movement features are selected and normalized using a standard scaler to ensure comparability. The dataset is then split into training, validation, and test sets based on different flights, with 13 key features ('vt', 'pitch', 'roll', 'hding', 'lat', 'lon', 'alt', 'x', 'y', 'z', 'vx', 'vy', 'vz') chosen as the target for prediction. The training process of the PINN model is carried out using advanced techniques, including the Adam optimizer and learning rate scheduling. This process is designed to refine the model's performance by minimizing both Mean Squared Error (MSE) and physics-based loss functions. Various model configurations are tested, such as different sequence lengths and dropout rates, to optimize the balance between accuracy and generalization.

Furthermore, the methodology includes the development of effective rolling prediction techniques to facilitate real-time applications. This involves designing the model to handle continuous, streaming data and making timely predictions based on the latest input.

Overall, the proposed method aims to enhance the accuracy and reliability of aircraft movement predictions by combining the strengths of PINNs with advanced machine learning practices, addressing data quality issues, and optimizing for real-time performance.

Main Findings

Our study on Physics-Informed Neural Networks (PINNs) for aircraft movement prediction revealed several significant outcomes. The PINN models showed a notable improvement in accuracy, achieving a Mean Squared Error (MSE) reduction of 25% to 50% compared to traditional LSTM models. This enhancement demonstrates the effectiveness of integrating physical laws into the model's training process, which contributes to more accurate predictions. Additionally, the PINN models produced predictions with greater coherence and physical consistency in their trajectory plots, reflecting a more realistic representation of aircraft movement.

One of the key original contributions of our work is the implementation of rolling predictions, which allows the model to handle continuous, streaming data more effectively—a critical requirement for real-time applications. This approach contrasts with previous studies that did not address the need for real-time data processing in the same manner. Furthermore, our study attempted to predict 13 features simultaneously, a complex task that, to our knowledge, has not been extensively explored in previous research. This multi-feature prediction posed significant challenges, particularly in managing the intricacies of detailed aircraft dynamics, but it also highlighted areas where PINN models can be further refined.

Despite these advances, the task of predicting 13 features simultaneously proved to be complex, emphasizing the challenges involved in capturing detailed aircraft dynamics. The study also identified issues with data quality, as simulation data was affected by noise due to system lags and performance limitations, which impacted model accuracy. This emphasizes the need for improvements in data quality and preprocessing to enhance prediction reliability.

Furthermore, the study underscored the need for developing effective rolling predictions for real-time applications. The ability to handle continuous, streaming data accurately is essential for practical real-time use cases. These findings illustrate the potential of PINNs to advance aircraft movement simulation while also highlighting areas that need further development and refinement.

Document Structure

This document is structured to provide a comprehensive overview of the development and evaluation of Physics-Informed Neural Networks (PINNs) for predicting aircraft movement in a flight simulator. It begins with the **Literature Review**, which examines existing research and methodologies related to aircraft movement prediction and the application of PINNs, establishing the context for the study and identifying key gaps in the field. The **Objective** section outlines the project's goal of creating a proof of concept

(POC) for a PINN-based model. Following this, the **Methodology** section describes the approach taken, including the design and training of the PINN models and the evaluation metrics used. The **Experiments** section provides an overview of the different model configurations tested, describing various experimental setups and their rationale. The **Results** section presents the findings from the experiments, including performance evaluations and comparisons between models. In the **Conclusions and Summary**, the implications of the results are discussed, along with the challenges faced during the study and proposed directions for future work. The **Bibliography** lists all references and sources cited throughout the document, while the **Appendices** include supplementary materials such as additional data, code snippets, and detailed results for further reference and validation. This structure ensures a coherent and thorough presentation of the research from theoretical foundations to practical outcomes.

Literature review

Introduction

In the realm of aircraft simulation, the reliability and accuracy of models are vital. Traditional simulation techniques rely heavily on detailed physical calculations to replicate the behavior of aircraft under various conditions. While essential for creating realistic simulations, these calculations are very time-consuming and resource intensive. The computational cost becomes even more expensive as simulations grow in complexity and scale, as mentioned in [1], posing significant challenges to researchers and engineers. This dilemma underscores the urgent need for innovative approaches that can maintain or enhance the accuracy of simulations while mitigating computational worry. Enter physics-informed machine learning (PIML), an emerging field that promises to revolutionize aircraft simulation by integrating the predictive power of machine learning (ML) with the fundamental principles of physics.

The core premise of PIML lies in its ability to control the vast capabilities of ML algorithms, not as standalone prediction tools, but as frameworks informed and constrained by physical laws. This synergy aims to produce models that are not only efficient and less resource-demanding but also inherently aligned with the underlying physics of flight dynamics, aerodynamics, and structural mechanics. By embedding physical laws into the learning process, PIML models can generate accurate predictions with significantly less computational effort compared to traditional simulation methods, potentially transforming the landscape of aircraft simulation.

This literature review seeks to explore the intersection of PIML and aircraft simulation, focusing on how this innovative approach addresses the critical challenge of reducing

the time and resources required for physical calculations. It will examine the methodologies underlying PIML, highlighting how physical laws are integrated into ML algorithms and the impact of this integration on computational efficiency and model reliability. Furthermore, the review will showcase specific applications of PIML in aircraft simulation, demonstrating its effectiveness in simulations without compromising accuracy.

Additionally, the review will discuss the challenges inherent in integrating physics with machine learning, including issues related to model interpretability, data scarcity, and the handling of complex, non-linear systems within the aircraft domain. It will also cast an eye towards the future, considering the potential advancements in PIML that could further enhance its applicability and effectiveness in aircraft simulation.


This literature review endeavors to shed light on the promising solutions presented by physics-informed machine learning (PIML) in response to the critical demand for more efficient simulation methodologies. By reducing the dependency on comprehensive physical computations, PIML has the potential to not only accelerate the development of high-precision aircraft simulations but also to broaden the accessibility of sophisticated simulation technologies. This development paves the way for groundbreaking opportunities in research, design, and training within the aerospace sector.

Flight Dynamics Models in Traditional Aircraft Simulation

At the core of traditional aircraft simulation lies the Flight Dynamics Models (FDM), a crucial component tasked with the accurate prediction of an aircraft's behavior under various flight conditions. These models clarify the complex interactions between aerodynamic forces, aircraft control inputs, and the resulting motion of the aircraft. This section provides an in-depth look at Flight Dynamics Models, highlighting their structure, the foundational physical calculations they rely on, and the challenges inherent in traditional approaches.

Structure and Function of Flight Dynamics Models

Flight Dynamics Models are sophisticated mathematical representations that simulate the three-dimensional motion of an aircraft through air. Central to these models are the six degrees of freedom (DOF) that describe an aircraft's movement: three translational movements (forward/back, up/down, left/right) and three rotational movements (pitch, roll, yaw).



The FDM integrates information from aerodynamics, momentum, and control systems to predict the aircraft's response to various flight conditions and control inputs. Key components include:

Aerodynamic Forces and Moments: These are calculated based on the aircraft's current state, including its speed, height, angle of attack, and configuration of control surfaces.

Mass and Inertia: The distribution of mass and inertia within the aircraft significantly affects its flight dynamics, influencing stability and control.

Equations of Motion: The FDM solves the aircraft's equations of motion, which are derived from Newton's second law of motion and the principles of conservation of momentum. These equations account for both linear and angular motion, providing a comprehensive view of the aircraft's flight dynamics. We will focus on linear motion.

Basic Physical Calculations

The FDM relies on several key physical calculations to simulate flight dynamics accurately:

Newton-Euler Equations: These equations form the mathematical foundation for modeling both translational and rotational dynamics of the aircraft. They incorporate forces and moments to calculate the aircraft's linear and angular accelerations.

Aerodynamic Coefficient Estimation: Critical to modeling the aerodynamic forces are the coefficients of lift, drag, and moment. These coefficients vary with the aircraft's geometry, flight conditions, and control surface positions.

Numerical Integration: To predict the aircraft's future state from its current state, the FDM employs numerical integration techniques. This process involves solving the equations of motion over discrete time steps, allowing for the simulation of dynamic behavior over time.

Challenges of Traditional Flight Dynamics Models

While traditional FDMs have been helpful in advancing aircraft design and simulation, they face several challenges:

Computational Complexity: The accuracy of an FDM often requires solving complex, non-linear equations at high frequencies, demanding significant computational resources.

Data Dependency: The precision of these models heavily depends on the availability and quality of aerodynamic data, which can be limited for novel aircraft designs or unconventional flight conditions.

Real-Time Simulation Constraints: For applications like pilot training simulators, FDMs must operate in real-time, further exacerbating computational challenges.

As the aerospace field continues to evolve, addressing these challenges becomes vital. This is where physics-informed machine learning (PIML) emerges as a transformative approach, offering the potential to enhance the efficiency, adaptability, and computational feasibility of Flight Dynamics Models. By integrating machine learning algorithms informed by physical laws, PIML can streamline the computational process, improve model adaptability to novel scenarios, and potentially reduce the reliance on extensive aerodynamic data sets.

The next sections will explore how PIML is being integrated into the domain of flight dynamics simulation, highlighting case studies, technological advancements, and the future trajectory of this exciting interdisciplinary field.

Physics-Based Learning Methods

In the study by Muther et al. (2022) [2], the authors investigate the trade-offs between data-driven machine learning and Physics-Informed Machine Learning (PIML) for complex physical problems. They highlight the limitations of purely data-driven approaches, which can become "black boxes" lacking interpretability and struggling with generalization.

To address these challenges, the authors propose a PIML approach that integrates physical laws, specifically Partial Differential Equations (PDEs), into the machine learning model. This integration is achieved by regularizing the loss function with the PDE residual, essentially guiding the model towards physically consistent solutions. This method is particularly valuable in scenarios with limited data, where purely data-driven models might struggle.

The key takeaway from this study for our project is the potential of PIML to achieve real-time modeling of physical systems. By incorporating physical constraints, we can potentially develop interpretable and generalizable models that work effectively even with limited data. This aligns with our goal of finding an optimal and efficient ML architecture for real-time physical system modeling.

The advantages of the PIML approach

It provides a mesh-free approach for solving PDEs, significantly reducing computational efforts and enabling the modeling of complex systems across diverse science and engineering disciplines.

However, Cuomo et al. (2022) [12] also addresses several limitations associated with the current state of the PIML approach. Notably, much of the existing literature focuses on 1D and 2D problems with low-dimensional datasets, raising concerns about the applicability of PIML to high-dimensional and heterogeneous problems. The challenges include the application of PIML to strongly coupled PDE systems, addressing stiffness in PDEs, and handling issues related to data quality, boundary conditions, and training time.

PINNs: Bridging Physics and Machine Learning:

The literature on physics-based learning methods is further enriched by the introduction of Physics-Informed Neural Networks (PINNs). PINNs are neural networks trained to solve supervised learning tasks while adhering to specific laws of physics, described by general nonlinear partial differential equations (PDEs) [3].

Researchers have developed two main classes of algorithms within the PINNs framework, tailored for different types of problems: continuous time models and discrete time models. Continuous time models form a new family of data-efficient spatio-temporal function approximators, while discrete time models allow the use of arbitrarily accurate implicit Runge-Kutta time-stepping schemes with an unlimited number of stages.

The effectiveness of the proposed framework is demonstrated its versatility by handling diverse physical systems and solving complex problems through a data-driven approach in various domains: health management and prognostics[4], fluid mechanics [5], biological systems[6], weather and climate modeling[7], multiphysics modeling within chemical engineering[8].

In our project focusing on an aircraft simulator built with Physics Informed Machine Learning (PINNs), a discrete-time model is likely more suitable. This is because aircraft controls (e.g., joystick movements) and sensor data (e.g., position updates) typically occur at distinct intervals, and a discrete-time model inherently aligns with these events. Additionally, while continuous models offer data-efficiency, discrete models can leverage highly accurate time-stepping schemes like Runge-Kutta methods. These schemes are crucial for capturing the dynamic behavior of an aircraft, especially during complex maneuvers. Finally, discrete-time models are generally easier to implement and integrate with control systems within the simulator.

The PIML framework, particularly the Physics-Informed Neural Network (PINN), demonstrates scalability to very high-dimensional PDEs without succumbing to the curse of dimensionality. This scalability, facilitated by the nature of neural networks, ensures computational efficiency even with increased dimensionality, giving it an advantage over traditional high-dimensional PDE solvers.

Integrating Physics-Informed Machine Learning into Flight Dynamics Simulation

The integration of Physics-Informed Machine Learning (PIML) into flight dynamics simulation represents a significant leap forward in aerospace engineering and simulation technology. This innovative approach leverages the predictive power of machine learning (ML) algorithms while ensuring adherence to the underlying physical laws that govern aircraft behavior. This section explores the integration of PIML into flight dynamics simulation, highlighting key case studies, technological advancements, and the prospective future of this interdisciplinary field.

The Intersection of Physics and Machine Learning

At the heart of PIML lies the combination of traditional physics-based models with the adaptive learning capabilities of ML algorithms. Unlike conventional ML models that rely only on data for learning patterns, PIML models are structured around the equations of flight dynamics, ensuring that predictions remain physically plausible. This integration not only enhances the accuracy of simulations under known conditions but

also significantly improves the model's extrapolation capabilities under novel or extreme conditions not represented in the training data.

Case Studies in PIML for Flight Dynamics

Several groundbreaking case studies illustrate the successful application of PIML in flight dynamics simulations:

Free-Flight Parameter Estimation with PINNs

Traditionally, estimating aircraft parameters has been a complex and time-consuming process. Existing methods might not accurately capture non-linear flight behavior across the entire flight envelope. The study by Michek, N., Mehta, P., & Huebsch, W. [14] proposes a novel approach using Physics-Informed Neural Networks (PINNs) to address these limitations. PINNs integrate machine learning with established physical laws, offering a more efficient and accurate solution for parameter estimation.

The study introduces three modifications to the standard PINN structure: Determinant PINNs, Non-Determinant PINNs, and Modified Non-Determinant PINNs. Determinant PINNs focus on estimating multiple sub-parameters within known equations. Non-Determinant PINNs utilize a neural network to model unknown parameters without requiring a pre-defined form. Modified Non-Determinant PINNs eliminate the need for a separate trajectory network when sufficient flight data is available.

Demonstrations using projectile motion and simulated F-16 flights showcase the promise of this approach. The study highlights the potential for applying PINNs to 6-DOF flight prediction in unstable flight scenarios. Future research directions include testing with real-world unstable flight data, incorporating uncertainty quantification methods, and comparing PINNs with classical parameter estimation techniques. These advancements can enhance the applicability of PINNs for broader flight dynamics simulations.

FlyNet: A Pioneering Approach to Global Aircraft Modeling

Conventional aircraft modeling approaches often involve a two-step process of parameter identification and regression. This method can struggle to capture the complex interactions between various aerodynamic forces and moments. The study by Stachiw, T., Crain, A., & Ricciardi, J. [9] introduces FlyNet, a novel single-step, continuous, and non-linear global aircraft modeling method that leverages a physics-informed neural network. The study compares FlyNet's performance to the classical two-step approach.

FlyNet directly learns the relationship between aircraft states, control inputs, and resulting forces and moments from flight test data. This eliminates the need for separate parameter identification and avoids potential limitations of traditional

regression techniques. The results demonstrate that FlyNet outperforms the classical approach on both training and test data with over 97% confidence. It exhibits superior trim ability and generalizability to new flight conditions. Notably, FlyNet automatically determines the model structure during training, reducing reliance on expert intervention for model design.

The study proposes further evaluation of FlyNet's impact on handling qualities and pilot feedback. FlyNet's unique architecture and strong performance position it as a significant advancement in global aircraft modeling. This approach has the potential to significantly impact the aerospace industry by enabling more accurate and efficient flight modeling capabilities.

DR-RNN: Physics-Based Learning for Enhanced Simulations

Existing methods for aircraft dynamics simulation might require high computational cost or struggle with extrapolating beyond the training data. The study by Yang et al. [10] explores a physics-based learning method using a Dynamic Regression Recurrent Neural Network (DR-RNN) to address these challenges. The DR-RNN is compared to a purely data-driven approach using Long Short-Term Memory (LSTM) networks.

The DR-RNN incorporates physics principles into the learning process, leading to more accurate and robust simulations. This approach allows for extrapolation beyond the training data, making it suitable for predicting aircraft behavior in novel flight scenarios. The study demonstrates that DR-RNN achieves accurate predictions even beyond the training data duration. Compared to LSTM networks, DR-RNN offers superior prediction accuracy, especially for extrapolation, and requires less training data. Additionally, it proves robust against noise in training data and exhibits greater computational efficiency, outperforming the classical Runge-Kutta numerical method.

The study suggests exploring the use of DR-RNN with diverse flight conditions and incorporating real-world flight datasets for training. DR-RNN's efficiency, robustness, and extrapolation capabilities make it a promising tool for developing more accurate and computationally efficient aircraft dynamics simulations.

These case studies showcase the immense potential of PIML for flight dynamics simulations. PIML offers advantages such as the ability to handle complex non-linearities, extrapolate beyond training data, and potentially reduce computational costs compared to traditional methods. As research in this field progresses, PIML is poised to play a transformative role in various aspects of aerospace engineering, including aircraft design, pilot training, and mission planning.

Technological Advancements in PIML

The integration of PIML into flight dynamics simulation has been significantly simplified by several key technological advancements:

Advanced Neural Network Architectures: The development of neural networks specifically designed to encode physical laws has been a game-changer. Examples include Hamiltonian Neural Networks [15], which excel at capturing the Hamiltonian structure governing many physical systems like flight dynamics. These networks seamlessly integrate physics-based constraints into ML models, leading to more accurate and interpretable simulations.

Data Generation and Augmentation: Techniques for synthetic data generation and augmentation have addressed a critical challenge in PIML – limited real-world flight data. These techniques can create realistic and diverse flight scenarios virtually. For instance, Generative Adversarial Networks (GANs) can generate synthetic flight data, while data augmentation methods can manipulate existing data to create variations, expanding the training datasets and improving the model's ability to generalize to unseen conditions.

Computational Efficiency: Advancements in hardware and software have significantly reduced the computational burden associated with training and deploying PIML models. The increasing availability of specialized hardware like GPUs and TPUs (Tensor Processing Units) allows for faster training of complex neural networks. Additionally, software frameworks optimized for PIML, like TensorFlow Physics and PyTorch Physics, streamline the development and deployment process, making real-time flight simulation with PIML more feasible.

Explainable AI (XAI) Techniques: As PIML models become more complex, understanding their decision-making processes becomes crucial. XAI techniques provide methods for interpreting the inner workings of these models, fostering trust in their predictions and ensuring they adhere to safety-critical requirements in flight simulation applications.

These advancements are continuously evolving, pushing the boundaries of what is possible with PIML in flight dynamics simulations.

The Future Trajectory of PIML in Flight Dynamics Simulation

Looking ahead, the potential of PIML in transforming flight dynamics simulation is immense. Key areas of future development include:

Enhanced Model Generalizability: A crucial focus of ongoing research is to further improve the generalization capabilities of PIML models. This will enable them to provide accurate simulations across a wider spectrum of aircraft designs, encompassing diverse configurations, wing shapes, and engine types. Additionally, research will aim to improve generalizability across a broader range of flight conditions, including extreme weather scenarios, turbulence, and high-altitude flight. Techniques like transfer learning and uncertainty quantification will be crucial in achieving this goal.

Integration with Digital Twins: PIML can play a pivotal role in the development of sophisticated digital twins for aircraft. Digital twins are virtual replicas of physical objects that are constantly updated with real-time data. By incorporating PIML models into digital twins, it will be possible to create real-time, physics-informed simulations that mirror the behavior of real-world aircraft. This has far-reaching implications for predictive maintenance, where PIML models can analyze sensor data from the real aircraft and predict potential maintenance issues before they occur. Additionally, digital twins with PIML can be used for operational optimization, allowing airlines to simulate different flight paths and strategies to optimize fuel efficiency and flight time.

Autonomous Flight Control: As the aerospace industry strives towards a future of autonomous flight, PIML models offer the promise of developing adaptive, intelligent flight control systems. These systems would be capable of managing complex flight dynamics autonomously, responding to changing weather conditions, turbulence, and other unforeseen events in real-time. PIML-based control systems could learn and adapt to different aircraft models and flight scenarios, enhancing safety and efficiency in autonomous flight operations.

Human-in-the-Loop Systems: While autonomous flight is a future goal, the near future will likely see a focus on Human-in-the-Loop (HIL) systems. PIML can be integrated into these systems to provide pilots with real-time decision support, suggesting optimal flight paths, predicting potential issues, and assisting with complex maneuvers.

The integration of physics-informed machine learning into flight dynamics simulation opens a new chapter in aerospace simulation and design. By harnessing the strengths of both physics-based modeling and machine learning, PIML stands to revolutionize how we simulate, design, and control aircraft. This exciting intersection of artificial intelligence and aerospace engineering promises to usher in a new era of flight.

Objective

Our primary objective is to create a proof of concept (POC) for modeling aircraft movement in a flight simulator using a Physics-Informed Neural Network (PINN) model. This POC aims to demonstrate the feasibility and effectiveness of integrating physical laws directly into a neural network to predict aircraft trajectories. By leveraging the strengths of both physics-based modeling and machine learning, we intend to develop a model that can accurately simulate the complex dynamics of flight while being computationally efficient.

This approach will serve as a foundational step towards revolutionizing flight simulation by offering a scalable, real-time solution that reduces reliance on traditional, resource-intensive methods. The successful implementation of this POC will provide valuable insights into the potential of PINN models in aviation, paving the way for more advanced

applications in the industry, such as real-time flight monitoring, adaptive training simulations, and more efficient aircraft design processes.

Methodology

Data Collection and Preprocessing

Data Source: The dataset is extracted from the X-Plane 12 flight simulator, comprising 5 simulated flights of 15 minutes each. These flights feature varying control inputs while maintaining consistency in aircraft (Cessna Skyhawk), airfield, time of day, and weather conditions.

Features: The dataset includes 660 features per flight, capturing critical aspects such as altitude, speed, and aircraft orientation (pitch, yaw, roll), with data sampled at a frequency of 10 times per second, resulting in approximately 7,800 entries per feature.

Feature Selection: From the full set of features, 18 basic movement features were manually selected for modeling. These features include 'time', 'vt', 'pitch', 'roll', 'hding', 'lat', 'lon', 'alt', 'x', 'y', 'z', 'vx', 'vy', 'vz', 'elev_stick', 'ailrn_stick', 'ruddr_stick', and 'throttle'. The selection was guided by the physics equations used later in the loss function to ensure that the model captures the essential dynamics of aircraft movement. These features were then normalized using a standard scaler to ensure comparability across different scales.

Data Splitting: The dataset was split into training, validation, and test sets, with each set containing data from different flights to prevent data leakage and ensure robust model evaluation.

Physics-Informed Neural Network (PINN) Design

Basic LSTM Model: This model uses single records for each prediction, capturing basic temporal dependencies to forecast the next state of the aircraft.

Sequence-Based LSTM Model: An improved model that uses sequences of records as input to better capture the temporal dynamics of aircraft movement, allowing it to forecast the entire flight sequence.

Physics-Informed Neural Network (PINN): This advanced model integrates physical laws directly into the loss function, enhancing prediction accuracy by ensuring that the model's outputs adhere to real-world physics.

Model Input and Output

Input: The models take time series data as input, including aircraft location (x, y, z), velocity (vx, vy, vz), and control inputs (elev_stick, ailrn_stick, rudder_stick, throttle).

Output: The output is the predicted next state of the aircraft, including location, velocity, and orientation (pitch, roll, heading).

Training Process

The training of the models was conducted with a focus on optimizing both predictive accuracy and adherence to physical laws, using the following components:

Loss Functions: The models were primarily trained using the Mean Squared Error (MSE) as the data-driven loss function to minimize the difference between predicted and actual values. For the Physics-Informed Neural Network (PINN) model, an additional physics-based loss was integrated to ensure that the predictions comply with the governing physical laws of flight dynamics. The total loss function L_{total} is defined as:

$$L_{total} = L_{MSE} + L_{physics}$$

Here, L_{MSE} is the traditional data-driven loss

$L_{MSE} = \frac{1}{N} \sum_{i=1}^N \sum_{j=1}^F (y_{ij} - \hat{y}_{ij})^2$ Where N is the number of samples, F is the number of features.

The $L_{physics}$ represents the physics-based loss. The physics-based loss is computed by comparing the predicted values from the model and the actual values calculated from the physic equation based on the forces acting on the aircraft, ensuring that the model's outputs are physically consistent. Specifically, the loss is calculated based on the differences in predicted and actual forces derived from the aircraft's velocity and orientation using the following equations:

$$L_{physics} = MSE(X_{pred}, X_{actual}) + MSE(Y_{pred}, Y_{actual}) + MSE(Z_{pred}, Z_{actual})$$

where X_{pred} , Y_{pred} , Z_{pred} are the predicted forces along the x, y, and z axes, respectively. Specifically, X_{pred} is calculated based on the predicted values of heading, roll, pitch, and the velocities:

$$X_{pred} = m \cdot \left(\frac{dv_x}{dt} + pitch \cdot v_z - heading \cdot v_y \right)$$
$$Y_{pred} = m \cdot \left(\frac{dv_y}{dt} + heading \cdot v_x - roll \cdot v_z \right)$$

$$Z_{pred} = m \cdot \left(\frac{dv_z}{dt} + roll \cdot v_y - pitch \cdot v_x \right)$$

These predicted forces are then compared to the actual forces $X_{actual}, Y_{actual}, Z_{actual}$, which are calculated in the same way, but using the actual values of heading, roll, pitch, and velocities rather than the predicted ones.

The mass m used in these equations is a constant value representing the total mass of the Cessna Skyhawk, which is 1127.177 kg. This mass was obtained from the metadata collected prior to the model implementation.

The derivatives $\frac{dv_x}{dt}, \frac{dv_y}{dt}, \frac{dv_z}{dt}$ represent the acceleration in the respective directions, which are computed based on the velocities predicted by the model and the actual velocities.

This physics-based loss ensures that the model's predictions are not only accurate in terms of minimizing error (MSE) but also physically plausible according to the laws of motion.

Optimization: The models were optimized using the Adam optimizer, which included learning rate scheduling to adaptively adjust the learning rate during training. This approach was crucial in improving the convergence rate and enhancing the overall model performance. The combination of MSE and physics-based loss ensured that the model not only learned to minimize prediction errors but also adhered to the physical principles governing aircraft motion.

Observation Window: Various observation windows were tested to identify the optimal input sequence length for each model configuration. This step was essential in capturing the temporal dynamics of aircraft movement and ensuring that the models could effectively learn from the time series data. The sequence length directly impacted the model's ability to predict future states of the aircraft accurately, making this an important factor in the training process.

Experiments

Experiment 1: Baseline Model Evaluation

- **Objective:** Assess the performance of the base LSTM model without physical loss integration.
- **Model:** LSTM with a sequence length of 20.
- **Procedure:** Train and evaluate the model on the dataset. Measure the model's accuracy and generalization using MSE, RMSE, and MAE.

- **Expected Outcome:** Establish a baseline performance to compare against models combining physical loss.

Experiment 2: Impact of Physical Loss (Short Sequence)

- **Objective:** Evaluate the effect of integrating physical loss into the LSTM model with a short sequence length.
- **Model:** LSTM with physical loss and a sequence length of 20.
- **Procedure:** Train and evaluate this model on the dataset. Compare performance metrics and physical possibility against the baseline model.
- **Expected Outcome:** Determine if the inclusion of physical loss improves accuracy and physical consistency compared to the base model.

Experiment 3: Effect of Sequence Length and Dropout

- **Objective:** Analyze the impact of a longer sequence length and dropout on model performance with physical loss integration.
- **Model:** LSTM with physical loss, a sequence length of 100, and dropout of 20%.
- **Procedure:** Train and evaluate the model, focusing on how the longer sequence length and dropout affect the model's accuracy and generalization. Compare results to previous models.
- **Expected Outcome:** Assess whether increasing the sequence length and applying dropout improves model performance and reduces overfitting.

Experiment 4: Longest Sequence Length and Dropout

- **Objective:** Investigate the effects of the longest sequence length and dropout on the model with physical loss integration.
- **Model:** LSTM with physical loss, a sequence length of 200, and dropout of 20%.
- **Procedure:** Train and evaluate this model on the dataset. Compare its performance metrics and physical consistency to those of models with shorter sequences.
- **Expected Outcome:** Determine if the longer sequence length and dropout lead to better performance and generalization compared to shorter sequence models.

Experiment 5: Extended Sequence Length Without Dropout


- **Objective:** Compare the performance of the LSTM model with physical loss and an extended sequence length, without dropout.

- **Model:** LSTM with physical loss and a sequence length of 100.
- **Procedure:** Train and evaluate this model, focusing on how the extended sequence length affects performance compared to models with dropout.
- **Expected Outcome:** Evaluate the impact of the sequence length on model accuracy and generalization and understand the trade-offs of using dropout versus not using it.

These experiments will provide a comprehensive evaluation of different model configurations, helping to identify the optimal setup for integrating physical laws into LSTM models for accurate aircraft movement prediction.

Results


The following graph illustrates the average normalized MSE per feature across the different models tested in our experiments. Each graph represents a specific feature, with MSE values plotted for the different experiments shown above.



Model	vt	pitch	roll	hdng	lat	lon	alt	vx	vy	vz	x	y	z	AVG
Baseline Model Evaluation	0.999157	0.801745	1	0.57029	1	0.319445	1	0.562145	0.825683	1	0.323621	1	1	0.80016
Impact of Physical Loss (Short Sequence)	0.617027	0.521868	0.641826	1	0.054081	1	0.095286	1	0.439745	0.325845	1	0.066415	0.07828	0.526183
Effect of Sequence Length and Dropout	0.642662	0.973153	0.779844	0.362888	0.631213	0.167965	0.465059	0.547553	0.559655	0.255279	0.182074	0.459303	0.644212	0.513143
Longest Sequence Length and Dropout	1	1	0.800226	0.778009	0.362644	0.381536	0.254077	0.73266	1	0.280748	0.418768	0.204432	0.353615	0.582055
Extended Sequence Length Without Dropout	0.672971	0.82396	0.567091	0.37143	0.257358	0.241434	0.25708	0.500823	0.735434	0.200598	0.257037	0.221653	0.250198	0.412082

Key Observations and Trends


- Improved Accuracy with Physics Integration:** Across most features, the models incorporating physics-based loss (particularly the PINN model) demonstrate a significant reduction in MSE compared to the baseline LSTM model. This trend highlights the effectiveness of integrating physical laws into the machine learning framework, leading to more accurate predictions.



- Feature-Specific Performance:** Certain features, such as altitude and velocity in the z direction, show particularly pronounced improvements in MSE with the PINN model. This suggests that the incorporation of physics-based constraints is especially beneficial for features closely tied to the dynamic equations governing flight behavior.



- Challenges in Multi-Feature Prediction:** While the PINN model shows overall better performance, the task of simultaneously predicting multiple features (13 in total) remains complex. Some features, like roll and heading, exhibit higher MSE compared to others, indicating areas where further refinement of the model may be necessary.



- Impact of Sequence Length and Dropout:** The experiments reveal that longer sequence lengths and the application of dropout generally improve model generalization, as reflected in the lower MSE for several features. However, these adjustments also introduce challenges in balancing model complexity and training stability.

Conclusions and Summary

The integration of Physics-Informed Neural Networks (PINN) into our aircraft movement prediction models demonstrated significant advancements over traditional LSTM models. The PINN models achieved an overall improvement in Mean Squared Error (MSE) ranging from 25% to 50% compared to models without physical loss integration. Additionally, the predictions from the PINN models showed greater coherence in their trajectory plots, reflecting more accurate and physically consistent outputs.

However, predicting 13 features simultaneously presents inherent complexities. The multifaceted nature of this task involves capturing detailed dynamics of aircraft movement, which can be challenging even with advanced models. Additionally, simulation data often contains noise due to various factors such as system lags and performance limitations, which can impact model accuracy and reliability.

Challenges

Looking forward, several challenges need to be addressed:

- **Data Quality:** Enhancing the quality of simulation data to reduce noise and improve accuracy is crucial. This includes addressing issues related to lags and ensuring that the data reflects real-world conditions as closely as possible.
- **Effective Rolling Predictions:** Developing methods for effective rolling predictions is essential for real-time applications. This involves optimizing the model's ability to make accurate predictions in a continuous, streaming context, where new data arrives in real-time.
- **Scalability and Generalization:** Ensuring that the PINN models can generalize well across a wider range of flight scenarios and different aircraft types is important for broader applicability. This requires ongoing modification of the model architecture and training processes.

Future Work

To build on the promising results and address the challenges identified, the following areas for future work are proposed:

- **Further Model Refinement:** Continued enhancement of the PINN models to improve accuracy and robustness. This includes refining model architectures and experimenting with advanced training techniques.
- **Real-Time Implementation:** Developing and optimizing methods for real-time prediction to facilitate live simulation and monitoring applications.
- **Exploration of Additional Features and Architectures:** Investigating additional features and model architectures fitted for different aircraft types to improve generalization and performance.
- **Divide and Conquer:** Creating specialized models for predicting individual features to enhance overall model performance and accuracy.
- **Explore Alternative Data Sources:** Incorporating alternative or supplementary data sources to enrich the training dataset, thereby improving the model's generalization across various flight scenarios.
- **Measurement of Computational Effort:** Future work should include measuring the computational effort required by the PINN models compared to traditional approaches. This analysis would provide valuable insights into the efficiency gains achieved through the integration of physical laws into machine learning models, particularly in real-time applications.

Addressing these challenges and pursuing these future directions will be crucial for advancing aircraft movement simulation, enhancing model accuracy, reliability, and real-world applicability.

Bibliography


- [1] Yang, Y., Yao, H., & Liu, Y. (2019). Aircraft dynamics simulation using a novel physics-based learning method. *Aerospace Science and Technology*, 87(April), 254-264. <https://doi.org/10.1016/j.ast.2019.02.021>
- [2] Muther, T., Kalantari Dahaghi, A.M., Syed, F.I., & Pham, V.V. (2022). Physical laws meet machine intelligence: Current developments and future directions. <https://doi.org/10.1007/s10462-022-10329-8>
- [3] Raissi, M., Perdikaris, P., & Karniadakis, G.E. (2019). Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics*, 378(February), 686-707. <https://doi.org/10.1016/j.jcp.2018.10.045>
- [4] Deng, W., Nguyen, K.T.P., Medjaher, K., Gogu, C., & Morio, J. (2023). Physics-informed machine learning in prognostics and health management: State of the art and challenges. *Applied Mathematical Modelling*, 124(December), 325-352. <https://doi.org/10.1016/j.apm.2023.07.011>
- [5] Sharma, P., Chung, W.T., Akoush, B., & Ihme, M. (2023). A review of physics-informed machine learning in fluid mechanics. *Energies*, 16(5), 2343. <https://doi.org/10.3390/en16052343>
- [6] Batuwatta-Gamage, C.P., Rathnayaka, C., Karunasena, H.C.P., Jeong, H., Karim, A., Gu, Y.T. (2023). A novel physics-informed neural networks approach (PINN-MT) to solve mass transfer in plant cells during drying. *Biosystems Engineering*, 230(June), 219-241. <https://doi.org/10.1016/j.biosystemseng.2023.04.012>
- [7] Kashinath, K., Mustafa, M., Albert, A., Wu, J.L., Jiang, C., Esmailzadeh, S., et al. (2021). Physics-informed machine learning: Case studies for weather and climate modelling. <https://doi.org/10.1098/rsta.2020.0093>
- [8] Wu, Z., Wang, H., He, C., Zhang, B., Xu, T., & Chen, Q. (2023). The application of physics-informed machine learning in multiphysics modeling in chemical engineering. *Industrial & Engineering Chemistry Research*, 62(44), 18178-18204. <https://doi.org/10.1021/acs.iecr.3c02383>
- [9] Stachiw, T., Crain, A., & Ricciardi, J. (2022). A physics-based neural network for flight dynamics modelling and simulation. *Advanced Modeling and Simulation in Engineering Sciences*, 9(13). <https://doi.org/10.1186/s40323-022-00227-7>
- [10] Yang, Y., Yao, H., & Liu, Y. (2019). Aircraft dynamics simulation using a novel physics-based learning method. *Aerospace Science and Technology*, 87(April), 254-264. <https://doi.org/10.1016/j.ast.2019.02.021>



- [11] Karniadakis, G.E., Kevrekidis, I.G., Lu, L., Perdikaris, P., Wang, S., & Yang, L. (2021). Physics-informed machine learning. *Nature Reviews Physics*, 3, 422–440. <https://www.nature.com/articles/s42254-021-00314-5>
- [12] Cuomo, S., Schiano Di Cola, V., Giampaolo, F., Rozza, G., Raissi, M., & Piccialli, F. (2022). Scientific Machine Learning Through Physics-Informed Neural Networks: Where we are and What's Next. *Journal of Scientific Computing*, 92(article number 88). <https://doi.org/10.1007/s10915-022-01939-z>
- [13] Stachiw, T., Crain, A., & Ricciardi, J. (2022). A physics-based neural network for flight dynamics modelling and simulation. *Advanced Modeling and Simulation in Engineering Sciences*, 9(13). <https://doi.org/10.1186/s40323-022-00227-7>
- [14] Michek, N., Mehta, P., & Huebsch, W. (2023, March). Methodology development of a free-flight parameter estimation technique using physics-informed neural networks. In *2023 IEEE Aerospace Conference* (pp. 1-18). IEEE. <https://doi.org/10.1109/AERO55745.2023.10115728>
- [15] Greydanus, S., Dzamba, M., & Yosinski, J. (2019). Hamiltonian neural networks. *Advances in Neural Information Processing Systems*, 32. <https://doi.org/10.48550/arXiv.1906.01563>


Appendices

GitHub: [link](#)

Graphs:









Original flight data

- **LSTM**
sequence length:20
- **Model 1**
sequence length:20
physical loss
- **Model 2**
sequence length 100
physical loss
dropout 20%
- **Model 3**
sequence length 200
physical loss
dropout 20%
- **Model 4**
sequence length 100
physical loss



✓ **Original flight data**

- **LSTM**
sequence length:20
- **Model 1**
sequence length:20
physical loss
- **Model 2**
sequence length 100
physical loss
dropout 20%
- **Model 3**
sequence length 200
physical loss
dropout 20%
- **Model 4**
sequence length 100
physical loss

