

HUMAN HEALTH

ENVIRONMENTAL HEALTH

PerkinElmer

ChemDraw

JavaScript API Reference Guide 1.5



**Last Updated:** 1/02/2022

## Table of Contents

<b>ChemDraw JavaScript API Reference Guide .....</b>	<b>9</b>
<b>Global Objects .....</b>	<b>10</b>
ChemDrawAPI .....	10
activeDocument : Document .....	10
Example .....	10
window : Window .....	10
Example .....	10
version : string .....	10
Example .....	10
openURLInDefaultBrowser(url) : void .....	11
Parameters .....	11
Returns .....	11
Throws Exceptions .....	11
Example .....	11
registerURLTriggeredCallback(callbackFunction) : string .....	11
Parameters .....	11
Returns .....	11
Throws Exceptions .....	11
Example .....	12
copyToClipboard(text) : void .....	12
Parameters .....	12
Returns .....	12
Throws Exceptions .....	12
Example .....	12
<b>Classes .....</b>	<b>13</b>

Document .....	13
selection : Selection .....	13
Example .....	13
addCDXML(cdxmlText) : void .....	13
Parameters .....	13
Returns .....	13
Throws Exceptions .....	13
Example .....	13
getCDXML() : string .....	13
Parameters .....	14
Returns .....	14
Throws Exceptions .....	14
Example .....	14
addCDXBase64Encoded(base64EncodedCDXText) : void .....	14
Parameters .....	14
Returns .....	14
Throws Exceptions .....	14
Example .....	14
getCDXBase64Encoded() : string .....	14
Parameters .....	15
Returns .....	15
Throws Exceptions .....	15
Example .....	15
addSMILES(smilesText) : void .....	15
Parameters .....	15
Returns .....	15
Throws Exceptions .....	15
Example .....	15

getSMILES() : string .....	16
Parameters .....	16
Returns .....	16
Throws Exceptions .....	16
Example .....	16
addInChI(inChIText) : void .....	16
Parameters .....	16
Returns .....	16
Throws Exceptions .....	16
Example .....	16
getInChI() : string .....	17
Parameters .....	17
Returns .....	17
Throws Exceptions .....	17
Example .....	17
getInChIKey() : string .....	17
Parameters .....	17
Returns .....	17
Throws Exceptions .....	18
Example .....	18
addMolV2000(molV2000Text) : void .....	18
Parameters .....	18
Returns .....	18
Throws Exceptions .....	18
Example .....	18
getMolV2000() : string .....	18
Parameters .....	19
Returns .....	19

Throws Exceptions .....	19
Example .....	19
addMolV3000(molV3000Text) : void .....	19
Parameters .....	19
Returns .....	19
Throws Exceptions .....	19
Example .....	19
getMolV3000() : string .....	20
Parameters .....	20
Returns .....	20
Throws Exceptions .....	20
Example .....	20
addMol(molText) : void .....	20
Parameters .....	20
Returns .....	20
Throws Exceptions .....	20
Example .....	21
addRXNV2000(rxnV2000Text) : void .....	21
Parameters .....	21
Returns .....	21
Throws Exceptions .....	21
Example .....	21
getRXNV2000() : string .....	21
Parameters .....	21
Returns .....	22
Throws Exceptions .....	22
Example .....	22
addRXNV3000(rxnV3000Text) : void .....	22

Parameters .....	22
Returns .....	22
Throws Exceptions .....	22
Example .....	22
getRXNV3000() : string .....	23
Parameters .....	23
Returns .....	23
Throws Exceptions .....	23
Example .....	23
getPNGBase64Encoded([options]) : string .....	23
Parameters .....	23
Returns .....	23
Throws Exceptions .....	23
Example .....	23
Window .....	24
resizeTo(width, height) : void .....	24
Parameters .....	24
Returns .....	24
Throws Exceptions .....	24
Example .....	24
setDefaultSize(width, height) : void .....	24
Parameters .....	25
Returns .....	25
Throws Exceptions .....	25
Example .....	25
close() : void .....	25
Parameters .....	25
Returns .....	25

Throws Exceptions .....	25
Example .....	25
onClose(callback) : void .....	25
Parameters .....	26
Returns .....	26
Example .....	26
Selection .....	26
containsPartialStructure() : boolean .....	26
Parameters .....	26
Returns .....	26
Example .....	26
getCDXML() : string .....	26
Parameters .....	26
Returns .....	27
Example .....	27
getSVG([options]) : string .....	27
Parameters .....	27
Returns .....	27
Example .....	27
getInChIKey() : string .....	27
Parameters .....	27
Returns .....	27
Example .....	28
getSMILES() : string .....	28
Parameters .....	28
Returns .....	28
Example .....	28
isEmpty() : boolean .....	28

Parameters .....	28
Returns .....	28
Example .....	28
onChange(callback) : void .....	28
Parameters .....	28
Returns .....	29
Example .....	29
JSON Structures .....	29
ImageOption .....	29
Properties .....	29



# ChemDraw JavaScript API Reference Guide

This guide provides information about the ChemDraw JavaScript API.

The ChemDraw JavaScript API enables ChemDraw add-ins to access the various features of ChemDraw with JavaScript. With the latest version, the API can support limited access to the active document and the add-in container window.

To access the guide and tutorials for creating ChemDraw add-ins and using ChemDraw JavaScript API in ChemDraw add-ins, go to **Help>Contents>ChemDraw Add-ins**.

**Note:** *The ChemDraw JavaScript API works only in ChemDraw add-ins. To access the add-in examples that demonstrate the usage of the API, go to [ChemDraw Add-in Examples](#).*

# Global Objects

## ChemDrawAPI

The singleton global object to access the active document, the add-in container window, etc.

### activeDocument : Document

Gets the active document that is currently open in ChemDraw.

#### Example

```
try {
    var activeDocument = ChemDrawAPI.activeDocument;
}
catch (err) {
    alert(err.message);
}
```

### window : Window

Gets the add-in container window that contains the add-in that is currently running.

#### Example

```
try {
    var addinContainerWindow = ChemDrawAPI.window;
}
catch (err) {
    alert(err.message);
}
```

### version : string

Gets the version of the ChemDraw JavaScript API.

#### Example

```
try {
    document.write(ChemDrawAPI.version);
}
catch (err) {
    alert(err.message);
}
```

**Note:** The add-in example **Hello World** demonstrates the usage of **ChemDrawAPI.version**. To access it, go to [ChemDraw Add-in Examples](#).

### **openURLInDefaultBrowser(url) : void**

Opens the specified URL in system's default browser. Only web URLs are supported i.e. The URL must start with an "http" or "https" otherwise an exception will be thrown.

#### Parameters

Name	Type	Description
url	<a href="#">string</a>	The URL to open in system's default browser

#### Returns

None

#### Throws Exceptions

Yes

#### Example

```
try {  
    ChemDrawAPI.openURLInDefaultBrowser (  
        "http://www.perkinelmer.com/category/chemdraw");  
}  
catch (err) {  
    alert(err.message);  
}
```

**Note:** The add-in example **Open URL** demonstrates the usage of **ChemDrawAPI.openURLInDefaultBrowser**. To access it, go to [ChemDraw Add-in Examples](#).

### **registerURLTriggeredCallback(callbackFunction) : string**

Registers a callback function with ChemDraw that will be called when ChemDraw is invoked by the URL handler. This API takes a callback function and returns a callback key that uniquely identifies this callback.

#### Parameters

Name	Type	Description
callbackFunction	<a href="#">Function</a>	The callback function that will be invoked

#### Returns

Return Type	Description
<a href="#">string</a>	A callback key that uniquely identifies this callback

#### Throws Exceptions

Yes

### Example

```
try {
    const callbackKey = ChemDrawAPI.registerURLTriggeredCallback((arg) => {
        alert(arg);
    });
}
catch (err) {
    alert(err.message);
}
```

**Note:** The add-in example **ChemDrawOAuthExample** demonstrates the usage of **ChemDrawAPI.registerURLTriggeredCallback**. To access it, go to [ChemDraw Add-in Examples](#). More information on the usage of this API can be found in the ChemDraw User Guide.

### copyToClipboard(text) : void

Copies the specified text to the clipboard.

#### Parameters

Name	Type	Description
text	<a href="#">string</a>	The text to be copied

#### Returns

None

#### Throws Exceptions

Yes

### Example

```
try {
    ChemDrawAPI.copyToClipboard("Hello World");
}
catch (err) {
    alert(err.message);
}
```

# Classes

## Document

Provides an API to add and get data in a ChemDraw document.

**Note:** The add-in example **Document Data Importer and Exporter** demonstrates the usage of the API for adding and getting data in the active document. To access it, go to [ChemDraw Add-in Examples](#).

### selection : Selection

Gets the selection in the document.

### Example

```
var selection = ChemDrawAPI.activeDocument.selection;
if (!selection.isEmpty()) {
    // Do something
}
```

### addCDXML(cdxmlText) : void

Adds a CDXML document to the active document. The active document honors the style and coordinates of the supplied CDXML document.

### Parameters

Name	Type	Description
cdxmlText	<a href="#">string</a>	The CDXML document to add to the active document

### Returns

None

### Throws Exceptions

Yes

### Example

```
try {
    ChemDrawAPI.activeDocument.addCDXML(cdxmlText);
}
catch (err) {
    alert(err.message);
}
```

### getCDXML() : string

Gets the contents of the active document as CDXML.

## Parameters

None

## Returns

Return Type	Description
<a href="#">string</a>	The contents of the active document as a CDXML string

## Throws Exceptions

Yes

## Example

```
try {
    var cdxmlText = ChemDrawAPI.activeDocument.getCDXML();
}
catch (err) {
    alert(err.message);
}
```

## addCDXBase64Encoded(base64EncodedCDXText) : void

Adds a CDX document, encoded as [Base64](#), to the active document. The active document honors the style and coordinates of the supplied CDX document.

## Parameters

Name	Type	Description
base64EncodedCDXText	<a href="#">string</a>	The CDX document to add to the active document. The string must be encoded as <a href="#">Base64</a>

## Returns

None

## Throws Exceptions

Yes

## Example

```
try {
    ChemDrawAPI.activeDocument.addCDXBase64Encoded(base64EncodedCDXText);
}
catch (err) {
    alert(err.message);
}
```

## getCDXBase64Encoded() : string

Gets the contents of the active document as [Base64](#) encoded CDX.

## Parameters

None

## Returns

Return Type	Description
<a href="#">string</a>	The contents of the active document as a <a href="#">Base64</a> encoded string

## Throws Exceptions

Yes

## Example

```
try {
    var base64EncodedCDXText = ChemDrawAPI.activeDocument.getCDXBase64Encoded();
}
catch (err) {
    alert(err.message);
}
```

## addSMILES(smilesText) : void

Adds a structure, encoded in a [SMILES](#) string, to the active document. The document retains its original styling. The structure will be placed at the center of the currently visible view of the document.

## Parameters

Name	Type	Description
smilesText	<a href="#">string</a>	The <a href="#">SMILES</a> encoded structure to add to the active document

## Returns

None

## Throws Exceptions

Yes

## Example

```
try {
    ChemDrawAPI.activeDocument.addSMILES(smilesText);
}
catch (err) {
    alert(err.message);
}
```

**getSMILES() : string**

Gets the contents of the active document as a [SMILES](#) string. If there is a mixture of structures and non-structures (e.g. clip-art, text etc), only the structures will be returned. If there are multiple structures, the [SMILES](#) string will be returned in dot-separated notation.

**Parameters**

None

**Returns**

Return Type	Description
<a href="#">string</a>	The contents of the active document as a <a href="#">SMILES</a> string

**Throws Exceptions**

Yes

**Example**

```
try {
    var smilesText = ChemDrawAPI.activeDocument.getSMILES();
}
catch (err) {
    alert(err.message);
}
```

**addInChI(inChIText) : void**

Adds a structure, encoded in an [InChI](#) string, to the active document. The document retains its original styling. The structure will be placed at the center of the currently visible view of the document.

**Parameters**

Name	Type	Description
inChIText	<a href="#">string</a>	The <a href="#">InChI</a> encoded structure to add to the active document

**Returns**

None

**Throws Exceptions**

Yes

**Example**

```
try {
    ChemDrawAPI.activeDocument.addInChI(inChIText);
}
```



```
catch (err) {  
    alert(err.message);  
}
```

### getInChI() : string

Gets the contents of the active document as an [InChI](#) string. If there is a mixture of structures and non-structures (e.g. clip-art, text etc), only the structures will be returned. If there are multiple structures, the [InChI](#) string will return them in its native format.

#### Parameters

None

#### Returns

Return Type	Description
<a href="#">string</a>	The contents of the active document as an <a href="#">InChI</a> string

#### Throws Exceptions

Yes

#### Example

```
try {  
    var inChIText = ChemDrawAPI.activeDocument.getInChI();  
}  
catch (err) {  
    alert(err.message);  
}
```

### getInChIKey() : string

Gets the contents of the active document as an [InChIKey](#) string. If there is a mixture of structures and non-structures (e.g. clip-art, text etc), only the structures will be returned. If there are multiple structures, the [InChIKey](#) string will return them in its native format.

**Note:** The InChIKey is a one-way format. A key can be generated from a structure, but a structure cannot be generated from a key. Thus there is no Add method for InChIKey.

#### Parameters

None

#### Returns

Return Type	Description
<a href="#">string</a>	The contents of the active document as an <a href="#">InChIKey</a> string

## Throws Exceptions

Yes

## Example

```
try {
    var inChIKeyText = ChemDrawAPI.activeDocument.getInChIKey();
}
catch (err) {
    alert(err.message);
}
```

## addMolV2000(molV2000Text) : void

Adds a structure, encoded in a [MolV2000](#) string to the active document. The document retains its original styling. If present, 2D coordinates will be honored for the structure, otherwise the structure will be placed at the center of the currently visible view of the document.

## Parameters

Name	Type	Description
molV2000Text	<a href="#">string</a>	The <a href="#">MolV2000</a> encoded structure to add to the active document

## Returns

None

## Throws Exceptions

Yes

## Example

```
try {
    ChemDrawAPI.activeDocument.addMolV2000(molV2000Text);
}
catch (err) {
    alert(err.message);
}
```

## getMolV2000() : string

Gets the contents of the active document as a [MolV2000](#) string. If there is a mixture of structures and non-structures (e.g. clip-art, text etc), only the structures will be returned. If there are multiple structures, the [MolV2000](#) string will return them in its native format.

## Parameters

None

## Returns

Return Type	Description
<a href="#">string</a>	The contents of the active document as a <a href="#">MolV2000</a> string

## Throws Exceptions

Yes

## Example

```
try {  
    var molV2000Text = ChemDrawAPI.activeDocument.getMolV2000();  
}  
catch (err) {  
    alert(err.message);  
}
```

## addMolV3000(molV3000Text) : void

Adds a structure, encoded in a [MolV3000](#) string to the active document. The document retains its original styling. If present, 2D coordinates will be honored for the structure, otherwise they will be placed at the center of the currently visible view of the document.

## Parameters

Name	Type	Description
molV3000Text	<a href="#">string</a>	The <a href="#">MolV3000</a> encoded structure to add to the active document

## Returns

None

## Throws Exceptions

Yes

## Example

```
try {  
    ChemDrawAPI.activeDocument.addMolV3000(molV3000Text);  
}  
catch (err) {  
    alert(err.message);  
}
```

**getMolV3000() : string**

Gets the contents of the active document as a [MolV3000](#) string. If there is a mixture of structures and non-structures (e.g. clip-art, text etc), only the structures will be returned. If there are multiple structures, the [MolV3000](#) string will return them in its native format.

**Parameters**

None

**Returns**

Return Type	Description
<a href="#">string</a>	The contents of the active document as a <a href="#">MolV3000</a> string

**Throws Exceptions**

Yes

**Example**

```
try {  
    var molV3000Text = ChemDrawAPI.activeDocument.getMolV3000();  
}  
catch (err) {  
    alert(err.message);  
}
```

**addMol(molText) : void**

This is a convenience method that will automatically detect whether the string is in [MolV2000](#) or [MolV3000](#) format, and add the structure to the active document. The document retains its original styling. If present, 2D coordinates will be honored for the structure, otherwise the structure will be placed at the center of the currently visible view of the document. If the supplied string is in neither [MolV2000](#) or [MolV3000](#) format, an exception will be thrown.

**Note:** There is no equivalent *getMol()* method. Call the *getMolV2000()* or *getMolV3000()* methods instead.

**Parameters**

Name	Type	Description
molText	<a href="#">string</a>	The <a href="#">MolV2000</a> or <a href="#">MolV3000</a> encoded structure to add to the active document

**Returns**

None

**Throws Exceptions**

Yes

## Example

```
try {  
    ChemDrawAPI.activeDocument.addMol(molText);  
}  
catch (err) {  
    alert(err.message);  
}
```

## addRXNV2000(rxnV2000Text) : void

Adds a reaction, encoded in an [RXNV2000](#) string, to the active document. The document retains its original styling. If present, 2D coordinates will be honored for the reaction, otherwise the reaction will be placed at the center of the currently visible view of the document.

### Parameters

Name	Type	Description
rxnV2000Text	<a href="#">string</a>	The <a href="#">RXNV2000</a> encoded structure to add to the active document

### Returns

None

### Throws Exceptions

Yes

## Example

```
try {  
    ChemDrawAPI.activeDocument.addRXNV2000(rxnV2000Text);  
}  
catch (err) {  
    alert(err.message);  
}
```

## getRXNV2000() : string

Gets the contents of the active document as an [RXNV2000](#) string. If there is a mixture of reactions and non-reactions (e.g. clip-art, text etc), only the reactions will be returned. If there are multiple reactions, the [RXNV2000](#) string will return them in its native format.

### Parameters

None

## Returns

Return Type	Description
<a href="#">string</a>	The contents of the active document as a <a href="#">RXNV2000</a> string

## Throws Exceptions

Yes

## Example

```
try {
    var rxnV2000Text = ChemDrawAPI.activeDocument.getRXNV2000();
}
catch (err) {
    alert(err.message);
}
```

## addRXNV3000(rxnV3000Text) : void

Adds a reaction, encoded in an [RXNV3000](#) string, to the active document. The document retains its original styling. If present, 2D coordinates will be honored for the reaction, otherwise the reaction will be placed at the center of the currently visible view of the document.

## Parameters

Name	Type	Description
rxnV3000Text	<a href="#">string</a>	The <a href="#">RXNV3000</a> encoded structure to add to the active document.

## Returns

None

## Throws Exceptions

Yes

## Example

```
try {
    ChemDrawAPI.activeDocument.addRXNV3000(rxnV3000Text);
}
catch (err) {
    alert(err.message);
}
```

**getRXNV3000() : string**

Gets the contents of the active document as a [RXNV3000](#) string. If there is a mixture of reactions and non-reactions (e.g. clip-art, text etc), only the reactions will be returned. If there are multiple reactions, the [RXNV3000](#) string will return them in its native format.

**Parameters**

None

**Returns**

Return Type	Description
<a href="#">string</a>	The contents of the active document as a <a href="#">RXNV3000</a> string

**Throws Exceptions**

Yes

**Example**

```
try {  
    var rxnV3000Text = ChemDrawAPI.activeDocument.getRXNV3000();  
}  
catch (err) {  
    alert(err.message);  
}
```

**getPNGBase64Encoded([options]) : string**

Gets the contents of the active document as a PNG image with the specified options. This can be used to generate a PNG image as a preview of the document.

**Parameters**

Name	Type	Description
options	Image options	<b>Optional</b> Options are for getting the PNG image.

**Returns**

Return Type	Description
<a href="#">string</a>	The contents of the active document as a <a href="#">Base64</a> encoded PNG string

**Throws Exceptions**

Yes

**Example**

```
try {  
    var pngBase64EncodedText = ChemDrawAPI.activeDocument.getPNGBase64Encoded({  
        transparent: false,  
    });  
}
```

```
        scalePercent: 100,  
        borderSizeInPixels: 100  
    });  
}  
catch (err) {  
    alert(err.message);  
}
```

## Window

### resizeTo(width, height) : void

Resizes the window using the specified width and height.

This API is deprecated.

### Parameters

Name	Type	Description
width	<a href="#">integer</a>	The new width of the window. A value greater than zero is expected, otherwise an exception will be thrown
height	<a href="#">integer</a>	The new height of the window. A value greater than zero is expected, otherwise an exception will be thrown

### Returns

None

### Throws Exceptions

Yes

### Example

```
try {  
    ChemDrawAPI.window.resizeTo(width, height);  
}  
catch (err) {  
    alert(err.message);  
}
```

### setDefaultSize(width, height) : void

Set default size for the window using the specified width and height.



## Parameters

Name	Type	Description
width	<a href="#">integer</a>	The new width of the window. A value greater than zero is expected, otherwise an exception will be thrown
height	<a href="#">integer</a>	The new height of the window. A value greater than zero is expected, otherwise an exception will be thrown

## Returns

None

## Throws Exceptions

Yes

## Example

```
try {  
    ChemDrawAPI.window.setDefaultSize(width, height);  
}  
catch (err) {  
    alert(err.message);  
}
```

## close() : void

Closes the add-in container window.

## Parameters

None

## Returns

None

## Throws Exceptions

Yes

## Example

```
try {  
    ChemDrawAPI.window.close();  
}  
catch (err) {  
    alert(err.message);  
}
```

## onClose(callback) : void

Registers a callback function which will be called when the add-in container window is about to close.

## Parameters

Name	Type	Description
callback	<a href="#">function</a>	(Optional) The callback function which will be called when the add-in container window is about to close.

## Returns

None

## Example

```
ChemDrawAPI.window.onClose(function () {  
    // Do clean up here when the add-in container window is about to close  
});
```

## Selection

Provides API to get the selected structures in a ChemDraw document.

**Note:** The add-in example Selection Monitor demonstrates the usage of the API for getting the preview image of the selected structures in the active document. To access it, go to [ChemDraw Add-in Examples](#).

### containsPartialStructure() : boolean

Determines whether the selection contains partially selected structure.

## Parameters

None

## Returns

Return Type	Description
<a href="#">boolean</a>	true if part of a single structure or grouped structures is selected, false otherwise

## Example

```
if ChemDrawAPI.activeDocument.selection.containsPartialStructure() {  
    // Do something  
}
```

### getCDXML() : string

Gets the contents of the selection as a CDXML document.

## Parameters

None

## Returns

Return Type	Description
<a href="#">string</a>	The contents of the selection as a CDXML document

## Example

```
var cdxmlText = ChemDrawAPI.activeDocument.selection.getCDXML();  
  
// Do something with the CDXML text here
```

## getSVG([options]) : string

Gets the contents of the selection as an SVG image with the specified options. This can be used to generate an SVG image as a preview of the selection.

## Parameters

Name	Type	Description
options	Image options	Optional Options for getting the SVG image

## Returns

Return Type	Description
<a href="#">string</a>	The contents of the selection as an SVG image

## Example

```
var svg = ChemDrawAPI.activeDocument.selection.getSVG({  
  transparent: false,  
  scalePercent: 100,  
  borderSizeInPixels: 20  
});  
  
// Do something with the svg image here
```

## getInChIKey() : string

Gets the contents of the selection as an [InChIKey](#) string.

## Parameters

None

## Returns

Return Type	Description
<a href="#">string</a>	The contents of the selection as an <a href="#">InChIKey</a> string

## Example

```
var inChIKey = ChemDrawAPI.activeDocument.selection.getInChIKey();  
  
// Do something with the inChIKey here
```

## getSMILES() : string

Gets the contents of the selection as a [SMILES](#) string.

### Parameters

None

### Returns

Return Type	Description
<a href="#">string</a>	The contents of the selection as a SMILES string

## Example

```
var smilesText = ChemDrawAPI.activeDocument.selection.getSMILES();  
  
// Do something with the SMILES here
```

## isEmpty() : boolean

Determines whether any object has been selected in the document.

### Parameters

None

### Returns

Return Type	Description
<a href="#">boolean</a>	true if nothing has been selected, false otherwise

## Example

```
if (!ChemDrawAPI.activeDocument.selection.isEmpty()) {  
    // Do something  
}
```

## onChange(callback) : void

Registers a callback function which will be called when the selection is changed in the document.

### Parameters

Name	Type	Description
callback	<a href="#">function</a>	The callback function which will be called when the selection is changed

## Returns

None

## Example

```
// Set the callback (or handler) for the selection change event
ChemDrawAPI.activeDocument.selection.onChange(function () {
    if (!ChemDrawAPI.activeDocument.selection.isEmpty()) {
        cdxmlText = ChemDrawAPI.activeDocument.selection.getCDXML();
        svg = ChemDrawAPI.activeDocument.selection.getSVG();

        // Do something with the cdxmlText and the svg image here
    }
});
```

## JSON Structures

### ImageOption

Options for getting an image. This can be used to specify the properties of the preview image for generating a preview of a document or a selection.

#### Properties

Name	Type	Default Value	Description
transparent	<a href="#">boolean</a>	true	(Optional) If true, the image will have a transparent background. If false, the background is generated along with the document contents
scalePercent	<a href="#">integer</a>	100	(Optional) The scaling applied to the image. 100% is the actual size. A value greater than zero is expected, otherwise an exception will be thrown
borderSizeInPixels	<a href="#">integer</a>	0	(Optional) The border (gap) to be placed around the image in pixels. A value of zero or greater is expected, otherwise an exception will be thrown