

Scan Report

August 20, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “New Quick Task”. The scan started at Thu Aug 20 14:43:10 2026 UTC and ended at Thu Aug 20 15:03:41 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
2	Results per Host	2
2.1	192.123.10.30	2
2.1.1	Medium 587/tcp	2
2.1.2	Medium 143/tcp	3
2.1.3	Medium 465/tcp	4
2.1.4	Low general/tcp	5
2.1.5	Low general/icmp	6

1 Result Overview

Host	High	Medium	Low	Log	False Positive
192.123.10.30	0	3	2	0	0
Total: 1	0	3	2	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 5 results selected by the filtering described above. Before filtering there were 25 results.

2 Results per Host

2.1 192.123.10.30

Host scan start Thu Aug 20 14:43:52 2026 UTC

Host scan end Thu Aug 20 15:03:36 2026 UTC

Service (Port)	Threat Level
587/tcp	Medium
143/tcp	Medium
465/tcp	Medium
general/tcp	Low
general/icmp	Low

2.1.1 Medium 587/tcp

Medium (CVSS: 4.8)

NVT: SMTP Unencrypted Cleartext Login

Summary

The remote host is running a SMTP server that allows cleartext logins over unencrypted connections.

... continues on next page ...

...continued from previous page ...
Quality of Detection (QoD): 70%
Vulnerability Detection Result The remote SMTP server accepts logins via the following cleartext authentication ↔ mechanisms over unencrypted connections: PLAIN LOGIN
Impact An attacker can uncover login names and passwords by sniffing traffic to the SMTP server.
Solution: Solution type: Mitigation Enable SMTPS or enforce the connection via the 'STARTTLS' command. Please see the manual of the SMTP server for more information.
Vulnerability Detection Method Evaluates from previously collected info if a non SMTPS enabled SMTP server is providing the 'PLAIN' or 'LOGIN' authentication methods without sending the 'STARTTLS' command first. Details: SMTP Unencrypted Cleartext Login OID:1.3.6.1.4.1.25623.1.0.108530 Version used: 2023-10-13T05:06:09Z

[[return to 192.123.10.30](#)]

2.1.2 Medium 143/tcp

Medium (CVSS: 4.8)
NVT: IMAP Unencrypted Cleartext Login
Summary The remote host is running an IMAP daemon that allows cleartext logins over unencrypted connections. NOTE: Valid credentials needs to given to the settings of 'Login configurations' OID: 1.3.6.1.4.1.25623.1.0.10870.
Quality of Detection (QoD): 70%
Vulnerability Detection Result The remote IMAP server accepts logins via the following cleartext authentication ↔ mechanisms over unencrypted connections: AUTH=LOGIN
... continues on next page ...

...continued from previous page ...
AUTH=PLAIN
Impact An attacker can uncover user names and passwords by sniffing traffic to the IMAP daemon if a less secure authentication mechanism (eg, LOGIN command, AUTH=PLAIN, AUTH=LOGIN) is used.
Solution: Solution type: Mitigation Configure the remote server to always enforce encrypted connections via SSL/TLS with the 'STARTTLS' command.
Vulnerability Detection Method Details: IMAP Unencrypted Cleartext Login OID:1.3.6.1.4.1.25623.1.0.15856 Version used: 2023-08-01T13:29:10Z
References osvdb: 3119 url: http://www.ietf.org/rfc/rfc2222.txt url: http://www.ietf.org/rfc/rfc2595.txt

[[return to 192.123.10.30](#)]

2.1.3 Medium 465/tcp

Medium (CVSS: 4.8)
NVT: SMTP Unencrypted Cleartext Login
Summary The remote host is running a SMTP server that allows cleartext logins over unencrypted connections.
Quality of Detection (QoD): 70%
Vulnerability Detection Result The remote SMTP server accepts logins via the following cleartext authentication ⇄ mechanisms over unencrypted connections: PLAIN LOGIN
Impact An attacker can uncover login names and passwords by sniffing traffic to the SMTP server.
... continues on next page ...

...continued from previous page ...

Solution:

Solution type: Mitigation

Enable SMTPS or enforce the connection via the 'STARTTLS' command. Please see the manual of the SMTP server for more information.

Vulnerability Detection Method

Evaluates from previously collected info if a non SMTPS enabled SMTP server is providing the 'PLAIN' or 'LOGIN' authentication methods without sending the 'STARTTLS' command first.

Details: SMTP Unencrypted Cleartext Login

OID:1.3.6.1.4.1.25623.1.0.108530

Version used: 2023-10-13T05:06:09Z

[\[return to 192.123.10.30 \]](#)

2.1.4 Low general/tcp

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

Summary

The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

It was detected that the host implements RFC1323/RFC7323.

The following timestamps were retrieved with a delay of 1 seconds in-between:

Packet 1: 4038810761

Packet 2: 4038811825

Impact

A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:

Solution type: Mitigation

To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.

To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.

The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.

... continues on next page ...

...continued from previous page ...
See the references for more information.
Affected Software/OS TCP implementations that implement RFC1323/RFC7323.
Vulnerability Insight The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.
Vulnerability Detection Method Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP Timestamps Information Disclosure OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2023-12-15T16:10:08Z
References url: https://datatracker.ietf.org/doc/html/rfc1323 url: https://datatracker.ietf.org/doc/html/rfc7323 url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152 url: https://www.fortiguard.com/psirt/FG-IR-16-090

[\[return to 192.123.10.30 \]](#)

2.1.5 Low general/icmp

Low (CVSS: 2.1)
NVT: ICMP Timestamp Reply Information Disclosure
Summary The remote host responded to an ICMP timestamp request.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following response / ICMP packet has been received: - ICMP Type: 14 - ICMP Code: 0
Impact This information could theoretically be used to exploit weak time-based random number generators in other services.
... continues on next page ...

...continued from previous page ...

Solution:

Solution type: Mitigation

Various mitigations are possible:

- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight

The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method

Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.

Details: ICMP Timestamp Reply Information Disclosure

OID:1.3.6.1.4.1.25623.1.0.103190

Version used: 2025-01-21T05:37:33Z

References

cve: CVE-1999-0524

url: <https://datatracker.ietf.org/doc/html/rfc792>

url: <https://datatracker.ietf.org/doc/html/rfc2780>

cert-bund: CB-K15/1514

cert-bund: CB-K14/0632

dfn-cert: DFN-CERT-2014-0658

[\[return to 192.123.10.30 \]](#)

This file was automatically generated.