

Scan Report

August 20, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “New Quick Task”. The scan started at Thu Aug 20 15:18:41 2026 UTC and ended at Thu Aug 20 15:28:21 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
2	Results per Host	2
2.1	192.123.20.40	2
2.1.1	High 1515/tcp	2
2.1.2	Medium 1515/tcp	3
2.1.3	Low general/icmp	5
2.1.4	Low general/tcp	6

1 Result Overview

Host	High	Medium	Low	Log	False Positive
192.123.20.40	1	1	2	0	0
Total: 1	1	1	2	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 4 results selected by the filtering described above. Before filtering there were 22 results.

2 Results per Host

2.1 192.123.20.40

Host scan start Thu Aug 20 15:19:23 2026 UTC

Host scan end Thu Aug 20 15:28:15 2026 UTC

Service (Port)	Threat Level
1515/tcp	High
1515/tcp	Medium
general/icmp	Low
general/tcp	Low

2.1.1 High 1515/tcp

High (CVSS: 7.5)

NVT: Unprotected OSSEC/Wazuh ossec-authd (authd Protocol)

Product detection result

cpe:/a:ossec:authd

Detected by OSSEC/Wazuh ossec-authd Service Detection (TCP) (OID: 1.3.6.1.4.1.25
↪623.1.0.108546)

... continues on next page ...

...continued from previous page ...
Summary The remote OSSEC/Wazuh ossec-authd service is not protected by password authentication or client certificate verification.
Quality of Detection (QoD): 99%
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.
Impact This issue may be misused by a remote attacker to register arbitrary agents at the remote service or overwrite the registration of existing ones taking them out of service.
Solution: Solution type: Workaround Enable password authentication or client certificate verification within the configuration of ossec-authd. Please see the manual of this service for more information.
Vulnerability Insight It was possible to connect to the remote OSSEC/Wazuh ossec-authd service without providing a password or a valid client certificate.
Vulnerability Detection Method Evaluate if the remote OSSEC/Wazuh ossec-authd service is protected by password authentication or client certificate verification. Note: If the scanned network is e.g. a private LAN which contains systems not accessible to the public (access restricted) and it is accepted that the target host is accessible without authentication please set the 'Network type' configuration of the following VT to 'Private LAN': Global variable settings (OID: 1.3.6.1.4.1.25623.1.0.12288) Details: Unprotected OSSEC/Wazuh ossec-authd (authd Protocol) OID:1.3.6.1.4.1.25623.1.0.108547 Version used: 2025-04-29T05:39:55Z
Product Detection Result Product: cpe:/a:ossec:authd Method: OSSEC/Wazuh ossec-authd Service Detection (TCP) OID: 1.3.6.1.4.1.25623.1.0.108546)

[[return to 192.123.20.40](#)]

2.1.2 Medium 1515/tcp

Medium (CVSS: 5.0)
NVT: SSL/TLS: Certificate Expired
Product detection result cpe:/a:ietf:transport_layer_security Detected by SSL/TLS: Collect and Report Certificate Details (OID: 1.3.6.1.4.1.25 ↪623.1.0.103692)
Summary The remote server's SSL/TLS certificate has already expired.
Quality of Detection (QoD): 99%
Vulnerability Detection Result The certificate of the remote service expired on 2026-05-07 13:31:17. Certificate details: fingerprint (SHA-1) 5692CE71E037CBE7041353F303ECE0A5E671DD85 fingerprint (SHA-256) 6B8F5CD306747EB77D1C7AB2E3DB04422F080E95C1A5FD ↪024B8591B8917E907B issued by CN=Wazuh,ST=California,C=US public key algorithm RSA public key size (bits) 2048 serial 0B985BC214649504B3C204EEAF4B9773AB1A6E86 signature algorithm sha256WithRSAEncryption subject CN=Wazuh,ST=California,C=US subject alternative names (SAN) None valid from 2025-05-07 13:31:17 UTC valid until 2026-05-07 13:31:17 UTC
Solution: Solution type: Mitigation Replace the SSL/TLS certificate by a new one.
Vulnerability Insight This script checks expiry dates of certificates associated with SSL/TLS-enabled services on the target and reports whether any have already expired.
Vulnerability Detection Method Details: SSL/TLS: Certificate Expired OID:1.3.6.1.4.1.25623.1.0.103955 Version used: 2024-06-14T05:05:48Z
Product Detection Result Product: cpe:/a:ietf:transport_layer_security ... continues on next page ...

...continued from previous page ...

Method: SSL/TLS: Collect and Report Certificate Details
 OID: 1.3.6.1.4.1.25623.1.0.103692)

[\[return to 192.123.20.40 \]](#)

2.1.3 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary

The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

The following response / ICMP packet has been received:

- ICMP Type: 14
- ICMP Code: 0

Impact

This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:

Solution type: Mitigation

Various mitigations are possible:

- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight

The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method

Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.

Details: ICMP Timestamp Reply Information Disclosure

OID:1.3.6.1.4.1.25623.1.0.103190

Version used: 2025-01-21T05:37:33Z

... continues on next page ...

...continued from previous page ...

References

cve: CVE-1999-0524

url: <https://datatracker.ietf.org/doc/html/rfc792>url: <https://datatracker.ietf.org/doc/html/rfc2780>

cert-bund: CB-K15/1514

cert-bund: CB-K14/0632

dfn-cert: DFN-CERT-2014-0658

[\[return to 192.123.20.40 \]](#)**2.1.4 Low general/tcp**

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

Summary

The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%**Vulnerability Detection Result**

It was detected that the host implements RFC1323/RFC7323.

The following timestamps were retrieved with a delay of 1 seconds in-between:

Packet 1: 228968850

Packet 2: 228969938

Impact

A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:**Solution type:** Mitigation

To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.

To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.

The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.

See the references for more information.

Affected Software/OS

TCP implementations that implement RFC1323/RFC7323.

... continues on next page ...

...continued from previous page ...

Vulnerability Insight

The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

Vulnerability Detection Method

Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.

Details: TCP Timestamps Information Disclosure

OID:1.3.6.1.4.1.25623.1.0.80091

Version used: 2023-12-15T16:10:08Z

References

url: <https://datatracker.ietf.org/doc/html/rfc1323>

url: <https://datatracker.ietf.org/doc/html/rfc7323>

url: <https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152>

url: <https://www.fortiguard.com/psirt/FG-IR-16-090>

[\[return to 192.123.20.40 \]](#)

This file was automatically generated.