

Never compile this.

```
;; -*- no-byte-compile: t; -*-
```

1. Org2blog

ID: org_gcr_2017-05-12_mara:B6246A7A-5514-4478-BC3D-7768B05B08B8

```
;; -*- no-byte-compile: t; -*-
```

Sysop is likely to use this periodically.

Start EMACS with this command:

```
emacs --debug-init --no-init-file --no-splash --background-color white --foreground-color black
(load-file "~/src/help/.org-mode-package-management.emacs.el")
```

2. Org2blog

ID: org_gcr_2017-05-12_mara:B6246A7A-5514-4478-BC3D-7768B05B08B8

Configure Org2blog for use, development, and support.

An elisp implementation of clientside XML-RPC

```
(add-to-list 'load-path "~/src/xml-rpc-el")
(require 'xml-rpc)
```

Weblog maintenance via XML-RPC APIs

```
(add-to-list 'load-path "~/src/metaweblog")
(require 'metaweblog)
```

Blog from Org mode to wordpress

```
(add-to-list 'load-path "~/src/org2blog")
(require 'org2blog)
(add-hook 'org-mode-hook #'org2blog/wp-org-mode-hook-fn)
```

Org2Blog depends on Org-Mode. This system loads Org-Mode from Git. Enter the ELPA cache directory and delete it.

This system works with WisdomAndWonder. It keeps its posts separate giving focus to each Web.

```
(setq org2blog/wp-track-posts nil)
```

Configure Org2Blog.

```
(setq org2blog/wp-blog-alist
  '(("wisdomandwonder"
    :url "https://www.wisdomandwonder.com/xmlrpc.php"
    :username "admin"
    :default-categories ("Article" "Link")
    :confirm t
    :show 'show)))
```

3. Pretty Mode

ID: org_gcr_2017-05-15_mara:CB452410-955E-4A91-A811-10755A35A142

Visualize ASCII values as their most likely Unicode representation.

```
(add-to-list 'load-path "~/src/pretty-mode")  
(require 'pretty-mode)  
(global-pretty-mode t)
```