Preprocessing and Layout Analysis for Offline Handwriting Recognition

東北大学大学院工学研究科 電子工学専攻川又研究室 Perttu Pitkänen

2016年02月26日

Overview

- Handwriting recognition
- Preprocessing
 - Stroke Width Analysis
- Layout Analysis
 - Bounding Box Expansion
 - RLSA
- Tests
- Test Results
- Conclusions
- Remaining Problems
- Future Work
- Questions and Answers

Handwriting recognition 1

- Offline handwriting recognition (HWR) is the process of extracting text in digital form from handwritten images.
- Offline recognition process can be divided into three main phases:
 - Preprocessing
 - Feature extraction
 - Classification
- Implementation done with MATLAB and its image processing toolbox

Handwriting recognition 2

Preprocessing

- Image is enhanced for feature extraction phase and the detected characters are segmented from the original image.
- Layout analysis can be considered to be a part of preprocessing.

Feature Extraction

Shape describing features are extracted from previously acquired objects (words).

Classification


Extracted features are used in machine learning algorithms to create the feature vector and to classify the inputs into word classes.

Preprocessing

- Most of the preprocessing is same than previously
 - Image aquisition
 - Noise removal
 - Adaptive Wiener filter
 - Binarization
 - Sauvola algorithm
 - Object property analysis
 - Features such as holes in object, size, area or aspect ratio
 - Stroke width variation
- All methods need pre-defined parameters!
- Object property analysis now uses sroke width instead of other features.
- Majority of methods proved to be useful in preprocessing.


Stroke Width Analysis 1

- One distinctive feature of text is that it consists of "strokes".
- Strokes have only a little variation in thickness.
- Other objects such as images can have lot of variation in thickness.
- The amount of variation can be used to distinquish text from other objects.




Dark blue represents thin stroke width and dark red thick strokes.

Stroke Width Analysis 2



For each pixel find distance to nearest black pixel


Get image skeleton



Calculating stroke width metric to represent the width variation.

Standard deviation of V divided by the mean value of V.

Remove areas which have stroke widith metric values larger than threshold.





V = [6.403, 8.5440, 6.4031, 8.0623, 5.6569, 7.2801,...]

$$\frac{\sigma}{\overline{V}} = 0.2360$$

 $\sigma = standard\ deviation$ of vector V

 $\overline{V} = mean \ of \ vector \ V$








Layout Analysis

- Analysing the image regions to find where the text is located and what kind of bodies of text it contains.
- Columns, rows, words.
- Proposed method to find the areas of interest is to draw bounding boxes over the text objects, expand them in all directions and combine overlapping boxes.
- Layout is saved hierarchically into areas of interest, rows and words.

Bounding box expansion








In the last phase boxes that take only a small fraction of the total area are removed.

= Area of interest box


Layout Analysis 2

- To find rows of text the run length smearing algorithm is used.
- The RLSA finds rows of black pixels and changes them to white if their lengths are under given threshold.
- The bounding box is aquired for each object generated by RLSA. These bounding boxes represent the rows.
- The same method is used to find individual words within rows. For words the RLSA is executed also vertically. Smaller threshold values are used.

RLSA for rows




RLSA for words



Same procedure but this time the algorithm is also run vertically to get dots or other broken characters into word.

Full layout visualized



Tests

- The system is still dependant on the parameter values.
- The tests goal is to find the optimal threshold values for IAM database images.
- First the optimal parameter values are found and then the accuracy is tested with these parameters.
- How to evaluate the accuracy of the system mathematically?
 - IAM database contains metadata about the number of rows and words.
 - Compare the real values to those detected by the system.

Example entries in IAM handwriting database.

MOVE to stop Mr. Gaitshell from wominating any more Labour life Poors is to be made at a meeting of Labour MPs tomorrow. Mr. Michael Foot has put down a resolution on the subject on a he is to be backed by Mr. Will Gistins, MP for Manchede Exchange.


though they may gather some left-wing support, a large majority of labour 19 B are likely to turn down the tood-crifths resolution. The trad's line with be that as labour 19 PE apposed the Covernment Bit which brought life greens into existence, they should not now put forward nominees. The believes that the House of Lords should be abelieved and that Labour should not take any steps which would appear to "prop up" an out-dated institution.

Delegates from Mr. Konneth Kaunda's United National Inclependence Party (280'000 member) and Mr. Harry Neumbula's African National Congress (400'000) will meet in London today to discuss a common course of action. Sir Poy is violently opposed to Africans getting an elected majority in Northern Phodesia, but the Colonial Secretary, Mr. lain Macleod, is insisting on a policy of Charge.


Mr. Maclack thought the two Rhodesian parties had refused to attend the tables because Siv Roy had found messages suffrom the Government were "unsatisfactory", african delegates to the tables yeshoday called on Mr. Macmillan to coose his negotations with Sir Roy's representative, Mr. Inlies Green field. He was at Chequers last week-end. They said they regarded with "growing angr" the gross and unconstitutional" interference by Sir Roy's Federal bovernment in the tables.

Only the handwritten part was used during the tests.

Test procedure to find optimal parameters



Example of test data



Result data for RLSA horizontal threshold test. Lowest difference is aquired with threshold 30.

Test results

Preprocessing parameters:


- wienerFilterSize = 15
- sauvolaNeighbourhoodSize = 180
- sauvolaThreshold = 0.3
- strokeWidthThreshold = 0.6

Layout analysis parameters:

- aoiXExpansionAmount = 40
- aoiYExpansionAmount = 60
- rlsaRowThreshold = 300
- rlsaWordHorizontalThreshold = 30
- rlsaWordVerticalThreshold = 30

With above parameters the system achieved following performance:

Number of images	Row detection accuracy	Word detection accuracy
5	100%	98%
10	92%	82%
15	92%	85%
20	92%	86%
25	92%	85%





Conclusions

- The chosen methods proved to be useful in preprocessing and layout analysis.
- The tests proved that the chosen parameters work well for IAM database images.
- Word detection is slightly more sensitive about parameter changes than the row detection.

Remaining problems

- The row and word detection isn't perfect
 - If two rows contain overlapping characters those rows are combined as one.
 - For the same reason multiple words can also be combined as one.






Result: 2 rows and 5 words

Real values: 9 rows and 68 words

Remaining problems: Overlapping characters





= Real word box (unrealized)

Future work

- Solve the overlapping rows/words problem.
 - Some papers have been published regarding this problem. More research is needed.
- Automatic parameter choosing.
 - Use some mathematical properties such as object area or size to choose appropriate parameter value for some functions.
 - Average object area → RLSA threshold?
- Continue to feature extraction phase.

Presentation time:

■ Presentation: 19:10


Questions: 19:40

- Okubo: (p.19) The accuracy of your proposed method is 92%. Is the error occurring only for the picture like in p.19?
 - The error can occur for multiple reasons. One reason is overlapping characters such as in p.19 and p.20 which are then combined into fewer large objects. Other reason can be broken characters/words which can make the word/row count higher than the real values.
- Okubo: (p.16) Please use vector image when you put a figure on the slide from MATLAB to avoid low resolution.
 - I will remember this for the next presentation.

- Kenya: You used the thickness information for text detection. Is the method better than your previous method? What is better than previous method? Accuracy or processing time? Comparing between the methods may show us interesting result.
 - I chose the thickness method because the previous methods based on area, aspect ratio, number of holes etc. were highly dependent on various parameters and were sensitive to change. The new method, on the other hand, only needs one threshold value and is more robust with varying text size. Mainly the motivation was to reduce the amount constant parameters in the system. I didn't compare the processing time at this point nor did I made any other accuracy tests between these two approaches. I concede that it would have been appropriate to compare these two approaches before choosing one or another.

- Konta: (p.19) Can you show the result of RSLA?
 - I did not have the image at the time of presentation. Here it is now.

Dalegates from Mr. Konneth Kaunda's United National Independence Party (280'000 member) and Mr. Harry Neumbrila's African National. Congress (400'000) will meet in london today to discuss a common course of action. Six Roy is violently opposed to Africans getting an elected majority in Northern Phodesia, but the Colonial Secretary, Mr. lain Nacleod, is insisting on a policy of Change.



- Konta: How about detecting a long black line existing on the horizontal direction? This line could be the line that is dividing the row of the text and useful for avoiding the row box miss detection.
 - (Note: I must have misunderstood this question at the time of presentation) The suggestion would be one good method to detect rows. I need to put more research into the subject of overlapping characters and some papers have been published considering this subject.

- Sone: How is the accuracy defined? For example, how do you calculate the accuracy in following condition?
 - 1. RealRow = 7, FoundRow = 8
 - 2. RealRow = 7, FoundRow = 6
 - $d = \frac{|r-f|}{r} \quad d = difference \ percentage,$ $r = amount \ of \ real \ rows,$ $f = amount \ of \ found \ rows$
 - $\frac{|7-8|}{7} = \frac{|7-6|}{7} \approx 0.1428$
- Sone: (p.17) What is the number of images? Are these images random and different?
 - Number of tested images is 25. The images have multiple different handwriting styles and texts. (All texts doesn't have different writers) There is quite lot of variation between the styles. The images were chosen randomly for the tests. The IAM handwriting database contains 1539 pages of text by 657 different writers. These images provide good amount of variation for future tests.

- Kawamata: The presentation was much better than previous time because you discussed a lot about the existing problem in your method.
- Kawamata: What is the meaning of RSLA?
 - Run Length Smearing Algorithm (see p.9)
- **Let May 1** Kawamata: (p.6) What is the meaning of $\frac{\sigma}{\overline{V}}$?
 - This is the stroke width variation metric. Standard deviation of stroke width divided by the mean value of stroke width. The value is used to describe how much the width of the given object varies. Small number means low amount of variation, high number means high variation. The high variation objects are then removed if they exceed the pre defined threshold.
- Kawamata: Could you try to speak in Japanese? It is OK if it is only in few minutes.
 - Sure, next time I'll try to speak a few minutes in Japanese.