# pTUM-base v6.0.0.0



## INITIALISATION

### `initCatDist(nvars, ncats, layers; shift=0.1)`

Allocate weights & biases arrays for a categorical distribution network. Output layer biases set to 0; hidden layers atanh-spaced + shift.

→ *(w, b, npars) :: (Array, Array, Int)*

| | | |
|---|---|---|
| `nvars` | `Int` | inputs including the category column |
| `ncats` | `Int` | number of categories |
| `layers` | `Vector{Int}` | hidden layer widths |
| `shift` KW | `Float64` | bias init offset |

### `initConDist(nvars, layers1, layers2; shift=0.1)`

Allocate weights & biases arrays for a continuous distribution network. Output layer bias set to 0; hidden layers atanh-spaced + shift.

→ *(w, b, npars) :: (Array, Array, Int)*

| | | |
|---|---|---|
| `nvars` | `Int` | total inputs including target |
| `layers1` | `Vector{Int}` | pre-warp hidden layer widths |
| `layers2` | `Vector{Int}` | post-warp hidden layer widths |
| `shift` KW | `Float64` | bias init offset |

### `initTimDist(nvars, nevents, layers1, layers2; shift=0.1)`

Allocate weights & biases arrays for a time-to-event with competing-risks network. Event-prob sub-layer and output biases set to 0; others atanh-spaced + shift.

→ *(w, b, npars) :: (Array, Array, Int)*

| | | |
|---|---|---|
| `nvars` | `Int` | inputs incl. time-start & time-end columns |
| `nevents` | `Int` | number of competing events |
| `layers1` | `Vector{Int}` | pre-warp layer widths |
| `layers2` | `Vector{Int}` | post-warp layer widths |
| `shift` KW | `Float64` | bias init offset |

## TRAINING

### `fitCatDist(w, b, data, categories, layers, iterations; …)`

Train categorical distribution via Adam on log-likelihood. Sequential sigmoid encoding. Mutates weights & biases.

→ *(w, b, llv) — updated params + log-likelihood trace Vector{Float64}*

| | | |
|---|---|---|
| `w, b` | `Array` | weights & biases (mutated) |
| `data` | `Matrix` | N × (nvars[+1]) observations |
| `categories` | `Vector` | ordered category labels |
| `layers` | `Vector{Int}` | hidden layer widths |
| `iterations` | `Int` | Adam steps |
| `hotvars` KW | `Vector{Int}` | sigma-hot group sizes |
| `obsweights` KW | `Bool` | last data col = obs weight |
| `α β1 β2 ϵ` KW | `Float64` | Adam hyperparameters |
| `c` KW | `Vector{Float64}` | weight clamp [c[1]=input, c[2]=rest] |

### `fitConDist(w, b, data, layers1, layers2, iterations; …)`

Train continuous distribution via Adam on log-likelihood. Jacobian via warp layer. Mutates weights & biases.

→ *(w, b, llv) — updated params + log-likelihood trace Vector{Float64}*

| | | |
|---|---|---|
| `w, b` | `Array` | weights & biases (mutated) |
| `data` | `Matrix` | N × (nvars[+1]) observations |
| `layers1/2` | `Vector{Int}` | pre-/post-warp layer widths |
| `iterations` | `Int` | Adam steps |
| `hotvars` KW | `Vector{Int}` | sigma-hot group sizes |
| `obsweights` KW | `Bool` | last data col = obs weight |
| `α β1 β2 ϵ` KW | `Float64` | Adam hyperparameters |
| `c` KW | `Vector{Float64}` | weight clamp [c[1]=input, c[2]=rest] |

### `fitTimDist(w, b, data, events, layers1, layers2, iterations; …)`

Train time-to-event network via Adam on log-likelihood. Handles exact events and interval-censored observations via two forward passes. Mutates weights & biases.

→ *(w, b, llv) — updated params + log-likelihood trace Vector{Float64}*

| | | |
|---|---|---|
| `w, b` | `Array` | weights & biases (mutated) |
| `data` | `Matrix` | N × (nvars+2[+1]); cols nvars & nvars+1 = time interval |
| `events` | `Vector` | event labels, length = nevents |
| `layers1/2` | `Vector{Int}` | pre-/post-warp layer widths |
| `iterations` | `Int` | full Adam steps |
| `hotvars` KW | `Vector{Int}` | sigma-hot group sizes |
| `obsweights` KW | `Bool` | last data col = obs weight |
| `α β1 β2 ϵ` KW | `Float64` | Adam hyperparameters |
| `c` KW | `Vector{Float64}` | weight clamp [c[1]=input, c[2]=rest] |

## EVALUATION — PDF

### `evalCatPDF(obs, ncats, layers, w, b)`

Returns the probability vector over all categories. Walks sequential sigmoid chain; last category gets remaining mass.

→ *pcats :: Vector{Float64} (length = ncats, sums to 1)*

| | | |
|---|---|---|
| `obs` | `Vector{Float64}` | covariates; last element = category value |
| `ncats` | `Int` | number of categories |
| `layers, w, b` | | trained network |

### `evalConPDF(obs, layers1, layers2, w, b)`

Continuous density at a single observation. Returns Jacobian from the forward pass.

→ *Float64 — density value*

| | | |
|---|---|---|
| `obs` | `Vector{Float64}` | covariates + target value (last element) |
| `layers1/2, w, b` | | trained network |

### `evalTimPDF(obs, nevents, layers1, layers2, w, b)`

Joint event-probability vector and per-event conditional density vector for all competing events.

→ *(pevents, devents) :: (Vector{Float64}, Vector{Float64}) each length = nevents*

| | | |
|---|---|---|
| `obs` | `Vector{Float64}` | covariates; obs[end-1]=event label, obs[end]=time |
| `nevents` | `Int` | number of competing events |
| `layers1/2, w, b` | | trained network |

## EVALUATION — CDF

### `evalConCDF(obs, layers1, layers2, w, b)`

CDF for continuous distribution at a single observation. Sigmoid at output layer; no Jacobian needed.

→ *Float64 ∈ (0, 1)*

| | | |
|---|---|---|
| `obs` | `Vector{Float64}` | covariates + target value |
| `layers1/2, w, b` | | trained network |

### `evalTimCDF(obs, nevents, layers1, layers2, w, b)`

Event-probability vector and per-event conditional time CDF vector at a single observation.

→ *(pevents, devents) :: (Vector{Float64}, Vector{Float64}) each length = nevents*

| | | |
|---|---|---|
| `obs` | `Vector{Float64}` | covariates; obs[end-1]=event label, obs[end]=time |
| `nevents` | `Int` | number of competing events |
| `layers1/2, w, b` | | trained network |

## CDF LIMITS

### `limitsConCDF(layers1, layers2, w, b)`

Infimum and supremum of the continuous CDF, used for scaling when computing quantiles.

→ *(inf, sup) :: (Float64, Float64)*

| | | |
|---|---|---|
| `layers1/2, w, b` | | trained network (no observation needed) |

### `limitsTimCDF(nevents, layers1, layers2, w, b)`

Per-event infimum and supremum of the time CDF, used for scaling when computing quantiles.

→ *(inf, sup) :: (Vector{Float64}, Vector{Float64}) each length = nevents*

| | | |
|---|---|---|
| `nevents` | `Int` | number of competing events |
| `layers1/2, w, b` | | trained network (no observation needed) |

## QUANTILES

### `quantileCon(cvars, p, layers1, layers2, w, b; accuracy, boundLow, boundUpp)`

Bisection-search quantile for continuous distribution. Bracket expands geometrically until p is enclosed.

→ *Float64 — target value at cumulative probability p*

| | | |
|---|---|---|
| `cvars` | `Vector{Float64}` | covariates (no target) |
| `p` | `Float64` | probability level ∈ (0,1) |
| `layers1/2, w, b` | | trained network |
| `accuracy` KW | `Float64` | bisection convergence tolerance |
| `boundLow/Upp` KW | `Float64` | maximum bracket expansion limits |

### `quantileTim(cvars, eventnr, nevents, p, layers1, layers2, w, b; accuracy, boundLow, boundUpp)`

Bisection-search quantile for time distribution of a specific competing event. Bracket expands geometrically until p is enclosed.

→ *Float64 — time at cumulative probability p for event eventnr*

| | | |
|---|---|---|
| `cvars` | `Vector{Float64}` | covariates (no time) |
| `eventnr` | `Int` | event index (1..nevents) to query |
| `nevents` | `Int` | number of competing events |
| `p` | `Float64` | probability level ∈ (0,1) |
| `layers1/2, w, b` | | trained network |
| `accuracy` KW | `Float64` | bisection convergence tolerance |
| `boundLow/Upp` KW | `Float64` | maximum bracket expansion limits |