

evalCatPDF (<i>obs</i> , <i>ncats</i> , <i>layers</i> , <i>w</i> , <i>b</i>) Returns the probability vector over all categories. Walks sequential sigmoid chain; last category gets remaining mass. → <i>pcats</i> :: Vector{Float64} (length = <i>ncats</i> , sums to 1)	<table><tr><td><i>obs</i></td><td>Vector{Float64}</td><td>covariates; last element = category value</td></tr><tr><td><i>ncats</i></td><td>Int</td><td>number of categories</td></tr><tr><td><i>layers</i>, <i>w</i>, <i>b</i></td><td></td><td>trained network</td></tr></table>	<i>obs</i>	Vector{Float64}	covariates; last element = category value	<i>ncats</i>	Int	number of categories	<i>layers</i> , <i>w</i> , <i>b</i>		trained network
<i>obs</i>	Vector{Float64}	covariates; last element = category value								
<i>ncats</i>	Int	number of categories								
<i>layers</i> , <i>w</i> , <i>b</i>		trained network								
evalConPDF (<i>obs</i> , <i>layers1</i> , <i>layers2</i> , <i>w</i> , <i>b</i>) Continuous density at a single observation. Returns Jacobian from the forward pass. → Float64 — density value	<table><tr><td><i>obs</i></td><td>Vector{Float64}</td><td>covariates + target value (last element)</td></tr><tr><td><i>layers1/2</i>, <i>w</i>, <i>b</i></td><td></td><td>trained network</td></tr></table>	<i>obs</i>	Vector{Float64}	covariates + target value (last element)	<i>layers1/2</i> , <i>w</i> , <i>b</i>		trained network			
<i>obs</i>	Vector{Float64}	covariates + target value (last element)								
<i>layers1/2</i> , <i>w</i> , <i>b</i>		trained network								
evalTimPDF (<i>obs</i> , <i>nevents</i> , <i>layers1</i> , <i>layers2</i> , <i>w</i> , <i>b</i>) Joint event-probability vector and per-event conditional density vector for all competing events. → (<i>pevents</i> , <i>devents</i>) :: (Vector{Float64}, Vector{Float64}) each length = <i>nevents</i>	<table><tr><td><i>obs</i></td><td>Vector{Float64}</td><td>covariates; <i>obs</i>[end-1]=event label, <i>obs</i>[end]=time</td></tr><tr><td><i>nevents</i></td><td>Int</td><td>number of competing events</td></tr><tr><td><i>layers1/2</i>, <i>w</i>, <i>b</i></td><td></td><td>trained network</td></tr></table>	<i>obs</i>	Vector{Float64}	covariates; <i>obs</i> [end-1]=event label, <i>obs</i> [end]=time	<i>nevents</i>	Int	number of competing events	<i>layers1/2</i> , <i>w</i> , <i>b</i>		trained network
<i>obs</i>	Vector{Float64}	covariates; <i>obs</i> [end-1]=event label, <i>obs</i> [end]=time								
<i>nevents</i>	Int	number of competing events								
<i>layers1/2</i> , <i>w</i> , <i>b</i>		trained network								

EVALUATION — CDF

evalConCDF (obs, layers1, layers2, w, b) CDF for continuous distribution at a single observation. Sigmoid at output layer; no Jacobian needed. → Float64 ∈ (0, 1)	<table><tr><td>obs</td><td>Vector{Float64}</td><td>covariates + target value</td></tr><tr><td>layers1/2, w, b</td><td></td><td>trained network</td></tr></table>	obs	Vector{Float64}	covariates + target value	layers1/2, w, b		trained network			
obs	Vector{Float64}	covariates + target value								
layers1/2, w, b		trained network								
evalTimCDF (obs, nevents, layers1, layers2, w, b) Event-probability vector and per-event conditional time CDF vector at a single observation. → (pevents, devents) :: (Vector{Float64}, Vector{Float64}) each length = nevents	<table><tr><td>obs</td><td>Vector{Float64}</td><td>covariates; obs[end-1]=event label, obs[end]=time</td></tr><tr><td>nevents</td><td>Int</td><td>number of competing events</td></tr><tr><td>layers1/2, w, b</td><td></td><td>trained network</td></tr></table>	obs	Vector{Float64}	covariates; obs[end-1]=event label, obs[end]=time	nevents	Int	number of competing events	layers1/2, w, b		trained network
obs	Vector{Float64}	covariates; obs[end-1]=event label, obs[end]=time								
nevents	Int	number of competing events								
layers1/2, w, b		trained network								

CDF LIMITS

limitsConCDF(layers1, layers2, w, b) Infimum and supremum of the continuous CDF, used for scaling when computing quantiles. → (inf, sup) :: (Float64, Float64)	layers1/2, w, b	trained network (no observation needed)
limitsTimCDF(nevents, layers1, layers2, w, b) Per-event infimum and supremum of the time CDF, used for scaling when computing quantiles. → (inf, sup) :: (Vector{Float64}, Vector{Float64}) each length = nevents	nevents layers1/2, w, b	Int number of competing events trained network (no observation needed)

QUANTILES

quantileCon (<i>cvars</i> , <i>p</i> , <i>layers1</i> , <i>layers2</i> , <i>w</i> , <i>b</i> ; <i>accuracy</i> , <i>boundLow</i> , <i>boundUpp</i>)	<table><tr><td><i>cvars</i></td><td>Vector{Float64}</td><td>covariates (no target)</td></tr><tr><td><i>p</i></td><td>Float64</td><td>probability level $\in (0,1)$</td></tr><tr><td><i>layers1/2</i>, <i>w</i>, <i>b</i></td><td></td><td>trained network</td></tr><tr><td><i>accuracy</i> KW</td><td>Float64</td><td>bisection convergence tolerance</td></tr><tr><td><i>boundLow/Upp</i> KW</td><td>Float64</td><td>maximum bracket expansion limits</td></tr></table>	<i>cvars</i>	Vector{Float64}	covariates (no target)	<i>p</i>	Float64	probability level $\in (0,1)$	<i>layers1/2</i> , <i>w</i> , <i>b</i>		trained network	<i>accuracy</i> KW	Float64	bisection convergence tolerance	<i>boundLow/Upp</i> KW	Float64	maximum bracket expansion limits						
<i>cvars</i>	Vector{Float64}	covariates (no target)																				
<i>p</i>	Float64	probability level $\in (0,1)$																				
<i>layers1/2</i> , <i>w</i> , <i>b</i>		trained network																				
<i>accuracy</i> KW	Float64	bisection convergence tolerance																				
<i>boundLow/Upp</i> KW	Float64	maximum bracket expansion limits																				
quantileTim (<i>cvars</i> , <i>eventnr</i> , <i>nevents</i> , <i>p</i> , <i>layers1</i> , <i>layers2</i> , <i>w</i> , <i>b</i> ; <i>accuracy</i> , <i>boundLow</i> , <i>boundUpp</i>)	<table><tr><td><i>cvars</i></td><td>Vector{Float64}</td><td>covariates (no time)</td></tr><tr><td><i>eventnr</i></td><td>Int</td><td>event index (1..<i>nevents</i>) to query</td></tr><tr><td><i>nevents</i></td><td>Int</td><td>number of competing events</td></tr><tr><td><i>p</i></td><td>Float64</td><td>probability level $\in (0,1)$</td></tr><tr><td><i>layers1/2</i>, <i>w</i>, <i>b</i></td><td></td><td>trained network</td></tr><tr><td><i>accuracy</i> KW</td><td>Float64</td><td>bisection convergence tolerance</td></tr><tr><td><i>boundLow/Upp</i> KW</td><td>Float64</td><td>maximum bracket expansion limits</td></tr></table>	<i>cvars</i>	Vector{Float64}	covariates (no time)	<i>eventnr</i>	Int	event index (1.. <i>nevents</i>) to query	<i>nevents</i>	Int	number of competing events	<i>p</i>	Float64	probability level $\in (0,1)$	<i>layers1/2</i> , <i>w</i> , <i>b</i>		trained network	<i>accuracy</i> KW	Float64	bisection convergence tolerance	<i>boundLow/Upp</i> KW	Float64	maximum bracket expansion limits
<i>cvars</i>	Vector{Float64}	covariates (no time)																				
<i>eventnr</i>	Int	event index (1.. <i>nevents</i>) to query																				
<i>nevents</i>	Int	number of competing events																				
<i>p</i>	Float64	probability level $\in (0,1)$																				
<i>layers1/2</i> , <i>w</i> , <i>b</i>		trained network																				
<i>accuracy</i> KW	Float64	bisection convergence tolerance																				
<i>boundLow/Upp</i> KW	Float64	maximum bracket expansion limits																				