

PENETRATION TESTING & SECURITY ASSESSMENT REPORT

Footprinting, OSINT, DNS Enumeration & Network Reconnaissance

Pentester Name (Cybersecurity Professional)	ADONGO PETER ODUOR
Program/Batch	B083
Target	1. Networkwalks (secured written permission already) 2. My own local LAN Network
Date	16 September 2026
Permission secured from client?	Yes
Phases covered	Phase 1: Reconnaissance & Footprinting Phase 2: Scanning & Network Discovery Phase 3-5: In Progress

1. EXECUTIVE SUMMARY

This report documents an authorized reconnaissance and attack-surface assessment of **Networkwalks** (networkwalks.com). The assessment focused on passive and active footprinting, DNS enumeration, web technology identification, HTTP response analysis, WAF identification, WHOIS reconnaissance, and infrastructure mapping using Maltego.

The objective was to identify publicly exposed information that could assist an attacker in understanding the organization's external attack surface and to provide practical recommendations for reducing unnecessary exposure.

The assessment identified several areas requiring security attention:

- Multiple publicly discoverable DNS names and infrastructure records.
- Concentration of several discovered services around IP address **192.232.216.135**.
- Public disclosure of web technologies including **WordPress 7.1** and **WordPress Download Manager 3.3.58**.
- Publicly observable DNS infrastructure and authoritative nameserver information.
- An externally identifiable hosting environment involving HostGator infrastructure and an Oracle-associated ASN.
- A publicly exposed WordPress REST API endpoint.
- A publicly identifiable administrative/root-style hosting email address.
- A [localhost.networkwalks.com](#) record resolving to [127.0.0.1](#), which should be reviewed to determine whether it is intentional.
- DNS zone-transfer attempts were refused by the authoritative nameservers, which is a positive security observation.
- A Web Application Firewall was detected through WAFW00F, indicating an existing defensive control.
- Maltego identified several suspicious or malformed domain names that require ownership and threat-intelligence validation before being classified as malicious.

No exploitation, credential attacks, denial-of-service testing, destructive activity, or unauthorized access was performed during this phase.

The findings in this report therefore represent **reconnaissance observations and attack-surface risks rather than confirmed exploitable vulnerabilities**, unless explicitly stated otherwise.

2. ASSESSMENT OBJECTIVES

The assessment objectives were to:

1. Identify publicly discoverable Networkwalks infrastructure.
2. Enumerate DNS records and subdomains.
3. Identify hosting and network infrastructure.
4. Determine technologies exposed by the public website.
5. Identify potentially unnecessary information disclosure.
6. Assess DNS configuration from an external perspective.
7. Identify defensive technologies such as WAF protection.

8. Map relationships between domains, IP addresses, netblocks, DNS records and autonomous systems.
 9. Identify areas requiring further security validation.
 10. Provide prioritized remediation recommendations.
-

3. SCOPE

3.1 Primary Target

Domain:

networkwalks.com

3.2 Discovered DNS Names

The reconnaissance process identified the following DNS names:

#	DNS Name
1	autoconfig.networkwalks.com
2	autodiscover.networkwalks.com
3	cpanel.networkwalks.com
4	cpcalendars.networkwalks.com
5	cpcontacts.networkwalks.com
6	ftp.networkwalks.com
7	localhost.networkwalks.com
8	mail.networkwalks.com
9	webdisk.networkwalks.com
10	webmail.networkwalks.com
11	whm.networkwalks.com
12	www.networkwalks.com

These records provide an external observer with information about potentially available web, mail, hosting-management and file-management services.

4. METHODOLOGY

The assessment followed a controlled reconnaissance methodology:

Phase 1 — Domain Reconnaissance

WHOIS and DNS information was collected to establish:

- Domain ownership information.
- Registrar information.
- Name servers.
- DNS configuration.
- Mail infrastructure.
- Domain lifecycle information.

Phase 2 — DNS Enumeration

DNSRecon and nslookup were used to identify:

- A records.
- MX records.
- NS records.
- SOA records.
- TXT records.
- DNSSEC observations.
- Authoritative DNS infrastructure.

Phase 3 — Web Technology Fingerprinting

WhatWeb was used to identify publicly observable technologies, including:

- Web server.
- CMS.
- JavaScript libraries.
- WordPress components.
- Web application plugins.

- Cookies.
- Frameworks and headers.

Phase 4 — HTTP Header Analysis

`curl -I` was used to inspect:

- HTTP status.
- Security-related headers.
- Server information.
- Cookies.
- WordPress endpoints.
- Cache infrastructure.

Phase 5 — WAF Detection

WAFW00F was used to determine whether a Web Application Firewall was present.

Phase 6 — OSINT & Infrastructure Mapping

Maltego was used to correlate:

- Domains.
- DNS names.
- IP addresses.
- Netblocks.
- MX records.
- Nameservers.
- Autonomous Systems.
- Associated organizations.

Phase 7 — Security Interpretation

The discovered information was categorized according to its potential security impact.

5. TOOLS USED

Tool	Purpose
WHOIS	Domain and registration reconnaissance

nslookup	DNS resolution
DNSRecon	DNS enumeration
WhatWeb	Web technology fingerprinting
cURL	HTTP/HTTPS response analysis
WAFW00F	WAF detection
Maltego	OSINT and infrastructure relationship mapping
Kali Linux	Security assessment platform

6. TECHNICAL FINDINGS

6.1 DNS Resolution

Command

nslookup networkwalks.com

Observation

The domain resolved to:

192.232.216.135

The DNS query was performed through:

8.8.8.8

Security Significance

The public IP address provides a direct infrastructure reference for further authorized security assessment.

A single IP address appearing to serve multiple discovered DNS names may indicate infrastructure concentration.

Risk

Low — Information Exposure / Attack-Surface Concentration

This is not itself a vulnerability.

Recommendation

Review which services are intentionally hosted on the address and ensure that:

- Only required services are exposed.
 - Unnecessary ports are closed.
 - Administrative interfaces are restricted.
 - Monitoring and logging are enabled.
 - Internet-facing services are regularly patched.
-

6.2 DNS Infrastructure Enumeration

DNSRecon identified:

SOA:

ns6135.hostgator.com

50.87.144.87

NS:

ns6135.hostgator.com

ns6136.hostgator.com

The assessment also identified:

MX:

mail.networkwalks.com

192.232.216.135

The SPF record observed was:

v=spf1 +a +mx +ip4:50.87.144.87 +include:websitewelcome.com ~all

Security Significance

DNS records expose infrastructure relationships that can assist attackers during reconnaissance.

The SPF record also provides information about authorized mail-sending infrastructure.

Risk

Low to Medium — Infrastructure Information Exposure

Recommendation

Conduct a DNS hygiene review and:

- Remove obsolete records.
 - Remove unused subdomains.
 - Verify every public DNS record has a business purpose.
 - Review SPF mechanisms.
 - Implement DKIM.
 - Implement DMARC with appropriate monitoring/enforcement.
 - Periodically audit DNS records.
-

6.3 DNS Software Version Disclosure

DNSRecon reported:

BIND 9.16.23-RH

on the identified authoritative DNS infrastructure.

Security Significance

Version disclosure can assist attackers in identifying potentially relevant vulnerabilities or targeting information.

However, **version disclosure alone does not establish that the DNS server is vulnerable.**

Risk

Low — Information Disclosure

Recommendation

Where operationally possible:

- Minimize unnecessary version disclosure.
 - Keep DNS infrastructure fully patched.
 - Monitor vendor security advisories.
 - Restrict administrative access.
 - Maintain separate authoritative and administrative infrastructure where appropriate.
-

6.4 DNS Zone Transfer Testing

Maltego attempted DNS zone-transfer operations against:

ns6135.hostgator.com

ns6136.hostgator.com

The results were:

AXFR — REFUSED

IXFR — REFUSED

Security Assessment

This is a **positive security observation**.

The authoritative servers did not provide an unauthorized zone transfer during the assessment.

Status

No unauthorized DNS zone transfer observed.

Recommendation

Continue maintaining restrictive AXFR/IXFR policies and ensure zone transfers, where required, are limited to authorized secondary DNS servers.

6.5 Web Technology Fingerprinting

WhatWeb identified:

Apache
WordPress 7.1
WordPress Download Manager 3.3.58
jQuery 3.7.1
Bootstrap 7.1
Google Tag Manager
HTML5
Open Graph Protocol

The website was identified as:

Networkwalks Academy

Security Significance

Public technology fingerprinting gives an attacker information about the application's technology stack.

In particular, publicly identifying:

- WordPress version
- WordPress plugins
- JavaScript libraries
- Web server technology

can assist vulnerability research.

Risk

Medium — Technology Fingerprinting / Information Disclosure

This is **not proof that the identified software contains a vulnerability**.

Recommendation

1. Keep WordPress updated.
2. Keep WordPress Download Manager updated.
3. Remove unused plugins and themes.
4. Regularly audit installed plugins.
5. Disable unnecessary version disclosure where practical.
6. Implement automated patch monitoring.

7. Perform authenticated vulnerability assessment of the WordPress installation under the approved scope.
-

6.6 HTTP Header Analysis

The HTTPS response returned:

HTTP/2 200

The response disclosed information including:

Server: Apache

Content-Type: text/html; charset=UTF-8

The response also exposed WordPress REST API references:

<https://networkwalks.com/wp-json/>

<https://networkwalks.com/wp-json/wp/v2/pages/53>

Security Significance

HTTP headers can reveal implementation details.

The WordPress REST API is a normal WordPress feature and **its presence is not automatically a vulnerability**.

However, exposed API endpoints should be tested to determine whether they disclose information that should not be publicly accessible.

Risk

Low — Information Disclosure

Recommendation

Review:

- Public REST API endpoints.
- Unauthenticated API responses.

- User enumeration exposure.
- Publicly accessible content.
- Plugin-generated REST endpoints.

Do not disable the WordPress REST API blindly because legitimate website functionality may depend on it.

6.7 WAF Detection

WAFW00F identified:

ModSecurity (SpiderLabs) WAF

Security Significance

The presence of a Web Application Firewall is a positive defensive control.

It can provide protection against certain classes of malicious HTTP requests and assist with filtering and monitoring.

Status

Positive Security Control Identified

Recommendation

Ensure ModSecurity:

- Uses an actively maintained ruleset.
- Generates useful security logs.
- Is monitored.
- Does not operate solely as a passive control.
- Is periodically tested against authorized application-security test cases.

A WAF should supplement secure application development rather than replace it.

6.8 Hosting and Infrastructure Mapping

Maltego identified the following IP addresses:

192.232.216.135
50.87.144.87
127.0.0.1

Associated netblocks included:

192.232.216.0 – 192.232.216.255
50.87.144.0 – 50.87.144.255
127.0.0.0 – 127.0.0.255

The assessment identified HostGator infrastructure and:

AS31898
ORACLE-BMC-31898

Security Significance

Infrastructure mapping shows how external systems and hosting providers relate to the target.

The concentration of multiple DNS entities around:

192.232.216.135

means that compromise or disruption of a shared infrastructure component could potentially affect multiple services.

This should be treated as an **architectural consideration**, not a confirmed single point of failure.

Risk

Medium — Infrastructure Concentration

Recommendation

Review service dependency and consider:

- Separation of critical services.
- Network segmentation.
- Independent backup infrastructure.

- Disaster recovery procedures.
 - Provider-level redundancy where justified.
 - Monitoring for unexpected infrastructure changes.
-

6.9 localhost.networkwalks.com

Resolution

Maltego identified:

localhost.networkwalks.com
→ 127.0.0.1

Security Significance

A hostname resolving to loopback is unusual for a public-facing DNS namespace and should be reviewed.

However, the presence of such a record **does not by itself demonstrate an exploitable vulnerability**.

Potential security relevance depends on how applications consume and trust DNS names.

Risk

Low — Configuration Review Required

Recommendation

Determine whether this DNS record is intentional.

If it is unnecessary:

- Remove it.
- Review DNS management procedures.
- Search application configurations for references to the hostname.

If it is intentional, document its purpose and ensure it cannot be abused by application logic.

6.10 Administrative Email Exposure

Maltego identified:

root@gator3068.hostgator.com

Security Significance

Public exposure of infrastructure-related administrative addresses can increase the amount of information available to attackers conducting:

- Social engineering.
- Phishing.
- Credential-targeting campaigns.

Risk

Low to Medium — Information Exposure

Recommendation

- Avoid using root/administrative accounts for normal communication.
 - Use role-based administrative addresses.
 - Protect administrative mailboxes with MFA.
 - Monitor authentication attempts.
 - Implement SPF, DKIM and DMARC.
 - Avoid publishing infrastructure-specific addresses unnecessarily.
-

6.11 Suspicious or Malformed Domains

The Maltego extraction reported domains resembling:

networlowwalks.cam
retwodovalka.cam

Security Significance

These names appear suspicious or malformed relative to the legitimate:

networkwalks.com

However, Maltego discovery alone does **not establish ownership, malicious intent, or phishing activity**.

Risk

Potential Medium — Requires Threat-Intelligence Validation

Recommendation

The Networkwalks security/IT team should verify:

1. Whether the domains are owned by Networkwalks.
2. Whether they resolve to Networkwalks infrastructure.
3. Whether they host cloned content.
4. Whether they are being used for phishing.
5. Whether registrar/WHOIS information indicates suspicious registration.
6. Whether the domains appear in threat-intelligence feeds.

If confirmed malicious, the domains should be documented as impersonation/phishing infrastructure and appropriate registrar, hosting-provider and domain-abuse channels should be considered.

6.12 HTTPS / SSL Validation Discrepancy

The Maltego-derived report indicated:

SSL disabled / Port 80 only.

However, the direct Kali assessment produced:

```
curl -I https://networkwalks.com
```

with:

```
HTTP/2 200
```

and successfully retrieved HTTPS response headers.

Security Assessment

These results conflict.

Therefore, the statement that HTTPS is completely disabled **cannot be treated as a confirmed finding based on the supplied evidence.**

The assessment should instead record:

HTTPS is demonstrably available from the tested environment.

Port 80 was also observed redirecting to HTTPS during WhatWeb reconnaissance.

Recommendation

Perform a dedicated TLS configuration assessment covering:

- Certificate validity.
- Certificate chain.
- TLS versions.
- Cipher suites.
- HSTS.
- HTTP-to-HTTPS redirection.
- Mixed content.
- Cookie security.
- Certificate renewal configuration.

This should be validated using a dedicated TLS assessment tool during the next authorized testing phase.

7. CONSOLIDATED RISK REGISTER

ID	Finding / Observation	Risk	Status
F-0 1	Public technology fingerprinting	Medium	Confirmed observation
F-0 2	Multiple DNS/service records exposed	Medium	Confirmed observation
F-0 3	Infrastructure concentration around 192.232.216.135	Medium	Architectural observation

F-0 4	DNS software version disclosure	Low	Confirmed observation
F-0 5	WordPress REST API publicly referenced	Low	Confirmed observation
F-0 6	Administrative/root-style email exposed	Low–Medium	Confirmed observation
F-0 7	<code>localhost</code> DNS record	Low	Requires validation
F-0 8	DNSSEC reported unsigned	Low	Configuration observation
F-0 9	Suspicious/malformed domains	Medium potential	Requires validation
F-1 0	HTTPS/SSL status discrepancy	Requires validation	Evidence conflict
F-1 1	DNS zone transfer	No issue observed	AXFR/IXFR refused
F-1 2	WAF protection	Positive control	ModSecurity detected

8. SECURITY STRENGTHS IDENTIFIED

The assessment also identified several positive controls.

8.1 Web Application Firewall

ModSecurity was detected protecting the web application.

8.2 HTTPS Availability

Direct testing successfully reached the website through HTTPS.

8.3 HTTP-to-HTTPS Redirection

The HTTP endpoint was observed redirecting to HTTPS.

8.4 DNS Zone Transfer Protection

AXFR and IXFR requests were refused.

8.5 WHOIS Privacy

The registration information included privacy protection, reducing direct exposure of registrant personal information.

These controls should be maintained and periodically validated.

9. PRIORITIZED SECURITY IMPROVEMENT PLAN

Priority 1 — Immediate

9.1 Verify All Public DNS Records

Perform an authoritative DNS inventory and classify every hostname as:

- Required.
- Legacy.
- Development.
- Administrative.
- Unused.

Remove unnecessary records.

9.2 Validate Suspicious Domains

Investigate:

networlowwalks.cam
retwodovalka.cam

and any additional typo-similar domains.

Determine whether they represent:

- Legitimate assets.
- Third-party references.
- Search-engine artifacts.
- Malicious impersonation domains.

9.3 Review Internet-Exposed Services

Conduct an authorized port/service assessment of the identified public infrastructure.

Focus particularly on unnecessary:

- FTP.
- cPanel.
- WHM.
- Webmail.
- WebDisk.
- Other administrative interfaces.

Administrative services should preferably be restricted by VPN, IP allowlisting, MFA or other strong access controls.

10. PRIORITY 2 — HARDENING

10.1 WordPress Security

Maintain current supported versions of:

- WordPress.
- WordPress Download Manager.
- Themes.
- Plugins.
- PHP.
- Web server components.

Remove unused components.

10.2 Authentication

Require MFA for:

- WordPress administrators.
- Hosting control panels.
- WHM/cPanel.
- Email administration.
- DNS administration.

10.3 Administrative Access

Restrict administrative interfaces from unrestricted Internet access where operationally possible.

10.4 Email Security

Implement and validate:

SPF
DKIM
DMARC

DMARC should initially be monitored before moving toward a stricter enforcement policy where appropriate.

11. PRIORITY 3 — MONITORING AND DETECTION

Networkwalks should establish continuous monitoring for:

- New DNS records.
- Certificate changes.
- New subdomains.
- Unexpected IP changes.
- New open ports.
- Suspicious authentication activity.
- WordPress plugin changes.
- WAF alerts.
- Phishing domains.
- Domain impersonation.

A centralized logging and alerting solution should be considered for security-critical infrastructure.

12. RECOMMENDED NEXT PENETRATION-TESTING PHASE

The current assessment is primarily reconnaissance.

A subsequent authorized technical assessment should validate the observations identified here.

Recommended activities include:

Web Application Assessment

- Authentication testing.
- Authorization testing.
- Session-management testing.
- Input-validation testing.
- OWASP Top 10 assessment.
- WordPress security assessment.
- Plugin vulnerability assessment.

Network Assessment

- TCP/UDP service enumeration.
- Service/version identification.
- TLS configuration assessment.
- External attack-surface validation.
- Administrative-interface exposure assessment.

DNS Assessment

- Full DNS record inventory.
- DNSSEC validation.
- DNS configuration review.
- Subdomain takeover checks where applicable.
- Zone-transfer validation.
- Dangling DNS record checks.


Email Security Assessment

- SPF validation.
- DKIM validation.
- DMARC validation.
- Mail-server configuration review.
- Email authentication testing.

All testing should remain within the written authorization and agreed rules of engagement.

13. ATTACK-SURFACE SUMMARY

The external attack surface discovered during reconnaissance can be summarized as:



This represents the observed relationships and should not be interpreted as a complete network topology.

14. OVERALL SECURITY ASSESSMENT

The reconnaissance phase demonstrates that Networkwalks has a **moderately observable external attack surface**, primarily due to publicly discoverable DNS records, identifiable technologies, hosting infrastructure and administrative service names.

The most important security improvement opportunity is not simply hiding this information. Instead, Networkwalks should ensure that every exposed asset is:

1. **Known**
2. **Required**
3. **Patched**
4. **Authenticated**
5. **Monitored**
6. **Properly segmented**
7. **Continuously reviewed**

The assessment did not establish unauthorized access or a confirmed critical vulnerability.

Several observations require a deeper technical assessment before their actual security impact can be determined.

15. EVIDENCES COLLECTED

```

(kali㉿kali)-[~]
$ whois networkwalks.com
Domain Name: NETWORKWALKS.COM
Registry Domain ID: 2452319255_DOMAIN_COM-VRSN
Registrar WHOIS Server: whois.godaddy.com
Registrar URL: http://www.godaddy.com
Updated Date: 2025-11-12T10:08:43Z
Creation Date: 2019-11-06T22:51:46Z
Registry Expiry Date: 2027-11-06T22:51:46Z
Registrar: GoDaddy.com, LLC
Registrar IANA ID: 146
Registrar Abuse Contact Email: abuse@godaddy.com
Registrar Abuse Contact Phone: 480-624-2505
Domain Status: clientDeleteProhibited https://icann.org/epp#clientDeleteProhibited
Domain Status: clientRenewProhibited https://icann.org/epp#clientRenewProhibited
Domain Status: clientTransferProhibited https://icann.org/epp#clientTransferProhibited
Domain Status: clientUpdateProhibited https://icann.org/epp#clientUpdateProhibited
Name Server: NS6135.HOSTGATOR.COM
Name Server: NS6136.HOSTGATOR.COM
DNSSEC: unsigned
URL of the ICANN Whois Inaccuracy Complaint Form: https://www.icann.org/wicf/
>>> Last update of whois database: 2026-09-16T10:33:09Z <<<

```

```

(kali㉿kali)-[~]
$ whatweb networkwalks.com
http://networkwalks.com [301 Moved Permanently] Apache, Cookies[__wpdm_client], Country[UNITED STATES][US], HTTPServer[Apache], HttpOnly[__wpdm_client], IP[192.232.216.135], RedirectLocation[https://networkwalks.com/], UncommonHeaders[permissions-policy,x-redirect-by,upgrade,referrer-policy,x-endurance-cache-level,x-nginx-cache]
https://networkwalks.com [200 OK] Apache, Bootstrap[7.1], Cookies[__wpdm_client], Country[UNITED STATES][US], Email[info@networkwalks.com], Frame, Google-Tag-Manager, HTML5, HTTPServer[Apache], HttpOnly[__wpdm_client], IP[192.232.216.135], JQuery[3.7.1], MetaGenerator[WordPress 7.1,WordPress Download Manager 3.3.58], Open-Graph-Protocol[website], Script[4684NR-IPIB&pidnVar2=50511&pvtVar2=7&scvVar2=12,application/json,application/ld+json,module,speculationrules,text/javascript], Title[Networkwalks Academy], UncommonHeaders[permissions-policy,link,upgrade,referrer-policy,x-endurance-cache-level,x-nginx-cache], WordPress[7.1]
https://networkwalks.com/ [200 OK] Apache, Bootstrap[7.1], Country[UNITED STATES][US], Email[info@networkwalks.com], Frame, Google-Tag-Manager, HTML5, HTTPServer[Apache], IP[192.232.216.135], JQuery[3.7.1], MetaGenerator[WordPress 7.1,WordPress Download Manager 3.3.58], Open-Graph-Protocol[website], Script[4684NR-IPIB&pidnVar2=50511&pvtVar2=7&scvVar2=12,application/json,application/ld+json,module,speculationrules,text/javascript], Title[Networkwalks Academy], UncommonHeaders[permissions-policy,link,upgrade,referrer-policy,x-endurance-cache-level,x-nginx-cache], WordPress[7.1]

```

```

(kali㉿kali)-[~]
$ nslookup networkwalks.com
Server:      8.8.8.8
Address:     8.8.8.8#53

Non-authoritative answer:
Name:   networkwalks.com
Address: 192.232.216.135

```

```

(kali㉿kali)-[~]
$

```

```

(kali@kali)-[~]
$ dnsrecon -d networkwalks.com
2026-09-16T07:36:28.072103-0400 INFO Starting enumeration for domain: networkwalks.com
2026-09-16T07:36:28.074012-0400 INFO std: Performing General Enumeration against: networkwalks.com...
2026-09-16T07:36:30.132260-0400 ERROR No answer for DNSSEC query for networkwalks.com
2026-09-16T07:36:31.103412-0400 INFO SOA ns6135.hostgator.com 50.87.144.87
2026-09-16T07:36:33.221625-0400 INFO NS ns6136.hostgator.com 192.232.216.131
2026-09-16T07:36:33.924673-0400 INFO Bind Version for 192.232.216.131 "9.16.23-RH"
2026-09-16T07:36:33.925171-0400 INFO NS ns6135.hostgator.com 50.87.144.87
2026-09-16T07:36:34.461999-0400 INFO Bind Version for 50.87.144.87 "9.16.23-RH"
2026-09-16T07:36:35.995649-0400 INFO MX mail.networkwalks.com 192.232.216.135
2026-09-16T07:36:36.880464-0400 INFO A networkwalks.com 192.232.216.135
2026-09-16T07:36:37.885119-0400 INFO TXT networkwalks.com v=spf1 +a +mx +ip4:50.87.144.87 +include:website
welcome.com ~all
2026-09-16T07:36:37.885869-0400 INFO TXT networkwalks.com google-site-verification=rr04eRmqHoWY3XemnizDNVK
4q75X-Ij-mjgEeg-UsYI
2026-09-16T07:36:38.558264-0400 INFO Enumerating SRV Records
2026-09-16T07:36:43.983453-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanel.emaildiscovery.cpanel.net 184.94.204.15 443
2026-09-16T07:36:43.983693-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanel.emaildiscovery.cpanel.net 184.94.204.9 443
2026-09-16T07:36:43.983849-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanel.emaildiscovery.cpanel.net 184.94.203.15 443
2026-09-16T07:36:43.983967-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanel.emaildiscovery.cpanel.net 184.94.203.14 443
2026-09-16T07:36:43.984167-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanel.emaildiscovery.cpanel.net 184.94.203.9 443
2026-09-16T07:36:43.984283-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanel.emaildiscovery.cpanel.net 184.94.203.11 443
2026-09-16T07:36:43.984417-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanel.emaildiscovery.cpanel.net

```

```

(kali@kali)-[~]
$ wafw00f networkwalks.com

```



404 Hack Not Found

405 Not Allowed

403 Forbidden

502 Bad Gateway

500 Internal Error

~ WAFW00F : v2.4.2 ~

The Web Application Firewall Fingerprinting Toolkit

```

[*] Checking https://networkwalks.com
[+] The site https://networkwalks.com is behind ModSecurity (SpiderLabs) WAF.
[~] Number of requests: 2

```

```

(kali@kali)-[~]
$

```

```
(kali㉿kali)-[~]
$ curl -I https://networkwalks.com
HTTP/2 200
permissions-policy: private-state-token-redemption=(self "https://www.google.com" "https://www.gstatic.com" "https://recaptcha.net" "https://challenges.cloudflare.com" "https://hcaptcha.com"), private-state-token-issuance=(self "https://www.google.com" "https://www.gstatic.com" "https://recaptcha.net" "https://challenges.cloudflare.com" "https://hcaptcha.com")
link: <https://networkwalks.com/wp-json/>; rel="https://api.w.org/", <https://networkwalks.com/wp-json/wp/v2/pages/53>; rel="alternate"; title="JSON"; type="application/json", <https://networkwalks.com/>; rel="shortlink"
set-cookie: __wpdm_client=aa4ab09ed8f9d6d6de47a79000fa8305; path=/; domain=networkwalks.com; secure; HttpOnly
referrer-policy: no-referrer-when-downgrade
x-endurance-cache-level: 0
x-nginx-cache: WordPress
content-type: text/html; charset=UTF-8
date: Wed, 16 Sep 2026 11:46:45 GMT
server: Apache

(kali㉿kali)-[~]
$
```

Nmap scans using Zenmap

Zenmap

Scan Tools Profile Help

Target: 10.0.0.0/24 Profile: Ping scan

Command: nmap -sn 10.0.0.0/24

Hosts Services Nmap Output Ports / Hosts Topology Host Details Scans

OS	Host
	10.0.0.1
	10.0.0.2
	10.0.0.10

nmap -sn 10.0.0.0/24

Starting Nmap 7.99 (<https://nmap.org>) at 2026-09-17 09:28 -0400

Nmap scan report for 10.0.0.1

Host is up (0.00055s latency).

MAC Address: 52:54:00:12:35:00 (QEMU virtual NIC)

Nmap scan report for 10.0.0.10


Host is up (0.0012s latency).

MAC Address: 08:00:27:86:CE:3E (Oracle VirtualBox virtual NIC)

Nmap scan report for 10.0.0.2

Host is up.

Nmap done: 256 IP addresses (3 hosts up) scanned in 3.05 seconds



16. CONCLUSION

The authorized reconnaissance assessment successfully mapped significant portions of the publicly visible Networkwalks infrastructure.

The assessment identified:

- 13 DNS names.
- Multiple public IP addresses.
- Two primary infrastructure netblocks.
- Mail infrastructure.
- HostGator-related DNS infrastructure.
- Oracle-associated ASN information.
- WordPress and plugin technology information.
- A publicly referenced WordPress REST API.
- An administrative/root-style email address.
- A localhost DNS record requiring review.
- Potentially suspicious typo-like domains requiring validation.

At the same time, important defensive controls were identified, including:

- ModSecurity WAF protection.
- HTTPS availability.
- HTTP-to-HTTPS redirection.
- Refused DNS zone transfers.
- WHOIS privacy protection.

The assessment therefore provides Networkwalks with a practical external attack-surface baseline.

The recommended next step is to transition from **reconnaissance into controlled vulnerability validation**, focusing on exposed administrative services, WordPress/plugin security, DNS hygiene, TLS configuration, authentication controls, email security and continuous external attack-surface monitoring.

APPENDIX A — COMMANDS USED

DNS Resolution

```
nslookup networkwalks.com
```

DNS Enumeration

`dnsrecon -d networkwalks.com`

WAF Detection

`wafw00f networkwalks.com`

HTTP Header Analysis

`curl -I https://networkwalks.com`

Web Technology Fingerprinting

`whatweb networkwalks.com`

WHOIS Enumeration

`whois networkwalks.com`

Maltego

The following transformation categories were used:

- Domain → DNS Names
 - Domain → Websites
 - Domain → SOA
 - Domain → MX
 - Domain → IP Addresses
 - DNS → Netblock
 - Netblock → ASN
 - ASN → Company
 - DNS → Zone Transfer Testing
 - Domain → Email addresses
-

APPENDIX B — EVIDENCE INTERPRETATION

The following classification was used throughout the report:

Confirmed observation

Directly demonstrated by the supplied tool output.

Requires validation

Identified by reconnaissance but requiring additional testing.

Potential risk

A condition that could increase attack surface but is not itself a confirmed vulnerability.

Positive security control

A defensive mechanism observed during testing.

This distinction prevents reconnaissance information from being incorrectly reported as an exploitable vulnerability.

APPENDIX C — PROFESSIONAL TESTER STATEMENT

This assessment was performed as an authorized cybersecurity learning and penetration-testing exercise.

Testing was limited to reconnaissance and attack-surface discovery. No attempt was made to obtain unauthorized access, steal credentials, modify data, disrupt services, or cause denial of service.

Any subsequent vulnerability validation should be conducted only under explicit written authorization and an agreed Rules of Engagement.

Prepared by:

ADONGO PETER ODUOR

**Cybersecurity & Ethical Hacking — B083
Networkwalks**

