

Data Structures and Algorithms

Lecture 3: Sorting

Heikki Peura

h.peura@imperial.ac.uk



Last time

Searching and complexity

- ▶ Big-O notation
- ▶ Binary search vs linear search

Plan for today:

- ▶ **Sorting** algorithms
- ▶ Selection sort and merge sort

Asymptotic analysis

Principle 0: measure number of basic operations as function of input size


Principle 1: focus on worst-case analysis

Principle 2: ignore constant factors and lower-order terms

Principle 3: only care about large inputs

Formal way to describe this approach:

- ▶ Big-O notation: upper bound on worst-case running time



Big O: for **large enough inputs**, an $O(n)$ algorithm will be slower than $O(\log(n))$

Basic operations

Operations that a **computer can perform “quickly”** (constant time $O(1)$ for any input)

- ▶ Arithmetic operations (eg $x * y$) (for not too big numbers)
- ▶ Comparisons (eg $x > 0$)
- ▶ Assign a variable (eg $x = 2$), read/write memory

Basic operations

Operations that a **computer can perform “quickly”** (constant time $O(1)$ for any input)

- ▶ Arithmetic operations (eg $x * y$) (for not too big numbers)
- ▶ Comparisons (eg $x > 0$)
- ▶ Assign a variable (eg $x = 2$), read/write memory

What if the data structure is more complicated?

- ▶ For example, if L is a `list`: `L.append()`, `L[5]` ?
- ▶ Are these basic constant-time operations?
- ▶ Wait for Lecture 4... assume for now that list operations are constant time

Complexity classes

Fast algorithm: worst-case running time grows slowly with input size

- ▶ $O(1)$: constant running time — basic operations
- ▶ $O(\log n)$: logarithmic running time — binary search
- ▶ $O(n)$: linear running time — linear search
- ▶ $O(n \log n)$: log-linear running time — ??
- ▶ $O(n^c)$: polynomial running time — ??
- ▶ $O(c^n)$: exponential running time — ??

Sorting algorithms

So if we have an unsorted list, should we sort it first?

- ▶ Suppose complexity $O(\text{sort}(n))$
- ▶ Is $\text{sort}(n) + \log(n) < n$?
- ▶ No...

But what if we need to search repeatedly, say k times?

- ▶ Is $\text{sort}(n) + k \log(n) < kn$?
- ▶ Depends on k ...

How would you intuitively sort a list?

| | | | | | | | |
|----|----|----|----|---|----|----|----|
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
|----|----|----|----|---|----|----|----|

How would you intuitively sort a list?

| | | | | | | | |
|----|----|----|----|----|----|----|----|
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |

How would you intuitively sort a list?

| | | | | | | | |
|----|----|----|----|---|----|----|----|
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
|----|----|----|----|---|----|----|----|

| | | | | | | | |
|---|----|----|----|----|----|----|----|
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
|---|----|----|----|----|----|----|----|

| | | | | | | | |
|---|----|----|----|----|----|----|----|
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
|---|----|----|----|----|----|----|----|

How would you intuitively sort a list?

| | | | | | | | |
|----|----|----|----|----|----|----|----|
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
| 9 | 24 | 32 | 99 | 56 | 61 | 57 | 79 |

How would you intuitively sort a list?

| | | | | | | | |
|----|----|----|----|----|----|----|----|
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
| 9 | 24 | 32 | 99 | 56 | 61 | 57 | 79 |
| 9 | 24 | 32 | 56 | 99 | 61 | 57 | 79 |

How would you intuitively sort a list?

| | | | | | | | |
|----|----|----|----|----|----|----|----|
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
| 9 | 24 | 32 | 99 | 56 | 61 | 57 | 79 |
| 9 | 24 | 32 | 56 | 99 | 61 | 57 | 79 |
| 9 | 24 | 32 | 56 | 57 | 61 | 99 | 79 |

How would you intuitively sort a list?

| | | | | | | | |
|----|----|----|----|----|----|----|----|
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
| 9 | 24 | 32 | 99 | 56 | 61 | 57 | 79 |
| 9 | 24 | 32 | 56 | 99 | 61 | 57 | 79 |
| 9 | 24 | 32 | 56 | 99 | 61 | 57 | 79 |
| 9 | 24 | 32 | 56 | 57 | 61 | 99 | 79 |
| 9 | 24 | 32 | 56 | 57 | 61 | 99 | 79 |

How would you intuitively sort a list?

| | | | | | | | |
|----|----|----|----|----|----|----|----|
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
| 9 | 24 | 32 | 99 | 56 | 61 | 57 | 79 |
| 9 | 24 | 32 | 56 | 99 | 61 | 57 | 79 |
| 9 | 24 | 32 | 56 | 57 | 99 | 61 | 79 |
| 9 | 24 | 32 | 56 | 57 | 61 | 99 | 79 |
| 9 | 24 | 32 | 56 | 57 | 61 | 79 | 99 |

How would you intuitively sort a list?

| | | | | | | | |
|----|----|----|----|----|----|----|----|
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
| 9 | 24 | 99 | 32 | 56 | 61 | 57 | 79 |
| 9 | 24 | 32 | 99 | 56 | 61 | 57 | 79 |
| 9 | 24 | 32 | 56 | 99 | 61 | 57 | 79 |
| 9 | 24 | 32 | 56 | 99 | 61 | 57 | 79 |
| 9 | 24 | 32 | 56 | 57 | 61 | 99 | 79 |
| 9 | 24 | 32 | 56 | 57 | 61 | 99 | 79 |
| 9 | 24 | 32 | 56 | 57 | 61 | 79 | 99 |

In words: Find smallest item and move to front (swap with first unsorted item). Repeat with remaining unsorted items.

Selection sort algorithm

Selection sort list L of length n :

Selection sort algorithm

Selection sort list L of length n :

- ▶ Repeat n times:
 - ▶ Find smallest unsorted element
 - ▶ Swap its position with the first unsorted element

Selection sort algorithm

Selection sort list L of length n :

- ▶ Repeat n times:
 - ▶ Find smallest unsorted element
 - ▶ Swap its position with the first unsorted element

Python:

```
1 def selection_sort(L):
2     n = len(L)
3     for index in range(n):
4         min_index = find_min_index(L, index) # index with smallest element
5         L[index], L[min_index] = L[min_index], L[index] # swap positions
6     return L
```

Let's assume the function is implemented. What is its complexity?

Selection sort complexity

Correctness (for those into math): can be proved by induction

Selection sort complexity

Correctness (for those into math): can be proved by induction

Complexity:

- ▶ $O(n)$ passes of main loop
- ▶ Each pass: search for the smallest element in $O(n)$
- ▶ Total $O(n^2)$

Selection sort complexity

Correctness (for those into math): can be proved by induction

Complexity:

- ▶ $O(n)$ passes of main loop
- ▶ Each pass: search for the smallest element in $O(n)$
- ▶ Total $O(n^2)$

Can we do better?

Selection sort complexity

Correctness (for those into math): can be proved by induction

Complexity:

- ▶ $O(n)$ passes of main loop
- ▶ Each pass: search for the smallest element in $O(n)$
- ▶ Total $O(n^2)$

Can we do better?

- ▶ Yes! **Merge sort** is $O(n \log n)$
- ▶ But you can't do any better than that...

How to merge two sorted lists?

x =

| | | |
|----|----|----|
| 24 | 32 | 56 |
|----|----|----|

y =

| | | |
|----|----|----|
| 19 | 57 | 61 |
|----|----|----|

z =

| |
|--|
| |
|--|

How to merge two sorted lists?

x =

| | | |
|----|----|----|
| 24 | 32 | 56 |
|----|----|----|

 i1 = 0

y =

| | | |
|----|----|----|
| 19 | 57 | 61 |
|----|----|----|

 i2 = 0

z =

| |
|--|
| |
|--|

How to merge two sorted lists?

x =

| | | |
|----|----|----|
| 24 | 32 | 56 |
|----|----|----|

 i1 = 0

y =

| | | |
|----|----|----|
| 19 | 57 | 61 |
|----|----|----|

 i2 = 1

z =

| |
|----|
| 19 |
|----|

How to merge two sorted lists?

x =

| | | |
|----|----|----|
| 24 | 32 | 56 |
|----|----|----|

 i1 = 1

y =

| | | |
|----|----|----|
| 19 | 57 | 61 |
|----|----|----|

 i2 = 1

z =

| | |
|----|----|
| 19 | 24 |
|----|----|

How to merge two sorted lists?

x =

| | | |
|----|----|----|
| 24 | 32 | 56 |
|----|----|----|

 i1 = 2

y =

| | | |
|----|----|----|
| 19 | 57 | 61 |
|----|----|----|

 i2 = 1

z =

| | | |
|----|----|----|
| 19 | 24 | 32 |
|----|----|----|

How to merge two sorted lists?

x =

| | | |
|----|----|----|
| 24 | 32 | 56 |
|----|----|----|

 i1 = 3

y =

| | | |
|----|----|----|
| 19 | 57 | 61 |
|----|----|----|

 i2 = 1

z =

| | | | |
|----|----|----|----|
| 19 | 24 | 32 | 56 |
|----|----|----|----|

How to merge two sorted lists?

x =

| | | |
|----|----|----|
| 24 | 32 | 56 |
|----|----|----|

 i1 = 3

y =

| | | |
|----|----|----|
| 19 | 57 | 61 |
|----|----|----|

 i2 = 2

z =

| | | | | |
|----|----|----|----|----|
| 19 | 24 | 32 | 56 | 57 |
|----|----|----|----|----|

How to merge two sorted lists?

x =

| | | |
|----|----|----|
| 24 | 32 | 56 |
|----|----|----|

 i1 = 3

y =

| | | |
|----|----|----|
| 19 | 57 | 61 |
|----|----|----|

 i2 = 3

z =

| | | | | | |
|----|----|----|----|----|----|
| 19 | 24 | 32 | 56 | 57 | 61 |
|----|----|----|----|----|----|

How to merge two sorted lists?

x =

| | | |
|----|----|----|
| 24 | 32 | 56 |
|----|----|----|

 i1 = 3

y =

| | | |
|----|----|----|
| 19 | 57 | 61 |
|----|----|----|

 i2 = 3

z =

| | | | | | |
|----|----|----|----|----|----|
| 19 | 24 | 32 | 56 | 57 | 61 |
|----|----|----|----|----|----|

What is the complexity of this operation?

- ▶ Lengths of lists are n_1 and n_2
- ▶ Comparisons $O(\max\{n_1, n_2\})$
- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)

Sidebar: recursion

The factorial of n is the product of integers $1, \dots, n$.

- ▶ As a function: $\text{fact}(n) = n * (n - 1) * (n - 2) * \dots * 2 * 1$
- ▶ By convention, $\text{fact}(0) = 1$

Sidebar: recursion

The factorial of n is the product of integers $1, \dots, n$.

- ▶ As a function: $\text{fact}(n) = n * (n - 1) * (n - 2) * \dots * 2 * 1$
- ▶ By convention, $\text{fact}(0) = 1$

```
1 def fact(n):
2     result = 1
3     for i in range(1, n+1):
4         result = result * i
5     return result
6 print(fact(4))
```

Sidebar: recursion

The factorial of n is the product of integers $1, \dots, n$.

- ▶ As a function: $\text{fact}(n) = n * (n - 1) * (n - 2) * \dots * 2 * 1$
- ▶ By convention, $\text{fact}(0) = 1$

```
1 def fact(n):
2     result = 1
3     for i in range(1, n+1):
4         result = result * i
5     return result
6 print(fact(4))
```

But we can also write the factorial as follows:

$$\text{fact}(n) = 1, \text{ for } n = 0$$

$$\text{fact}(n) = n * \text{fact}(n - 1), \text{ for } n > 0$$

Sidebar: recursion

We can also write the factorial as follows:

$$\text{fact}(n) = 1, \text{ for } n = 0$$

$$\text{fact}(n) = n * \text{fact}(n - 1), \text{ for } n > 0$$

Factorial can be expressed as a smaller version of itself:

Sidebar: recursion

We can also write the factorial as follows:

$$\text{fact}(n) = 1, \text{ for } n = 0$$

$$\text{fact}(n) = n * \text{fact}(n - 1), \text{ for } n > 0$$

Factorial can be expressed as a smaller version of itself:

```
1 def fact_rec(n):
2     if n == 0:
3         return 1
4     else:
5         return n*fact_rec(n-1)
6 print(fact_rec(4))
```

This is called **recursion**

- ▶ Function calls itself
- ▶ Can make some problems easier to define -> merge sort!

Merge sort idea

Divide and conquer:

- ▶ Identify smallest possible “base case” subproblems that are easy to solve
- ▶ Divide large problem and solve smaller subproblems
- ▶ Find a way to combine subproblem solutions to solve larger problems

Merge sort idea

Divide and conquer:

- ▶ Identify smallest possible “base case” subproblems that are easy to solve
- ▶ Divide large problem and solve smaller subproblems
- ▶ Find a way to combine subproblem solutions to solve larger problems

Merge sort:

Merge sort idea

Divide and conquer:

- ▶ Identify smallest possible “base case” subproblems that are easy to solve
- ▶ Divide large problem and solve smaller subproblems
- ▶ Find a way to combine subproblem solutions to solve larger problems

Merge sort:

- ▶ Base case: if list length $n < 2$, the list is sorted

Merge sort idea

Divide and conquer:

- ▶ Identify smallest possible “base case” subproblems that are easy to solve
- ▶ Divide large problem and solve smaller subproblems
- ▶ Find a way to combine subproblem solutions to solve larger problems

Merge sort:

- ▶ Base case: if list length $n < 2$, the list is sorted
- ▶ Divide: if list length $n \geq 2$, split into two lists and merge sort each

Merge sort idea

Divide and conquer:

- ▶ Identify smallest possible “base case” subproblems that are easy to solve
- ▶ Divide large problem and solve smaller subproblems
- ▶ Find a way to combine subproblem solutions to solve larger problems

Merge sort:

- ▶ Base case: if list length $n < 2$, the list is sorted
- ▶ Divide: if list length $n \geq 2$, split into two lists and merge sort each
- ▶ Combine (merge) the results of the two smaller merge sorts

Merge sort

Dividing

| | | | | | | | |
|----|----|----|----|---|----|----|----|
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
|----|----|----|----|---|----|----|----|

Merge sort

Dividing

| | | | | | | | |
|----|----|----|----|---|----|----|----|
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
|----|----|----|----|---|----|----|----|

| | | | | | | | |
|----|----|----|----|---|----|----|----|
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
|----|----|----|----|---|----|----|----|


Merge sort

Dividing

| | | | | | | | |
|----|----|----|----|---|----|----|----|
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |
| 56 | 24 | 99 | 32 | 9 | 61 | 57 | 79 |


Merge sort

Dividing



Merge sort

Dividing




Merging




Merge sort

Dividing




Merging




Merge sort

Dividing



Merging



Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Comparisons $O(\max\{n_1, n_2\})$

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Comparisons $O(\max\{n_1, n_2\})$
- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Comparisons $O(\max\{n_1, n_2\})$
- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ If original list length is n , total $O(n)$ work for each round of merging

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Comparisons $O(\max\{n_1, n_2\})$
- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ If original list length is n , total $O(n)$ work for each round of merging

Merge sort complexity = merging * # number of divisions

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Comparisons $O(\max\{n_1, n_2\})$
- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ If original list length is n , total $O(n)$ work for each round of merging

Merge sort complexity = merging * # number of divisions

- ▶ Number of division levels $O(\log n)$ (like binary search)

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Comparisons $O(\max\{n_1, n_2\})$
- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ If original list length is n , total $O(n)$ work for each round of merging

Merge sort complexity = merging * # number of divisions

- ▶ Number of division levels $O(\log n)$ (like binary search)
- ▶ Log-linear: $O(n \log n)$

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Comparisons $O(\max\{n_1, n_2\})$
- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ If original list length is n , total $O(n)$ work for each round of merging

Merge sort complexity = merging * # number of divisions

- ▶ Number of division levels $O(\log n)$ (like binary search)
- ▶ Log-linear: $O(n \log n)$
- ▶ Big improvement over selection sort!

Merge sort complexity

What is the complexity of merge? Two lists of lengths n_1, n_2 :

- ▶ Comparisons $O(\max\{n_1, n_2\})$
- ▶ Two lists of lengths n_1 and n_2 : $O(n_1 + n_2)$ copy operations (need to copy each item)
- ▶ If original list length is n , total $O(n)$ work for each round of merging

Merge sort complexity = merging * # number of divisions

- ▶ Number of division levels $O(\log n)$ (like binary search)
- ▶ Log-linear: $O(n \log n)$
- ▶ Big improvement over selection sort!
- ▶ Does need some more space due to copying lists

Complexity classes

Fast algorithm: worst-case running time grows slowly with input size

- ▶ $O(1)$: constant running time — primitive operations
- ▶ $O(\log n)$: logarithmic running time — binary search
- ▶ $O(n)$: linear running time — linear search
- ▶ $O(n \log n)$: log-linear time — merge sort
- ▶ $O(n^c)$: polynomial running time — selection sort
- ▶ $O(c^n)$: exponential running time — ??

Sorting is a canonical algorithms problem

Many algorithms exist: bubble sort, insertion sort, quick sort, radix sort, heap sort, ...

- ▶ Useful for developing algorithmic thinking – eg randomized algorithms

Sorting is a canonical algorithms problem

Many algorithms exist: bubble sort, insertion sort, quick sort, radix sort, heap sort, ...

- ▶ Useful for developing algorithmic thinking – eg randomized algorithms

Theoretical bound for worst-case performance is $O(n \log n)$ – **we can't do better than merge sort**

Sorting is a canonical algorithms problem

Many algorithms exist: bubble sort, insertion sort, quick sort, radix sort, heap sort, ...

- ▶ Useful for developing algorithmic thinking – eg randomized algorithms

Theoretical bound for worst-case performance is $O(n \log n)$ – **we can't do better than merge sort**

But other algorithms are **better on average**

- ▶ Python uses **timsort** (In 2002, a Dutch guy called Tim got frustrated with existing algorithms)
- ▶ Exploit the fact that lists tend to be partly sorted already

Sorting is a canonical algorithms problem

Many algorithms exist: bubble sort, insertion sort, quick sort, radix sort, heap sort, ...

- ▶ Useful for developing algorithmic thinking – eg randomized algorithms

Theoretical bound for worst-case performance is $O(n \log n)$ – **we can't do better than merge sort**

But other algorithms are **better on average**

- ▶ Python uses **timsort** (In 2002, a Dutch guy called Tim got frustrated with existing algorithms)
- ▶ Exploit the fact that lists tend to be partly sorted already

Review

Sorting is a canonical computer science problem

- ▶ We've looked at two (of many) algorithms
- ▶ Selection sort involves repeatedly finding minimum element – intuitive but slow
- ▶ Merge sort is blazingly fast and has a neat recursive structure

Workshop after the break

- ▶ Implement sorting
- ▶ More looping and function practice

Workshop

Workshop zip file on the Hub

- ▶ HTML instructions
- ▶ At some point, you'll need the `.py`-file with skeleton code (open in Spyder)