
ClaimClarity architecture

ClaimClarity answers questions about a customer's claims (837P) and remittances (835). Each customer's data sits in its own S3 prefix, under its own KMS key and IAM roles. Six AWS checks, the numbered diamonds, enforce that on every write and read. The main board shows the whole system, and drill-downs 00–04 zoom into each part, and 05 is the access matrix.

The numbered diamonds on every board are the six permission checks. Each number means the same check on every board, and sits on the arrow it guards. Board 05 shows where each one is defined and what every role can do.


Gate	What has to be true	Defined in
1	The `_SUCCESS` file is in this customer's `raw/` folder	EventBridge rule, one per customer
2	The launcher passes only this customer's parser role, only to ECS	Launcher role's IAM policy (`iam:PassRole`)
3	The parser role and the customer's key allow the read or write	Parser role's IAM policy, customer key's key policy
4	The token is valid and names the customer	Chat API: checks Cognito's signature on every request
5	The reader role trusts this token's customer	Reader role's trust policy (STS)
6	The reader role and the customer's key allow the read	Reader role's IAM policy, customer key's key policy

Data backend




Part	What it does	Key facts
SFTP	Each customer sends daily 837 · 835 · 277 files	AWS Transfer Family, customer IP addresses only, straight into `raw/`
ClaimClarity data bucket	One prefix per customer: raw → silver → gold, plus quarantine and audit	One bucket for all customer data
Compute · write	EventBridge → ECS RunTask → one Fargate parser task per batch	Runs as the customer's parser role. Gates 1–3.
Access	Entra ID → Cognito → token naming the customer	The token is the only source of the customer. Gate 4.
Compute · read	Chat API → run worker (the Claim Query Agent) → DuckDB query service → STS → gold	15-minute credentials, this customer's gold only. Gates 5–6.

00 · Storage & isolation




Part	Key facts
Bucket	One bucket for all customer data, one prefix per customer. The web app and the access logs have their own buckets.
Prefixes	`raw/` (write-once, Object Lock 7 years, _SUCCESS written last), `parquet/` (silver), `semantic_layer/` (gold), `quarantine/` (bad files, kept 1 year), `audit/`
IAM roles	Per customer: SFTP copy, parser, reader, audit. IAM prefix policies keep the roles apart.
Data encryption key	Each customer's folder is encrypted with that customer's own KMS key, which covers every folder in the prefix, `audit/` included
Isolation	Each customer's roles reach only that customer's prefix (IAM). Customer A's roles are denied by IAM and by customer B's key policy.
Query audit	The DuckDB query service writes one JSON Lines record per SQL statement: write-once, kept 6 years, each record chained by hash to the one before
Gates	3 on the parser's reads and writes, 6 on the reader's reads

01 · Ingestion & parse




Step	What happens
Intake	The customer uploads over SFTP (port 22, customer IP addresses only). Transfer Family writes straight into `raw/` as the SFTP copy role, `_SUCCESS` last.
Gate 1	The customer's EventBridge rule matches `_SUCCESS` under `customer_b/raw/` only
Launch	ECS RunTask starts one parser task. EventBridge retries the launch 3 times.
Gate 2	`iam:PassRole` lets the launcher pass only customer B's parser role, and only to ECS tasks
Parser task	Fargate, 4–8 GB of memory, one per batch. It holds the batch lease, a lock object, while it runs. Bad files go to `quarantine/`.
Gate 3	IAM + KMS on every read of `raw/` and every write to silver and gold
Publish	Gold is written as a new version, and `CURRENT` moves by compare-and-set. Old versions stay readable for sessions already open.

02 · Login & customer mapping




Part	Key facts
Microsoft Entra ID	Company sign-in. The ClaimClarity app is assigned to groups.
Assigned group	One group per customer
Amazon Cognito	Single sign-on with Entra ID. Maps the user's group to exactly one customer and issues a token naming that customer. A user in no ClaimClarity group, or in more than one, is refused.
Gate 4	The chat API accepts a request only with a valid token, and takes the customer only from it


03 · Query path



Part	Key facts
Run worker	The Claim Query Agent sends SQL through `cli.py` and the SQL guard. It holds no AWS credentials.
SQL guard	Read-only SELECT. Blocks queries that would fail against the schema. Refuses keyless joins over 100 million row pairs.
Quack	SQL goes to the DuckDB query service over Quack with a per-run token, and rows come back the same way
Gate 5	The reader role's trust policy accepts only this token's customer. STS returns read-only credentials for 15 minutes, renewed with the same token when fewer than 3 minutes remain.
Gate 6	IAM + KMS allow reader role B only the current gold version in `customer_b/semantic_layer/`, and `customer_b/parquet/` after an escalation
`lossless.*`	PHI-stripped tables published next to gold, read only after the agent escalates with a reason
Customer A	Denied twice: the API takes the customer only from the token, and IAM + KMS deny reader role B on `customer_a/`

04 · Analyzer



04 · ANALYZER
The Claim Query Agent is the run worker. The DuckDB query service holds the credentials.
Frontend User interface
What should we look into?
USER QUERY
FOLLOW UP QUESTION OR CLARIFY ANSWERS
ANSWER W/ FORMATTING OR CLARIFYING QUESTIONS
Claim Query Agent · run worker on Fargate
Preset KPI queries
Preset fixed SQL · The agent fills in parameters to the preset queries
YES
KPI gate
does a preset answer it?
NO
Solved Example Question Bank
Tool & CLI reference
(prompt cached)



Part	Key facts
KPI gate	One Claude Haiku call with structured output. If a preset fits, it fills the parameters (payer, payer class, month, CPT, CARC), which are checked against the data. Anything else goes to the agent.
Preset KPI queries	16 fixed SQL queries. They pass the SQL guard like any other SQL.
Claim Query Agent	The run worker itself (Fargate): Claude Haiku, Strands on Amazon Bedrock
Prompt	Cached: rules, EDI glossary, semantic schema with allowed values, tool and CLI reference, system prompt and history. Per question: the 3 most similar solved examples and the newest prompt.
First decision	Answer, ask a clarifying question, or escalate to the lossless tables with a reason, which is logged
`cli.py` · SQL guard	The agent's one tool: `sql`, `lookup`, `describe`, `list`, `escalate`, then `answer`, `ask` or `refuse`. Every query passes the guard's checks. A failed check goes back to the agent as an error.
Answer	Streams back with live steps. The server re-runs the final SQL, so the numbers come from the database.

Network, operations, log retention and session handling are owned by IT.

05 · Access matrix



05 · ACCESS MATRIX

Role used by	raw/	quarantine/	parquet/	semantic_layer/	audit/	KMS key	Gates
SFTP copy role Transfer Family	Write once	–	–	–	–	Customer key encrypt	–
Launcher EventBridge → ECS RunTask	–	–	–	–	–	–	1 · 2
Parser role Fargate parser task	Read	Write	Write	Write a new version	–	Customer key	3
Reader role DuckDB query service	–	–	Read only after escalation	Read current version only	–	Customer key decrypt only	5 · 6
Audit role DuckDB query service	–	–	–	–	Append, write once	Customer key	–
Chat API · run worker Claim Query Agent · no data credentials	–	–	–	–	–	–	4

Gates · where each check is defined

	What has to be true	Defined in
1	The _SUCCESS file is in this customer's raw/ folder	EventBridge rule, one per customer
2	The launcher passes only this customer's parser role, only to ECS	Launcher role's IAM policy (iam:PassRole)
3	The parser role and the customer's key allow the read or write	Parser role's IAM policy · customer key's key policy
4	The token is valid and names the customer	Chat API: checks Cognito's signature on every request
5	The reader role trusts this token's customer	Reader role's trust policy (STS)
6	The reader role and the customer's key allow the read	Reader role's IAM policy · customer key's key policy

Part	Key facts
Roles	Four per customer (SFTP copy, parser, reader, audit), plus the launcher
No data credentials	The chat API and the run worker (the Claim Query Agent) hold no AWS data credentials

Open decisions

Question	Default shown
SFTP: AWS Transfer Family or an EC2 host?	Transfer Family, writing straight into `raw/`
Does the audit record keep the SQL text?	Yes, the first 500 characters
Queue and run workers	SQS + Fargate run workers
Per-customer limits	Concurrency and token budgets still need values