SMALL REGIONS LOOK HOMOGENEOUS: FINITE-SAMPLE BIAS OF RADIOMIC TEXTURE FEATURES AND A MODEL-FREE BLOCK-JACKKNIFE CORRECTION

Anonymous Author(s)

Affiliation

ABSTRACT

Radiomic texture features such as entropy or GLCM statistics are computed by plugging the histogram of a region of interest (ROI) into a nonlinear formula. For small ROIs these plug-in estimates are biased, so heterogeneity features partly measure lesion size. We show that the bias scales as c/N with a constant that depends on the unknown spatial correlation of the image, which defeats classical corrections, and that a delete-a-block jackknife over ROI octants removes it without knowing the correlation, wrapping any feature extractor unchanged. An ROI-specific criterion, $N/\xi^3 \geq 20$ with ξ the correlation length, decides when the correction is valid, and we identify a second, independent size artefact: PyRadiomics anchors grey levels at the ROI minimum. On synthetic textures and 6,560 real CT ROIs with an internal reference, including scanner reconstructions with sharp and smooth kernels at 1.25–5 mm, the jackknife removes the bias of GLCM joint entropy at 123 voxels ($-0.63 \rightarrow -0.01$ bits) and cuts its error by up to 59%; gated by the criterion, it never increases the error of entropy and energy features, leaves test–retest repeatability unchanged, and across 93 PyRadiomics features never raises the error of smooth histogram/GLCM features by more than 10%.

***Index Terms*—** Radiomics, texture analysis, bias correction, jackknife, reproducibility

1. INTRODUCTION

Radiomics quantifies lesion heterogeneity with texture features computed inside a segmented ROI: first-order entropy and uniformity of the grey-level histogram, and grey-level co-occurrence (GLCM) statistics [1], standardized by IBSI [2] and implemented in PyRadiomics [3]. Each feature is a nonlinear function of probabilities estimated from the ROI's own voxels. When the ROI is small these *plug-in* estimates are biased—the entropy of an under-sampled histogram is too low—so small lesions look homogeneous for purely statistical reasons. Radiomic features are notoriously confounded with volume [4]; Brooks and Grigsby [5] attributed this to under-sampling and proposed to exclude lesions below a fixed volume, and Shafiq-ul-Hassan et al. [6] proposed empirical normalizations. No correction exists, and a fixed volume threshold ignores that the information content of an ROI depends on the spatial correlation of the image. Classical entropy corrections [7, 8] assume independent samples, which neighbouring voxels are not.

Contributions. (i) A bias analysis showing that the plug-in bias of smooth texture features is c/N with c proportional to the unknown spatial correlation of the image. (ii) A model-free correction: a delete-a-block jackknife over ROI octants, which cancels c/N without estimating c and wraps any extractor, with an ROI-specific reliability criterion. Block resampling for dependent data is classical [9]; what is new is recognizing finite-ROI radiomic bias as this type of problem, turning it into a drop-in wrapper, and replacing fixed volume thresholds by a criterion that adapts to each ROI's correlation length. (iii) A second size artefact in PyRadiomics' discretization and its fix. (iv) An evaluation on synthetic textures, 120 real CT regions with an internal reference, all 93 non-shape PyRadiomics features, and 66 lung tumours, with a taxonomy of which features can and cannot be corrected.

2. THEORY AND METHOD

Plug-in bias under spatial correlation. Let the image inside an ROI S of N voxels be a stationary random field, and let a texture feature be $\theta = F(\pi)$, a smooth function of a probability vector π: the grey-level distribution (first order) or the distribution of grey-level pairs at a given offset (GLCM). The plug-in estimate is $\hat{\theta}_S = F(\hat{\pi}_S)$, with $\hat{\pi}_S$ the empirical frequencies in S. A second-order expansion gives

$$\mathbb{E}\,\hat{\theta}_S - \theta \approx \tfrac{1}{2}\,\mathrm{tr}\big(\nabla^2 F(\pi)\ \mathrm{Cov}(\hat{\pi}_S)\big). \qquad (1)$$

For independent voxels $\mathrm{Cov}(\hat{\pi}_S) = (\mathrm{diag}\,\pi - \pi\pi^\top)/N$, which for entropy yields the Miller–Madow bias $-(K-1)/(2N\ln 2)$ bits for K occupied bins [7]. For a correlated field, $\mathrm{Cov}(\hat{\pi}_S) \approx \Sigma_\infty/N$, where the long-run covariance $\Sigma_\infty = \sum_h \mathrm{Cov}(e_{X_0}, e_{X_h})$ sums the auto-covariances of the bin indicators over all lags h. The bias is therefore still c/N, but c is inflated by a "design effect" roughly equal to the correlation volume ξ^3, where ξ is the correlation length. It is unknown and image-dependent, so Miller–Madow-type corrections under-correct.

Block jackknife. Split S into B contiguous blocks S_b (we use $B = 8$ octants at equal voxel quantiles along each axis)

and recompute the feature on $S \setminus S_b$. If $\mathbb{E}\hat{\theta}_{S'} = \theta + c/|S'| + o(1/|S'|)$ for every contiguous region S' much larger than ξ, the delete-a-group jackknife for unequal groups [10],

$$\hat{\theta}_{\mathrm{JK}} = B\,\hat{\theta}_S - \textstyle\sum_b \left(1 - \frac{n_b}{N}\right)\hat{\theta}_{S\setminus S_b}, \qquad n_b = |S_b|, \qquad (2)$$

cancels the c/N term for any c, because deleting a contiguous block reduces the effective sample size in proportion to its voxel count. This is the block-resampling principle for dependent data [9, 11], here applied to finite ROIs. Eq. (2) needs only $B+1 = 9$ calls of an unmodified extractor and no parameter.

Reliability criterion. The expansion requires $\mathrm{Cov}(\hat{\pi}_S) \propto 1/N$, i.e. an ROI spanning several correlation lengths. When it does not, the ROI samples only part of the texture's variability, the bias is $O(1)$ rather than $O(1/N)$, and no estimator based on the ROI alone can recover θ. We estimate ξ inside the ROI as the lag at which the intensity autocorrelation falls to $1/e$ (averaged over the three axes) and use the effective sample size N/ξ^3 as a per-ROI reliability index. Our *gated* estimator returns $\hat{\theta}_{\mathrm{JK}}$ if $N/\xi^3 \geq 20$ (threshold from the synthetic study, Sec. 4) and otherwise the plug-in value together with an "unreliable" flag, since outside the $1/N$ regime the jackknife can add variance without removing bias.

Bin anchoring. With a fixed bin width w, PyRadiomics assigns grey level $\lfloor x/w \rfloor - \lfloor x_{\min}/w \rfloor + 1$, i.e. it numbers bins from the ROI minimum $x_{\min}$. Features that use grey-level *values* (GLCM joint/sum average, autocorrelation) then inherit the size dependence of an extreme-value statistic, which shrinks only logarithmically with N and cannot be removed by Eq. (2). Using absolute bin indices $\lfloor x/w \rfloor$, i.e. a fixed anchor, removes it.

Scope. Eq. (1) applies to smooth functionals of histograms and co-occurrences (first-order moments and entropies, GLCM). It does not apply to non-smooth statistics (percentiles, range), for which the jackknife is known to fail; to extensive features (energy, total energy), which scale with N by definition; or to run-, zone- and neighbourhood-based features (GLRLM, GLSZM, GLDM, NGTDM), whose runs and zones are truncated by the ROI boundary, so that part of their size dependence is definitional.

3. EXPERIMENTS

Synthetic textures. Gaussian random fields on 128^3 grids (Gaussian kernels $\sigma = 0.75, 1.5, 3$ voxels, i.e. $\xi = 2\sigma$), scaled to CT-like intensities (s.d. 60, bin width 25), 10 realizations each. Spherical ROIs of radius 3–14 voxels (123–11,513 voxels) are compared with the population value, taken from a radius-60 sphere. We use a NumPy re-implementation of the PyRadiomics first-order and GLCM features, verified to match PyRadiomics 3.0.1 to five decimals.

Real CT regions with an internal reference. In the 63 CTs of the Medical Segmentation Decathlon lung task [12] we place up to three spheres of radius 14 voxels (about 11,500 voxels) entirely inside soft tissue (HU in $[-50, 150]$), giving 120 regions from 46 scans. Each large sphere is the reference; ROIs of radius 3–8 voxels are sampled inside it (1,045 ROIs). The texture is real CT texture and noise (ξ median 0.86 voxels). To cover smoother textures we repeat the experiment after Gaussian smoothing of the scans ($\sigma = 0.7, 1.4, 2$ voxels; median $\xi = 1.6, 3.6, 6.4$; 524, 499, 319 ROIs) and, with real reconstructions, on RIDER Lung CT [13], where 32 patients were scanned twice on the same day and each scan was reconstructed with a sharp and a smooth kernel at 1.25, 2.5 and 5 mm (251 series with uniform slice spacing, 640 regions, 4,173 ROIs).

All PyRadiomics features. On 96 ROIs (radius 4 and 6, from 29 scans) we wrap the full PyRadiomics extractor—all 93 first-order, GLCM, GLRLM, GLSZM, GLDM and NGTDM features—in Eq. (2) without modification, and report bias and root-mean-square error (RMSE) in units of the between-region standard deviation of the reference.

Lung tumours. For the 66 MSD tumour components (68–338,472 voxels, median 6,866) we compute all features with and without correction and their Spearman correlation ρ with tumour volume; for the RIDER tumours (radiologist segmentations) we compute test–retest ICC(3,1) per reconstruction.

Table 1. Real CT soft tissue with an internal reference: bias and RMSE over radii 3–8 voxels, plug-in / block jackknife / gated jackknife ($N/\xi^3 \geq 20$; share of ROIs where applied). Top: MSD scans, native and smoothed (median ξ). Bottom: RIDER, real reconstructions (kernel, slice thickness).

setting (ξ)	applied	bias	RMSE
MSD, JointEntropy (bits)			
native (0.9)	99%	$-0.27/+0.00/-0.00$	0.40/0.23/0.23
smoothed (1.6)	90%	$-0.15/-0.07/-0.08$	0.31/0.30/0.31
smoothed (3.6)	29%	$-0.24/-0.21/-0.24$	0.50/0.50/0.50
smoothed (6.4)	6%	$-0.14/-0.11/-0.14$	0.47/0.49/0.47
Correlation, (3.6)	29%	$-0.05/-0.12/-0.06$	0.36/0.52/0.38
RIDER, JointEntropy (bits)			
sharp, 1.25 mm (0.8)	100%	$-0.34/+0.03/+0.03$	0.46/0.19/0.19
sharp, 2.5 mm (0.8)	100%	$-0.33/-0.01/-0.01$	0.45/0.23/0.23
sharp, 5 mm (0.8)	100%	$-0.35/-0.09/-0.09$	0.51/0.37/0.37
smooth, 1.25 mm (1.1)	98%	$-0.17/-0.05/-0.05$	0.30/0.25/0.25
smooth, 2.5 mm (1.0)	96%	$-0.13/-0.03/-0.04$	0.33/0.31/0.30
smooth, 5 mm (5.6)	32%	$-0.39/-0.31/-0.37$	0.63/0.60/0.62
Contrast, smooth 5 mm	32%	$-0.01/-0.01/-0.01$	0.61/0.72/0.62

Table 2. 93 PyRadiomics features at radius 4 and 6: median |bias| in reference-s.d. units (plug-in $\rightarrow$ jackknife), and number of features whose RMSE decreases ($\downarrow$) or increases by $>10\%$ ($\uparrow$), radius 4/6.

type	n	|bias|, r=4	|bias|, r=6	$\downarrow$	$\uparrow$
smooth (1st ord., GLCM)	34	$0.15 \rightarrow 0.06$	$0.08 \rightarrow 0.04$	22/22	0/0
quantiles	8	$0.05 \rightarrow 0.09$	$0.05 \rightarrow 0.04$	4/3	3/3
geometry (run, zone)	51	$0.63 \rightarrow 0.48$	$0.57 \rightarrow 0.38$	35/28	12/19




Fig. 1. (a) Bias of GLCM joint entropy on synthetic textures vs. effective sample size N/ξ^3 (markers: $\xi = 1.5, 3, 6$; dotted: criterion $N/\xi^3 = 20$). (b) Same on real CT soft tissue with an internal reference in four correlation regimes (markers: $\xi = 0.9, 1.6, 3.6, 6.4$; mean, 95% CI). (c) Absolute bias of 93 PyRadiomics features without (x) and with (y) the block jackknife at radius 4, by feature type; points below the diagonal are improved. (d) Bias of the mean grey-level index with PyRadiomics' ROI-minimum anchoring and with a fixed anchor.

4. RESULTS

Synthetic textures (Fig. 1a). Plug-in joint entropy is biased by up to -2.1 bits and still by -0.02 to -0.14 bits at 11,500 voxels. The plug-in bias does not depend on N/ξ^3 alone, since sparse co-occurrence matrices add a term in the raw N. After correction, however, the residual collapses onto one curve: it stays within ± 0.1 bits whenever $N/\xi^3 \geq 20$, for every correlation length. The correction raised the RMSE by more than 0.02 only for contrast, which is unbiased (up to $+0.13$ at radius 3). Below $N/\xi^3 \approx 5$ all estimators remain strongly biased, as predicted.

Real CT (Fig. 1b, Table 1). In native-resolution soft tissue, a 123-voxel ROI underestimates joint entropy by 0.63 bits; the jackknife removes this bias (-0.01 ± 0.05, 95% CI) and halves the RMSE, and over all radii it removes the joint-entropy bias completely ($-0.27 \to 0.00$). With smoother texture the picture follows the criterion: at $\xi = 1.6$ the jackknife removes about half of the bias; at $\xi = 3.6$ and 6.4, where most ROIs have $N/\xi^3 < 20$, it removes little and can even hurt (correlation: RMSE 0.36 $\to$ 0.52), which the gate prevents (0.38). Part of the residual at $\xi \geq 1.6$ is not sampling error: the plug-in bias also persists at large N/ξ^3, because smoothing makes larger-scale anatomy dominate, i.e. the texture is not stationary at that scale. Real reconstructions confirm both regimes (Table 1, bottom): with the sharp kernel at every slice thickness and the smooth kernel up to 2.5 mm ($\xi \leq 1.1$), the jackknife removes 70–100% of the joint-entropy bias and cuts the RMSE by up to 59%; with the smooth kernel at 5 mm ($\xi = 5.6$) the gate is mostly closed and the estimate stays near the plug-in, protecting e.g. contrast (RMSE 0.61 instead of 0.72). Across all 6 reconstructions, gating never raised the RMSE of entropy, energy and uniformity features ($\leq$0.1%); for nearly unbiased features (correlation, contrast, IDM) it raised it by up to 18%, 5% and 6%.

All PyRadiomics features (Fig. 1c, Table 2). 62 of 93 features are biased by more than 0.2 reference s.d. at radius 4. For smooth first-order and GLCM features the jackknife reduces the median bias from 0.15 to 0.06 s.d., lowers the RMSE for 22 of 34 and never raises it by more than 10%; e.g. GLCM MCC $+1.79 \to -0.03$ s.d., joint entropy $-0.23 \to -0.01$. The remaining large biases of this group come from definitions, not sampling: energy and total energy are extensive, and joint average, sum average and autocorrelation inherit the ROI-minimum anchoring, which shifts the mean grey-level index by -5.5 levels at radius 3 and still -1.7 at radius 14, whereas a fixed anchor is unbiased (Fig. 1d). Quantile features behave as jackknife theory predicts (no gain), and region-geometry features are only partly corrected.

Lung tumours. Most tumours are large, so the correction changes most features little, and correlations with volume that are presumably biological (mean intensity, skewness) are unaffected. Where the bias is large, it removes the size dependence: the correlation of GLCM Imc1 with volume drops from $\rho = 0.65$ to 0.01, of joint entropy from 0.13 to -0.02, and the number of region-geometry features with $|\rho| > 0.3$ from 35 to 22. The correction costs no repeatability: on RIDER tumours, the test–retest ICC of joint entropy is 0.973 (plug-in) vs. 0.974 (gated), of entropy 0.963 vs. 0.963 (correlation: 0.89 vs. 0.85).

5. DISCUSSION

Plug-in texture features of small ROIs are biased estimators, and the bias depends on the image's spatial correlation, so

neither a fixed volume threshold [5] nor an independent-sample correction is adequate. The block jackknife is a wrapper around any extractor that removes the c/N bias of smooth features without tuning, and N/ξ^3 tells, per ROI, when no correction can work; the criterion is necessary rather than sufficient, since non-stationary texture also separates small ROIs from large ones. We recommend (1) the gated jackknife for first-order and GLCM entropy/energy-type features, not for linear or quantile features; (2) fixed-anchor discretization; (3) reporting N/ξ^3 and treating ROIs below 20 as unreliable. Limitations: the bias analysis assumes stationarity within the ROI; real tumours are heterogeneous, so their size–feature relations mix bias and biology; and run- and zone-based features need definitional, not statistical, fixes. Code: `https://github.com/Hannibal0319/isbi2027-texture-bias`.

6. COMPLIANCE WITH ETHICAL STANDARDS

Only public, anonymized datasets were used; no ethical approval was required.

7. ACKNOWLEDGMENTS

No funding or conflicts of interest. Claude (Anthropic, an AI assistant) helped write code and text; the authors verified all results.

8. REFERENCES

[1] R. M. Haralick, K. Shanmugam, and I. Dinstein, "Textural features for image classification," *IEEE Trans. Systems, Man, and Cybernetics*, vol. SMC-3, no. 6, pp. 610–621, 1973.

[2] A. Zwanenburg, M. Vallières, et al., "The Image Biomarker Standardization Initiative: standardized quantitative radiomics for high-throughput image-based phenotyping," *Radiology*, vol. 295, no. 2, pp. 328–338, 2020.

[3] J. J. M. van Griethuysen, A. Fedorov, C. Parmar, et al., "Computational radiomics system to decode the radiographic phenotype," *Cancer Research*, vol. 77, no. 21, pp. e104–e107, 2017.

[4] M. L. Welch, C. McIntosh, B. Haibe-Kains, et al., "Vulnerabilities of radiomic signature development: the need for safeguards," *Radiotherapy and Oncology*, vol. 130, pp. 2–9, 2019.

[5] F. J. Brooks and P. W. Grigsby, "The effect of small tumor volumes on studies of intratumoral heterogeneity of tracer uptake," *Journal of Nuclear Medicine*, vol. 55, no. 1, pp. 37–42, 2014.

[6] M. Shafiq-ul Hassan, G. G. Zhang, K. Latifi, et al., "Intrinsic dependencies of CT radiomic features on voxel size and number of gray levels," *Medical Physics*, vol. 44, no. 3, pp. 1050–1062, 2017.

[7] G. A. Miller, "Note on the bias of information estimates," in *Information Theory in Psychology: Problems and Methods*, pp. 95–100. Free Press, 1955.

[8] L. Paninski, "Estimation of entropy and mutual information," *Neural Computation*, vol. 15, no. 6, pp. 1191–1253, 2003.

[9] H. R. Künsch, "The jackknife and the bootstrap for general stationary observations," *The Annals of Statistics*, vol. 17, no. 3, pp. 1217–1241, 1989.

[10] F. M. T. A. Busing, E. Meijer, and R. van der Leeden, "Delete-m jackknife for unequal m," *Statistics and Computing*, vol. 9, no. 1, pp. 3–8, 1999.

[11] S. N. Lahiri, *Resampling Methods for Dependent Data*, Springer, 2003.

[12] M. Antonelli, A. Reinke, S. Bakas, et al., "The Medical Segmentation Decathlon," *Nature Communications*, vol. 13, pp. 4128, 2022.

[13] B. Zhao, L. Dercle, H. Yang, G. J. Riely, M. G. Kris, and L. H. Schwartz, "Annotated test-retest dataset of lung cancer CT scan images reconstructed at multiple imaging parameters," *Scientific Data*, vol. 11, pp. 1259, 2024.