

F-Strings (Exercises)

1.

```
n = 3  
  
x = 2.71828  
  
f'The number is {n}'
```

'The number is 3'
2.

```
f'2 + 2 = {2 + 2}'
```

3.

```
f'{x}'
```

4.

```
f'{x:.2}'
```

5.

```
f'{2.1:.4}'
```

6.

```
word = 'the'  
  
f'{word:<5}'
```

7.

```
f'{word:>5}'
```

8.

```
f'{x:>6.3}'
```

9.

```
nums = [2, 40, 1, 353]  
  
s = [f'{n:<4}' for n in nums]  
  
''.join(s)
```

F-Strings

If a string is preceded by `f` (just outside the quotation marks), anything within curly braces `{ }` inside that string is evaluated rather than taken as literal text.

A number of specifications can be provided, inside the curly braces after a colon `:`, for how the resulting value should be formatted. Specifically:

- `'.'` and a number specifies the maximum number of digits to show after the decimal point.
- `'<'` and a number adds spaces to pad the representation to the specified total length. The value is therefore left justified, which can be handy when printing tables.
- `'>'` and a number similarly adds spaces, but at the beginning, giving right justification.

F-Strings (Solutions)

1.

```
n = 3
```

```
x = 2.71828
```

```
f'The number is {n}'
```

'The number is 3'
2.

```
f'2 + 2 = {2 + 2}'
```

'2 + 2 = 4'
3.

```
f'{x}'
```

'2.71828'
4.

```
f'{x:.2}'
```

'2.7'
5.

```
f'{2.1:.4}'
```

'2.1'
6.

```
word = 'the'
```

```
f'{word:<5}'
```

'the '
7.

```
f'{word:>5}'
```

' the'
8.

```
f'{x:>6.3}'
```

' 2.72'
9.

```
nums = [2, 40, 1, 353]
```

```
s = [f'{n:<4}' for n in nums]
```

```
''.join(s)
```

'2 40 1 353 '